

Standard Operating Procedure: Server Data Backup

Document ID: IT-SOP-042

Effective Date: May 27, 2026

Version: 2.1

Owner: IT Infrastructure Team

1. Purpose & Scope

This procedure defines the mandatory steps for executing the weekly full data backup of the primary application servers. This ensures data redundancy and disaster recovery capabilities for all corporate user data.

2. Responsibilities

- IT Support Technicians:** Responsible for executing the manual backup sequence every Friday evening.
- System Administrators:** Responsible for verifying backup integrity and handling any system exceptions or failures.

3. Procedure

1. Verify system status: (Estimated time: 5 mins)
Log into the IT Admin Dashboard and confirm that no active user sessions are writing to the database. The system load must be below 15% before initiating the backup.

2. Initialize the backup script: (Estimated time: 2 mins)
Open the secure terminal and execute the backup command:
`./scripts/backup_main.sh --target=nas-storage-01`

3. Monitor data transfer: (Estimated time: 30-45 min)
Observe the progress bar on the dashboard. Ensure the transfer rate remains above 100 MB/s. Do not close the terminal window until the "Transfer Complete" status code appears.

4. Confirm backup integrity: (Estimated time: 5 min)
Run the checksum validation tool to ensure the backup file matches the source data. A successful verification will generate a green PASS token in the log file.

4. Troubleshooting & Exceptions

Critical Warning: If the checksum validation fails or throws a FAIL token, do not attempt to rerun the script immediately. Contact the on-call System Administrator immediately to prevent data corruption.

Error Code	Potential Cause	Immediate Action
ERR-401	Destination storage full	Route backup to secondary server nas-storage-02.
ERR-503	Network timeout	Check the Ethernet switch connection and restart Step 2.