



Department of Materials
Science and Engineering
Inaugural High School Science Competition

Utilizing Machine Learning to Predict Failure and Enhance Material Strength Through Hall-Petch

Ashwin Krishnamurthy

Edison Academy Magnet School, Edison, NJ 08837, Rutgers University, Piscataway, NJ 08854



Abstract

As implants and prosthetics become increasingly prevalent, efficient techniques are necessary to predict and improve product lifespan. Relying on common statistics like the mean lifetime may overlook important factors, such as material anomalies and overuse. The study of grain boundaries is essential for advancements in this sector of biomedical engineering.

With five macroscopic and many microscopic degrees of freedom, grain boundaries (GBs) can have substantial impacts on the mechanical, electrical, thermal, and chemical behavior of materials. The correlation between yield strength and GBs, in particular, is elucidated by the Hall-Petch relationship, stating that strength increases with decreasing grain size (Hansen, 2004). This is a direct consequence of GB strengthening, which is the process by which large GBs impede dislocation motion. However, the model cannot be applied at scales below a threshold of 30 nanometers due to GB sliding and diffusion. To resolve these limitations, the inverse Hall-Petch relationship can be used, accounting for the loss with an additional term (Naik & Walley, 2020).

Recent advancements have contributed significantly to understanding the nature of GBs. The creation of a dataset comprising 7304 unique aluminum grain boundaries, totaling over 43 million structures, offers a plethora of data for analysis (Homer et al., 2022). More specifically, the dataset can be examined with Interfacial Line Defect Analysis (ILDA) (Deka et al., 2023) in OVITO (Open Visualization Tool) (Stukowski, 2010). An innovative software allowing for detailed analysis of defects in materials, ILDA can offer insight into the impact of GBs on the entire structure.

This requires proper categorization of GBs derived from grain boundary energy (GBE), boundary angle, and grain size. Through the identification of patterns, machine learning models can be trained to predict the effect of applied force or stress. This enables the identification of high-impact GBs and their responses, improving the understanding of material behavior under stress. Vieira (2021) explored this, using a neural network to model and predict the strain behavior at GBs in polycrystalline metals. The results indicated that certain GBs were more prone to strain accumulation under load. This can also be integrated with Hall-Petch to determine optimal conditions for material strengthening. This optimization may significantly extend implant lifespan, highlighting the potential for machine learning in product development within the biomedical engineering industry.

Background

The core issue is the need for more reliable and longer-lasting biomedical implants and prosthetics. As these devices become more common, predicting their lifespan and preventing premature failure is crucial for patient health, safety, and reducing healthcare costs.

Traditional methods often rely on average material properties or simple statistical measures like mean lifetime. However, these approaches are often insufficient because:



- Importance of Grain Boundaries (GBs) - The mechanical behavior of implant materials is heavily influenced by GBs, the complex interfaces between crystal grains, which have at least five degrees of freedom affecting material properties.
- Standard Model Limitations (Hall-Petch) - While the Hall-Petch relationship shows that average grain size impacts strength (Hansen, 2004), it doesn't capture the varied behavior of specific GBs. Furthermore, Hall-Petch parameters themselves can depend on GB structure and texture (Wyrzykowski & Grabski, 1986).
- Nanoscale Deviations (Inverse Hall-Petch) - Below a threshold (~30 nm), the standard Hall-Petch model often fails due to mechanisms like GB sliding and diffusion, sometimes leading to strength reduction (Naik & Walley, 2020).
- Current methods struggle to efficiently predict how the diverse characteristics of individual GBs affect material performance under load, hindering targeted material design for durability.

This research employs a data-driven strategy:


- Utilize large computational GB datasets (e.g., Homer et al., 2022) containing specific structural/energetic features (GBE, angle, size). Analyze internal GB defects with tools like ILDA (Deka et al., 2023) for deeper insights.
- Train ML models (inspired by precedents like Vieira, 2021) using these detailed GB features to learn complex structure-response relationships.
- Use trained models to predict how specific GBs respond to stress, identifying high-impact GBs. Utilize this granular understanding to inform material design and processing, aiming for enhanced implant lifespan.

Methodology

- Data Acquisition and Initial Processing:
 - The primary data source will be the large-scale aluminum GB dataset generated by Homer et al. (2022), containing 7304 unique GB configurations and over 43 million associated atomic structures (including metastable states).
 - Python will be used for overall workflow management and data handling (e.g., using Pandas library). OVITO (Open Visualization Tool) will be employed for atomistic data visualization, processing, and analysis via its Python scripting interface (Stukowski, 2010).
- Interfacial Defect Characterization using ILDA via OVITO:
 - The Interfacial Line Defect Analysis (ILDA) tool (Deka et al., 2023) will be used to characterize the dislocation and disconnection content within each GB structure.
 - An OVITO Python script will be developed to automate the process:
 - Load the atomic structure into OVITO.
 - Execute the ILDA algorithm script within OVITO. ILDA identifies atoms near co-incidence sites, constructs a surface mesh, performs Burgers circuits across mesh edges, and inserts line defect segments (Deka et al., 2023). ILDA requires specification of the Coherent Reference Frame (CRF), which can be defined using the known crystal orientations from the Homer et al. (2022) data, or estimated automatically by ILDA based on local atomic deformation gradients near the interface. Both exact and estimated CRFs may be explored.
 - Key outputs from ILDA for each GB, such as the types, lengths, densities, Burgers vectors (b), and step heights (h) of identified interfacial line defects, will be calculated and stored.



- Feature Engineering:
 - A comprehensive feature set will be constructed for each unique GB by combining:
 - Macroscopic Features: GBE, parameters describing misorientation and boundary plane.
 - Microscopic Defect Features: Quantitative metrics derived from ILDA analysis, such as total defect line length, density of specific Burgers vector types, etc.
 - Inspired by Vieira (2021), geometric factors like the angle between the GB plane normal and a hypothetical applied stress direction could be calculated and included as features relevant for predicting response under specific loading scenarios.
- Machine Learning Model Development:
 - Objective is to train ML models to predict a target variable indicative of GB mechanical response or impact. Since the dataset contains static structures, the target variable might be:
 - A classification label ("high-impact" vs "low-impact") derived from features like GBE and ILDA defect density.
 - A regression target predicting a propensity for strain accumulation or failure initiation under hypothetical load (e.g., a score combining GBE, defect density, and geometric factors).
 - Directly predicting GBE itself to validate feature sets.
 - Inspired by Vieira (2021), Neural Networks (NNs) will be explored using libraries like TensorFlow or PyTorch. Other robust algorithms like Support Vector Machines/Regression (SVM/SVR), Random Forests, or Gradient Boosting Trees will also be tested using Scikit-learn.
 - Training and Validation:
 - The dataset (7304 unique GBs with their features) will be split into training, validation, and testing sets (e.g., 70%/15%/15%).
 - Appropriate feature scaling (e.g., standardization) will be applied.
 - Cross-validation (e.g., 5-fold) will be performed on the training set to optimize model hyperparameters.
 - Models will be trained on the full training set using the optimized hyperparameters.
 - Model performance will be evaluated on the unseen test set using relevant metrics (e.g., R-squared, RMSE for regression; accuracy, precision, recall, F1-score, AUC for classification).
 - The best performing model will be used to predict the target outcome for all GBs in the dataset. This will allow ranking or classifying GBs to identify those predicted to be "high-impact" under stress, as mentioned in the abstract.



Results

- The feature importance analysis is expected to show that both macroscopic features (like GBE, boundary plane/misorientation) and microscopic defect features (derived from ILDA) contribute significantly to predicting GB behavior. It is anticipated that the ILDA-derived defect characteristics will provide additional predictive power beyond what can be achieved using macroscopic features alone, highlighting the value of detailed defect analysis (Deka et al., 2023).
- It is expected that GBs with higher Grain Boundary Energy (GBE) and/or higher densities of specific types of interfacial defects (e.g., those with larger Burgers vectors or step heights identified by ILDA) will generally correlate with a higher predicted mechanical impact (e.g., higher propensity for strain accumulation or failure).
- The analysis is expected to pinpoint specific combinations of the 5D crystallographic parameters (Homer et al., 2022) and defect structures that consistently lead to predictions of high mechanical impact. These might include certain high-angle boundaries or boundaries accommodating specific types of complex defect networks.
- Conversely, it is anticipated that well-known low-energy boundaries (e.g., low-angle GBs, potentially certain low-Σ CSL boundaries present in the AI dataset) with low defect content will be predicted as having low mechanical impact, aligning with concepts like GB strengthening (Hansen, 2004) where such boundaries might be less prone to sliding or acting as failure initiation sites.

5. The results are expected to provide a more nuanced understanding of GB structure-property relationships in aluminum, potentially highlighting specific defect arrangements or crystallographic configurations that lead to deviations from generalized trends like the Hall-Petch or Inverse Hall-Petch relationships (Naik & Walley, 2020).

Number in Fig. 1	AI purity (%)	Range of used grain or sub-grain sizes (μm)	σ_y (MPa)	σ_y (MPa)	Plastic working process	Conditions of anneal after plastic working	Reference
1	9999	35-1300	5.6	0.0411	Cold rolling or cold drawing, strain 15-80%	1 h, 300-500°C	a
2	9999	71-760	8.5	0.0474	Hot extrusion	10-60 min, 150-500°C	b
3	9999	30-490	9.0	0.063	Cold rolling	30-400°C (no texture observed)	c
4	9999	33-135	12.2	0.050	Cold drawing from Ø 12 mm to Ø 8 mm, cold hydrostatic extrusion to Ø 3 mm, cold hydrostatic extrusion to Ø 20 mm, cold hydrostatic extrusion to Ø 3 mm	1 h, 300-400°C	d
5	9999	2-35	9.1	0.056	Hot rolling, rolling liquid nitrogen temperatures	1 h, 250-320°C	e
6	9999	35-180	17.0	0.013	Hot rolling, rolling liquid nitrogen temperatures	1 h, 250-300°C	f
7	9999	2-14	8.3	0.058	Hot rolling, rolling liquid nitrogen temperatures	1 h, 250-300°C	f
8	9998	25-1000	3.0	0.032	Cold drawing over 90% reduction	320°C	g
9	999	15-320	3.0	0.060		Various temperatures	h

Conclusion

This study proposed a machine learning framework to predict grain boundary (GB) mechanical impact using detailed features derived from large-scale datasets (Homer et al., 2022) and advanced defect analysis via ILDA (Deka et al., 2023). By combining macroscopic GB descriptors with microscopic defect metrics, the trained models are expected to identify "high-impact" GBs critical to material performance. This data-driven approach aims to move beyond average property models (Hansen, 2004; Naik & Walley, 2020), offering a more granular understanding necessary for designing optimized microstructures and ultimately improving the reliability and lifespan of biomedical implants.

Future Directions

- Applying the methodology to other implant materials (e.g., Ti, CoCr) and incorporating explicit loading conditions into predictions.
- Exploring more sophisticated ML models and feature representations, including analysis of metastable GB states from the dataset (Homer et al., 2022).
- Experimentally validating predictions on real materials and integrating the ML-derived GB behavior into multi-scale simulations (e.g., CP-FEM).
- Extending the framework to predict dynamic GB phenomena like migration or interaction outcomes.

References and Acknowledgements

- Deka, N., Stukowski, A., & Sills, R. B. (2023). Automated extraction of interfacial dislocations and disconnections from atomistic data. *Acta Materialia*, 256(119096), 119096. doi:10.1016/j.actamat.2023.119096
- Hansen, N. (2004). Hall-Petch relation and boundary strengthening. *Scripta Materialia*, 51(8), 801-806. doi:10.1016/j.scriptamat.2004.06.002
- Homer, E. R., Hart, G. L. W., Braxton Owens, C., Hensley, D. M., Spendlove, J. C., & Serafin, L. H. (2022). Examination of computed aluminum grain boundary structures and energies that span the 5D space of crystallographic character. *Acta Materialia*, 234(118006), 118006. doi:10.1016/j.actamat.2022.118006
- Naik, S. N., & Walley, S. M. (2020). The Hall-Petch and inverse Hall-Petch relations and the hardness of nanocrystalline metals. *Journal of Materials Science*, 55(7), 2661-2681. doi:10.1007/s10853-019-04160-w
- Stukowski, A. (2009). Visualization and analysis of atomistic simulation data with OVITO-the Open Visualization Tool. *Modelling and Simulation in Materials Science and Engineering*, 18(1), 015012. https://doi.org/10.1088/0965-0393/18/1/015012
- Vieira, R. B., & Lambros, J. (2021). Machine learning neural-network predictions for grain-boundary strain accumulation in a polycrystalline metal. *Experimental Mechanics*, 61(4), 627-639. doi:10.1007/s11340-020-00687-1
- Wyrzykowski, J. W., & Grabski, M. W. (1986). The Hall-Petch relation in aluminum and its dependence on the grain boundary structure. *Philosophical Magazine A*, 53(4), 505-520. doi:10.1080/01418618608242849