

# Linux Shell

Jan Pribošek

7.4.2017

# I. Basic commands

## MAN

---

Manual pages - built in documentation

```
1  # usage
2  man [command]
3
4  man man
5  man ls
6  man firefox
```

## LS

---

List directory contents

```
1  # usage
2  ls -[options]
3
4  ls
5  ls -a      # display hidden files
6  ls -la     # display hidden files in long format
7  ls -la -r  # display all in reverse order
8  ls -la -h  # display file sizes in human readable format
```

- hidden files: dotfiles [filename]
- file extensions: no file extensions, everything in Linux is file
- naming files: use [file\_name], [fileName], [file-name] instead of spaces

## PWD

---

Print working directory

```
1  pwd
```

## SHEBANG LINE

---

Shebang line is used to tell the system the name of the interpreter that should be used to execute the script

```
1  #!/bin/bash
2  #!/usr/bin/python3
```

## CD

---

### Change directory

```
1  # usage
2  cd [path]
3
4  cd          # change to home folder
5  cd -        # change to previous working directory
6  cd ..       # change to parent folder
```

```
1  # Tips
2
3  /var/log    # absolute path - begins with root directory
4  var/log     # relative path - begins with current working directory
5
6  .          # working directory
7  ..         # working directory parent directory
8
9  (TAB)       # autocomplete
10 (TAB,TAB)   # show all possibilities
11 (Select,middle mouse button) # copy & paste
```

## CAT

---

### Concatenate files and print on standard input

```
1  # usage
2  cat [file1] [file2] [file3] ...
3
4  # print from bottom to top
5  tac [file1] [file2] [file3] ...
```

## TAIL

---

### Display last n lines

```
1  # usage
2  tail -n 5 [file]    # display last 5 lines of file
```

## HEAD

---

### Display first n lines

```
1  # usage
2  head -n 3 [file]    # display first 3 lines of file
```

## II. Manipulating files and directories

### TOUCH

---

Create new empty file

```
1 touch [filename]
```

### MKDIR

---

Create new empty folder

```
1 mkdir [directory]
2 mkdir [dir2] [dir2] [dir3]
```

### CP

---

Copy files

```
1 # usage
2 cp [/path/to/input] [/path/to/output]
3
4 cp [file1] [file2] [dir]
5 cp -r [dir1] [dir2]      # copy recursively (when copying directories)
6 cp -u [input] [output]  # copy only files that do not exist or are newer
```

### MV

---

Move or rename files

```
1 # usage
2 mv [path/to/input] [path/to/output_folder]
3
4 # rename file
5 mv ~/Documents/file123 ~/Documents/file
```

## RM

---

Remove files or folders

**THIS IS DANGEROUS COMMAND, BE CAREFUL!**

```
1  # Be careful when using these
2  rm [file]          # remove file
3  rm -r [folder]     # remove folder recursively
4  rm -rf [folder]    # remove folder recursively, and do not prompt
5
6  rm -r -i [folder]  # prompt before every removal
7  rm -r -I [folder] # prompt once
```

## III. Intermediate commands

### WILDCARDS

---

Select filenames based on patterns

```
1  *           # Any characters
2  ?           # Any single character
3  [:alnum:]   # Any alphanumeric character
4  [:alpha:]   # Any alphabetic character
5  [:digit:]   # Any digit
6  [:lower:]   # Any lowercase letter
7
8             # There are more but we are ending here
```

```
1  # Examples:
2  a*          # show everything that starts with a
3  *.txt       # show everything that ends with .txt
4  a*.txt      # Any file beginning with 'a' and ending with .txt
5  ab??def     # File: ab + "any 2 characters" + def
6  [[:digit:]]* # Any file starting with digit
7  [![:lower:]]* # Any file not starting with lowercase
```

### GREP

---

Print lines matching a pattern (filter)

```
1  grep [text]
2  grep -v [text] # display lines not containing [text]
3  egrep [text + wildcards]
```

## PIPE

---

Piping standard output of left command to standard input of the right command

```
1  # pipe from left to right command
2  cmd1 | cmd2 | cmd3 | cmd 4
3
4  cat [file] | grep [text]  # read file and print lines matching a pattern
5
6  # helpers
7  uniq      # removes any duplicates from the list
8  uniq -d   # show only duplicates
9  sort      # sorting output of commands
10
11 [cmd] | sort | uniq  # show sorted unique lines of cmd output
```

## REDIRECT (>, >>)

---

Used to redirect standard output to files. All errors are sent to standard error.

```
1  [cmd] [operator] [filename]
2
3  ls -l /usr/bin > output.txt    # text file is always overwritten
4  ls -l /usr/bin >> output.txt    # output is appended to text file
5  ls -l /bin/usr 2> error.txt     # 2> is used to redirect error stream
6  ls -l /usr/bin &> output.txt    # redirect both outputs to text file
7  [cmd] 2> /dev/null             # throw away unwanted output
```

## ARCHIVING

---

Archiving and compressing

```
1  # c - create, x - extract, v - verbose, f - file, - standard IO
2  tar cvf archive.tar file1 file2 # create archive
3  tar xvf archive.tar              # unpack tar
4  gzip [file]                      # compress
5  gunzip [file]                   # uncompress file.gz
6  tar z[xvf/cvf] file.tar.gz       # extract tar.gz
```

## CHMOD

---

Change permissions of file or folder

```
1  chmod [permissions] [file]
```

## A) Octal representation (base 8)

Number	Meaning
0	---
1	--X
2	-W-
3	-WX
4	r--
5	r-X
6	rW-
7	rWX

```
1 chmod [owner group other] [file]
2
3 # Examples
4 chmod 777 build_script.sh
5 chmod 755 build_script.sh
6 chmod 000 build_script.sh
```

## B) Symbolic representation

User	Meaning	Operators
u	user	+
g	group	-
o	other	=
a	all	

```
1 chmod [user][operator] [file]
2
3 # Examples:
4 chmod a+x # Added execution rights to all
5 chmod g-w # Remove write permissions from group
6 chmod u-x # Remove execute permissions from owner
```

## Use what works for you

## SCP

### Moving files over network

```
1 # local files to remote
2 scp [file1] [file2] [username]@[server_ip]:[/path/to/remote/folder]
3 # remote files to local
4 scp [username]@[server_ip]:[filename] [/local/folder]
5 # copying local directory to remote server
6 scp -r [directory] [username]@[server_ip]:[/path/to/remote/folder]
7
8 # if you are transferring large numbers of files often, take a look at rsync
```

## IV. Shell scripts

### COMMAND SUBSTITUTION

---

Use bash commands in bash commands

```
1 $(command)
2
3 # Example:
4 echo $(uname -a) # prints system information
5 echo $((1+5))    # note the double braces around arithmetic expressions
6
7 echo `uname -a`  # alternative notation
```

### BRACE EXPANSIONS

---

Execute the same command

```
1 echo folder_{1, 2, 3}
2 echo folder_{1..5}
3 echo folder_{A..Z}
```

### QUOTES

---

#### Double quotes (")

All special characters lose their meaning, exceptions: \$, \, '

```
1 echo "$(hostname) computer uptime: $(uptime)"
```

#### Single quotes (')

Suppress all expansions

```
1 echo '$(hostname) computer uptime: $(uptime)'
```

### SIMPLE SHELL SCRIPT

---

```
1 #!/bin/bash
2 echo "Hello from bash"
3 python3 hello_world.py
4 echo "End of script"
```



## V. Tips & Tricks

### 1. Subshell

```
1 (cd [path] && [cmd]) # execute this and jump to current working directory
```

### 2. Bang Bang

```
1 !! # execute previous command
2 sudo !! # execute previous command with sudo privileges
```

### 3. Quick copy

Share files to another computer on localhost

```
1 # start basic web server on port 8000 from current working directory
2 python -m SimpleHTTPServer
```

## VI. Tasks:

### TASK 1

---

Check syslogs in /var/log/syslog

- whole file
- last 20 lines
- first 5 lines
- dump last 100 lines containing "systemd" into file named systemd.log

### TASK 2

---

Create 2017 txt calendar. Use `cal` command for producing calendar

```
1 cal -y 2017 > calendar.txt
```

### TASK 3

---

Copy all html files from directory<sub>1</sub> to directory<sub>2</sub>, but only those that do not exist in the destination directory or are newer than the versions in the destination directory.

```
1 cp -u *.html destination
```