



```
print(X[:,2])
```

```
['Female' 'Female' 'Female' 'Female' 'Female' 'Male'] ... will now become:
[0 0 0 0 0 1]
```

```
# Converting the string features into their own dimensions. Gender doesn't matter here because
countryhotencoder = OneHotEncoder(categorical_features = [1]) # 1 is the country column
X = countryhotencoder.fit_transform(X).toarray()
```

```
/usr/local/lib/python3.6/dist-packages/sklearn/preprocessing/_encoders.py:415: FutureWarning:
If you want the future behaviour and silence this warning, you can specify "categories="
In case you used a LabelEncoder before this OneHotEncoder to convert the categories to integers.
warnings.warn(msg, FutureWarning)
/usr/local/lib/python3.6/dist-packages/sklearn/preprocessing/_encoders.py:451: DeprecationWarning:
"use the ColumnTransformer instead.", DeprecationWarning)
```

X

```
array([[1.0000000e+00, 0.0000000e+00, 0.0000000e+00, ..., 1.0000000e+00,
        1.0000000e+00, 1.0134888e+05],
       [0.0000000e+00, 0.0000000e+00, 1.0000000e+00, ..., 0.0000000e+00,
        1.0000000e+00, 1.1254258e+05],
       [1.0000000e+00, 0.0000000e+00, 0.0000000e+00, ..., 1.0000000e+00,
        0.0000000e+00, 1.1393157e+05],
       ...,
       [1.0000000e+00, 0.0000000e+00, 0.0000000e+00, ..., 0.0000000e+00,
        0.0000000e+00, 1.0000000e+00],
       [1.0000000e+00, 0.0000000e+00, 0.0000000e+00, ..., 1.0000000e+00,
        0.0000000e+00, 3.8190780e+04]])
```

The shortcut "Print notebook" is disabled when a code cell output iframe is active. Use the escape key to leave the iframe and enter the shortcut again.

```
[1.0000000e+00, 0.0000000e+00, 0.0000000e+00, ..., 1.0000000e+00,
 0.0000000e+00, 3.8190780e+04]])
```

```
X = X[:,1:] # Got rid of Spain as a dimension. It is still there through out inferences
```

```
# Splitting the dataset into the Training and Testing set.
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X,y, test_size = 0.2, random_state = 0)
```

```
# Feature Scaling
from sklearn.preprocessing import StandardScaler
sc=StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)
```

X\_train

```
array([[ -0.5698444 ,  1.74309049,  0.16958176, ...,  0.64259497,
        -1.03227043,  1.10643166],
       [ 1.75486502, -0.57369368, -2.30455945, ...,  0.64259497,
        0.9687384 , -0.74866447],
       [-0.5698444 , -0.57369368, -1.19119591, ...,  0.64259497,
        -1.03227043,  1.48533467],
       ...,
       [-0.5698444 , -0.57369368,  0.9015152 , ...,  0.64259497,
        -1.03227043,  1.41231994],
       [-0.5698444 ,  1.74309049, -0.62420521, ...,  0.64259497,
        0.9687384 ,  0.84432121],
       [ 1.75486502, -0.57369368, -0.28401079, ...,  0.64259497,
        -1.03227043,  0.32472465]])
```

```
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense
```

```
# Initializing the ANN
classifier = Sequential()
```

```
classifier.add(Dense(activation = 'relu', input_dim = 11, units=6, kernel_initializer='unifor
```

```
# Adding the second hidden layer
# Notice that we do not need to specify input dim.
```

The shortcut "Print notebook" is disabled when a code cell output iframe is active. Use the escape key to leave the iframe and enter the shortcut again. 

```
classifier.add(Dense(activation = 'sigmoid', units=1, kernel_initializer='uniform'))
```

```
classifier.compile(optimizer='adam', loss = 'binary_crossentropy', metrics=['accuracy'])
```

```
classifier.fit(X_train, y_train, batch_size=10, epochs=5)
```

 Train on 8000 samples

Epoch 1/5

8000/8000 [=====] - 2s 265us/sample - loss: 0.5044 - accuracy:

Epoch 2/5

8000/8000 [=====] - 1s 175us/sample - loss: 0.4313 - accuracy:

Epoch 3/5

8000/8000 [=====] - 1s 169us/sample - loss: 0.4272 - accuracy:

Epoch 4/5

8000/8000 [=====] - 1s 167us/sample - loss: 0.4225 - accuracy:

Epoch 5/5

8000/8000 [=====] - 1s 169us/sample - loss: 0.4190 - accuracy:

<tensorflow.python.keras.callbacks.History at 0x7fb1da158ac8>

```
y_pred = classifier.predict(X_test)
print(y_pred)
```

```
↳ [[0.26550376]
    [0.33042324]
    [0.20455596]
    ...
    [0.15818965]
    [0.15559867]
    [0.1560629 ]]
```

```
y_pred = (y_pred > 0.5)
print(y_pred)
```

```
↳ [[False]
    [False]
    [False]
    ...
    [False]
    [False]
    [False]]
```

```
from sklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, y_pred)
print(cm)
```

```
↳ [[1570  25]
    [ 313  92]]
```

The shortcut "Print notebook" is disabled when a code cell output iframe is active. Use the escape key to leave the iframe and enter the shortcut again. ✕