

MyProject Documentation

Contents

Module SuperHelper	3
Sub-modules	4
Variables	4
Variable AppDir	4
Variable AppName	4
Module SuperHelper.Core	4
Sub-modules	4
Functions	4
Function load_added_modules	4
Function load_core_commands	4
Function main_entry	4
Function pass_config	5
Function run_startup	5
Function save_config	5
Module SuperHelper.Core.Config	5
Sub-modules	5
Functions	5
Function load_app_config	5
Function make_config_global	6
Function pass_config	6
Function save_app_config	6
Classes	6
Class Config	6
Static methods	7
Methods	7
Module SuperHelper.Core.Config.app_config	9
Functions	9
Function load_app_config	9
Function save_app_config	9
Module SuperHelper.Core.Config.config_class	9
Functions	9
Function make_config_global	9
Function pass_config	9
Classes	10
Class Config	10
Static methods	10
Methods	10
Module SuperHelper.Core.Utils	12
Sub-modules	12
Functions	12
Function setup_core_logger	12

Classes	12
Class BitOps	12
Static methods	12
Class Cryptographer	13
Static methods	13
Methods	15
Class FP	15
Ancestors (in MRO)	16
Class variables	16
Class FileOps	16
Static methods	16
Class TypeCheck	19
Static methods	19
Module SuperHelper.Core.Utills.bit_ops	24
Classes	24
Class BitOps	24
Static methods	24
Module SuperHelper.Core.Utills.crypto_ops	24
Classes	24
Class Cryptographer	24
Static methods	25
Methods	26
Module SuperHelper.Core.Utills.file_ops	27
Classes	27
Class FP	27
Ancestors (in MRO)	27
Class variables	27
Class FileOps	28
Static methods	28
Module SuperHelper.Core.Utills.logger	30
Functions	30
Function setup_core_logger	30
Module SuperHelper.Core.Utills.type_ensure	31
Classes	31
Class TypeCheck	31
Static methods	31
Module SuperHelper.Core.Utills.type_hinting	35
Variables	35
Variable PathLike	35
Module SuperHelper.Core.core_cli	35
Functions	35
Function load_config	35
Function main_entry	36
Function run_startup	36
Function save_config	36
Module SuperHelper.Core.core_commands	36
Functions	36
Function load_core_commands	36
Module SuperHelper.Core.core_loader	36
Functions	36
Function load_added_modules	36

Module SuperHelper.Modules	36
Sub-modules	36
Module SuperHelper.Modules.FocusEnabler	37
Module SuperHelper.Modules.Stenographer	37
Module SuperHelper.Tests	37
Sub-modules	37
Functions	37
Function run	37
Function setup_and_cleanup	37
Module SuperHelper.Tests.test_base	37
Functions	37
Function run	37
Function setup_and_cleanup	37
Module SuperHelper.Tests.test_config	37
Classes	37
Class TestConfig	37
Static methods	37
Module SuperHelper.Tests.test_core	38
Functions	38
Function test_main_entry	38
Module SuperHelper.Tests.test_core_command	38
Classes	38
Class TestCore	38
Static methods	38
Class TestOtherUtils	39
Static methods	39
Module SuperHelper.Tests.test_module_FocusEnabler	39
Classes	39
Class TestFocusEnabler	39
Static methods	39
Module SuperHelper.Tests.test_module_Stenographer	41
Classes	41
Class TestStenographer	41
Static methods	41
Module SuperHelper.Tests.test_utils	41
Classes	41
Class TestBitOps	41
Static methods	41
Class TestCryptographer	42
Static methods	42
Class TestFileOps	44
Static methods	44
Class TestTypeCheck	44
Static methods	44

Module SuperHelper

Sub-modules

- [SuperHelper.Core](#)
- [SuperHelper.Modules](#)
- [SuperHelper.Tests](#)

Variables

Variable `AppDir`

Path to the application directory.

Variable `AppName`

Name of the application.

Module `SuperHelper.Core`

Sub-modules

- [SuperHelper.Core.Config](#)
- [SuperHelper.Core.Utills](#)
- [SuperHelper.Core.core_cli](#)
- [SuperHelper.Core.core_commands](#)
- [SuperHelper.Core.core_loader](#)

Functions

Function `load_added_modules`

```
def load_added_modules(  
    config: dict  
) -> list
```

Loads all added modules.

Returns ---= A list of a 2-tuple elements, where the first index is the `click.command` object, and the second index is the technical name of the command. For example:

```
[(main, "main"), ...]
```

The first index can be added to a `click.group`, i.e the cli function.

Function `load_core_commands`

```
def load_core_commands() -> list
```

Loads the Core CLI commands.

Returns ---= A list of a 2-tuple elements, where the first index is the `click.command` object, and the second index is the technical name of the command. For example:

```
[(add_modules, "core_add"), ...]
```

The first index can be added to a `click.group`, i.e the cli function.

Function `main_entry`

```
def main_entry() -> NoReturn
```

Function `pass_config`

```
def pass_config(
    core: bool = None,
    module_name: str = None,
    lock: bool = False,
    param_name: str = 'config'
) -> Callable
```

Passes the requested config to decorated functions.

The wrapped function will receive the config (as requested). When the function returns (or raises `SystemExit`), this decorator will capture that signal, save the config (if locked) before returning (or re-raising `SystemExit`).

Args ---= `core : bool` : Whether to request core config.

`module_name : str` The name of the module.

`lock : bool` Whether to lock the config, i.e allow writing to the config.

`param_name : str` The name of the parameter that the config will be passed as.

Returns ---= A Callable instance (the decorated function).

Raises ---= `SystemExit` : Re-raises the `SystemExit()` raised by the wrapped function.

`ValueError` Both `core` and `module_name` are specified.

Function `run_startup`

```
def run_startup()
```

Function `save_config`

```
def save_config()
```

Saves application config.

Module `SuperHelper.Core.Config`

Sub-modules

- [SuperHelper.Core.Config.app_config](#)
- [SuperHelper.Core.Config.config_class](#)

Functions

Function `load_app_config`

```
def load_app_config(
    config_path: ~PathLike
) -> NoneType
```

Loads the configuration of the application.

Args ---= `config_path : PathLike` : The path to config file.

Returns ---= `None`

Raises ---= `SystemExit` : Config file is unreadable.

Function `make_config_global`

```
def make_config_global(
    cfg: Config
) -> NoneType
```

Makes the configuration global.

Args ---= `cfg` : `Config` : The `Config` instance.

Returns ---= `None`

Function `pass_config`

```
def pass_config(
    core: bool = None,
    module_name: str = None,
    lock: bool = False,
    param_name: str = 'config'
) -> Callable
```

Passes the requested config to decorated functions.

The wrapped function will receive the config (as requested). When the function returns (or raises `SystemExit`), this decorator will capture that signal, save the config (if locked) before returning (or re-raising `SystemExit`).

Args ---= `core` : `bool` : Whether to request core config.

`module_name` : `str` The name of the module.

`lock` : `bool` Whether to lock the config, i.e allow writing to the config.

`param_name` : `str` The name of the parameter that the config will be passed as.

Returns ---= A `Callable` instance (the decorated function).

Raises ---= `SystemExit` : Re-raises the `SystemExit()` raised by the wrapped function.

`ValueError` Both `core` and `module_name` are specified.

Function `save_app_config`

```
def save_app_config(
    config: SuperHelper.Core.Config.config_class.Config,
    config_path: ~PathLike
) -> NoneType
```

Saves the configuration of the application.

Args ---= `config` : `Config` : The global `Config` instance

`config_path` : `PathLike` The path to config file

Returns ---= `None`

Raises ---= `SystemExit` : Config file is not writable.

Classes

Class `Config`

```
class Config(
    core: dict[str, ...] = None,
    modules: dict[str, dict[str, ...]] = None
)
```

The configuration of the application.

Static methods

Method from_dict

```
def from_dict(
    config: dict[str]
) -> SuperHelper.Core.Config.config_class.Config
```

Methods

Method apply_core_patch

```
def apply_core_patch(
    self,
    config: dict[str, ...]
) -> NoneType
```

Applies a new patch to core configuration.

This function should only be used by Core CLI.

Args ---= `config : dict[str, ...]` : The patch of the configuration.

Returns ---= None

Raises ---= `RuntimeError` : An error has occurred in `self.get_core_config()`

Method apply_module_patch

```
def apply_module_patch(
    self,
    module_name: str,
    config: dict[str, ...]
) -> NoneType
```

Applies a new patch to the module configuration.

Args ---= `module_name : str` : The name of the module to apply patch to.

`config : dict[str, ...]` The patch of the configuration.

Returns ---= None

Method get_core_config

```
def get_core_config(
    self,
    lock: bool = True
) -> dict
```

Gets the configuration of Core CLI.

This function is intended for internal use only, used for the decorator [pass_config\(\)](#).

Args ---= `lock : bool` : Whether to lock the config or not.

Returns ---= A dictionary mapping keys to corresponding values of the core config. Each entry is represented by a key-value pair of the dictionary. For example:

```
{"DEBUG": ..., "INSTALLED_MODULES": [...]}
```

The keys are always strings, and the values can be of any JSON-serializable type.

Raises ---= `RuntimeError` : The core config is locked by another call.

Method `get_module_config`

```
def get_module_config(
    self,
    module_name: str,
    lock: bool = True
) -> dict
```

Gets the configuration of the specified module.

This function is intended for internal use only, used for the decorator [pass_config\(\)](#).

Args ---= `module_name` : str : The name of the module that the config belongs to.

`lock` : bool Whether to lock the config or not.

Returns ---= A dictionary mapping keys to corresponding values of the module config. Each entry is represented by a key-value pair of the dictionary. For example:

```
{"DEBUG": ..., "INSTALLED_MODULES": [...]}
```

The keys are always strings, and the values can be of any JSON-serializable type.

Raises ---= `RuntimeError` : The module config is locked by another call.

Method `set_core_config`

```
def set_core_config(
    self,
    config: dict[str, ...]
) -> NoneType
```

Sets the configuration of Core CLI.

This function is intended for internal use only, used for the decorator [pass_config\(\)](#).

Args ---= `config` : dict[str, ...] : A dictionary with string keys of the core configuration.

Returns ---= None

Raises ---= `RuntimeError` : The last retrieval of the core config was not locked, hence it is read-only.

Method `set_module_config`

```
def set_module_config(
    self,
    module_name: str,
    config: dict[str, ...]
) -> NoneType
```

Sets the module configuration.

This function is intended for internal use only, used for the decorator [pass_config\(\)](#).

Args ---= `module_name` : str : The name of the module that the config belongs to.

`config` : dict[str, ...] A dictionary with string keys of the core configuration.

Returns ---= None

Raises ---= `RuntimeError` : The last retrieval of the module config was not locked, hence it is read-only.

Module `SuperHelper.Core.Config.app_config`

Functions

Function `load_app_config`

```
def load_app_config(
    config_path: ~PathLike
) -> NoneType
```

Loads the configuration of the application.

Args ---= `config_path` : `PathLike` : The path to config file.

Returns ---= `None`

Raises ---= `SystemExit` : Config file is unreadable.

Function `save_app_config`

```
def save_app_config(
    config: SuperHelper.Core.Config.config_class.Config,
    config_path: ~PathLike
) -> NoneType
```

Saves the configuration of the application.

Args ---= `config` : `Config` : The global `Config` instance

`config_path` : `PathLike` The path to config file

Returns ---= `None`

Raises ---= `SystemExit` : Config file is not writable.

Module `SuperHelper.Core.Config.config_class`

Functions

Function `make_config_global`

```
def make_config_global(
    cfg: Config
) -> NoneType
```

Makes the configuration global.

Args ---= `cfg` : `Config` : The `Config` instance.

Returns ---= `None`

Function `pass_config`

```
def pass_config(
    core: bool = None,
    module_name: str = None,
    lock: bool = False,
    param_name: str = 'config'
) -> Callable
```

Passes the requested config to decorated functions.

The wrapped function will receive the config (as requested). When the function returns (or raises `SystemExit`), this decorator will capture that signal, save the config (if locked) before returning (or re-raising `SystemExit`).

Args `---= core : bool` : Whether to request core config.

`module_name : str` The name of the module.

`lock : bool` Whether to lock the config, i.e allow writing to the config.

`param_name : str` The name of the parameter that the config will be passed as.

Returns `---=` A Callable instance (the decorated function).

Raises `---= SystemExit` : Re-raises the `SystemExit()` raised by the wrapped function.

`ValueError` Both `core` and `module_name` are specified.

Classes

Class `Config`

```
class Config(  
    core: dict[str, ...] = None,  
    modules: dict[str, dict[str, ...]] = None  
)
```

The configuration of the application.

Static methods

Method `from_dict`

```
def from_dict(  
    config: dict[str]  
) -> SuperHelper.Core.Config.config_class.Config
```

Methods

Method `apply_core_patch`

```
def apply_core_patch(  
    self,  
    config: dict[str, ...]  
) -> NoneType
```

Applies a new patch to core configuration.

This function should only be used by Core CLI.

Args `---= config : dict[str, ...]` : The patch of the configuration.

Returns `---=` None

Raises `---= RuntimeError` : An error has occurred in `self.get_core_config()`

Method `apply_module_patch`

```
def apply_module_patch(  
    self,  
    module_name: str,  
    config: dict[str, ...]  
) -> NoneType
```

Applies a new patch to the module configuration.

Args `---= module_name : str` : The name of the module to apply patch to.

`config : dict[str, ...]` The patch of the configuration.

Returns `---=` None

Method `get_core_config`

```
def get_core_config(
    self,
    lock: bool = True
) -> dict
```

Gets the configuration of Core CLI.

This function is intended for internal use only, used for the decorator [pass_config\(\)](#).

Args —== `lock` : bool : Whether to lock the config or not.

Returns —== A dictionary mapping keys to corresponding values of the core config. Each entry is represented by a key-value pair of the dictionary. For example:

```
{"DEBUG": ..., "INSTALLED_MODULES": [...]}
```

The keys are always strings, and the values can be of any JSON-serializable type.

Raises —== `RuntimeError` : The core config is locked by another call.

Method `get_module_config`

```
def get_module_config(
    self,
    module_name: str,
    lock: bool = True
) -> dict
```

Gets the configuration of the specified module.

This function is intended for internal use only, used for the decorator [pass_config\(\)](#).

Args —== `module_name` : str : The name of the module that the config belongs to.

`lock` : bool Whether to lock the config or not.

Returns —== A dictionary mapping keys to corresponding values of the module config. Each entry is represented by a key-value pair of the dictionary. For example:

```
{"DEBUG": ..., "INSTALLED_MODULES": [...]}
```

The keys are always strings, and the values can be of any JSON-serializable type.

Raises —== `RuntimeError` : The module config is locked by another call.

Method `set_core_config`

```
def set_core_config(
    self,
    config: dict[str, ...]
) -> NoneType
```

Sets the configuration of Core CLI.

This function is intended for internal use only, used for the decorator [pass_config\(\)](#).

Args —== `config` : dict[str, ...] : A dictionary with string keys of the core configuration.

Returns —== None

Raises —== `RuntimeError` : The last retrieval of the core config was not locked, hence it is read-only.

Method `set_module_config`

```
def set_module_config(
    self,
    module_name: str,
    config: dict[str, ...]
) -> NoneType
```

Sets the module configuration.

This function is intended for internal use only, used for the decorator [pass_config\(\)](#).

Args ---= `module_name` : `str` : The name of the module that the config belongs to.

`config` : `dict[str, ...]` A dictionary with string keys of the core configuration.

Returns ---= `None`

Raises ---= `RuntimeError` : The last retrieval of the module config was not locked, hence it is read-only.

Module `SuperHelper.Core.Utills`

Sub-modules

- [SuperHelper.Core.Utills.bit_ops](#)
- [SuperHelper.Core.Utills.crypto_ops](#)
- [SuperHelper.Core.Utills.file_ops](#)
- [SuperHelper.Core.Utills.logger](#)
- [SuperHelper.Core.Utills.type_ensure](#)
- [SuperHelper.Core.Utills.type_hinting](#)

Functions

Function `setup_core_logger`

```
def setup_core_logger(
    logging_path: ~PathLike
) -> logging.Logger
```

Sets up the core logger.

Args ---= `logging_path` : `PathLike` : The path to the logging file.

Returns ---= A `logging.Logger` instance with name set to [SuperHelper](#).

Classes

Class `BitOps`

```
class BitOps
```

A utility class for bitwise operations.

Static methods

Method `is_bit_set`

```
def is_bit_set(
    i: int,
    pos: int
) -> bool
```

Checks if the pos-th bit of the integer i is set.

Args ---= i : int : The integer to check.

pos : int The zero-indexed position of the bit (from LSB) to check.

Returns ---= True if the specified bit is set, otherwise False

Method set_bit

```
def set_bit(
    i: int,
    pos: int
) -> int
```

Sets the the pos-th bit of the integer i.

Args ---= i : int : The integer to modify.

pos : int The zero-indexed position of the bit (from LSB) to set.

Returns ---= The integer with the specified bit set.

Method unset_bit

```
def unset_bit(
    i: int,
    pos: int
) -> int
```

Unsets the the pos-th bit of the integer i.

Args ---= i : int : The integer to modify.

pos : int The zero-indexed position of the bit (from LSB) to unset.

Returns ---= The integer with the specified bit unset.

Class Cryptographer

```
class Cryptographer(
    salt: bytes,
    auth_key: bytes,
    encrypt: bool = True
)
```

A utility class for cryptographic functions.

Initialises a [Cryptographer](#) instance.

Args ---= salt : bytes : The raw salt, in bytes.

auth_key : bytes The authentication key, in bytes.

encrypt : bool True to make an encrypter, otherwise False.

Static methods

Method decode_salt

```
def decode_salt(
    salt: str
) -> bytes
```

Decodes the salt string to raw salt.

Args ---= `salt : str` : The Base64-encoded string of the raw salt.

Returns ---= The raw salt

Method `encode_salt`

```
def encode_salt(  
    salt: bytes  
) -> str
```

Encodes the raw salt as string.

Args ---= `salt : bytes` : The raw salt, in bytes.

Returns ---= The Base64-encoded string of the raw salt

Method `make_decrypter`

```
def make_decrypter(  
    salt: str,  
    key: str  
) -> SuperHelper.Core.Utils.crypto_ops.Cryptographer
```

Makes a Fernet decrypter for salt and key.

Args ---= `salt : str` : The Base64-encoded string of the raw salt.

`key : str` The authentication key.

Returns ---= A [Cryptographer](#) instance, which can be used to decrypt data.

Method `make_encrypter`

```
def make_encrypter(  
    salt: str,  
    key: str  
) -> SuperHelper.Core.Utils.crypto_ops.Cryptographer
```

Makes a Fernet encrypter for salt and key.

Args ---= `salt : str` : The Base64-encoded string of the raw salt.

`key : str` The authentication key.

Returns ---= A [Cryptographer](#) instance, which can be used to encrypt data.

Method `make_fernet`

```
def make_fernet(  
    key: bytes  
) -> cryptography.fernet.Fernet
```

Makes a Fernet encrypter/decrypter from the derived key.

Args ---= `key : bytes` : The derived key, in bytes.

Returns ---= A Fernet instance, which can be used to either encrypt or decrypt data.

Method `make_kdf`

```
def make_kdf(  
    salt: bytes  
) -> cryptography.hazmat.primitives.kdf.pbkdf2.PBKDF2HMAC
```

Makes a key derivation function from raw salt.

Args ---= `salt : bytes` : The raw salt, in bytes.

Returns ---= A PBKDF2HMAC instance, which can be used to derive key from the authentication key.

Method `make_salt`

```
def make_salt() -> bytes
```

Generates a cryptographically secure salt for cryptography.

Returns ---= A 16-byte raw salt

Methods

Method `decrypt`

```
def decrypt(
    self,
    encrypted_data: bytes
) -> bytes
```

Decrypts the encrypted data.

Args ---= `encrypted_data : bytes` : The encrypted data to be decrypted.

Returns ---= The decrypted data, in bytes, which is decrypted using the Fernet (created by `Cryptography.make_fernet`)

Method `encrypt`

```
def encrypt(
    self,
    raw_data: bytes
) -> bytes
```

Encrypts raw data.

Args ---= `raw_data : bytes` : The raw data to be encrypted.

Returns ---= The encrypted data, in bytes, which is encrypted using the Fernet (created by `Cryptography.make_fernet`)

Raises ---= `ValueError` : A decrypter is used to encrypt.

Method `get_salt_string`

```
def get_salt_string(
    self
) -> str
```

String-ify the raw salt.

Returns ---= The Base64-encoded string of the raw salt.

Class `FP`

```
class FP(
    value,
    names=None,
    *,
    module=None,
```

```

        qualname=None,
        type=None,
        start=1
    )

```

Contains file permission flags.

R = Read

W = Write

X = Execute

USR = User (file owner)

GRP = Group owner

OTH = Other users/groups

Ancestors (in MRO)

- [enum.Flag](#)
- [enum.Enum](#)

Class variables

Variable `R_GRP` Group readable.

Variable `R_OTH` Other readable.

Variable `R_USR` User readable.

Variable `W_GRP` Group writable.

Variable `W_OTH` Other writable.

Variable `W_USR` User writable.

Variable `X_GRP` Group executable.

Variable `X_OTH` Other executable.

Variable `X_USR` User executable.

Class `FileOps`

```
class FileOps
```

A utility class for file ownership and permissions.

Static methods

Method `check_fp`

```
def check_fp(  
    path: ~PathLike,  
    fp: SuperHelper.Core.Uutils.file_ops.FP  
) -> bool
```

Checks if the file contains the specified file permissions.

:param path: Path to the file to check :type path: PathLike :param fp: The flags of the file permissions to check. :type fp: FP :return: True if all the flags are valid, otherwise False :rtype: bool

Method `get_stat`

```
def get_stat(  
    path: ~PathLike  
) -> os.stat_result
```

Gets the stat of file pointed by the path.

This function is decorated by `@cache` to reduce the amount of syscall, since `os.stat` is an expensive function.

Args ---= path : PathLike : Path to the file to check

Returns ---= An `os.stat_result` instance containing the stat of the file.

Method `is_group_executable`

```
def is_group_executable(  
    path: ~PathLike  
) -> bool
```

Checks if the group owner of the file can execute it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is executable by its group owner, otherwise False :rtype: bool

Method `is_group_readable`

```
def is_group_readable(  
    path: ~PathLike  
) -> bool
```

Checks if the group owner of the file can read it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is readable by its group owner, otherwise False :rtype: bool

Method `is_group_writable`

```
def is_group_writable(  
    path: ~PathLike  
) -> bool
```

Checks if the group owner of the file can write to it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is writable by its group owner, otherwise False :rtype: bool

Method `is_mine`

```
def is_mine(  
    path: ~PathLike  
) -> bool
```

Checks if the file is owned by the current user.

:param path: Path to the file to check :type path: PathLike :return: True if the file is owned by the current user, otherwise False :rtype: bool

Method `is_other_executable`

```
def is_other_executable(  
    path: ~PathLike  
) -> bool
```

Checks if the other users or groups can execute the file.

:param path: Path to the file to check :type path: PathLike :return: True if the file is executable by them, otherwise False :rtype: bool

Method `is_other_readable`

```
def is_other_readable(  
    path: ~PathLike  
) -> bool
```

Checks if the other users or groups can read the file.

:param path: Path to the file to check :type path: PathLike :return: True if the file is readable by them, otherwise False :rtype: bool

Method `is_other_writable`

```
def is_other_writable(  
    path: ~PathLike  
) -> bool
```

Checks if the other users or groups can write the file.

:param path: Path to the file to check :type path: PathLike :return: True if the file is writable by them, otherwise False :rtype: bool

Method `is_owner_executable`

```
def is_owner_executable(  
    path: ~PathLike  
) -> bool
```

Checks if the owner of the file can execute it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is executable by its owner, otherwise False :rtype: bool

Method `is_owner_readable`

```
def is_owner_readable(  
    path: ~PathLike  
) -> bool
```

Checks if the owner of the file can read it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is readable by its owner, otherwise False :rtype: bool

Method `is_owner_writable`

```
def is_owner_writable(  
    path: ~PathLike  
) -> bool
```

Checks if the owner of the file can write to it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is writable by its owner, otherwise False :rtype: bool

Method `is_root`

```
def is_root(  
    path: ~PathLike  
) -> bool
```

Check if the file is owned by root.

:param path: Path to the file to check :type path: PathLike :return: True if the file is owned by root, otherwise False :rtype: bool

Method `is_user_own`

```
def is_user_own(  
    uid: int,  
    path: ~PathLike  
) -> bool
```

Checks if the file is owned by the user with uid.

:param uid: The UID of the user :type uid: int :param path: Path to the file to check :type path: PathLike :return: True if the file is owned by the uid, otherwise False :rtype: bool

Class `TypeCheck`

```
class TypeCheck
```

A utility class for type checking functions.

Static methods

Method `ensure_bool`

```
def ensure_bool(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type bool.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method `ensure_bytearray`

```
def ensure_bytearray(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type bytearray.

Args ---= `obj` : object : The object to check.

`name` : str The name of the object.

Returns ---= None

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_bytes`

```
def ensure_bytes(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type bytes.

Args ---= `obj` : object : The object to check.

`name` : str The name of the object.

Returns ---= None

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_complex`

```
def ensure_complex(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type complex.

Args ---= `obj` : object : The object to check.

`name` : str The name of the object.

Returns ---= None

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_custom`

```
def ensure_custom(  
    t: type,  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of the expected type.

Args ---= `t` : type : The expected type of the object.

`obj` : object The object to check.

`name` : str The name of the object.

Returns ---= None

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_dict`

```
def ensure_dict(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type dict.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= None

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_float`

```
def ensure_float(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type float.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= None

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_frozenset`

```
def ensure_frozenset(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type frozenset.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= None

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_function`

```
def ensure_function(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is a function.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= None

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_generator`

```
def ensure_generator(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is a generator.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_int`

```
def ensure_int(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type `int`.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_list`

```
def ensure_list(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type `list`.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_memoryview`

```
def ensure_memoryview(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type `memoryview`.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_path_like`

```
def ensure_path_like(
    obj: Ellipsis,
    name: str = None
)
```

Ensures the object can be used as a path.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_set`

```
def ensure_set(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is of type set.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_str`

```
def ensure_str(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is of type str.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_tuple`

```
def ensure_tuple(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is of type tuple.

Args ---= `obj : object` : The object to check.

`name : str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Module SuperHelper.Core.Utills.bit_ops

Classes

Class BitOps

```
class BitOps
```

A utility class for bitwise operations.

Static methods

Method is_bit_set

```
def is_bit_set(  
    i: int,  
    pos: int  
) -> bool
```

Checks if the pos-th bit of the integer i is set.

Args ---= i : int : The integer to check.

pos : int The zero-indexed position of the bit (from LSB) to check.

Returns ---= True if the specified bit is set, otherwise False

Method set_bit

```
def set_bit(  
    i: int,  
    pos: int  
) -> int
```

Sets the the pos-th bit of the integer i.

Args ---= i : int : The integer to modify.

pos : int The zero-indexed position of the bit (from LSB) to set.

Returns ---= The integer with the specified bit set.

Method unset_bit

```
def unset_bit(  
    i: int,  
    pos: int  
) -> int
```

Unsets the the pos-th bit of the integer i.

Args ---= i : int : The integer to modify.

pos : int The zero-indexed position of the bit (from LSB) to unset.

Returns ---= The integer with the specified bit unset.

Module SuperHelper.Core.Utills.crypto_ops

Classes

Class Cryptographer

```
class Cryptographer(  
    ...  
)
```



```

        salt: bytes,
        auth_key: bytes,
        encrypt: bool = True
    )

```

A utility class for cryptographic functions.

Initialises a [Cryptographer](#) instance.

Args ---= salt : bytes : The raw salt, in bytes.

auth_key : bytes The authentication key, in bytes.

encrypt : bool True to make an encrypter, otherwise False.

Static methods

Method decode_salt

```

def decode_salt(
    salt: str
) -> bytes

```

Decodes the salt string to raw salt.

Args ---= salt : str : The Base64-encoded string of the raw salt.

Returns ---= The raw salt

Method encode_salt

```

def encode_salt(
    salt: bytes
) -> str

```

Encodes the raw salt as string.

Args ---= salt : bytes : The raw salt, in bytes.

Returns ---= The Base64-encoded string of the raw salt

Method make_decrypter

```

def make_decrypter(
    salt: str,
    key: str
) -> SuperHelper.Core.Utils.crypto_ops.Cryptographer

```

Makes a Fernet decrypter for salt and key.

Args ---= salt : str : The Base64-encoded string of the raw salt.

key : str The authentication key.

Returns ---= A [Cryptographer](#) instance, which can be used to decrypt data.

Method make_encrypter

```

def make_encrypter(
    salt: str,
    key: str
) -> SuperHelper.Core.Utils.crypto_ops.Cryptographer

```

Makes a Fernet encrypter for salt and key.

Args ---= salt : str : The Base64-encoded string of the raw salt.

key : str The authentication key.

Returns ---= A [Cryptographer](#) instance, which can be used to encrypt data.

Method `make_fernet`

```
def make_fernet(  
    key: bytes  
) -> cryptography.fernet.Fernet
```

Makes a Fernet encrypter/decrypter from the derived key.

Args ---= **key** : bytes : The derived key, in bytes.

Returns ---= A Fernet instance, which can be used to either encrypt or decrypt data.

Method `make_kdf`

```
def make_kdf(  
    salt: bytes  
) -> cryptography.hazmat.primitives.kdf.pbkdf2.PBKDF2HMAC
```

Makes a key derivation function from raw salt.

Args ---= **salt** : bytes : The raw salt, in bytes.

Returns ---= A PBKDF2HMAC instance, which can be used to derive key from the authentication key.

Method `make_salt`

```
def make_salt() -> bytes
```

Generates a cryptographically secure salt for cryptography.

Returns ---= A 16-byte raw salt

Methods

Method `decrypt`

```
def decrypt(  
    self,  
    encrypted_data: bytes  
) -> bytes
```

Decrypts the encrypted data.

Args ---= **encrypted_data** : bytes : The encrypted data to be decrypted.

Returns ---= The decrypted data, in bytes, which is decrypted using the Fernet (created by `Cryptography.make_fernet`)

Method `encrypt`

```
def encrypt(  
    self,  
    raw_data: bytes  
) -> bytes
```

Encrypts raw data.

Args ---= **raw_data** : bytes : The raw data to be encrypted.

Returns ---= The encrypted data, in bytes, which is encrypted using the Fernet (created by `Cryptography.make_fernet`)

Raises ---= `ValueError` : A decrypter is used to encrypt.

Method `get_salt_string`

```
def get_salt_string(  
    self  
) -> str
```

String-ify the raw salt.

Returns ---= The Base64-encoded string of the raw salt.

Module `SuperHelper.Core.Utils.file_ops`

Classes

Class `FP`

```
class FP(  
    value,  
    names=None,  
    *,  
    module=None,  
    qualname=None,  
    type=None,  
    start=1  
)
```

Contains file permission flags.

`R` = Read

`W` = Write

`X` = Execute

`USR` = User (file owner)

`GRP` = Group owner

`OTH` = Other users/groups

Ancestors (in MRO)

- [enum.Flag](#)
- [enum.Enum](#)

Class variables

Variable `R_GRP` Group readable.

Variable `R_OTH` Other readable.

Variable `R_USR` User readable.

Variable `W_GRP` Group writable.

Variable `W_OTH` Other writable.

Variable `W_USR` User writable.

Variable `X_GRP` Group executable.

Variable `X_OTH` Other executable.

Variable `X_USR` User executable.

Class `FileOps`

```
class FileOps
```

A utility class for file ownership and permissions.

Static methods

Method `check_fp`

```
def check_fp(
    path: ~PathLike,
    fp: SuperHelper.Core.Utills.file_ops.FP
) -> bool
```

Checks if the file contains the specified file permissions.

:param path: Path to the file to check :type path: PathLike :param fp: The flags of the file permissions to check. :type fp: FP :return: True if all the flags are valid, otherwise False :rtype: bool

Method `get_stat`

```
def get_stat(
    path: ~PathLike
) -> os.stat_result
```

Gets the stat of file pointed by the path.

This function is decorated by `@cache` to reduce the amount of syscall, since `os.stat` is an expensive function.

Args ---= `path` : PathLike : Path to the file to check

Returns ---= An `os.stat_result` instance containing the stat of the file.

Method `is_group_executable`

```
def is_group_executable(
    path: ~PathLike
) -> bool
```

Checks if the group owner of the file can execute it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is executable by its group owner, otherwise False :rtype: bool

Method `is_group_readable`

```
def is_group_readable(  
    path: ~PathLike  
) -> bool
```

Checks if the group owner of the file can read it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is readable by its group owner, otherwise False :rtype: bool

Method `is_group_writable`

```
def is_group_writable(  
    path: ~PathLike  
) -> bool
```

Checks if the group owner of the file can write to it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is writable by its group owner, otherwise False :rtype: bool

Method `is_mine`

```
def is_mine(  
    path: ~PathLike  
) -> bool
```

Checks if the file is owned by the current user.

:param path: Path to the file to check :type path: PathLike :return: True if the file is owned by the current user, otherwise False :rtype: bool

Method `is_other_executable`

```
def is_other_executable(  
    path: ~PathLike  
) -> bool
```

Checks if the other users or groups can execute the file.

:param path: Path to the file to check :type path: PathLike :return: True if the file is executable by them, otherwise False :rtype: bool

Method `is_other_readable`

```
def is_other_readable(  
    path: ~PathLike  
) -> bool
```

Checks if the other users or groups can read the file.

:param path: Path to the file to check :type path: PathLike :return: True if the file is readable by them, otherwise False :rtype: bool

Method `is_other_writable`

```
def is_other_writable(  
    path: ~PathLike  
) -> bool
```

Checks if the other users or groups can write the file.

:param path: Path to the file to check :type path: PathLike :return: True if the file is writable by them, otherwise False :rtype: bool

Method `is_owner_executable`

```
def is_owner_executable(  
    path: ~PathLike  
) -> bool
```

Checks if the owner of the file can execute it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is executable by its owner, otherwise False :rtype: bool

Method `is_owner_readable`

```
def is_owner_readable(  
    path: ~PathLike  
) -> bool
```

Checks if the owner of the file can read it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is readable by its owner, otherwise False :rtype: bool

Method `is_owner_writable`

```
def is_owner_writable(  
    path: ~PathLike  
) -> bool
```

Checks if the owner of the file can write to it.

:param path: Path to the file to check :type path: PathLike :return: True if the file is writable by its owner, otherwise False :rtype: bool

Method `is_roots`

```
def is_roots(  
    path: ~PathLike  
) -> bool
```

Check if the file is owned by root.

:param path: Path to the file to check :type path: PathLike :return: True if the file is owned by root, otherwise False :rtype: bool

Method `is_user_own`

```
def is_user_own(  
    uid: int,  
    path: ~PathLike  
) -> bool
```

Checks if the file is owned by the user with uid.

:param uid: The UID of the user :type uid: int :param path: Path to the file to check :type path: PathLike :return: True if the file is owned by the uid, otherwise False :rtype: bool

Module `SuperHelper.Core.Utills.logger`

Functions

Function `setup_core_logger`

```
def setup_core_logger(  
    ...  
)
```

```

        logging_path: ~PathLike
    ) -> logging.Logger

```

Sets up the core logger.

Args ---= `logging_path` : `PathLike` : The path to the logging file.

Returns ---= A `logging.Logger` instance with name set to [SuperHelper](#).

Module `SuperHelper.Core.Uutils.type_ensure`

Classes

Class `TypeCheck`

```

class TypeCheck

```

A utility class for type checking functions.

Static methods

Method `ensure_bool`

```

def ensure_bool(
    obj: Ellipsis,
    name: str = None
) -> NoneType

```

Ensures the object is of type `bool`.

Args ---= `obj` : `object` : The object to check.

`name` : `str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_bytearray`

```

def ensure_bytearray(
    obj: Ellipsis,
    name: str = None
) -> NoneType

```

Ensures the object is of type `bytearray`.

Args ---= `obj` : `object` : The object to check.

`name` : `str` The name of the object.

Returns ---= `None`

Raises ---= `TypeError` : The type of the object is not the specified type.

Method `ensure_bytes`

```

def ensure_bytes(
    obj: Ellipsis,
    name: str = None
) -> NoneType

```

Ensures the object is of type `bytes`.

Args ---= `obj` : `object` : The object to check.

`name : str` The name of the object.

Returns `---` `None`

Raises `---` `TypeError` : The type of the object is not the specified type.

Method `ensure_complex`

```
def ensure_complex(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type `complex`.

Args `---` `obj : object` : The object to check.

`name : str` The name of the object.

Returns `---` `None`

Raises `---` `TypeError` : The type of the object is not the specified type.

Method `ensure_custom`

```
def ensure_custom(  
    t: type,  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of the expected type.

Args `---` `t : type` : The expected type of the object.

`obj : object` The object to check.

`name : str` The name of the object.

Returns `---` `None`

Raises `---` `TypeError` : The type of the object is not the specified type.

Method `ensure_dict`

```
def ensure_dict(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type `dict`.

Args `---` `obj : object` : The object to check.

`name : str` The name of the object.

Returns `---` `None`

Raises `---` `TypeError` : The type of the object is not the specified type.

Method `ensure_float`

```
def ensure_float(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```


Ensures the object is of type float.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method ensure_frozenset

```
def ensure_frozenset(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is of type frozenset.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method ensure_function

```
def ensure_function(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is a function.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method ensure_generator

```
def ensure_generator(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is a generator.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method ensure_int

```
def ensure_int(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is of type int.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method ensure_list

```
def ensure_list(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type list.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method ensure_memoryview

```
def ensure_memoryview(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type memoryview.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method ensure_path_like

```
def ensure_path_like(  
    obj: Ellipsis,  
    name: str = None  
)
```

Ensures the object can be used as a path.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method ensure_set

```
def ensure_set(  
    obj: Ellipsis,  
    name: str = None  
) -> NoneType
```

Ensures the object is of type set.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method `ensure_str`

```
def ensure_str(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is of type str.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Method `ensure_tuple`

```
def ensure_tuple(
    obj: Ellipsis,
    name: str = None
) -> NoneType
```

Ensures the object is of type tuple.

Args ---= obj : object : The object to check.

name : str The name of the object.

Returns ---= None

Raises ---= TypeError : The type of the object is not the specified type.

Module `SuperHelper.Core.Utils.type_hinting`

Variables

Variable `PathLike`

Type: `type`

PathLike objects can be used as a path. It can be of type str, bytes or os.PathLike.

Module `SuperHelper.Core.core_cli`

Functions

Function `load_config`

```
def load_config()
```

Loads application config.

Function `main_entry`

```
def main_entry() -> NoReturn
```

Function `run_startup`

```
def run_startup()
```

Function `save_config`

```
def save_config()
```

Saves application config.

Module `SuperHelper.Core.core_commands`

Functions

Function `load_core_commands`

```
def load_core_commands() -> list
```

Loads the Core CLI commands.

Returns `---` A list of a 2-tuple elements, where the first index is the `click.command` object, and the second index is the technical name of the command. For example:

```
[(add_modules, "core_add"), ...]
```

The first index can be added to a `click.group`, i.e the cli function.

Module `SuperHelper.Core.core_loader`

Functions

Function `load_added_modules`

```
def load_added_modules(  
    config: dict  
) -> list
```

Loads all added modules.

Returns `---` A list of a 2-tuple elements, where the first index is the `click.command` object, and the second index is the technical name of the command. For example:

```
[(main, "main"), ...]
```

The first index can be added to a `click.group`, i.e the cli function.

Module `SuperHelper.Modules`

Sub-modules

- [SuperHelper.Modules.FocusEnabler](#)
- [SuperHelper.Modules.Stenographer](#)

Module `SuperHelper.Modules.FocusEnabler`

Module `SuperHelper.Modules.Stenographer`

Module `SuperHelper.Tests`

Sub-modules

- [SuperHelper.Tests.test_base](#)
- [SuperHelper.Tests.test_config](#)
- [SuperHelper.Tests.test_core](#)
- [SuperHelper.Tests.test_core_command](#)
- [SuperHelper.Tests.test_module_FocusEnabler](#)
- [SuperHelper.Tests.test_module_Stenographer](#)
- [SuperHelper.Tests.test_utils](#)

Functions

Function `run`

```
def run(  
    args: str = None  
) -> click.testing.Result
```

Function `setup_and_cleanup`

```
def setup_and_cleanup()
```

Module `SuperHelper.Tests.test_base`

Functions

Function `run`

```
def run(  
    args: str = None  
) -> click.testing.Result
```

Function `setup_and_cleanup`

```
def setup_and_cleanup()
```

Module `SuperHelper.Tests.test_config`

Classes

Class `TestConfig`

```
class TestConfig
```

Static methods

Method `test_core_and_module`

```
def test_core_and_module()
```

Method `test_core_and_no_module`
`def test_core_and_no_module()`

Method `test_from_dict`
`def test_from_dict()`

Method `test_no_core_and_module_a`
`def test_no_core_and_module_a()`

Method `test_no_core_and_module_b`
`def test_no_core_and_module_b()`

Module `SuperHelper.Tests.test_core`

Functions

Function `test_main_entry`
`def test_main_entry()`

Module `SuperHelper.Tests.test_core_command`

Classes

Class `TestCore`
`class TestCore`

Static methods

Method `test_add_invalid`
`def test_add_invalid()`

Method `test_add_multiple`
`def test_add_multiple()`

Method `test_add_same`
`def test_add_same()`

Method `test_add_single`
`def test_add_single()`

Method `test_add_single_again`
`def test_add_single_again()`

Method `test_list_all`
`def test_list_all()`

Method test_list_multiple_negative
def test_list_multiple_negative()

Method test_list_multiple_positive
def test_list_multiple_positive()

Method test_list_negative
def test_list_negative()

Method test_list_single_negative
def test_list_single_negative()

Method test_list_single_positive
def test_list_single_positive()

Method test_remove_invalid
def test_remove_invalid()

Method test_remove_multiple
def test_remove_multiple()

Method test_remove_same
def test_remove_same()

Method test_remove_single
def test_remove_single()

Class TestOtherUtils
class TestOtherUtils

Static methods

Method test_load_installed_modules_a
def test_load_installed_modules_a()

Module SuperHelper.Tests.test_module_FocusEnabler

Classes

Class TestFocusEnabler
class TestFocusEnabler

Static methods

Method setup

```
def setup()
```

Method test_add_invalid

```
def test_add_invalid()
```

Method test_add_multiple

```
def test_add_multiple()
```

Method test_add_same

```
def test_add_same()
```

Method test_add_single

```
def test_add_single()
```

Method test_add_single_again

```
def test_add_single_again()
```

Method test_help

```
def test_help()
```

Method test_list_multiple_negative

```
def test_list_multiple_negative()
```

Method test_list_multiple_positive

```
def test_list_multiple_positive()
```

Method test_list_single_negative

```
def test_list_single_negative()
```

Method test_list_single_positive

```
def test_list_single_positive()
```

Method test_remove_invalid

```
def test_remove_invalid()
```

Method test_remove_multiple

```
def test_remove_multiple()
```

Method test_remove_same

```
def test_remove_same()
```

Method test_remove_single

```
def test_remove_single()
```


Method test_validate_setup

```
def test_validate_setup(  
    setup  
)
```

Module SuperHelper.Tests.test_module_Stenographer

Classes

Class TestStenographer

```
class TestStenographer
```

Static methods

Method setup

```
def setup()
```

Method test_help

```
def test_help()
```

Method test_validate_setup

```
def test_validate_setup(  
    setup  
)
```

Module SuperHelper.Tests.test_utils

Classes

Class TestBitOps

```
class TestBitOps
```

Static methods

Method a

```
def a()
```

Method test_is_bit_set

```
def test_is_bit_set(  
    a  
)
```

Method test_set_bit

```
def test_set_bit(  
    a  
)
```

Method test_unset_bit

```
def test_unset_bit(  
    a  
)
```

Class TestCryptographer

```
class TestCryptographer
```

Static methods

Method binary_salt

```
def binary_salt()
```

Method data

```
def data()
```

Method decrypted_data

```
def decrypted_data(  
    decrypter,  
    encrypted_data  
)
```

Method decrypter

```
def decrypter(  
    string_salt,  
    true_key  
)
```

Method encrypted_data

```
def encrypted_data(  
    encrypter,  
    data  
)
```

Method encrypter

```
def encrypter(  
    string_salt,  
    true_key  
)
```

Method false_key

```
def false_key()
```

Method string_salt

```
def string_salt(  
    binary_salt  
)
```

Method test_decrypt_with_encrypter

```
def test_decrypt_with_encrypter(  
    encrypter,  
    encrypted_data  
)
```

Method test_decrypted_data

```
def test_decrypted_data(  
    decrypted_data  
)
```

Method test_encode_and_decode_salt

```
def test_encode_and_decode_salt(  
    string_salt,  
    binary_salt  
)
```

Method test_encrypt_with_decrypter

```
def test_encrypt_with_decrypter(  
    decrypter,  
    data  
)
```

Method test_encrypted_data

```
def test_encrypted_data(  
    encrypted_data  
)
```

Method test_make_decrypter

```
def test_make_decrypter(  
    decrypter  
)
```

Method test_make_encrypter

```
def test_make_encrypter(  
    encrypter  
)
```

Method test_make_kdf

```
def test_make_kdf(  
    binary_salt,  
    true_key,  
    false_key  
)
```

Method test_salt_in_class

```
def test_salt_in_class(  
    encrypter,  
    decrypter,  
    string_salt
```

```

    )

Method test_salt_length
    def test_salt_length(
        binary_salt
    )

Method true_key
    def true_key()

Class TestFileOps
    class TestFileOps

Static methods

Method test_check_fp_grp
    def test_check_fp_grp()

Method test_check_fp_oth
    def test_check_fp_oth()

Method test_check_fp_usr
    def test_check_fp_usr()

Method test_is_mine_negative
    def test_is_mine_negative()

Method test_is_mine_positive
    def test_is_mine_positive()

Method test_is_root_negative
    def test_is_root_negative()

Method test_is_root_positive
    def test_is_root_positive()

Class TestTypeCheck
    class TestTypeCheck

Static methods

Method test_ensure_bool
    def test_ensure_bool()

```

```
Method test_ensure_bytearray
    def test_ensure_bytearray()

Method test_ensure_bytes
    def test_ensure_bytes()

Method test_ensure_complex
    def test_ensure_complex()

Method test_ensure_custom
    def test_ensure_custom()

Method test_ensure_dict
    def test_ensure_dict()

Method test_ensure_float
    def test_ensure_float()

Method test_ensure_frozenset
    def test_ensure_frozenset()

Method test_ensure_function
    def test_ensure_function()

Method test_ensure_generator
    def test_ensure_generator()

Method test_ensure_int
    def test_ensure_int()

Method test_ensure_list
    def test_ensure_list()

Method test_ensure_memoryview
    def test_ensure_memoryview()

Method test_ensure_path_like
    def test_ensure_path_like()

Method test_ensure_set
    def test_ensure_set()

Method test_ensure_str
    def test_ensure_str()
```

Method `test_ensure_tuple`

```
def test_ensure_tuple()
```

Method `test_ensure_with_name`

```
def test_ensure_with_name()
```

Generated by pdoc 0.9.2 (<https://pdoc3.github.io>).