

Documentation for Financial Transactions HTML Page
Jason N.
April 26, 2020

Contents

1	Foreword	1
2	HTML	1
2.1	Preamble and head	1
2.2	Inputs	1
2.2.1	Common attributes	2
2.2.2	Labels	2
2.2.3	Date	2
2.2.4	Text	2
2.2.5	List	3
2.2.6	Buttons	3
2.3	Table	4
2.3.1	thead	4
2.3.2	tbody	5
3	Javascript	6
3.1	getData()	6
3.2	validate()	7
3.3	generateId()	7
3.4	calculateCostBasis()	8
3.5	addTransaction()	8
3.6	deleteRow()	9
3.7	editRow()	9
3.8	saveChanges()	9
3.9	discardChanges()	10
3.10	sortTable()	10
4	CSS	11
4.1	Vertical Scrolling Table	11
4.2	Horizontal Scrolling on Overflow	11
4.3	Miscellaneous	11
4.3.1	Sort buttons	11
4.3.2	Editing highlight	12
4.3.3	Table borders	12
A	HTML Source Code	13
B	Javascript Source Code	17
C	CSS Source Code	22

1 Foreword

Some of the code samples in this document were copied by hand. If there are any discrepancies between code in this document and in the source files, refer to the source files.

This does not apply to the appendix. Code in the appendix was generated directly from the source files.

2 HTML

2.1 Preamble and head

This line declares that the document is an HTML5 document.

```
1 <!DOCTYPE html>
```

`<head>` tags are used to contain meta information about the document.

```
2 <head>
3   <meta charset = "UTF-8"/>
4   <link rel="stylesheet" type="text/css" href="./style.css"/>
5   <script src="./script.js"></script>
6 </head>
```

Within the `head` element:

- The first line defines the character set of the document.
- The second line defines the source of an external CSS document.
- The third line defines the source of an external Javascript document.

2.2 Inputs

The input section of this page is contained within `<article>` tags for the purpose of organisation. This can be used to facilitate styling this part of the page with CSS if desired.

```
10 <article id="inputFields">
```

The `article` element has been assigned a unique id for the purpose of styling. Specifically, this id is used to define padding and overflow. This is described in further detail in section 4.2 of this document.

All input fields and buttons are contained within `<form>` tags. Although this is not strictly necessary for the purpose of this project, it is useful for organising data and specifying the fields from which data should be submitted.

```
11 <form onsubmit="return false" autocomplete="off">
```

The attribute `onsubmit` is used to define a Javascript function to be executed when pressed. The form expects that `true` is returned when data is successfully submitted. If so, the default behaviour is to clear

the fields and enter the data in the browser URL bar as arguments. To prevent this behaviour, `onsubmit` is set to `return false`.

The attribute `autocomplete` can be used to specify whether user input from a previous session should be used to populate input fields. This attribute also determines whether or not suggestions are displayed when the user enters data. In this case, `autocomplete` has been set to `off` to prevent these actions from occurring. This does not affect the functionality of the program.

The buttons and input fields within the `form` element are contained within `<section>` tags for organisation. This is primarily done to allow elements to be positioned properly by the CSS file.

2.2.1 Common attributes

All `input` elements in this `form` have been assigned a `name` attribute. The `name` attribute is not strictly relevant in this case, but is often used to identify the data when submitting to a database.

All `input` elements have the `required` attribute. Normally this prevents a `form` from being submitted unless all `required` fields contain data. This does not apply to our case as we have disabled the built-in submit function. However, it does still outline missing fields in red.

2.2.2 Labels

Each of the inputs are given a label to specify to a user the type of information which should be entered in the given field. This is done with the `input` element.

```
12 <label for="date">Date:</label><br/>
```

The `for` attribute is used to specify an element which corresponds to this label. This is done by setting the attribute to the id of the other element. Labels allow a user to select an input field by clicking the label rather than the field itself. Labels are also used to facilitate the use of assistive technologies.

2.2.3 Date

The date of a transaction is specified through the use of an `input` element with a `type` attribute of `date`. This can be used to effectively restrict the input to a valid date format and provides an intuitive method for inputting data.

```
11 <section>
12   <label for="date">Date:</label><br/>
13   <input id="date" name="date" type="date" required/>
14 </section>
```

This type of input field is also useful for interpreting dates in Javascript, as it provides methods which return the date in various formats to facilitate displaying and comparing dates.

2.2.4 Text

`input` elements with a `type` attribute of `text` can be used to retrieve a string from a user. This is also the field used for numbers, as these can be easily verified and converted in Javascript.

```

16 <section>
17   <label for="account">Account Number:</label><br/>
18   <input id="account" name="account" type="text" placeholder="Account
    ↳ Number" required/>
19 </section>

```

The advantage of taking numbers from an input field is that it allows for characters such as \$ to be included. In the case of this project, users are able to submit Dollar Amounts as purely numeric values, or in a currency format. Currently, the program only accepts dollars as a currency, however, it is possible to allow and store any number of currencies. These characters, of course, have to be filtered out before the number is interpreted and re-inserted before displaying the value.

2.2.5 List

Dropdown lists are created using `<select>` tags containing `option` elements. Each `option` element represents a possible value, the first element is selected by default.

```

21 <section>
22   <label for="type">Transaction Type:</label><br/>
23   <select id="type" name="type">
24     <option value=""></option>
25     <option value="BUY">BUY</option>
26     <option value="SELL">SELL</option>
27     <option value="DIVIDEND">DIVIDEND</option>
28     <option value="INTEREST">INTEREST</option>
29     <option value="WITHDRAW">WITHDRAW</option>
30     <option value="DEPOSIT">DEPOSIT</option>
31   </select>
32 </section>

```

The `innerHTML` of an `option` element is the text that will be displayed to the user. The `value` attribute of the element is the value that will be read by Javascript. For this project, the `value` and `innerHTML` were made to be identical so that the text in the table would be the same as the text the user had seen in the list.

2.2.6 Buttons

`button` elements are clickable elements which can execute Javascript code specified by an `onclick` attribute. Text within the `innerHTML` of the `button` will be displayed as text within the button, which is useful for communicating the purpose of the button.

```

49 <section>
50   <button id="add" type="submit" onclick="addTransactionButton();">Add
    ↳ Transaction</button>
51   <button id="save" type="submit" hidden="true" onclick="saveChanges()
    ↳ ;">Save</button>
52   <button id="discard" type="button" hidden="true" onclick="
    ↳ discardChanges();">Discard</button>
53 </section>

```

In this case, three buttons are present, each set to execute a different Javascript function when clicked.

Two of the three buttons have a **type** attribute of **submit**. This causes each function to trigger the **submit** event along with the Javascript function. However, for this project, this event has been disabled by the **form onsubmit="return false"** attribute. Thus, the only difference is that this causes missing fields to be outlined in red when the button is pressed.

The last button is of **type button**. This element functions exactly the same, except it does not trigger the **submit** event. For this project, this means that missing fields will not be highlighted red, as this is not necessary for the 'Discard Changes' button.

Two of the three buttons also have the **hidden="true"** attribute. This causes the page to render as if these elements did not exist, as these elements are only relevant when editing a row. All three buttons are given unique ids so that **hidden** attributes can be added or removed as needed.

2.3 Table

2.3.1 **thead**

The header of the table is enclosed in **<thead>** tags. This element includes the first row of the table, denoted by **<tr>** tags, which contains headers for each column.

Every cell in the header is denoted by **<td>** tags. These cells differ from normal cells, such as those in the body of the table, in how they format their contents. Using this element for header cells makes them stand out slightly as well as making it easier to differentiate when styling with CSS.

```
61 <th>
62     <section>
63         Transaction ID
64     </section>
65     <section class="sort">
66         <button type="button" onclick="sortTable(0, true)">^</button>
67         <button type="button" onclick="sortTable(0, false)">V</button>
68     </section>
69 </th>
```

The first 8 header cells are split into two separate **section** elements. This was done to allow for the proper positioning of the header text and the sort buttons. For this reason, the latter **section** element is given the class **sort** to differentiate between the two.

Each of the first 8 header cells contain two buttons for sorting. All sorting buttons call the same function **sort(column, ascending)**, however, they pass different arguments to this function. The first argument is the column number, starting from 0, which allows the Javascript function to determine which column to use when comparing rows. The second argument defines whether data should be sorted in ascending or descending order.

The last header cell contains nothing but text. This column is used to contain the delete and edit buttons created for each row.

```
133 <th>Actions</th>
```

2.3.2 tbody

The table body is enclosed in `<tbody>` tags. This element is meant to be the main container of data in a table.

```
136 <tbody id="tableBody">
```

The table body is important for this project as it is the parent element of all data which will be manipulated. For this reason, it has been given a unique id to reference in Javascript. This was not strictly necessary, as it is also possible to reference this element by its tag name, being the only `tbody` element. Nevertheless, I consider this to be good practice as it is clear which element is being referred to in Javascript and allows for other tables to be added in the future if necessary without breaking the current functionality.

3 Javascript

3.1 getData()

This function is used to retrieve and format data from the input fields.

```
1 function getData() {
2     var date = document.getElementById("date");
3     var account = document.getElementById("account").value;
4     var type = document.getElementById("type").value;
5     var security = document.getElementById("security").value;
6     var amount = document.getElementById("amount").value;
7     var dAmount = document.getElementById("dAmount").value;
8
9     amount = Number(amount);
10
11     if(dAmount[0] == '$') {
12         dAmount = dAmount.substr(1);
13     }
14     dAmount = Number(dAmount);
15
16     if(validate(date, account, type, security, amount, dAmount)) {
17         var costBasis = calculateCostBasis(amount, dAmount);
18         date = date.value;
19         dAmount = '$' + dAmount.toFixed(2);
20
21         return [ date, account, type, security, amount, dAmount, costBasis
22                 ↪ ];
23     }
24     else return false;
25 }
```

The function checks whether the data is valid by calling the `validate()` function. If so, data is formatted and sent to the function which called `getData()`. Currently, the caller is either `addTransactionButton()` or `saveChanges()`.

The function first stores the `date` element and the raw values of the other input fields. `date` is treated differently as the element includes useful methods for comparing the date in different formats.

```
2 var date = document.getElementById("date");
3 var account = document.getElementById("account").value;
4 var type = document.getElementById("type").value;
5 var security = document.getElementById("security").value;
6 var amount = document.getElementById("amount").value;
7 var dAmount = document.getElementById("dAmount").value;
```

Next, some of the data is processed. `amount` is converted from a string, as it originated from a text field, to a number. This is done with the built-in `Number()` function, which takes a string as an argument and returns it as a numeric value when possible. If the argument cannot be converted, the function returns `NaN` or 'Not a Number'. We are not concerned with validating that the value can be converted at this stage, as we can simply check if the value is `NaN` during the validation stage, therefore it is safe to convert to a number here.

```
9 amount = Number(amount);
```


A similar conversion is performed on the `dAmount` value. However, before this occurs, we check whether the first character in the string is a dollar sign. If so, we remove the dollar sign by taking a substring of `dAmount` which includes everything including and after the second character. This effectively removes the dollar sign from the string, allowing it to be converted to a numeric value.

```
9  if(dAmount[0] == '$') {
10      dAmount = dAmount.substr(1);
11  }
12  dAmount = Number(dAmount);
```

The function then calls `validate` and passes all the stored variables as arguments to determine whether all the data is valid. If not, the function will return `false` and exit, preventing subsequent steps from occurring.

```
16  if(validate(date, account, type, security, amount, dAmount)) {
17      var costBasis = calculateCostBasis(amount, dAmount);
18      date = date.value;
19      dAmount = '$' + dAmount.toFixed(2);
20
21      return [ date, account, type, security, amount, dAmount, costBasis ];
22  }
23  else return false;
```

If all data is valid, the function calculates and stores the `costBasis` by calling `calculateCostBasis()` and passing the necessary values. The function also formats the date and dollar amount in the correct formats to be exported to the table. Lastly, the function returns a list including all the data to the caller.

3.2 validate()

```
26  function validate(date, account, type, security, amount, dAmount) {
27      if(!validateDate(date)) return false;
28      if(!validateAccount(account)) return false;
29      if(!validateType(type)) return false;
30      if(!validateSecurity(security)) return false;
31      if(!validateAmount(amount)) return false;
32      if(!validateDAmount(dAmount)) return false;
33
34      return true;
35  }
```

3.3 generateId()

```
109 function generateId() {
110     var id = '';
111     var idLength = 6;
112
113     var characters = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ0123456789';
114     var charactersLength = characters.length;
115
116     var unique = false;
117
118     while(!unique) {
```

```

119     for(var i = 0; i < idLength; i++) {
120         id += characters.charAt(Math.floor(Math.random() *
           ↪ charactersLength));
121     }
122
123     unique = true;
124     for(var i = 0; i < document.getElementsByClassName('idCell').
           ↪ length; i++) {
125         if(document.getElementsByClassName('idCell')[i].innerText ==
           ↪ id) {
126             unique = false;
127             break;
128         }
129     }
130 }
131 return id;
132 }

```

3.4 calculateCostBasis()

```

134 function calculateCostBasis(amount, dAmount) {
135     costBasis = '$' + (dAmount / amount).toFixed(2);
136     return costBasis;
137 }

```

3.5 addTransaction()

```

139 function addTransaction(id, date, account, type, security, amount, dAmount
           ↪ , costBasis) {
140     var tableBody = document.getElementById('tableBody');
141     var newRow = tableBody.insertRow(0);
142     newRow.classList += "bodyRow";
143
144     var actionsContent = "<button type='button' onclick='editRow(this)'"
           ↪ "Edit</button> <button type='button' onclick='deleteRow(this)'"
           ↪ "Delete</button>";
145     var rowContents = [id, date, account, type, security, amount, dAmount,
           ↪ costBasis, actionsContent];
146
147     for(var i = 0; i < rowContents.length; i++) {
148         var newCell = newRow.insertCell(i);
149         newCell.innerHTML = rowContents[i];
150         if(i == 0) {
151             newCell.classList += "idCell";
152         }
153     }
154 }

```

3.6 deleteRow()

```
173 function deleteRow(button) {
174     var row = button.parentElement.parentElement;
175     document.getElementById("tableBody").removeChild(row);
176
177     if(document.getElementsByClassName('editing').length == 0) {
178         document.getElementById('add').removeAttribute('hidden');
179         document.getElementById('save').setAttribute('hidden', true);
180         document.getElementById('discard').setAttribute('hidden', true);
181     }
182 }
```

3.7 editRow()

```
184 function editRow(button) {
185     if(document.getElementsByClassName('editing').length > 0)
186         document.getElementsByClassName('editing')[0].classList = "bodyRow
187         ↪ ";
188
189     var row = button.parentElement.parentElement;
190     var rowContent = row.getElementsByTagName('td');
191     row.classList = "bodyRow editing";
192
193     document.getElementById('date').value = rowContent[1].innerText;
194     document.getElementById('account').value = rowContent[2].innerText;
195     document.getElementById('type').value = rowContent[3].innerText;
196     document.getElementById('security').value = rowContent[4].innerText;
197     document.getElementById('amount').value = rowContent[5].innerText;
198     document.getElementById('dAmount').value = rowContent[6].innerText;
199
200     document.getElementById('add').setAttribute('hidden', true);
201     document.getElementById('save').removeAttribute('hidden');
202     document.getElementById('discard').removeAttribute('hidden');
203 }
```

3.8 saveChanges()

```
204 function saveChanges() {
205     data = getData();
206     if(data) {
207         rowToEdit = document.getElementsByClassName('editing')[0];
208         cellsToEdit = rowToEdit.getElementsByTagName('td');
209
210         for(var i = 0; i < data.length; i++) {
211             cellsToEdit[i + 1].innerHTML = data[i];
212         }
213         rowToEdit.classList = "bodyRow";
214     }
215 }
```

```

216     document.getElementById('add').removeAttribute('hidden');
217     document.getElementById('save').setAttribute('hidden', true);
218     document.getElementById('discard').setAttribute('hidden', true);
219 }

```

3.9 discardChanges()

```

221 function discardChanges() {
222     document.getElementsByClassName('editing')[0].classList = "bodyRow";
223
224     document.getElementById('add').removeAttribute('hidden');
225     document.getElementById('save').setAttribute('hidden', true);
226     document.getElementById('discard').setAttribute('hidden', true);
227 }

```

3.10 sortTable()

```

229 function sortTable(column, ascending) {
230     var tableBody = document.getElementById('tableBody');
231     var rows = document.getElementsByClassName('bodyRow');
232
233     var sorting = true;
234     while(sorting) {
235         sorting = false;
236         for(var i = 0; i < (rows.length - 1); i++) {
237             rowA = rows[i].getElementsByTagName('td')[column];
238             rowB = rows[i + 1].getElementsByTagName('td')[column];
239
240             var swap = false;
241
242             if(ascending && rowA.innerHTML.toLowerCase() > rowB.innerHTML.
                ↪ toLowerCase()) swap = true;
243             else if(!ascending && rowA.innerHTML.toLowerCase() < rowB.
                ↪ innerHTML.toLowerCase()) swap = true;
244
245             if(swap) {
246                 sorting = true;
247                 rows[i].parentNode.insertBefore(rows[i + 1], rows[i]);
248             }
249         }
250     }
251 }

```

4 CSS

4.1 Vertical Scrolling Table

```
29 #table {  
30     max-height: 80vh;  
31     overflow: auto;  
32 }
```

```
39 th {  
40     min-width: 200px;  
41     width: 10%;  
42     position: sticky;  
43     background: white;  
44     top: 0;  
45 }
```

4.2 Horizontal Scrolling on Overflow

```
5 #inputFields {  
6     padding: 10px 0;  
7     overflow-x: auto;  
8 }  
9  
10 form {  
11     min-width: 1900px;  
12 }
```

4.3 Miscellaneous

4.3.1 Sort buttons

```
47 th > section {  
48     width: 80%;  
49     display: inline-block;  
50     padding: 0;  
51     margin: 0;  
52 }  
53  
54 .sort {  
55     width: 10%;  
56 }  
57  
58 .sort > button {  
59     padding: 0;  
60     border: 0;  
61     display: block;  
62     width: 100%;  
63 }
```

4.3.2 Editing highlight

```
65 .editing {  
66     background-color: yellow;  
67 }
```

4.3.3 Table borders

```
69 #table,  
70 table,  
71 td,  
72 th {  
73     box-shadow: 1px 1px black, inset 1px 1px black;  
74 }
```

A HTML Source Code

```
1 <!DOCTYPE html>
2 <html>
3   <head>
4     <meta charset = "UTF-8"/>
5     <link rel="stylesheet" type="text/css" href="./style.css"/>
6     <script src="./script.js"></script>
7   </head>
8   <body>
9     <article id="inputFields">
10       <form onsubmit="return false" autocomplete="off">
11         <section>
12           <label for="date">Date:</label><br/>
13           <input id="date" name="date" type="date" required/>
14         </section>
15
16         <section>
17           <label for="account">Account Number:</label><br/>
18           <input id="account" name="account" type="text"
19             ↪ placeholder="Account Number" required/>
20         </section>
21
22         <section>
23           <label for="type">Transaction Type:</label><br/>
24           <select id="type" name="type">
25             <option value=""></option>
26             <option value="BUY">BUY</option>
27             <option value="SELL">SELL</option>
28             <option value="DIVIDEND">DIVIDEND</option>
29             <option value="INTEREST">INTEREST</option>
30             <option value="WITHDRAW">WITHDRAW</option>
31             <option value="DEPOSIT">DEPOSIT</option>
32           </select>
33         </section>
34
35         <section>
36           <label for="security">Security:</label><br/>
37           <input id="security" name="security" type="text"
38             ↪ placeholder="Security" required/>
39         </section>
40
41         <section>
42           <label for="amount">Amount:</label><br/>
43           <input id="amount" name="amount" type="text"
44             ↪ placeholder="Unit Amount" required/>
45         </section>
46
47         <section>
48           <label for="dAmount">$ Amount:</label><br/>
49           <input id="dAmount" name="dAmount" type="text"
50             ↪ placeholder="$ Amount" required/>
51         </section>
52       </form>
53     </article>
54   </body>
55 </html>
```

```

49         <section>
50             <button id="add" type="submit" onclick="
                    ↪ addTransactionButton();">Add Transaction</button>
                    ↪ >
51             <button id="save" type="submit" hidden="true" onclick
                    ↪ ="saveChanges();">Save</button>
52             <button id="discard" type="button" hidden="true"
                    ↪ onclick="discardChanges();">Discard</button>
53         </section>
54     </form>
55 </article>
56
57 <article id="table">
58     <table>
59         <thead>
60             <tr>
61                 <th>
62                     <section>
63                         Transaction ID
64                     </section>
65                     <section class="sort">
66                         <button type="button" onclick="sortTable
                                ↪ (0, true)">^</button>
67                         <button type="button" onclick="sortTable
                                ↪ (0, false)">v</button>
68                     </section>
69                 </th>
70                 <th>
71                     <section>
72                         Date
73                     </section>
74                     <section class="sort">
75                         <button type="button" onclick="sortTable
                                ↪ (1, true)">^</button>
76                         <button type="button" onclick="sortTable
                                ↪ (1, false)">v</button>
77                     </section>
78                 </th>
79                 <th>
80                     <section>
81                         Account Number
82                     </section>
83                     <section class="sort">
84                         <button type="button" onclick="sortTable
                                ↪ (2, true)">^</button>
85                         <button type="button" onclick="sortTable
                                ↪ (2, false)">v</button>
86                     </section>
87                 </th>
88                 <th>
89                     <section>
90                         Transaction Type
91                     </section>
92                     <section class="sort">

```



```

93         <button type="button" onclick="sortTable
94             ↪ (3, true)">^</button>
95         <button type="button" onclick="sortTable
96             ↪ (3, false)">v</button>
97     </section>
98 </th>
99 <th>
100     <section>
101         Security
102     </section>
103     <section class="sort">
104         <button type="button" onclick="sortTable
105             ↪ (4, true)">^</button>
106         <button type="button" onclick="sortTable
107             ↪ (4, false)">v</button>
108     </section>
109 </th>
110 <th>
111     <section>
112         Amount
113     </section>
114     <section class="sort">
115         <button type="button" onclick="sortTable
116             ↪ (5, true)">^</button>
117         <button type="button" onclick="sortTable
118             ↪ (5, false)">v</button>
119     </section>
120 </th>
121 <th>
122     <section>
123         $ Amount
124     </section>
125     <section class="sort">
126         <button type="button" onclick="sortTable
127             ↪ (6, true)">^</button>
128         <button type="button" onclick="sortTable
129             ↪ (6, false)">v</button>
130     </section>
131 </th>
132 <th>
133     <section>
134         Cost Basis
135     </section>
136     <section class="sort">
137         <button type="button" onclick="sortTable
138             ↪ (7, true)">^</button>
139         <button type="button" onclick="sortTable
140             ↪ (7, false)">v</button>
141     </section>
142 </th>
143 <th>Actions</th>
144 </tr>
145 </thead>
146 <tbody id="tableBody">

```

```
137         </tbody>
138     </table>
139 </article>
140 </body>
141 </html>
```

B Javascript Source Code

```
1 function getData() {
2     var date = document.getElementById("date");
3     var account = document.getElementById("account").value;
4     var type = document.getElementById("type").value;
5     var security = document.getElementById("security").value;
6     var amount = document.getElementById("amount").value;
7     var dAmount = document.getElementById("dAmount").value;
8
9     amount = Number(amount);
10
11     if(dAmount[0] == '$') {
12         dAmount = dAmount.substr(1);
13     }
14     dAmount = Number(dAmount);
15
16     if(validate(date, account, type, security, amount, dAmount)) {
17         var costBasis = calculateCostBasis(amount, dAmount);
18         date = date.value;
19         dAmount = '$' + dAmount.toFixed(2);
20
21         return [ date, account, type, security, amount, dAmount, costBasis
22                 ↪ ];
23     }
24     else return false;
25 }
26
27 function validate(date, account, type, security, amount, dAmount) {
28     if(!validateDate(date)) return false;
29     if(!validateAccount(account)) return false;
30     if(!validateType(type)) return false;
31     if(!validateSecurity(security)) return false;
32     if(!validateAmount(amount)) return false;
33     if(!validateDAmount(dAmount)) return false;
34
35     return true;
36 }
37
38 function validateDate(date) {
39     realDate = new Date();
40     inputDate = date.valueAsNumber;
41
42     if(isNaN(inputDate)) {
43         alert('Error: No date specified');
44         return false;
45     }
46
47     if(realDate.valueOf() < inputDate) {
48         alert('Error: Date is in the future');
49         return false;
50     }
51
52     return true;
```

```

52 }
53
54 function validateAccount(account) {
55     if(account == '') {
56         alert('Error: Missing Account Number');
57         return false;
58     }
59
60     return true;
61 }
62
63 function validateType(type) {
64     if(type == '') {
65         alert('Error: Missing Transaction Type');
66         return false;
67     }
68
69     return true;
70 }
71
72 function validateSecurity(security) {
73     if(security == '') {
74         alert('Error: Missing Security');
75         return false;
76     }
77
78     return true;
79 }
80
81 function validateAmount(amount) {
82     if(amount == '') {
83         alert('Error: Missing Amount');
84         return false;
85     }
86
87     if(isNaN(amount)) {
88         alert('Error: Invalid Amount');
89         return false;
90     }
91
92     return true;
93 }
94
95 function validateDAmount(dAmount) {
96     if(dAmount == '') {
97         alert('Error: Missing $ Amount');
98         return false;
99     }
100
101     if(isNaN(dAmount)) {
102         alert('Error: Invalid $ Amount');
103         return false;
104     }
105

```

```

106     return true;
107 }
108
109 function generateId() {
110     var id = '';
111     var idLength = 6;
112
113     var characters = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ0123456789';
114     var charactersLength = characters.length;
115
116     var unique = false;
117
118     while(!unique) {
119         for(var i = 0; i < idLength; i++) {
120             id += characters.charAt(Math.floor(Math.random() *
121                 ↪ charactersLength));
122         }
123
124         unique = true;
125         for(var i = 0; i < document.getElementsByClassName('idCell').
126             ↪ length; i++) {
127             if(document.getElementsByClassName('idCell')[i].innerText ==
128                 ↪ id) {
129                 unique = false;
130                 break;
131             }
132         }
133     }
134     return id;
135 }
136
137 function calculateCostBasis(amount, dAmount) {
138     costBasis = '$' + (dAmount / amount).toFixed(2);
139     return costBasis;
140 }
141
142 function addTransaction(id, date, account, type, security, amount, dAmount
143     ↪ , costBasis) {
144     var tableBody = document.getElementById('tableBody');
145     var newRow = tableBody.insertRow(0);
146     newRow.classList += "bodyRow";
147
148     var actionsContent = "<button type='button' onclick='editRow(this)'"
149     ↪ "Edit</button> <button type='button' onclick='deleteRow(this)'"
150     ↪ "Delete</button>";
151     var rowContents = [id, date, account, type, security, amount, dAmount,
152     ↪ costBasis, actionsContent];
153
154     for(var i = 0; i < rowContents.length; i++) {
155         var newCell = newRow.insertCell(i);
156         newCell.innerHTML = rowContents[i];
157         if(i == 0) {
158             newCell.classList += "idCell";
159         }
160     }
161 }

```

```

153     }
154 }
155
156 function addTransactionButton() {
157     var data = getData();
158     if(data) {
159         var date = data[0];
160         var account = data[1];
161         var type = data[2];
162         var security = data[3];
163         var amount = data[4];
164         var dAmount = data[5];
165         var costBasis = data[6];
166
167         var id = generateId();
168
169         addTransaction(id, date, account, type, security, amount, dAmount,
170             ↪ costBasis);
171     }
172 }
173
174 function deleteRow(button) {
175     var row = button.parentElement.parentElement;
176     document.getElementById("tableBody").removeChild(row);
177
178     if(document.getElementsByClassName('editing').length == 0) {
179         document.getElementById('add').removeAttribute('hidden');
180         document.getElementById('save').setAttribute('hidden', true);
181         document.getElementById('discard').setAttribute('hidden', true);
182     }
183 }
184
185 function editRow(button) {
186     if(document.getElementsByClassName('editing').length > 0)
187         document.getElementsByClassName('editing')[0].classList = "bodyRow
188             ↪ ";
189
190     var row = button.parentElement.parentElement;
191     var rowContent = row.getElementsByTagName('td');
192     row.classList = "bodyRow editing";
193
194     document.getElementById('date').value = rowContent[1].innerText;
195     document.getElementById('account').value = rowContent[2].innerText;
196     document.getElementById('type').value = rowContent[3].innerText;
197     document.getElementById('security').value = rowContent[4].innerText;
198     document.getElementById('amount').value = rowContent[5].innerText;
199     document.getElementById('dAmount').value = rowContent[6].innerText;
200
201     document.getElementById('add').setAttribute('hidden', true);
202     document.getElementById('save').removeAttribute('hidden');
203     document.getElementById('discard').removeAttribute('hidden');
204 }
205
206 function saveChanges() {

```

```

205     data = getData();
206     if(data) {
207         rowToEdit = document.getElementsByClassName('editing')[0];
208         cellsToEdit = rowToEdit.getElementsByTagName('td');
209
210         for(var i = 0; i < data.length; i++) {
211             cellsToEdit[i + 1].innerHTML = data[i];
212         }
213         rowToEdit.classList = "bodyRow";
214     }
215
216     document.getElementById('add').removeAttribute('hidden');
217     document.getElementById('save').setAttribute('hidden', true);
218     document.getElementById('discard').setAttribute('hidden', true);
219 }
220
221 function discardChanges() {
222     document.getElementsByClassName('editing')[0].classList = "bodyRow";
223
224     document.getElementById('add').removeAttribute('hidden');
225     document.getElementById('save').setAttribute('hidden', true);
226     document.getElementById('discard').setAttribute('hidden', true);
227 }
228
229 function sortTable(column, ascending) {
230     var tableBody = document.getElementById('tableBody');
231     var rows = document.getElementsByClassName('bodyRow');
232
233     var sorting = true;
234     while(sorting) {
235         sorting = false;
236         for(var i = 0; i < (rows.length - 1); i++) {
237             rowA = rows[i].getElementsByTagName('td')[column];
238             rowB = rows[i + 1].getElementsByTagName('td')[column];
239
240             var swap = false;
241
242             if(ascending && rowA.innerHTML.toLowerCase() > rowB.innerHTML.
                ↪ toLowerCase()) swap = true;
243             else if(!ascending && rowA.innerHTML.toLowerCase() < rowB.
                ↪ innerHTML.toLowerCase()) swap = true;
244
245             if(swap) {
246                 sorting = true;
247                 rows[i].parentNode.insertBefore(rows[i + 1], rows[i]);
248             }
249         }
250     }
251 }

```

C CSS Source Code

```
1 body {
2     font-size: 14px;
3 }
4
5 #inputFields {
6     padding: 10px 0;
7     overflow-x: auto;
8 }
9
10 form {
11     min-width: 1900px;
12 }
13
14     form > section {
15         width: 14%;
16         display: inline-block;
17     }
18
19     input,
20     select {
21         min-width: 100px;
22         width: 80%;
23     }
24
25     button {
26         width: 40%;
27     }
28
29 #table {
30     max-height: 80vh;
31     overflow: auto;
32 }
33
34 table {
35     width: 100%;
36     margin: auto;
37     border-collapse: collapse;
38 }
39     th {
40         min-width: 200px;
41         width: 10%;
42         position: sticky;
43         background: white;
44         top: 0;
45     }
46
47     th > section {
48         width: 80%;
49         display: inline-block;
50         padding: 0;
51         margin: 0;
52     }
```



```
53
54     .sort {
55         width: 10%;
56     }
57
58     .sort > button {
59         padding: 0;
60         border: 0;
61         display: block;
62         width: 100%;
63     }
64
65     .editing {
66         background-color: yellow;
67     }
68
69     #table,
70     table,
71     td,
72     th {
73         box-shadow: 1px 1px black, inset 1px 1px black;
74     }
```