

---

# **GRID**

***Version 0.1***

**GRID Team**

**avr. 17, 2021**



---

## Contents:

---

<b>1</b>	<b>app</b>	<b>1</b>
1.1	app package . . . . .	1
1.1.1	Subpackages . . . . .	1
1.1.1.1	app.base package . . . . .	1
1.1.1.2	app.home package . . . . .	3
1.1.2	Module contents . . . . .	4
<b>2</b>	<b>Indices and tables</b>	<b>5</b>
	<b>Index des modules Python</b>	<b>7</b>
	<b>Index</b>	<b>9</b>



## 1.1 app package

### 1.1.1 Subpackages

#### 1.1.1.1 app.base package

##### Submodules

##### app.base.forms module

Copyright (c) 2019 - present AppSeed.us

```
class app.base.forms.CreateAccountForm(*args, **kwargs)
    Bases: flask_wtf.form.FlaskForm
    email = <UnboundField(TextField, ('Email',)), {'id': 'email_create', 'validators': [<wt
    password = <UnboundField(PasswordField, ('Password',)), {'id': 'pwd_create', 'validator
    username = <UnboundField(TextField, ('Username',)), {'id': 'username_create', 'validato

class app.base.forms.LoginForm(*args, **kwargs)
    Bases: flask_wtf.form.FlaskForm
    password = <UnboundField(PasswordField, ('Password',)), {'id': 'pwd_login', 'validators
    username = <UnboundField(TextField, ('Username',)), {'id': 'username_login', 'validato

class app.base.forms.Questionnaires(*args, **kwargs)
    Bases: flask_wtf.form.FlaskForm
    address = <UnboundField(TextField, ('Address',)), {'id': 'address', 'validators': [<wtf
    name_exploit = <UnboundField(TextField, ('Nom exploitation',)), {'id': 'exploit', 'vali
    submit = <UnboundField(SubmitField, ('Enregistrer',)), {}>
```

### app.base.index\_renderer module

```
app.base.index_renderer.plot_alerte()  
app.base.index_renderer.plot_co2()  
app.base.index_renderer.plot_ebitda()  
app.base.index_renderer.plot_pct()  
app.base.index_renderer.plots()
```

### app.base.models module

Copyright (c) 2019 - present AppSeed.us

```
class app.base.models.User(**kwargs)  
    Bases: sqlalchemy.ext.declarative.api.Model, flask_login.mixins.UserMixin  
    email  
    id  
    password  
    username  
  
app.base.models.request_loader(request)  
app.base.models.user_loader(id)
```

### app.base.routes module

Copyright (c) 2019 - present AppSeed.us

```
app.base.routes.access_forbidden(error)  
app.base.routes.internal_error(error)  
app.base.routes.login()  
app.base.routes.logout()  
app.base.routes.not_found_error(error)  
app.base.routes.register()  
app.base.routes.route_default()  
app.base.routes.shutdown()  
app.base.routes.unauthorized_handler()
```

## app.base.util module

Copyright (c) 2019 - present AppSeed.us

`app.base.util.hash_pass` (*password*)

Hash a password for storing.

`app.base.util.verify_pass` (*provided\_password, stored\_password*)

Verify a stored password against one provided by user

## app.base.zone\_innondable module

Created on Thu Apr 15 16:02:54 2021

@author : Clement

**class** `app.base.zone_innondable.DataImport` (*dpt, town, list\_db*)

Bases: `object`

**create\_folder** (*directory*)

**import\_data** ()

**quick\_plot** ()

**read\_json** ()

**to\_json** ()

**class** `app.base.zone_innondable.InternalPlot` (*geo\_df*)

Bases: `object`

**plot** ()

`app.base.zone_innondable.main` (*list\_db, dpt, town*)

`app.base.zone_innondable.read_json` (*list\_db, dpt, town*)

## Module contents

Copyright (c) 2019 - present AppSeed.us

### 1.1.1.2 app.home package

#### Submodules

## app.home.routes module

Copyright (c) 2019 - present AppSeed.us

`app.home.routes.get_segment` (*request*)

`app.home.routes.index` ()

`app.home.routes.route_template` (*template*)

## Module contents

Copyright (c) 2019 - present AppSeed.us

### 1.1.2 Module contents

Copyright (c) 2019 - present AppSeed.us

`app.configure_database` (*app*)

`app.create_app` (*config*)

`app.register_blueprints` (*app*)

`app.register_extensions` (*app*)



## CHAPITRE 2

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`



### a

- `app`, 4
- `app.base`, 3
  - `app.base.forms`, 1
  - `app.base.index_renderer`, 2
  - `app.base.models`, 2
  - `app.base.routes`, 2
  - `app.base.util`, 3
  - `app.base.zone_innondable`, 3
- `app.home`, 4
  - `app.home.routes`, 3



## A

`access_forbidden()` (dans le module `app.base.routes`), 2  
`address` (attribut `app.base.forms.Questionnaires`), 1  
`app`  
    module, 4  
`app.base`  
    module, 3  
`app.base.forms`  
    module, 1  
`app.base.index_renderer`  
    module, 2  
`app.base.models`  
    module, 2  
`app.base.routes`  
    module, 2  
`app.base.util`  
    module, 3  
`app.base.zone_innondable`  
    module, 3  
`app.home`  
    module, 4  
`app.home.routes`  
    module, 3

## C

`configure_database()` (dans le module `app`), 4  
`create_app()` (dans le module `app`), 4  
`create_folder()` (méthode `app.base.zone_innondable.DataImport`), 3  
`CreateAccountForm` (classe dans `app.base.forms`), 1

## D

`DataImport` (classe dans `app.base.zone_innondable`), 3

## E

`email` (attribut `app.base.forms.CreateAccountForm`), 1

`email` (attribut `app.base.models.User`), 2

## G

`get_segment()` (dans le module `app.home.routes`), 3

## H

`hash_pass()` (dans le module `app.base.util`), 3

## I

`id` (attribut `app.base.models.User`), 2  
`import_data()` (méthode `app.base.zone_innondable.DataImport`), 3  
`index()` (dans le module `app.home.routes`), 3  
`internal_error()` (dans le module `app.base.routes`), 2  
`InternalPlot` (classe dans `app.base.zone_innondable`), 3

## L

`login()` (dans le module `app.base.routes`), 2  
`LoginForm` (classe dans `app.base.forms`), 1  
`logout()` (dans le module `app.base.routes`), 2

## M

`main()` (dans le module `app.base.zone_innondable`), 3  
`module`  
    `app`, 4  
    `app.base`, 3  
    `app.base.forms`, 1  
    `app.base.index_renderer`, 2  
    `app.base.models`, 2  
    `app.base.routes`, 2  
    `app.base.util`, 3  
    `app.base.zone_innondable`, 3  
    `app.home`, 4  
    `app.home.routes`, 3

## N

`name_exploit` (attribut `app.base.forms.Questionnaires`), 1  
`not_found_error()` (dans le module `app.base.routes`), 2

## P

`password` (attribut `app.base.forms.CreateAccountForm`), 1  
`password` (attribut `app.base.forms.LoginForm`), 1  
`password` (attribut `app.base.models.User`), 2  
`plot()` (méthode `app.base.zone_innondable.InternalPlot`), 3  
`plot_alerte()` (dans le module `app.base.index_renderer`), 2  
`plot_co2()` (dans le module `app.base.index_renderer`), 2  
`plot_ebitda()` (dans le module `app.base.index_renderer`), 2  
`plot_pct()` (dans le module `app.base.index_renderer`), 2  
`plots()` (dans le module `app.base.index_renderer`), 2

## Q

`Questionnaires` (classe dans `app.base.forms`), 1  
`quick_plot()` (méthode `app.base.zone_innondable.DataImport`), 3

## R

`read_json()` (dans le module `app.base.zone_innondable`), 3  
`read_json()` (méthode `app.base.zone_innondable.DataImport`), 3  
`register()` (dans le module `app.base.routes`), 2  
`register_blueprints()` (dans le module `app`), 4  
`register_extensions()` (dans le module `app`), 4  
`request_loader()` (dans le module `app.base.models`), 2  
`route_default()` (dans le module `app.base.routes`), 2  
`route_template()` (dans le module `app.home.routes`), 3

## S

`shutdown()` (dans le module `app.base.routes`), 2  
`submit` (attribut `app.base.forms.Questionnaires`), 1

## T

`to_json()` (méthode `app.base.zone_innondable.DataImport`), 3

## U

`unauthorized_handler()` (dans le module `app.base.routes`), 2  
`User` (classe dans `app.base.models`), 2  
`user_loader()` (dans le module `app.base.models`), 2  
`username` (attribut `app.base.forms.CreateAccountForm`), 1  
`username` (attribut `app.base.forms.LoginForm`), 1  
`username` (attribut `app.base.models.User`), 2

## V

`verify_pass()` (dans le module `app.base.util`), 3