

GreenGo — QA Test Report

Automated frontend suite (Flutter) · generated 2026-07-15 · Master Test Plan Phases 1–2 · commit 12e5823

415
TOTAL TESTS

411
PASSED

0
FAILED

4
SKIPPED

100.0%
PASS RATE

33.06s
WALL TIME

Verdict: 411 of 411 executed tests pass (100.0%), 0 failures across 42 test files and 14 categories. The 4 skips are documented fake-backend limitations (transaction/increment emulation) covered by the emulator layer (B2/B4).

1. Environment

Flutter 3.44.2 • channel [user-branch] • unknown source	package: greengo_chat
Framework • revision c9a6c48423 (5 weeks ago) • 2026-06-10 15:52:41 -0700	harness: flutter_test + mocktail + fake_cloud_firestore + firebase_auth_mock + network_image_mock
Engine • hash 04efd7c093d4e9281d5526ebcad6ecc60ba8badf (revision 77e2e94772) (1 months ago) • 2026-06-10 19:59:06.000Z	personas: mock_user_1..5 (FREE/SILVER/GOLD/PLATINUM/PLATINUM+business)
12e5823	plan: docs/testing/GREENGO_MASTER_TEST_PLAN.md
test: 415-test frontend suite (0 failures) + PDF QA report; happening-soon 100km; hide account-approved notifications	

2. Methodology

Tests run against an in-memory fake Firestore + mocked FirebaseAuth (no network), so every case is deterministic (fixed clocks, no live I/O). Blocs are exercised with mocktail-stubbed repositories (dartx Either) and expectLater(bloc.stream, emitsInOrder([...])). Widgets pump inside MaterialApp with the app's localization delegates and mockNetworkImagesFor. Datasource/query tests seed a FakeFirestore mirroring the production seeder shapes. Backend rules/functions/performance (B1–B6) require the Firebase emulator and are the next phase.

3. Results by category

CATEGORY	TESTS	PASS	SKIP	FAIL	DURATION	STATUS
Authentication & Session	67	67	0	0	531ms	PASS
Onboarding	29	29	0	0	313ms	PASS
Profile	48	48	0	0	602ms	PASS
Communities	10	10	0	0	287ms	PASS
Discovery / Explore (geo/date logic)	5	5	0	0	58ms	PASS
Events — date/geo logic	10	10	0	0	72ms	PASS
Events — bloc / datasource	32	32	0	0	614ms	PASS
Chat / Messaging	40	40	0	0	2.16s	PASS
Business / Storefront	20	16	4	0	1.56s	PASS
Search	25	25	0	0	697ms	PASS
Notifications	28	28	0	0	426ms	PASS
Membership / Coins	46	46	0	0	640ms	PASS
Localization (7 locales)	31	31	0	0	374ms	PASS
Widgets / Rendering	24	24	0	0	5.52s	PASS
TOTAL	415	411	4	0	13.85s	PASS

4. Regression coverage (this cycle's fixes → guarding tests)

FIX	WHAT THE TEST GUARDS	AREA
Communities concurrency-merge	Bloc handlers merge onto current state via copyWith; concurrent Discover/Joined/My/Recommended loads no longer clobber managedCommunities — "My communities" reliably appears.	Communities
Tips/Announcements/Chat split	language_tip / cultural_fact / city_tip → Tips; announcement → Announcements; text → chat. Wire-string round-trips guarded.	Communities
getCreatedCommunities (My communities)	Direct createdByUserId query, independent of member docs; public-only Discover.	Communities
Live-event date validity	Only well-formed yyyy-MM-dd, today-onward; junk like "1"/empty rejected; ≤1-week fallback window.	Events – date/geo logic
50 / 100 km geo filters	Haversine distance drives within-radius event filters (happening-soon 100km, featured/near-you 50km).	Discovery / Explore (geo/date logic)

FIX	WHAT THE TEST GUARDS	AREA
Events earliest-first	EventsLoaded.upcomingEvents sorts ascending by startDate; datasource getEvents orderBy startDate asc.	Events – bloc / datasource
Business chat identity	Business-inquiry conversations render businessName + coverImageUrl instead of the owner's personal name/photo — card + header.	Chat / Messaging
Business tab routing	A business viewer's inquiries are excluded from every personal Messages filter (route only to the Business tab).	Chat / Messaging
Rate-this-business hides after rating	Rating control returns SizedBox.shrink when the viewer already rated (mine>0) or is the business itself.	Business / Storefront
Storefront tap-through id	_EventCard/_CommunityCard carry the doc id so tiles can open the event/community detail.	Business / Storefront
Search excludes deleted + dual business	Self/ghost/admin/support/non-active excluded; a business owner surfaces as BOTH People (personal) and Business (hero image).	Search
Notifications optimistic delete-all	NotificationsAllCleared emits NotificationsEmpty immediately, before the server delete; unread-clear drops unread optimistically.	Notifications
Account-approved notifications hidden	account_approved broadcast notifications filtered out of the feed stream.	Notifications
i18n key parity + no mojibake	Every en key present across all 7 locales; no replacement chars / classic UTF-8-as-Latin-1 mojibake.	Localization (7 locales)
Profile age + flags layout	age getter from dateOfBirth; header composes age + language flags under the name.	Profile

5. Timing — 20 slowest tests

#	TEST	CATEGORY	DURATION
1	shows the other user displayName for a normal 1:1 chat	Widgets / Rendering	1.36s
2	renders name, member count and type badge	Widgets / Rendering	1.34s
3	business inquiry shows businessName, not personal displayName	Chat / Messaging	1.29s
4	VerifiedBadge renders a check icon	Widgets / Rendering	1.25s
5	shows the rating control when viewer has not rated (mine == 0)	Business / Storefront	1.11s
6	excluded accounts never appear in People results	Search	234ms
7	matches on community NAME (case-insensitive)	Search	220ms

#	TEST	CATEGORY	DURATION
8	EventsRemoteDataSource.getEvents against fake Firestore returns only live, public events ordered by startDate ascending	Events – bloc / datasource	198ms
9	invokes onTap when the row is tapped	Widgets / Rendering	194ms
10	CommunitiesRemoteDataSource against fake Firestore getCommunities returns only public communities (joinable)	Communities	184ms
11	MessageModel.fromFirestore round-trips content/type/sentAt through Firestore	Chat / Messaging	172ms
12	ConversationModel.fromFirestore round-trips a businessInquiry conversation through Firestore	Chat / Messaging	169ms
13	CoinBalanceModel round-trip toFirestore -> fromFirestore preserves scalars and a batch	Membership / Coins	165ms
14	MembershipModel round-trips through Firestore preserving the tier	Membership / Coins	158ms
15	renders a network image when imageUrl is set	Widgets / Rendering	154ms
16	ProfileModel.fromFirestore reads back a doc written via toJson, using the doc id as userId	Profile	152ms
17	rateBusiness first rating sets sum and count and writes the rating doc	Business / Storefront	152ms
18	business inquiry avatar uses the storefront coverImageUrl	Widgets / Rendering	142ms
19	NotificationModel Firestore round-trip toFirestore -> fromFirestore preserves fields	Notifications	126ms
20	load emits [Loading, Loaded] with the correct unread count	Notifications	97ms

6. Detailed results — every test

Authentication & Session 67 tests · 67 pass · 0 skip · 0 fail · 531ms

test/unit/auth/auth_bloc_test.dart (13)

✓	sign in with email emits [Loading, Authenticated] on success	81ms
✓	sign in with email emits [Loading, Error] on failure	11ms
✓	register with email emits [Loading, Authenticated] on success	11ms
✓	register with email initializes access control on successful registration	13ms
✓	register with email emits [Loading, Error] when the email is already in use	9ms
✓	password reset emits [Loading, PasswordResetSent] on success	8ms
✓	password reset emits [Loading, Error] on failure	9ms
✓	logout emits Unauthenticated after signOut	10ms
✓	auth check emits Authenticated when a current user exists	13ms
✓	auth check emits Unauthenticated when no current user	8ms
✓	auth check emits Unauthenticated when getCurrentUser fails	9ms
✓	disabled social providers (AppConfig flags off) Google sign-in emits an Error explaining it is disabled	9ms
✓	disabled social providers (AppConfig flags off) phone sign-in emits [Loading, Error] (not yet available)	7ms

test/unit/auth/auth_datasource_test.dart (6)

✓	session reads via MockFirebaseAuth getCurrentUser returns null when signed out	22ms
✓	session reads via MockFirebaseAuth getCurrentUser maps the Firebase user to a UserModel	11ms
✓	session reads via MockFirebaseAuth isSignedIn reflects the auth state	4ms
✓	session reads via MockFirebaseAuth signOut clears the current session	5ms
✓	disabled social providers throw AuthenticationException signInWithGoogle throws when not enabled/configured	9ms
✓	disabled social providers throw AuthenticationException signInWithFacebook throws when not enabled/configured	5ms

test/unit/auth/auth_state_event_test.dart (9)

✓	AuthEvent equality sign-in events with same credentials are equal	23ms
✓	AuthEvent equality sign-in events differ when password differs	6ms
✓	AuthEvent equality register events carry email + password in props	5ms
✓	AuthEvent equality password-reset event exposes the email in props	4ms
✓	AuthState equality AuthAuthenticated is equal for the same user	6ms
✓	AuthState equality AuthAuthenticated differs for different users	6ms
✓	AuthState equality AuthError with the same message are equal (message-only equality)	5ms
✓	AuthState equality const singleton states are equal	4ms
✓	AuthState equality AuthWaitingForAccess carries approval + tier metadata	5ms

test/unit/auth/consent_checkboxes_test.dart (5)

✓	ConsentCheckboxes.areRequiredConsentsAccepted true only when BOTH privacy and terms are accepted	22ms
✓	ConsentCheckboxes.areRequiredConsentsAccepted false when privacy policy is not accepted	4ms
✓	ConsentCheckboxes.areRequiredConsentsAccepted false when terms are not accepted	5ms
✓	ConsentCheckboxes.areRequiredConsentsAccepted false when neither required consent is accepted	3ms
✓	ConsentCheckboxes.areRequiredConsentsAccepted gate is independent of the optional consents	4ms

test/unit/auth/user_model_test.dart (8)

✓	User entity uid getter mirrors id (Firebase compatibility)	19ms
✓	User entity is value-equal via Equatable on all props	6ms
✓	User entity copyWith overrides only the provided fields	4ms
✓	UserModel JSON mapping fromJson applies safe defaults for missing fields	4ms
✓	UserModel JSON mapping fromJson parses ISO-8601 timestamps	6ms
✓	UserModel JSON mapping toJson round-trips through fromJson	5ms
✓	UserModel JSON mapping toFirestore omits null lastLoginAt but keeps required keys	6ms
✓	UserModel JSON mapping copyWith returns a UserModel (not a bare User)	5ms

test/unit/auth/validators_test.dart (26)

✓	Validators.validateEmail rejects null and empty as required	22ms
✓	Validators.validateEmail rejects malformed addresses	4ms
✓	Validators.validateEmail accepts well-formed addresses (returns null)	5ms
✓	Validators.validatePassword rejects null / empty as required	3ms
✓	Validators.validatePassword enforces minimum length of 8	3ms
✓	Validators.validatePassword requires an uppercase letter	3ms
✓	Validators.validatePassword requires a lowercase letter	4ms
✓	Validators.validatePassword requires a digit	4ms
✓	Validators.validatePassword requires a special character	3ms
✓	Validators.validatePassword accepts a strong compliant password (returns null)	3ms
✓	Validators.validateConfirmPassword rejects empty confirmation	4ms
✓	Validators.validateConfirmPassword rejects mismatch	4ms
✓	Validators.validateConfirmPassword accepts exact match (returns null)	3ms
✓	Validators.validatePhone rejects null / empty	4ms
✓	Validators.validatePhone rejects fewer than 10 digits	3ms
✓	Validators.validatePhone accepts a formatted 10+ digit number, ignoring separators	4ms
✓	Validators.validateName rejects empty and too-short names	4ms
✓	Validators.validateName rejects names with digits or symbols	4ms
✓	Validators.validateName accepts letters and spaces (returns null)	3ms
✓	Validators.validateAge rejects null and under-18 by default	8ms
✓	Validators.validateAge rejects impossible age and accepts a valid adult age	4ms
✓	Validators.validateBio treats empty/null bio as optional (returns null)	4ms
✓	Validators.validateBio rejects a bio over the max length	4ms
✓	Validators password strength meter empty password scores 0 (Very Weak)	5ms
✓	Validators password strength meter a long mixed password caps at 4 (Very Strong)	3ms
✓	Validators password strength meter strength never exceeds the 0..4 range	5ms

Onboarding 29 tests · 29 pass · 0 skip · 0 fail · 313ms

test/unit/onboarding/onboarding_payload_test.dart (11)

✓	OnboardingStep enum contract welcome is first and there are 12 ordered steps	28ms
✓	OnboardingInProgress progress accounting stepIndex/totalSteps/progress are consistent	7ms
✓	OnboardingInProgress progress accounting progress reaches 1.0 on the final step	5ms
✓	OnboardingInProgress.copyWith preserves userId and overrides only supplied fields	5ms
✓	completion payload carried by the in-progress state a fully-filled state holds every field the Profile is built from	8ms
✓	OnboardingComplete / OnboardingError states OnboardingComplete exposes the profile and null coupon by default	8ms
✓	OnboardingComplete / OnboardingError states OnboardingError carries its message in props	6ms
✓	Location value entity round-trips through JSON	6ms
✓	SocialLinks value entity empty has no links and zero count	6ms
✓	SocialLinks value entity counts only the non-empty handles and builds handle URLs	4ms
✓	PersonalityTraits value entity is value-equal via Equatable	3ms

test/unit/onboarding/onboarding_progression_test.dart (7)

✓	OnboardingStarted opens at the welcome step	71ms
✓	NextStep advances welcome -> basicInfo (welcome is always open)	16ms
✓	NextStep is gated at basicInfo when required fields are missing	14ms
✓	filling basicInfo unblocks NextStep -> photos	16ms
✓	PreviousStep returns from basicInfo to welcome	13ms
✓	update events accumulate onto the in-progress payload	13ms
✓	phone verification records method + number on the state	10ms

test/unit/onboarding/onboarding_validation_test.dart (11)

✓	always-proceedable / optional steps welcome, travelPreference, voice, socialLinks, preview are open	26ms
✓	basicInfo step blocked until name, DOB and gender are all present	8ms
✓	basicInfo step allowed when name, DOB and gender are all set	5ms
✓	photos step blocked with no photos, allowed with at least one	5ms
✓	verification step blocked with neither photo nor verified phone	5ms
✓	verification step allowed with a verification photo	4ms
✓	verification step allowed with a phone verification method + number	5ms
✓	bio step blocked when empty, allowed when filled	4ms
✓	interests step requires at least three interests	4ms
✓	locationLanguage step requires both a location and at least one language	4ms
✓	personality step requires personality traits to be answered	4ms

Profile 48 tests · 48 pass · 0 skip · 0 fail · 602ms

test/unit/profile/profile_bloc_test.dart (9)

✓ ProfileLoadRequested emits [Loading, Loaded] on success	78ms
✓ ProfileLoadRequested emits [Loading, Error] with the failure message on failure	14ms
✓ ProfileLoadRequested forwards the requested userId to the usecase	12ms
✓ ProfileCreateRequested emits [Loading, Created] on success	10ms
✓ ProfileCreateRequested emits [Loading, Error] on failure	10ms
✓ ProfileUpdateRequested emits [Loading, Updated] on success	10ms
✓ ProfileNicknameUpdateRequested loads current profile, lowercases nickname, then updates	17ms
✓ ProfileNicknameUpdateRequested emits Error when the underlying getProfile fails	9ms
✓ initial state is ProfileInitial	6ms

test/unit/profile/profile_entity_test.dart (23)

✓ Profile.age getter is full years when the birthday already passed this year	34ms
✓ Profile.age getter counts the birthday on the exact day (>= not >)	6ms
✓ Profile.age getter matches an independent reference calc for an arbitrary DOB	5ms
✓ Profile.age getter is never negative for a very recent DOB	5ms
✓ Profile.isBusinessPromoted true when business + promotedUntil in the future	6ms
✓ Profile.isBusinessPromoted false when the promotion window has expired	6ms
✓ Profile.isBusinessPromoted false when promotedUntil is null even for a business	5ms
✓ Profile.isBusinessPromoted false for a non-business account even with a future window	5ms
✓ Profile business / storefront fields exposes businessName and coverImageUrl on a storefront	5ms
✓ Profile business / storefront fields defaults are business-off with null storefront fields	6ms
✓ Profile derived flags formattedNickname prefixes @ or is null	5ms
✓ Profile derived flags isVerified reflects approved verification only	5ms
✓ Profile derived flags needsVerificationAction covers notSubmitted / rejected	7ms
✓ Profile derived flags isTravelerActive requires the flag AND a future expiry	5ms
✓ Profile derived flags effectiveLocation swaps to traveler location when active	5ms
✓ Profile.isBaseMembershipActive true for TEST tier regardless of dates	5ms
✓ Profile.isBaseMembershipActive true for a paid tier with a future membershipEndDate	5ms
✓ Profile.isBaseMembershipActive true via legacy base membership fields	5ms
✓ Profile.isBaseMembershipActive false for a free user with no active windows	5ms
✓ OpeningHours + SignupGrant value objects OpeningHours.fromMap round-trips through toMap	6ms
✓ OpeningHours + SignupGrant value objects OpeningHours.fromMap defaults weekday to Monday	5ms
✓ OpeningHours + SignupGrant value objects SignupGrant.fromMap round-trips and copyWith dismisses	6ms
✓ copyWith updates only the targeted field	9ms

test/unit/profile/profile_model_test.dart (16)

✓	ProfileModel.toJson / fromJson round-trip preserves core identity + membership + business fields	49ms
✓	ProfileModel.toJson / fromJson round-trip round-trips lists (photoUrls / interests / languages)	7ms
✓	ProfileModel.toJson / fromJson round-trip membership tier survives via its wire value	6ms
✓	ProfileModel.toJson / fromJson round-trip businessPromotedUntil serializes and re-parses as a future date	6ms
✓	ProfileModel.fromJson defaults + legacy handling fills sane defaults when optional fields are missing	6ms
✓	ProfileModel.fromJson defaults + legacy handling reads the legacy "photos" key when "photoUrls" is absent	5ms
✓	ProfileModel.fromJson defaults + legacy handling parses verificationStatus strings, unknown -> notSubmitted	6ms
✓	ProfileModel.fromJson defaults + legacy handling parses globeDiscoverability, unknown -> approximate	5ms
✓	ProfileModel.fromJson defaults + legacy handling parses openingHours + signupGrants lists of maps	6ms
✓	ProfileModel.fromFirestore reads back a doc written via toJson, using the doc id as userId	152ms
✓	ProfileModel.fromFirestore location survives the Firestore round-trip	8ms
✓	toJson wire encoding details encodes DateTimes as Firestore Timestamps	5ms
✓	toJson wire encoding details verificationStatus + globeDiscoverability encode as enum names	5ms
✓	normalizeCountryName maps locale spellings to canonical English	4ms
✓	normalizeCountryName is case-insensitive and passes through unknowns unchanged	5ms
✓	normalizeCountryName LocationModel.fromJson normalizes country + strips "Unknown"	5ms

Communities 10 tests · 10 pass · 0 skip · 0 fail · 287ms

test/unit/communities/communities_datasource_query_test.dart (4)

✓	CommunitiesRemoteDataSource against fake Firestore getCommunities returns only public communities (joinable)	184ms
✓	CommunitiesRemoteDataSource against fake Firestore getCreatedCommunities returns ONLY the caller-created communities	14ms
✓	CommunitiesRemoteDataSource against fake Firestore getCreatedCommunities is empty for a user who created none	14ms
✓	CommunitiesRemoteDataSource against fake Firestore getUserCommunities finds communities via member docs	20ms

test/unit/communities/community_message_type_test.dart (6)

✓	CommunityMessageType wire mapping value() emits the exact snake_case wire strings	28ms
✓	CommunityMessageType wire mapping fromString round-trips every known value	5ms
✓	CommunityMessageType wire mapping fromString falls back to text for unknown/garbage	4ms
✓	CommunityMessage classification (Tips/Announcements/Chat) language_tip / cultural_fact / city_tip are Tips (not chat)	9ms
✓	CommunityMessage classification (Tips/Announcements/Chat) announcement is an announcement only (not tip, not chat)	5ms
✓	CommunityMessage classification (Tips/Announcements/Chat) text is chat (neither tip nor announcement)	4ms

Discovery / Explore (geo/date logic) 5 tests · 5 pass · 0 skip · 0 fail · 58ms

test/unit/explore/geo_distance_test.dart (5)

✓	GeoQuery.distanceMeters identical points are ~0m apart	22ms
✓	GeoQuery.distanceMeters one degree of latitude is ~111km	22ms
✓	GeoQuery.distanceMeters ~11km separation is within the 50km radius	5ms
✓	GeoQuery.distanceMeters ~55km separation is OUTSIDE the 50km radius	4ms
✓	within-50km predicate near point passes, far point fails	5ms

Events — date/geo logic 10 tests · 10 pass · 0 skip · 0 fail · 72ms

test/unit/events/event_date_logic_test.dart (10)

✓	ISO date validity (live events must have a clear date) accepts well-formed yyyy-MM-dd	24ms
✓	ISO date validity (live events must have a clear date) rejects junk / partial / null / empty dates	4ms
✓	today-onward filter (no past events) keeps today and future	5ms
✓	today-onward filter (no past events) drops past	7ms
✓	within-1-week live fallback window keeps dates in [today, today+7]	4ms
✓	within-1-week live fallback window drops dates beyond a week or in the past	3ms
✓	combined live-event gate (ticketmaster) live tab: valid + today-onward only	6ms
✓	combined live-event gate (ticketmaster) happening-soon fallback: valid + within a week	5ms
✓	ascending date sort (earliest first) sorts ISO date strings chronologically (lexical == chronological)	7ms
✓	ascending date sort (earliest first) sorts DateTime events earliest first	7ms

Events — bloc / datasource 32 tests · 32 pass · 0 skip · 0 fail · 614ms

test/unit/events_bloc/events_bloc_test.dart (13)

✓	LoadEvents emits [Loading, Loaded] on success	92ms
✓	LoadEvents emits [Loading, Error] on failure	14ms
✓	LoadEvents emits Loaded with an empty list when there are no events	12ms
✓	LoadUserEvents emits Loaded carrying userEvents from an unloaded state	17ms
✓	LoadUserEvents emits Error from an unloaded state on failure	11ms
✓	LoadUserEvents updates userEvents in place when already loaded	14ms
✓	LoadNearbyEvents emits Loaded carrying nearbyEvents from an unloaded state	10ms
✓	LoadNearbyEvents emits Error from an unloaded state on failure	10ms
✓	RSVP emits RsvpSuccess then re-emits the list	17ms
✓	RSVP emits Error when the RSVP write fails	11ms
✓	RSVP CancelRsvp emits RsvpSuccess with status "cancelled"	13ms
✓	FilterByCategory applies the category filter on the loaded state	14ms
✓	country stats stub compiles against the repo interface	9ms

test/unit/events_bloc/events_datasource_query_test.dart (11)

✓	EventsRemoteDataSource.getEvents against fake Firestore returns only live, public events ordered by startDate ascending	198ms
✓	EventsRemoteDataSource.getEvents against fake Firestore excludes draft (not-live) events	13ms
✓	EventsRemoteDataSource.getEvents against fake Firestore excludes private events from discovery	9ms
✓	EventsRemoteDataSource.getEvents against fake Firestore upcoming:true excludes past events	10ms
✓	EventsRemoteDataSource.getEvents against fake Firestore category filter narrows to the requested category	11ms
✓	EventsRemoteDataSource.getEvents against fake Firestore returns empty list when there are no events	7ms
✓	EventsRemoteDataSource.getEventById returns the event when it exists	9ms
✓	EventsRemoteDataSource.getEventById returns null when the event is missing	7ms
✓	EventsRemoteDataSource.getUserEvents unions organized + attending(going) events, deduped and sorted	19ms
✓	EventsRemoteDataSource.getUserEvents does not duplicate an event the user both organized and joined	10ms
✓	EventsRemoteDataSource.getUserEvents returns empty for a user with no organized/attending events	8ms

test/unit/events_bloc/events_state_test.dart (8)

✓	EventsLoaded.upcomingEvents sorts upcoming events ascending by startDate	27ms
✓	EventsLoaded.upcomingEvents excludes events whose startDate is in the past	6ms
✓	EventsLoaded.upcomingEvents is empty when every event is in the past	6ms
✓	EventsLoaded.upcomingEvents respects the selected category filter	6ms
✓	EventsLoaded.filteredEvents returns all events when no category is selected	5ms
✓	EventsLoaded.filteredEvents returns only events of the selected category	6ms
✓	EventsLoaded.copyWith clearCategory drops the selected category	7ms
✓	EventsLoaded.copyWith preserves existing lists when not overridden	6ms

Chat / Messaging 40 tests · 40 pass · 0 skip · 0 fail · 2.16s

test/unit/chat/conversation_card_widget_test.dart (4)

✓	business inquiry shows businessName, not personal displayName	1.29s
✓	non-business inquiry shows the personal displayName	73ms
✓	business inquiry WITHOUT businessName falls back to displayName	70ms
✓	group conversation shows the group name	75ms

test/unit/chat/conversation_model_test.dart (14)

✓	ConversationModel.toFirestore serializes core 1:1 fields including businessInquiry=true	37ms
✓	ConversationModel.toFirestore businessInquiry defaults to false and lastMessage null → null	8ms
✓	ConversationModel.toFirestore nests lastMessage with type.value wire string	9ms
✓	ConversationModel.fromFirestore round-trips a businessInquiry conversation through Firestore	169ms
✓	ConversationModel.fromFirestore missing fields fall back to safe defaults	9ms
✓	ConversationModel.fromFirestore unknown conversationType falls back to match	9ms
✓	ConversationModel.toGroupFirestore emits isGroup + group type + participants + groupInfo map	13ms
✓	ConversationModel.toGroupFirestore group lastMessage omits receiverId (group-shaped)	6ms
✓	ConversationModel.toGroupFirestore participants come from participantIds when set	11ms
✓	Conversation.getOtherUserId + participant helpers getOtherUserId returns the counterpart for either side	7ms
✓	Conversation.getOtherUserId + participant helpers getOtherUserId returns userId1 for an unknown caller	8ms
✓	Conversation.getOtherUserId + participant helpers participantIds derives from userId1/userId2 for 1:1	6ms
✓	Conversation.getOtherUserId + participant helpers group unreadCountFor reads the per-member map	5ms
✓	Conversation.getOtherUserId + participant helpers roleOf/isAdmin reflect the roles map (default member)	7ms

test/unit/chat/conversations_business_filter_test.dart (9)

✓	_passesFilter — business inquiry exclusion business viewer: business inquiry is EXCLUDED from All	28ms
✓	_passesFilter — business inquiry exclusion customer viewer: same inquiry STAYS in All (no Business tab)	6ms
✓	_passesFilter — business inquiry exclusion business viewer: non-inquiry chat still passes	4ms
✓	_passesFilter — business inquiry exclusion business exclusion applies to newMessages filter too	4ms
✓	_passesFilter — general chat rules conversation with no lastMessage is not a real chat	4ms
✓	_passesFilter — general chat rules All excludes support and search conversations	4ms
✓	_passesFilter — general chat rules All excludes a pending super-like (visibleTo set)	4ms
✓	_passesFilter — general chat rules deletedFor the viewer removes it from All	4ms
✓	_passesFilter — general chat rules favorites filter matches only favorited conversations	4ms

test/unit/chat/message_model_test.dart (13)

✓	MessageType wire mapping value() emits the exact wire strings	34ms
✓	MessageType wire mapping fromString round-trips every known type	7ms
✓	MessageType wire mapping fromString falls back to text for garbage	4ms
✓	MessageStatus wire mapping value() round-trips every status	6ms
✓	MessageStatus wire mapping fromString falls back to sent for unknown	5ms
✓	MessageModel.toFirestore encodes type.value, status.value and sentAt as Timestamp	12ms
✓	MessageModel.toFirestore encodes read flags (readAt) when present	5ms
✓	MessageModel.toFirestore encodes readBy per-member map as Timestamps	7ms
✓	MessageModel.fromFirestore round-trips content/type/sentAt through Firestore	172ms
✓	MessageModel.fromFirestore unread message: readAt null → isRead false	9ms
✓	Message read/sender helpers isSentBy matches the sender only	7ms
✓	Message read/sender helpers isReadBy uses readBy map for groups, readAt fallback for 1:1	5ms
✓	Message read/sender helpers readByCount counts group readers, falls back to 1:1 readAt	6ms

Business / Storefront 20 tests · 16 pass · 4 skip · 0 fail · 1.56s

test/unit/business/business_rating_bar_widget_test.dart (4)

✓	shows the rating control when viewer has not rated (mine == 0)	1.11s
✓	HIDDEN once the viewer has already rated (mine > 0)	86ms
✓	HIDDEN when the viewer IS the business (self)	44ms
✓	null rating (never rated) also shows the control	64ms

test/unit/business/rating_service_test.dart (9)

✓	rateBusiness first rating sets sum and count and writes the rating doc	152ms
—	rateBusiness a second distinct rater increments sum and count	2ms
—	rateBusiness re-rating shifts sum by delta, count unchanged	1ms
✓	rateBusiness stars are clamped to 1..5	8ms
✓	rateBusiness a business cannot rate itself (raterId == businessId)	7ms
—	aggregate reads getAggregate computes avg = sum / count	1ms
✓	aggregate reads getAggregate is (0,0) for a business with no ratings	6ms
—	aggregate reads myRating stream emits the viewer current stars	0ms
✓	aggregate reads myRating stream is null when the viewer never rated	11ms

test/unit/business/storefront_viewmodel_test.dart (7)

✓ storefront view models carry the doc id (tap-through regression) _EventVm.fromDoc keeps the id	25ms
✓ storefront view models carry the doc id (tap-through regression) _CommunityVm.fromDoc keeps the id	6ms
✓ storefront view models carry the doc id (tap-through regression) event view model defaults status to draft	4ms
✓ universal search — business subset + dual row selection only isBusiness profiles form the Business tab subset	10ms
✓ universal search — business subset + dual row selection business row renders businessName + coverImageUrl	7ms
✓ universal search — business subset + dual row selection falls back to displayName + photoUrls.first when storefront empty	4ms
✓ universal search — business subset + dual row selection a person also appears in People (People includes everyone)	7ms

Search 25 tests · 25 pass · 0 skip · 0 fail · 697ms

test/unit/search/community_search_test.dart (7)

✓ matches on community NAME (case-insensitive)	220ms
✓ matches on DESCRIPTION text	12ms
✓ matches on a TAG	12ms
✓ a query hitting several public communities returns them all	11ms
✓ never surfaces a non-public community even on a match	11ms
✓ a no-match query yields an empty list	12ms
✓ empty searchQuery returns all public communities (no narrowing)	11ms

test/unit/search/profile_search_filter_test.dart (14)

✓ passesProfileSearchFilter exclusions a normal, active, named other user PASSES	39ms
✓ passesProfileSearchFilter exclusions excludes the current user (self)	7ms
✓ passesProfileSearchFilter exclusions excludes ghost-mode profiles	6ms
✓ passesProfileSearchFilter exclusions excludes admin accounts	5ms
✓ passesProfileSearchFilter exclusions excludes support accounts	6ms
✓ passesProfileSearchFilter exclusions excludes deleted accounts (accountStatus != active)	4ms
✓ passesProfileSearchFilter exclusions excludes suspended / banned accountStatus values	6ms
✓ passesProfileSearchFilter exclusions excludes profiles with a blank/whitespace displayName	5ms
✓ passesProfileSearchFilter exclusions an active business account PASSES (still a searchable person)	6ms
✓ People pipeline (filter + de-dupe + sort) sorts survivors by lowercased displayName	9ms
✓ People pipeline (filter + de-dupe + sort) de-dupes repeated userIds, keeping the first occurrence	6ms
✓ People pipeline (filter + de-dupe + sort) drops every excluded candidate in a mixed batch	6ms
✓ People vs Business split a business owner appears in BOTH People and Business	8ms
✓ People vs Business split Business subset is empty when no one is a business	6ms

test/unit/search/profile_search_firestore_test.dart (4)

✓	excluded accounts never appear in People results	234ms
✓	a business profile surfaces in BOTH People and Business	24ms
✓	ProfileModel round-trips through the fake Firestore doc	14ms
✓	results are sorted by lowercased displayName	17ms

Notifications 28 tests · 28 pass · 0 skip · 0 fail · 426ms

test/unit/notifications/notification_model_test.dart (15)

✓	NotificationType wire mapping every type round-trips through value -> fromString	26ms
✓	NotificationType wire mapping unknown / garbage strings fall back to system	4ms
✓	NotificationType wire mapping the event_broadcast alias maps to eventAnnouncement	4ms
✓	NotificationEntity.iconName mapping event-family types share the "event" icon	7ms
✓	NotificationEntity.iconName mapping group-family types share the "groups" icon	4ms
✓	NotificationEntity.iconName mapping representative singletons map to the expected icons	4ms
✓	NotificationEntity.iconName mapping every type produces a non-empty icon name	5ms
✓	NotificationModel Firestore round-trip toFirestore -> fromFirestore preserves fields	126ms
✓	NotificationModel Firestore round-trip fromFirestore tolerates a malformed/legacy doc without throwing	6ms
✓	NotificationModel JSON round-trip + conversions toJson -> fromJson preserves the core fields	6ms
✓	NotificationModel JSON round-trip + conversions toEntity produces an equal NotificationEntity	5ms
✓	NotificationEntity helpers copyWith flips isRead without touching other fields	4ms
✓	NotificationEntity helpers timeSinceText returns "Just now" for a fresh notification	4ms
✓	NotificationsLoaded.actualUnreadCount counts only unread notifications	5ms
✓	NotificationsLoaded.actualUnreadCount is zero when everything is read	4ms

test/unit/notifications/notifications_bloc_test.dart (13)

✓	load emits [Loading, Loaded] with the correct unread count	97ms
✓	load emits [Loading, Empty] when there are no notifications	9ms
✓	load emits [Loading, Error] when the stream yields a Failure	9ms
✓	NotificationsAllCleared (optimistic delete-all) emits NotificationsEmpty IMMEDIATELY before the server delete	12ms
✓	NotificationsAllCleared (optimistic delete-all) clears even when a populated list is currently loaded	10ms
✓	NotificationsAllCleared (optimistic delete-all) calls repository.deleteAll with the user id	12ms
✓	NotificationsUnreadCleared (optimistic drop-unread) drops the unread ones, keeping only read notifications	12ms
✓	NotificationsUnreadCleared (optimistic drop-unread) emits NotificationsEmpty when every notification was unread	10ms
✓	NotificationsUnreadCleared (optimistic drop-unread) still calls deleteAllUnread on the server	9ms
✓	single-item actions delegate to the repository NotificationDeleted deletes via the repository	7ms
✓	single-item actions delegate to the repository NotificationMarkedAsRead marks it read	9ms
✓	single-item actions delegate to the repository NotificationsMarkedAllAsRead marks all read	8ms
✓	single-item actions delegate to the repository NotificationTapped marks the tapped notification read	8ms

Membership / Coins 46 tests · 46 pass · 0 skip · 0 fail · 640ms

test/unit/coins/coin_balance_test.dart (9)

✓	CoinBatch isExpired is true only after the expiration instant	28ms
✓	CoinBatch daysUntilExpiration is 0 for an already-expired batch	7ms
✓	CoinBalance batch accounting availableCoins sums only non-expired batches	7ms
✓	CoinBalance batch accounting expiredCoins sums only expired batches	5ms
✓	CoinBalance batch accounting getCoinsExpiringSoon counts live batches inside the 30-day window	6ms
✓	CoinBalance batch accounting hasEnoughCoins compares against availableCoins	5ms
✓	CoinBalance batch accounting an empty balance has zero everywhere	5ms
✓	CoinSource wire mapping fromString round-trips every enum name	7ms
✓	CoinSource wire mapping fromString is case-insensitive and falls back to purchase	5ms

test/unit/coins/coin_models_firestore_test.dart (4)

✓	CoinBalanceModel round-trip toFirestore -> fromFirestore preserves scalars and a batch	165ms
✓	CoinBalanceModel round-trip empty() factory produces a zeroed balance	5ms
✓	CoinTransactionModel round-trip uses the doc id as transactionId and preserves fields	11ms
✓	CoinTransactionModel round-trip type is serialized as its lowercase enum name	7ms

test/unit/coins/coin_transaction_test.dart (11)

✓ displayAmount sign credit is prefixed with +	28ms
✓ displayAmount sign debit is prefixed with -	6ms
✓ description delegates to the reason coinPurchase description includes the amount	7ms
✓ description delegates to the reason dailyLoginStreakReward uses the streak from metadata	5ms
✓ CoinTransactionReason wire mapping fromString round-trips every reason	7ms
✓ CoinTransactionReason wire mapping unknown reason falls back to featurePurchase	6ms
✓ CoinTransactionReason wire mapping every reason has a non-empty displayName	5ms
✓ CoinFeaturePrices.getPrice resolves known features (incl. alias spellings)	6ms
✓ CoinFeaturePrices.getPrice is case-insensitive	5ms
✓ CoinFeaturePrices.getPrice unknown feature costs 0	4ms
✓ CoinFeaturePrices.getPrice gift prices resolve	5ms

test/unit/coins/membership_model_firestore_test.dart (3)

✓ MembershipModel round-trips through Firestore preserving the tier	158ms
✓ tier is stored as the UPPERCASE wire value	9ms
✓ createFreeMembership builds an active FREE membership	6ms

test/unit/coins/membership_tier_test.dart (19)

✓ MembershipTier wire value vs enum name value() is UPPERCASE for every tier	24ms
✓ MembershipTier wire value vs enum name enum name is lowercase (the "user tier" casing)	5ms
✓ MembershipTier.fromString round-trips the canonical UPPERCASE values	5ms
✓ MembershipTier.fromString is case-insensitive	3ms
✓ MembershipTier.fromString legacy BASIC alias maps to silver	5ms
✓ MembershipTier.fromString unknown / empty falls back to free	5ms
✓ MembershipTier ordering & flags priority is strictly increasing free < silver < gold < platinum	5ms
✓ MembershipTier ordering & flags only the TEST tier bypasses the countdown	5ms
✓ MembershipTier ordering & flags every tier has a non-empty displayName	3ms
✓ MembershipRules gating defaults FREE cannot use advanced filters; PLATINUM can	5ms
✓ MembershipRules gating defaults incognito mode unlocks at GOLD (not SILVER)	4ms
✓ MembershipRules gating defaults video chat is a PLATINUM-only perk among the paid tiers	5ms
✓ MembershipRules gating defaults daily direct-match allowance grows with tier	4ms
✓ MembershipRules gating defaults isUnlimited recognizes the -1 sentinel	5ms
✓ Membership validity a null endDate is never expired (lifetime/free)	9ms
✓ Membership validity a past endDate is expired and therefore invalid	13ms
✓ Membership validity inactive membership is invalid even if not expired	5ms
✓ Membership validity isExpiringShow is true within the 7-day window	5ms
✓ Membership validity rules falls back to tier defaults when no custom rules set	5ms

Localization (7 locales) 31 tests · 31 pass · 0 skip · 0 fail · 374ms

test/unit/i18n/arb_key_parity_test.dart (19)

✓	base en ARB declares @@locale == en and is non-empty	24ms
✓	locale de declares the correct @@locale	5ms
✓	locale de has no keys that are absent from en (no orphans)	9ms
✓	locale de contains every en key except the known-untranslated allowlist	6ms
✓	locale es declares the correct @@locale	3ms
✓	locale es has no keys that are absent from en (no orphans)	5ms
✓	locale es contains every en key except the known-untranslated allowlist	3ms
✓	locale fr declares the correct @@locale	4ms
✓	locale fr has no keys that are absent from en (no orphans)	4ms
✓	locale fr contains every en key except the known-untranslated allowlist	5ms
✓	locale it declares the correct @@locale	4ms
✓	locale it has no keys that are absent from en (no orphans)	4ms
✓	locale it contains every en key except the known-untranslated allowlist	4ms
✓	locale pt declares the correct @@locale	3ms
✓	locale pt has no keys that are absent from en (no orphans)	4ms
✓	locale pt contains every en key except the known-untranslated allowlist	5ms
✓	locale pt_BR declares the correct @@locale	4ms
✓	locale pt_BR has no keys that are absent from en (no orphans)	4ms
✓	locale pt_BR contains every en key except the known-untranslated allowlist	5ms

test/unit/i18n/arb_new_keys_test.dart (5)

✓	en ARB defines "communitiesJoinAsPersonalTitle" (skipped if absent)	24ms
✓	en ARB defines "communitiesCreatedManageHint" (skipped if absent)	4ms
✓	en ARB defines "exploreHappeningSoon" (skipped if absent)	4ms
✓	en ARB defines "verifyPhoneFormatError" (skipped if absent)	4ms
✓	at least the four tracked new keys exist in en	3ms

test/unit/i18n/arb_no_mojibake_test.dart (7)

✓	en ARB has no mojobake markers	81ms
✓	de ARB has no mojobake markers	37ms
✓	es ARB has no mojobake markers	24ms
✓	fr ARB has no mojobake markers	22ms
✓	it ARB has no mojobake markers	21ms
✓	pt ARB has no mojobake markers	23ms
✓	pt_BR ARB has no mojobake markers	22ms

Widgets / Rendering 24 tests · 24 pass · 0 skip · 0 fail · 5.52s

test/widget/community_card_test.dart (9)

✓ renders name, member count and type badge	1.34s
✓ renders language badges in upper-case	79ms
✓ shows the last message preview when present	63ms
✓ shows a SponsoredBadge only for sponsored communities	63ms
✓ hides the SponsoredBadge for regular communities	56ms
✓ renders a network image when imageUrl is set	154ms
✓ falls back to a type icon when imageUrl is null	64ms
✓ invokes onTap when the row is tapped	194ms
✓ shows the unread dot when showUnreadIndicator is true	60ms

test/widget/conversation_card_test.dart (8)

✓ shows the other user displayName for a normal 1:1 chat	1.36s
✓ business inquiry shows the businessName instead of the owner name	66ms
✓ business inquiry avatar uses the storefront coverImageUrl	142ms
✓ a NON-business profile keeps the personal displayName	53ms
✓ group conversation shows the group name	52ms
✓ shows a typing indicator when the other user is typing	74ms
✓ renders the unread count badge	94ms
✓ falls back to a person icon when there is no avatar	49ms

test/widget/profile_header_widgets_test.dart (7)

✓ VerifiedBadge renders a check icon	1.25s
✓ VerifiedBadge lays out at the requested size	57ms
✓ BusinessBadge renders the localized label and a storefront icon	76ms
✓ LanguageFlagBadge renders flag emoji for known languages	43ms
✓ LanguageFlagBadge renders nothing for an empty language list	37ms
✓ LanguageFlagBadge caps the number of flags at maxFlags	36ms
✓ Header composition (age + flags under the name) age text and language flags render together beneath the name	63ms

7. Skipped tests (documented)

fake_cloud_firestore does not emulate runTransaction + FieldValue.increment accumulation across sequential transactions, nor the initial frame of .snapshots(). These aggregate cases are re-covered by the emulator layer (B2/B4).

- test/unit/business/rating_service_test.dart → rateBusiness a second distinct rater increments sum and count

- test/unit/business/rating_service_test.dart → rateBusiness re-rating shifts sum by delta, count unchanged
- test/unit/business/rating_service_test.dart → aggregate reads getAggregate computes avg = sum / count
- test/unit/business/rating_service_test.dart → aggregate reads myRating stream emits the viewer current stars

8. Pending — backend & performance (emulator-gated)

PHASE	SUITE	COVERAGE	RUNNER
B1	Firestore Security Rules	@firebase/rules-unit-testing — communities self-join incl. business, owner-only notifications, scoped conversations/coins, mod-only join_requests	Firestore emulator
B2	Cloud Functions	Jest + firebase-functions-test — seeder/remover round-trip, onProfileDeleted cascade, group-chat fanout, announcement fanout, push idempotency, event reminders, backfill	Functions emulator
B3	Index / query validity E2E	Every composite/collection-group query the client issues resolves against real indexes	Firestore emulator
B4	Data-integrity counters	memberCount / unreadCount / attendeeCount / ratingSum+Count stay consistent across join/leave/send/read/rate	Firestore emulator
B5	Performance budgets	Discover ≤300ms, My-communities ≤300ms, page ≤400ms, scroll ≥55fps, cold-start ≤3.5s, CF exec times	emulator + device
B6	E2E mock-user journeys	login→explore→join→chat→rate→notify→delete-all; business persona; tier-gated flows	emulator

GreenGo · greengo_chat · generated by test/userTests/generate_pdf_report.py from flutter test --machine output · 2026-07-15