


# RR61

## COLOR

### OPTIONS



White



Grey /  
Black

White

01

Grey / Black

74



Attention!

Complete final technical data will be available starting from June 2023.

### PART OF

Le Perroquet ø89mm

### DESCRIPTION

Small body spotlight - warm white - DALI - MEDIUM - 17W  
2080lm - 3000K - CRI 90

**warm white**

**DALI**

**MEDIUM**

**17W 2080lm**

**3000K**



**CRI 90**



## Accessories to order

- Optical accessories
- 9528 - Horizontal directional fins
- 9532 - 45° cylindrical
- Mounting accessories
- MXZ2 - Ceiling base
- MXZ3 - Recessed base Hole for installation 110-115mm
- MXZ5 - Casing for adapter IP40

# OPTIONAL ACCESSORIES



### Optical accessories



- 



**9528**  
Horizontal directional fins
- 

**9532**  
45° cylindrical

### Mounting accessories

- 

**MXZ2**  
Ceiling base
- 

**MXZ3**  
Recessed base Hole for installation 110-115mm
- 

**MXZ5**  
Casing for adapter IP40

# TECHNICAL DATA


LAST UPDATE: 31/05/2023

## DESCRIPTION


Adjustable spotlight with adapter for installation on an electrified DALI track. High yield LED lamp with high color rendering index. Luminaire body made of die-cast aluminium and thermoplastic material. Swivel joints allow the spotlight to be rotated by 360° about the vertical axis and tilted by 90° tilting relative to the horizontal plane. Mechanical aiming locks fitted on both the spotlight and adapter allow rotation and tilting movements to be locked in position to ensure efficient light aiming even after the original installation or during maintenance. The optical assembly is equipped with an accessory holding ring designed to contain a flat accessory. Another external component can also be applied - asymmetric screen / directional flaps; the external accessories can rotate freely about the spotlight longitudinal axis. DALI dimmable power supply unit integrated in the spotlight body.

## PRODUCT DETAILS

Size (mm)	ø89x208
Weight	.7 (Kg)



## TECHNICAL PERFORMANCE



Class I



Class I



IP20 - protected against penetration of solids larger than 12 mm, not protected against penetration of liquids.



IP40: protected against the penetration of solids larger than 1 mm, not protected against penetration of liquids. <br /> for optical assembly the



Complies with EN60598-1 and pertinent regulations

## PHYSICAL PROPERTIES

Weight	.7 (Kg)
Material	die-cast aluminium and thermoplastic

## PRODUCT CERTIFICATION



# LIGHTING

## LIGHTNING PARAMETERS

Im system	1705.60
W system	22.30
Im source	2080.00
W source	17.00
Luminous efficiency (real value)	76.48
Im in emergency mode	-
Total light flux at or above an angle of 90°	0
Light output ratio (LOR)	82
CRI	90.00
Colour temperature	3000K

# ELECTRICAL

## ELECTRICAL PARAMETERS

Ballast losses	5.3
No. of lamps for optical assembly	1
ZVEI code	LED
Power Supply	Driver Electronic included
Mounting options	Integral

# INSTALLATION

## DESCRIPTION

Installation on an electrified track.

Mounting	dali track
Wiring	Integrated DALI dimmer power supply unit.

## ADDITIONAL INFORMATION

Collection of recessed downlights for architectural applications. Excellent build quality with features for the most demanding professional applications. Available in 2 apertures with complete light distributions offering fixed, adjustable and wall washer optics. Generous light outputs with excellent chromatic performance and enhanced visual comfort (UGR<10). Also available with a Safety glass with a sealing system to increase the IP rating (IP65)