DualPI2 Prague T Prague vs. Cubic Prague vs. BBRv2 2.5 Throughput std (% of 17.5) 0.6 0.3 0.2 0.3 0.3 0.2 0.6 0.4 4.6 0.7 0.3 0.1 0.2 0.1 0.1 0.2 8.0 0.7 2.0 0.7 0.5 2.4 0.7 0.1 0.1 16 1.0 0.4 0.4 0.4 0.4 0.4 0.4 0.8 0.6 1.3 2.7 2.3 0.4 1.5 0.9 0.9 0.7 0.6 8.0 2.1 1.1 1.4 1.4 1.4 0.9 0.9 0.7 0.9 32 -0.7 1.6 1.3 1.4 1.3 1.1 1.1 0.9 1.9 1.0 1.0 0.6 0.4 0.1 64 of 5.0 data 0.5 1.9 1.6 1.5 1.5 0.8 0.9 2.2 0.8 0.7 0.5 0.6 0.3 0.0 128 -2.5 rate)Prague T 256 32 128 8 16 32 128 64 16 64 256 8 4 4 RTT (ms) CoDel Prague vs. Cubic Prague vs. BBRv2 0.3 2.1 0.9 2.9 3.5 3.4 0.6 0.7 1.1 1.9 1.5 0.5 0.6 4 --17.5 Throu 1.1 2.5 0.6 1.7 4.2 1.3 0.3 0.8 0.8 1.1 1.8 0.6 2.7 3.1 8 -12.5 10.0 10.0 0.6 2.8 1.0 1.5 1.5 2.8 2.2 0.8 0.7 1.5 3.7 1.1 1.4 0.9 16 1.1 4.3 1.2 0.9 1.9 1.9 2.5 3.4 1.3 1.5 3.1 1.4 1.5 1.2 32 -7.5 (% 6.3 5.4 3.3 3.9 2.0 1.7 1.3 64 1.3 1.4 2.4 1.9 1.7 1.4 1.6 of 5.0 data rate) 3.1 2.0 2.2 4.1 4.3 4.7 7.7 6.0 2.4 1.3 1.1 1.8 1.1 0.9 128 -2.5 128 32 64 8 16 32 64 128 256 8 16 4 4 256 0.0 Data Rate (Mb/s)