## DualPI2 Prague T Prague vs. BBRv2 Prague vs. Cubic Throughput std (% o 0.7 0.6 0.7 0.5 0.6 1.2 1.4 8.0 0.7 1.0 1.5 2.3 1.2 1.0 1.4 1.9 0.7 0.7 4.0 4.4 2.4 1.0 0.7 1.0 0.7 0.8 1.0 0.5 8 -1.8 2.0 5.4 16 0.9 1.3 1.2 1.0 1.6 2.6 0.9 1.2 2.1 5.3 3.0 1.0 0.7 1.7 2.5 3.5 1.4 3.7 2.1 3.5 2.4 2.6 4.8 1.7 32 -2.3 4.0 3.4 2.7 1.5 2.9 2.4 2.1 2.6 2.7 1.7 3.2 3.9 2.3 64 of 5.0 data 1.2 3.7 3.0 2.2 5.4 2.6 2.2 2.8 128 -1.7 4.0 2.3 2.7 3.8 0.4 2.5 rate)Prague T 32 128 256 8 32 128 64 64 16 16 8 4 256 4 RTT (ms) CoDel Prague vs. Cubic Prague vs. BBRv2 1.4 9.4 0.5 1.1 6.5 13.0 0.9 2.9 2.5 7.6 0.6 1.0 1.1 0.6 4 --17.5 Throu 11.1 0.6 3.3 4.1 0.3 0.7 1.0 1.3 1.6 1.8 0.6 2.1 1.4 2.3 12.5 - 10.0 - 10.0 3.2 0.5 0.9 8.0 2.0 2.6 8.0 0.7 1.5 3.0 3.4 1.3 1.3 16 1.4 1.3 3.0 3.1 4.7 1.2 0.9 1.8 1.1 0.8 1.1 1.9 2.8 1.5 1.1 32 -7.5 (% 6.2 6.3 1.4 1.9 2.4 3.3 5.3 2.4 1.6 1.6 64 1.1 2.0 1.7 1.3 약 5.0 data rate) 1.6 2.4 3.7 4.9 4.0 6.1 7.1 2.7 2.5 1.6 1.1 0.9 0.8 1.5 128 -2.5 128 256 16 32 8 32 8 16 64 128 4 64 4 256 0.0

Data Rate (Mb/s)