

# MaxiCharger DC HiPower

360kW/640kW



# MaxiCharger DC HiPower

## Unleash The Power Of Charging



### Ultra-Fast

**Deliver a seamless and efficient charging experience**

- Max. 650A liquid-cooling and low-temp fast charging tech provides up to 250 miles of range in 10 mins
- Smart Power Distribution can charge up to 8 vehicles simultaneously, increasing efficiency and utilization



### Intelligent

**Unlock new levels of battery health and charging Intelligence**

- Revolutionary AI algorithm increases EV battery life by up to 20%
- Intelligent charging navigation planning system enhances battery health



### Future-Proof

**Built for energy-saving and a green future**

- Dynamic module dispatching and load balancing reduce power expansion, saving up to 20,000 kWh per year
- Compatible with solar power, energy storage, and EMS for efficient energy management



### Robust

**Designed for high reliability to reduce costs**

- Ultimate modularity for easy O&M with single person operation and 98% availability
- Self-protection system includes 21 system-level safety features



# Technical Specification (Dispenser)

## DC Output Connection

## Liquid Cooling Dispenser

## Boost Dispenser

Charging mode  
Output1 power  
Output1 voltage  
Output1 current  
Output2 power  
Output2 voltage  
Output2 current  
Number of outputs

Mode 4: CCS1  
360kW(Max. 480kW)  
150-950V  
CCS1 500A (Max. 650A)  
360kW(Max. 480kW)  
150-950V  
CCS1 500A (Max. 650A)  
2\*CCS1

Mode 4: CCS1  
240kW  
150-950V  
CCS1 300A (Max. 400A), 200A (Optional)  
240kW  
150-950V  
CCS1 300A (Max. 400A), 200A (Optional)  
2\*CCS1, or 1\*CCS1+1\*CHAdemo

## General Characteristics

## Liquid Cooling Dispenser

## Boost Dispenser

Enclosure rating  
Operating altitude  
Operating temperature range  
Storage temperature range  
Mounting  
Dimensions (H×W×D)  
Screen type  
Cable length

NEMA 3S  
3000m  
-31°F ~ +131°F (-35°C ~ +55°C)  
-40°F ~ +158°F (-40°C ~ +70°C)  
Floor Standing  
2075×580×320 mm  
8/15.6 inch LCD Touch Screen (1920\*1080)  
4m standard; 5m or 7m Optional

NEMA 3S  
3000m  
-31°F ~ +131°F (-35°C ~ +55°C)  
-40°F ~ +158°F (-40°C ~ +70°C)  
Floor Standing  
2075×580×320 mm  
8/15.6 inch LCD Touch Screen (1920\*1080)  
4m standard; 5m or 7m Optional

## User Interface

## Liquid Cooling Dispenser

## Boost Dispenser

Status indication  
User interface  
Connectivity  
Communication protocols  
User authentication

LED/LCD/APP  
Autel Charge APP; Autel Charge Cloud  
Ethernet  
OCPP 1.6J (OCPP 2.0.1 Optional)  
APP, RFID card, QR code, Credit Card (Optional)

LED/LCD/APP  
Autel Charge APP; Autel Charge Cloud  
Ethernet  
OCPP 1.6J (OCPP 2.0.1 Optional)  
APP, RFID card, QR code, Credit Card (Optional)

## Software Update

## Liquid Cooling Dispenser

## Boost Dispenser

Software update

OTA updates via web portal

OTA updates via web portal

## Certification and Standards

## Liquid Cooling Dispenser

## Boost Dispenser

Safety standards  
  
Certification  
Design life  
Warranty

UL 2202, UL 2231-1, UL 2231-2,  
NEC Article 625, CSA C22.2 No. 107.1-16;  
CSA, FCC part 15 Class A  
10 years  
24 months, warranty extension possible

UL 2202, UL 2231-1, UL 2231-2,  
NEC Article 625, CSA C22.2 No. 107.1-16;  
CSA, FCC part 15 Class A  
10 years  
24 months, warranty extension possible

# Technical Specification (Cabinet)

## AC Input

### 360kW

### 640kW

Earthing system  
Input voltage  
Input frequency  
Power factor  
Harmonic distortion (THDi)

3P, PE (No neutral)  
3-phase 480V AC  $\pm 15\%$  (2 Routes)  
60Hz  
 $\geq 0.99$   
 $\leq 5\%$

3P, PE (No neutral)  
3-phase 480V AC  $\pm 15\%$  (2 Routes)  
60Hz  
 $\geq 0.99$   
 $\leq 5\%$

## General Characteristics

### 360kW

### 640kW

Number of power modules  
Power of each module  
Connectivity  
Peak efficiency  
Enclosure rating  
Operating altitude  
Operating temperature range  
Storage temperature range  
Mounting  
Dimensions (H×W×D)

9  
40kW  
4G, Wi-Fi, Ethernet  
 $\geq 96\%$   
NEMA 3S  
3000m  
-31°F ~ +131°F (-35°C ~ +55°C)  
-40°F ~ +158°F (-40°C ~ +70°C)  
Floor Standing  
2000×1700×900 mm

16  
40kW  
4G, Wi-Fi, Ethernet  
 $\geq 96\%$   
NEMA 3S  
3000m  
-31°F ~ +131°F (-35°C ~ +55°C)  
-40°F ~ +158°F (-40°C ~ +70°C)  
Floor Standing  
2000×1700×900 mm

## Certification and Standards

### 360kW

### 640kW

Safety standards  
Certification  
Design life  
Warranty

UL 2202, UL 2231-1, UL 2231-2,  
NEC Article 625, CSA C22.2 No. 107.1-16;  
CSA, FCC part 15 Class A  
10 years  
24 months, warranty extension possible

UL 2202, UL 2231-1, UL 2231-2,  
NEC Article 625, CSA C22.2 No. 107.1-16;  
CSA, FCC part 15 Class A  
10 years  
24 months, warranty extension possible

\* All pictures shown are for illustration purpose only, actual product and specifications may vary due to product enhancement

# AUTEL<sup>®</sup>

**Autel Intelligent Technology Corp., Ltd**

☎ Phone: (844) 765-0150  
✉ E-mail: [evsupport@autel.com](mailto:evsupport@autel.com)  
🌐 Website: [autelenergy.com](http://autelenergy.com)

**Autel Energy**

