



1.a) Find the x and y components of each displacement vector shown below using the given coordinate axes.




i)



$$\Delta d_x = 120 \text{ m} \cos 35^\circ = 98.3 \text{ m}$$

$$\Delta d_y = 120 \text{ m} \sin 35^\circ = 68.8 \text{ m}$$


ii)



$$\Delta d_x = 0$$

$$\Delta d_y = -5.4 \text{ km}$$


iii)




$$\Delta d_x = 86 \text{ m} \cos 12^\circ = -84.1 \text{ m}$$

$$\Delta d_y = -86 \text{ m} \sin 12^\circ = -17.9 \text{ m}$$

b) Find the x and y components of each displacement vector shown below using the given coordinate axes.




i)



$$\Delta d_x = 4.2 \text{ m} \sin 75^\circ = 4.06 \text{ m}$$

$$\Delta d_y = 4.2 \text{ m} \cos 75^\circ = -1.09 \text{ m}$$


ii)




$$\Delta d_x = -2.9 \text{ km} \cos 50^\circ = -1.86 \text{ km}$$

$$\Delta d_y = -2.9 \text{ km} \sin 50^\circ = -2.22 \text{ km}$$

2. Perform the following vector operations using component analysis. Recombine the components of the resultant to express the resultant in magnitude and direction form. Use the x/y coordinate axes shown below for your analysis.



a)  $\Delta d_1 = 85.0 \text{ km} [36^\circ \text{ W of N}]$ ,  $\Delta d_2 = 122.0 \text{ km} [15^\circ \text{ S of W}]$ ,  $\Delta d_R = \Delta d_1 + \Delta d_2 = ?$



$$\Delta d_{Rx} = \Delta d_{1x} + \Delta d_{2x}$$

$$= -85.0 \sin 36^\circ - 122.0 \cos 15^\circ$$

$$= -167.80 \text{ km}$$

$$\Delta d_y = \Delta d_{1y} + \Delta d_{2y}$$

$$= 85.0 \cos 36^\circ - 122.0 \sin 15^\circ$$

$$= 37.19 \text{ km}$$

$$\Delta d_R = \sqrt{(-167.80)^2 + (37.19)^2} = 171.87 \text{ km}$$

$$\theta = \tan^{-1}\left(\frac{37.19}{167.80}\right) = 12.5^\circ$$

$$\Delta d_R = 172 \text{ km} [12.5^\circ \text{ N of W}]$$

b)  $\Delta d_1 = 250 \text{ m} [\text{E}]$ ,  $\Delta d_2 = 560 \text{ m} [35^\circ \text{ S of E}]$ ,  $\Delta d_3 = 370 \text{ m} [18^\circ \text{ W of S}]$ ,  $\Delta d_R = \Delta d_1 + \Delta d_2 + \Delta d_3 = ?$



$$\Delta d_{Rx} = \Delta d_{1x} + \Delta d_{2x} + \Delta d_{3x}$$

$$= 250 + 560 \cos 35^\circ - 370 \sin 18^\circ$$

$$= 594.39 \text{ m}$$

$$\Delta d_y = \Delta d_{1y} + \Delta d_{2y} + \Delta d_{3y}$$

$$= 0 - 560 \sin 35^\circ - 370 \cos 18^\circ$$

$$= -673.09 \text{ m}$$

$$\Delta d_R = 898 \text{ m} [49^\circ \text{ S of E}]$$

$$\Delta d_R = \sqrt{594.39^2 + 673.09^2} = 898 \text{ m}$$

$$\theta = \tan^{-1}\left(\frac{673.09}{594.39}\right) = 49^\circ$$