Access Tokens – Coplito (Bitbucket, Confluence & Jira)

How to Create Access Tokens — Bitbucket, Confluence & Jira

This guide walks you through creating Personal Access Tokens (PATs) for **Bitbucket**, **Confluence**, and **Jira**. These tokens are used by AI tools (e.g. GitHub Copilot agents) and scripts to authenticate with Atlassian services without using your password.

> ⓘ **Why do I need these?** Personal Access Tokens let AI agents and automation scripts access Atlassian APIs securely on your behalf — no password sharing required. Tokens can be revoked anytime.

Quick Reference

Service	Token Type	Environment Variable	Used By
Bitbucket	HTTP Access Token	`BITBUCKET_PAT`	Git operations, API calls
Confluence	Personal Access Token	`CONFLUENCE_PAT`	fetch-confluence-page agent
Jira	Personal Access Token	`JIRA_PAT`	Jira API queries, automation

---

1 Bitbucket — Create an HTTP Access Token

> ⚠ Bitbucket Server/Data Center uses **HTTP Access Tokens** (also called Personal Access Tokens). These are different from OAuth tokens.

Step-by-step

Step	Action	Details
1	**Open Bitbucket**	Navigate to your Bitbucket instance in a browser `https://bitbucket.srv.westpac.com.au`
2	**Go to Profile**	Click your **avatar / profile icon** in the top-right corner
3	**Manage Account**	Select **"Manage account"** from the dropdown menu
4	**HTTP Access Tokens**	In the left sidebar, click **"HTTP access tokens"** (under Security)
5	**Create Token**	Click the **"Create token"** button
6	**Token Name**	Enter a descriptive name, e.g. `copilot-agent-token`
7	**Permissions**	Select permissions: **Repository Read** (minimum for git clone/pull) **Repository Write** (if you need to push) **Project Read** (for listing repos)

8	**Expiry**	Set an expiry date (recommended: **360 days**). You can always create a new one.
9	**Create**	Click **"Create"** — **copy the token immediately!** It won't be shown again.
10	**Save to shell**	Add to `~/.zshrc`: `export BITBUCKET_PAT_TOKEN="your-token-here"` Then run: `source MAC: ~/.zshrc.  Windows: ~/.bashrc.`

Navigation Path

```
Bitbucket -> Profile Icon (top-right) -> Manage Account -> HTTP access tokens -> Create token

+-----------------------------------------+
|  Token name:  [ copilot-agent-token    ] |
|                                          |
|  Permissions:                            |
|  [x] Repository Read                    |
|  [x] Repository Write                   |
|  [x] Project Read                       |
|                                          |
|  Expiry: [ 360 days ]                     |
|                                          |
|           [ Create ]                     |
+-----------------------------------------+
```

---

2 Confluence — Create a Personal Access Token

> This is the token used by the **fetch-confluence-page** agent to read Confluence pages directly from VS Code.

Step-by-step

Step	Action	Details
1	**Open Confluence**	Navigate to `https://confluence.srv.westpac.com.au`
2	**Go to Profile**	Click your **avatar / profile icon** in the top-right corner
3	**Settings**	Select **"Settings"** from the dropdown
4	**Personal Access Tokens**	In the left sidebar, click **"Personal Access Tokens"**
5	**Create Token**	Click **"Create token"**
6	**Token Name**	Enter a name, e.g. `copilot-confluence-agent`
7	**Expiry**	Choose expiry (recommended:**360 days**) or leave as automatic
8	**Create**	Click **"Create"** — **copy the token immediately!**

9	**Save to shell**	Add to `~/.zshrc`: `export CONFLUENCE_PAT_TOKEN="your-token-here"` Then run: `source MAC: ~/.zshrc.  Windows: ~/.bashrc.`

Navigation Path

```
Confluence -> Profile Icon (top-right) -> Settings -> Personal Access Tokens -> Create token

+-----------------------------------------+
|  Token name:  [ copilot-confluence     ] |
|                                         |
|  Automatic expiry: [x]                  |
|  Expiry date: [ 2026-05-23 ]            |
|                                         |
|           [ Create ]                    |
+-----------------------------------------+

After creation:
+-----------------------------------------+
|  Token created successfully!            |
|                                         |
|  MTQ5ODE1MjY5NDkyOslIcUCT32eWBn...      |
|                                         |
|  WARNING: Copy now, won't see it again! |
|           [ Copy ]                      |
+-----------------------------------------+
```

Verify it works

```
# Test your Confluence token
curl -s -H "Authorization: Bearer $CONFLUENCE_PAT_TOKEN" \
  "https://confluence.srv.westpac.com.au/rest/api/user/current" | python3 -c "
import json, sys
d = json.load(sys.stdin)
print(f'Authenticated as: {d.get(\"displayName\", \"unknown\")}')"
```

---

3 Jira — Create a Personal Access Token

Step-by-step

Step	Action	Details
1	**Open Jira**	Navigate to `https://jira.srv.westpac.com.au`
2	**Go to Profile**	Click your **avatar / profile icon** in the top-right corner
3	**Profile**	Select **"Profile"** from the dropdown
4	**Personal Access Tokens**	In the left sidebar, click **"Personal Access Tokens"**

5	**Create Token**	Click **"Create token"**
6	**Token Name**	Enter a name, e.g. `copilot-jira-agent`
7	**Expiry**	Choose expiry (recommended:**360 days**) or leave as automatic
8	**Create**	Click **"Create"** — **copy the token immediately!**
9	**Save to shell**	Add to `~/.zshrc`: `export JIRA_PAT_TOKEN="your-token-here"` Then run: `source MAC: ~/.zshrc.  Windows: ~/.bashrc.`

Navigation Path

```
Jira -> Profile Icon (top-right) -> Profile -> Personal Access Tokens -> Create token

+-----------------------------------------+
|  Token name:  [ copilot-jira-agent     ] |
|                                          |
|  Automatic expiry: [x]                   |
|  Expiry date: [ 2026-05-23 ]             |
|                                          |
|           [ Create ]                     |
+-----------------------------------------+
```

Verify it works

```
# Test your Jira token
curl -s -H "Authorization: Bearer $JIRA_PAT_TOKEN" \
  "https://jira.srv.westpac.com.au/rest/api/2/myself" | python3 -c "
import json, sys
d = json.load(sys.stdin)
print(f'Authenticated as: {d.get(\"displayName\", \"unknown\")}')"
```

Final Setup — Add All Tokens to Your Shell

Add all three tokens to your `~/.zshrc` (macOS) or `~/.bashrc` (Linux):

```
# === Atlassian Access Tokens ===
export BITBUCKET_PAT_TOKEN="your-bitbucket-token"
export CONFLUENCE_PAT_TOKEN="your-confluence-token"
export JIRA_PAT_TOKEN="your-jira-token"
```

Then reload:

```
source ~/.zshrc
```

Security Reminders

- **Never commit tokens** to source control (Git). They belong in your shell config only.
- **Never share tokens** in Slack, email, or Confluence pages.
- **Set expiry dates** — 360 days is recommended. Renew before they expire.
- **Revoke immediately** if compromised — go back to the same settings page and delete the token.
- **Use minimal permissions** — only grant what the tool needs (usually read-only).

Troubleshooting

Problem	Solution
`401 Unauthorized`	Token expired or incorrect. Create a new one.
`404 Not Found`	You don't have access to the page/resource, or the ID is wrong.
Token not found in terminal	Run `source ~/.zshrc` or restart your terminal.
Token works in terminal but not in VS Code	Restart VS Code so it picks up the new environment variables.
"Personal Access Tokens" not visible	Your admin may have disabled PATs. Contact IT support.

---

4 Using Access Tokens with Amp (AI Coding Agent)

> **What is Amp?** Amp is an AI coding agent (from ampcode.com) that runs in VS Code. It can connect to Bitbucket, Confluence, Jira, and Splunk via **MCP (Model Context Protocol) servers** to read pages, query issues, search logs, and more — all from within your editor.

How it works

Amp uses MCP servers defined in `.vscode/mcp.json` in your workspace. Each server uses the same Personal Access Tokens you created above, referenced via environment variables from your `~/.zshrc`.

Step-by-step

Step	Action	Details
1	**Install Amp**	Install the Amp extension in VS Code from ampcode.com

2	**Ensure tokens are in ~/.zshrc**	You should already have these from the steps above:
		`export BITBUCKET_PAT_TOKEN="your-token"`
		`export CONFLUENCE_PAT_TOKEN="your-token"`
		`export JIRA_PAT_TOKEN="your-token"`
		`export SPLUNK_PASSWORD="your-password"`

3	**Create .vscode /mcp.json**	In your workspace root, create `.vscode/mcp.json` with the MCP server configuration (see below)
4	**Reload VS Code**	Run **Cmd+Shift+P "Developer: Reload Window"** so Amp picks up the MCP servers
5	**Verify in Amp**	Open the Amp chat panel — the MCP servers should show as connected. You can now ask Amp to read Confluence pages, query Jira issues, search Bitbucket repos, and query Splunk logs.

.vscode/mcp.json Configuration

Create this file in your workspace:

```
{
  "servers": {
    "splunk": {
      "type": "stdio",
      "command": "node",
      "args": [
        "${workspaceFolder}/ai-common/tools/nodemcp/cli.js",
        "--layers",
        "splunk",
        "--verbose"
      ],
      "env": {
        "SPLUNK_HOST": "https://wbc.splunkcloud.com",
        "SPLUNK_USERNAME": "your-username@westpacgroup.com",
        "SPLUNK_PASSWORD": "${env:SPLUNK_PASSWORD}"
      }
    },
    "bitbucket": {
      "type": "stdio",
      "command": "npx",
      "args": ["-y", "mcp-bitbucket-server@latest"],
      "env": {
        "BITBUCKET_URL": "https://bitbucket.srv.westpac.com.au",
        "BITBUCKET_TOKEN": "${env:BITBUCKET_PAT_TOKEN}"
      }
    },
    "confluence": {
      "type": "stdio",
      "command": "npx",
      "args": ["-y", "mcp-confluence-server"],
      "env": {
        "CONFLUENCE_BASE_URL": "https://confluence.srv.westpac.com.au",
        "CONFLUENCE_PAT": "${env:CONFLUENCE_PAT_TOKEN}"
      }
    },
    "jira": {
      "type": "stdio",
      "command": "npx",
      "args": ["-y", "mcp-jira-server"],
      "env": {
        "JIRA_BASE_URL": "https://jira.srv.westpac.com.au",
        "JIRA_PAT": "${env:JIRA_PAT_TOKEN}"
      }
    }
  }
}
```

Example Usage in Amp

Once configured, you can ask Amp things like:

- **Confluence:** *"Read the Confluence page at https://confluence.srv.westpac.com.au/pages/viewpage.action?pageId=12345"*
- **Jira:** *"Show me the details of Jira ticket ART-12345"*
- **Bitbucket:** *"Find the repository galaxy-account-microfrontend in Bitbucket"*
- **Splunk:** *"Search Splunk for errors in the last 24 hours for galaxy-account"*

Notes

- The `${env:VAR_NAME}` syntax in `mcp.json` tells VS Code to read the variable from your shell environment. Make sure VS Code is launched from a terminal where `~/.zshrc` has been sourced, or restart VS Code after setting the variables.
- The **splunk** MCP server requires the `ai-common` repository to be cloned in your workspace.
- MCP packages (`mcp-bitbucket-server`, `mcp-confluence-server`, `mcp-jira-server`) are installed automatically via `npx` on first use.