

# L14

- Clicker questions on using built-in abstract functions
  - match the argument and result of your function
  - to argument and result of one or more built-in abstract functions
- multi-type fold functions
  - [https://en.wikipedia.org/wiki/Fold\\_\(higher-order\\_function\)](https://en.wikipedia.org/wiki/Fold_(higher-order_function))
  - easy data traversal shows up in most languages (visitor pattern etc.)
  - designing
  - using
  - complications

```
;; Course is (make-course Natural Natural (listof Course))
```

(listof Course) is one of:

- empty
- (cons Course (listof Course))

;; Course is (`make-course` Natural Natural (listof Course))

MR

(listof Course) is one of:

MR

- `empty`

SR

- (`cons` Course (listof Course))

```
(define (fn-for-course c)
  (local [(define (fn-for-course c)
            (... (course-number c)
                (course-credits c)
                (fn-for-loc (course-dependents c))))
          (define (fn-for-loc loc)
            (cond [(empty? loc) (...)]
                  [else
                   (... (fn-for-course (first loc))
                       (fn-for-loc (rest loc)))]))]
    (fn-for-course c)))
```

C1

C2

B1

;; Course is (make-course Natural Natural (listof Course))

MR

(listof Course) is one of:

MR

- empty

SR

- (cons Course (listof Course))

```
(define (fn-for-course c)
  (local [(define (fn-for-course c)
            (... (course-number c)
                  (course-credits c)
                  (fn-for-loc (course-dependents c))))
          (define (fn-for-loc loc)
            (cond [(empty? loc) (...)]
                  [else
                   (... (fn-for-course (first loc))
                        (fn-for-loc (rest loc)))]))]
    (fn-for-course c)))
```

C1

C2

B1

;; Course is (`make-course` Natural Natural (listof Course))

MR

(listof Course) is one of:

MR

- `empty`

SR

- (`cons` Course (listof Course))

```
(define (fn-for-course c)
  (local [(define (fn-for-course c)
            (... (course-number c)
                  (course-credits c)
                  (fn-for-loc (course-dependents c))))
          (define (fn-for-loc loc)
            (cond [(empty? loc) (...)]
                  [else
                   (... (fn-for-course (first loc))
                        (fn-for-loc (rest loc)))]))]
    (fn-for-course c)))
```

C1

C2

B1

;; Course is (`make-course` Natural Natural (listof Course))

MR

(listof Course) is one of:

MR

- `empty`

SR


- (`cons` Course (listof Course))

```
(define (fn-for-course c)
  (local [(define (fn-for-course c)
            (... (course-number c)
                (course-credits c)
                (fn-for-loc (course-dependents c))))
          (define (fn-for-loc loc)
            (cond [(empty? loc) (...)]
                  [else
                   (... (fn-for-course (first loc))
                       (fn-for-loc (rest loc)))]))]
    (fn-for-course c)))
```


C1

C2

B1




| C1 | C2 | B1 |
|----|----|----|
|    |    |    |
|    |    |    |
|    |    |    |
|    |    |    |



|               | <b>C1</b>      | <b>C2</b> | <b>B1</b> |
|---------------|----------------|-----------|-----------|
| All nums      | (cons num rmr) | append    | empty     |
| Total credits | (+ cr rmr)     | +         | 0         |
|               |                |           |           |
|               |                |           |           |





|                    | <span style="color: red;">C1</span>     | <span style="color: red;">C2</span> | <span style="color: red;">B1</span> |
|--------------------|---|-------------------------------------|-------------------------------------|
| All nums           | (cons num rmr)                          | append                              | empty                               |
| Total credits      | (+ cr rmr)                              | +                                   | 0                                   |
| Courses w/ credits | (if (>= cr n)<br>(cons <C> rmr)<br>rmr) | append                              | empty                               |
| find               |   |                                     |                                     |

no access to actual course

whole tree every time