Wall time per step: Parse 1M PBMC

Seconds per step. Colour is scaled per step and size: fastest framework 0, slowest 1, on square−root seconds.

100k (69,412 cells)

	bixverse mtx	bixverse h5ad	bixverse GPU*	bixverse MLX*	Scanpy mtx	Scanpy h5ad	Scanpy dask	scrapper mtx	scrapper h5ad	Seurat std mtx	Seurat std h5ad	Seurat BPCells
load	10	6.0	5.8	5.5	19	2.3	6.1	38	6.5	43	10	15
qc	0.7	0.8	0.5	0.4	0.7	0.8	1.1	0.5	0.5	2.6	2.7	1.2
normalise	n/a	n/a	n/a	n/a	2.0	1.9	0.0	0.1	0.1	0.1	0.1	0.5
hvg	0.3	0.3	0.3	0.3	1.4	1.4	1.7	0.2	0.2	4.0	4.0	4.0
pca	1.3	1.2	0.5	0.4	1.4	1.4	4.0	1.7	1.7	7.1	6.3	73
harmony	0.6	0.6	0.6	0.4	0.6	0.6	0.5	12	12	13	13	14
knn_snn	2.1	2.1	1.2	1.1	27	27	24	4.3	4.6	5.3	5.4	5.5
cluster	0.8	1.0	0.8	0.7	2.0	2.0	1.9	8.8	8.7	18	18	18
cluster_fast	0.8	0.8	0.4	0.3	n/a	n/a	n/a	10	11	n/a	n/a	n/a
umap	2.6	2.6	0.6	0.5	27	27	26	32	33	35	35	35
dge	0.7	0.7	0.6	0.6	56	52	–	6.2	6.3	15	16	196
tsne_default	26	26	24	24	96	95	102	n/a	n/a	66	71	71
tsne_fft	7.6	7.9	2.3	2.1	32	32	31	n/a	n/a	24	24	24
tsne_quick	4.6	4.8	3.2	2.8	n/a	n/a	n/a	17	18	n/a	n/a	n/a
total (no tSNE)	19	15	11	9.9	137	116	65	104	73	143	110	361

500k (346,259 cells)

	bixverse mtx	bixverse h5ad	bixverse GPU*	bixverse MLX*	Scanpy mtx	Scanpy h5ad	Scanpy dask	scrapper mtx	scrapper h5ad	Seurat std mtx	Seurat std h5ad	Seurat BPCells
load	55	27	30	23	OOM	12	23	OOM	162	OOM	OOM	70
qc	1.9	1.9	1.4	1.3	–	3.8	4.0	–	2.2	–	–	4.2
normalise	n/a	n/a	n/a	n/a	–	3.5	0.0	–	0.4	–	–	2.5
hvg	0.9	1.1	0.8	0.8	–	3.2	5.0	–	0.9	–	–	14
pca	2.5	2.4	0.9	1.3	–	5.7	9.8	–	10	–	–	350
harmony	2.1	2.2	1.3	0.6	–	2.4	2.3	–	87	–	–	92
knn_snn	11	11	5.8	5.2	–	31	27	–	26	–	–	33
cluster	4.0	4.1	3.3	3.1	–	14	13	–	89	–	–	111
cluster_fast	12	12	1.9	1.6	n/a	n/a	n/a	–	117	n/a	n/a	n/a
umap	22	22	2.5	2.4	–	155	153	–	150	–	–	198
dge	2.6	2.6	2.4	2.3	–	602	–	–	36	–	–	953
tsne_default	150	149	132	129	–	796	806	n/a	n/a	–	–	598
tsne_fft	37	38	9.5	13	–	109	109	n/a	n/a	–	–	110
tsne_quick	24	25	14	13	n/a	n/a	n/a	–	96	n/a	n/a	n/a
total (no tSNE)	102	75	48	40	failed	832	237	failed	565	failed	failed	1,829

full (684,932 cells)

	bixverse mtx	bixverse h5ad	bixverse GPU*	bixverse MLX*	Scanpy mtx	Scanpy h5ad	Scanpy dask	scrapper mtx	scrapper h5ad	Seurat std mtx	Seurat std h5ad	Seurat BPCells
load	102	74	64	47	OOM	OOM	40	OOM	OOM	OOM	OOM	143
qc	3.6	4.4	2.5	2.3	–	–	7.4	–	–	–	–	9.4
normalise	n/a	n/a	n/a	n/a	–	–	0.0	–	–	–	–	4.6
hvg	1.6	1.7	1.5	1.4	–	–	8.5	–	–	–	–	27
pca	4.4	4.2	3.4	2.3	–	–	17	–	–	–	–	703
harmony	3.6	3.7	2.2	1.1	–	–	4.5	–	–	–	–	218
knn_snn	24	24	12	11	–	–	33	–	–	–	–	70
cluster	8.3	8.3	6.9	6.9	–	–	30	–	–	–	–	258
cluster_fast	38	39	4.8	3.8	n/a	n/a	n/a	–	–	n/a	n/a	n/a
umap	50	50	5.6	5.2	–	–	349	–	–	–	–	451
dge	4.6	4.7	4.2	4.1	–	–	–	–	–	–	–	1,348
tsne_default	368	371	320	309	–	–	1,941	n/a	n/a	–	–	1,531
tsne_fft	116	114	20	19	–	–	247	n/a	n/a	–	–	229
tsne_quick	82	81	41	40	n/a	n/a	n/a	–	–	n/a	n/a	n/a
total (no tSNE)	202	175	102	81	failed	failed	490	failed	failed	failed	failed	3,231

per step: fastest … slowest

Black: n/a (step not in that framework), OOM or TIMEOUT where the run died, − not reached.
Each step is scaled over the runs that finished it: at 1M the bixverse CPU tSNE is red because the others timed out.
Scanpy dask has no DGE step. bixverse GPU and MLX run natively without a memory cap.
bixverse CPU tSNE builds its kNN with IVF from 500k (kmknn at 100k). (qd) steps are not in the total.