# **Project Summary: Cisco Network Configuration**

- Equipment Used: 4 PCs, 2 Cisco switches, 1 Cisco router,
- Connections:
  - PCs connected to switches via copper straight-through cables.
  - Switches connected to the router using Gigabit Ethernet ports (g0/0 and g0/1).

### • Initial Setup:

- Encountered red lights in Packet Tracer, indicating no connection; needed to enable router ports, which are disabled by default.
- Accessed router CLI and entered privileged mode.

## • Configuration Steps:

To configure the gigabit ports on the router, I declined the initial configuration offer by typing **no** and pressing Enter. Then, I entered privileged mode by typing **enable** and pressing Enter, followed by another Enter. Next, I accessed global configuration with **configure terminal**. I configured the first port by typing **interface g0/0** and pressing Enter(The port is labeled on the router). I assigned the IP address by typing **ip address 192.168.1.1 255.255.255.0** and pressing Enter. With the subnet mask I chose, the first 3 octets are for the network portion. The last octet is reserved for the hosts, with 256 IP addresses available. 2 of those 256 addresses must be reserved for the network ID and the default gateway. The ports on Cisco routers are turned off by default, so I typed **no shutdown** and pressed Enter. Finally, I typed **exit** and pressed Enter to complete the configuration for the first port. I repeated the process for the other port. Summary of what I did on the CLI:

- Configured Gigabit port g0/0 with IP address 192.168.1.1/24 and enabled it.
- Configured Gigabit port g0/1 with IP address 192.168.2.1/24 and enabled it.

#### • PC Configuration:

- Assigned static IP addresses to PCs in the 192.168.1.x and 192.168.2.x ranges with the corresponding subnet masks and default gateways.
- Tested connectivity by sending PDU from PCs across the network.
- **Outcome**: Successfully established communication between PCs on different broadcast domains, confirming proper configuration of the network.
- Note: This was a basic setup without advanced configurations like firewall rules or DNS.

#### Diagram of configured network:

