# OPTIMUS: a multidimensional global optimization package

Ioannis G. Tsoulos, Vasileios Charilogis, Alexandros Tzallas

Department of Informatics and Telecommunications, University of Ioannina,

#### Abstract

A significant number of applications from many research areas can be considered global optimization problems, such as applications in the area of image processing, medical informatics, economic models, etc. This paper presents a programming tool written in ANSI C++, which researchers can use to formulate the problem to be solved and then make use of the local and global optimization methods provided by this tool to efficiently solve such problems. The main features of the suggested software are: a) Coding of the objective problem in a high level language such as ANSI C++ b) Incorporation of many global optimization techniques to tackle the objective problem c)Parameterization of global optimization methods using user-defined parameters.

Keywords: Global optimization, local optimization, stochastic methods, evolutionary techniques, termination rules

#### 1 1. Introduction

The location of the global minimum for a continuous and differentiable

function  $f: S \to R, S \subset \mathbb{R}^n$  is formulated as

$$x^* = \arg\min_{x \in S} f(x) \tag{1}$$

where the set S is defined as:

$$S = [a_1, b_1] \otimes [a_2, b_2] \otimes \dots [a_n, b_n]$$

- 5 Methods that aim to locate the global minimum finds application in prob-
- 6 lems from the area of economics [1, 2], problems that appear very often in the
- area of physics [3, 4], chemistry [5, 6], common problems from medicine [7, 8],
- s job scheduling problems [9, 10], water resources planning [11, 12], network
- security problems [13, 14], robotics [15, 16] etc. In the relevant literature

there are a number of global optimization techniques, such as Adaptive Random Search methods [17, 18], Controlled Random Search methods [19, 20], Simulated Annealing [21, 22, 23], Genetic algorithms [24, 25], Ant Colony Optimization [26, 27], Particle Swarm Optimization [28, 29] etc.

In this paper, a new integrated computing environment for performing global optimization methods for multidimensional functions is suggested, where the user can code the objective problem to ANSI C++. In addition to the objective function, the programmer can also provide information that the objective problem should have at the start of the optimization process and, in addition, can formulate a series of actions that will take place after the optimization process is finished. Similar software environments can be found, such as the BARON software package [30], the MERLIN optimization software [31], the DEoptim software [32], the PDoublePop optimization software [33] etc.

The rest of this article is structured as follows: in section 2 the proposed software is outlined in detail, in section 3 some experiments are conducted to show the effectiveness of the proposed software and finally in section 4 some conclusions and guidelines for future work are presented.

# 2. Software description

# 2.1. Distribution

14

15

16

17

18

19

21

22

23

24

37

38

40

41

42

43

44

45

The suggested software is entirely coded in ANSI C++, using the freely available QT programming library, which can be downloaded from https:
//qt.io . At the present time, the software package can only be installed on computers with the Linux operating system. The instructions to install the package on a computer are as follows:

- 1. Download and install the QT programming library from https://qt.
  io.
  - 2. Download software from https://github.com/itsoulos/OPTIMUS.
  - 3. Set the *OPTIMUSPATH* environment variable pointing at the installation directory of OPTIMUS e.g. OPTIMUSPATH=/home/user/OPTIMUS/, where user is the user name in the Linux operating system.
  - 4. Set the *LD\_LIBRAPY\_PATH* to include the OPTIMUS/lib subdirectory e.g.
  - LD\_LIBRAPY\_PATH=\$LD\_LIBRAPY\_PATH:\$OPTIMUSPATH/lib/:
  - 5. Issue the command: cd \$OPTIMUSPATH
  - 6. Execute the compilation script: ./compile.sh
- When the compilation is complete, the *lib* folder will contain the supported global optimization methods, the *PROBLEMS* folder will contain a number

of example optimization problems from the relevant literature, and the *bin* folder will contain the main executable of the software named *OptimusApp*.

#### 2.2. Implemented optimization methods

51

52

53

54

55

56

57

59

60

61

62

63

64

65

66

67

68

69

70

71

72

74

83

84

85

86

87

In the proposed software, each implemented global optimization method has a set of parameters that can determine the global optimization path and the effectiveness of the method. The implemented global optimization methods are:

- 1. Differential Evolution[34], denoted as **de**.
- 2. Improved Differential Evolution. The modified Differential Evolution method as suggested by Charilogis et al [35] is implemented and denoted as **gende**.
- 3. Parallel Differential Evolution. A parallel implementation of the Differential Evolution method as suggested in [36] is considered with the name **ParallelDe**.
- 4. A double precision genetic algorithm [38] is included and it is denoted as **DoubleGenetic**.
- 5. Integer precision genetic algorithm. The method denoted as **IntegerGenetic** is a copy of the **DoubleGenetic** method, but with the usage of integer values as chromosomes.
  - 6. Improved Controlled Random Search [39] is denoted as gcrs.
  - 7. Particle Swarm Optimization, denoted as **Pso**.
  - 8. Improved Particle Swarm Optimization, denoted as **iPso**, an Particle Swarm method [40].
  - 9. Multistart. A simple method that initiates local searches from different initial points is also implemented in the software.
- 10. Topographical Multi level single linkage [41], denoted as **Tmlsl**.
  - 11. The MinCenter method, denoted as **MinCenter** [42].
- NeuralMinimizer. A novel method that incorporates Radial Basis Functions (RBF)[43] to create an estimation of the objective function introduced in [44] is implemented and denoted by the name **NeuralMinimizer**.

Also, the parameter used to determine the used local optimization procedure is the ——localsearch\_method parameter and the implemented methods are:

- 1. The **bfgs** method, denoting The Broyden–Fletcher–Goldfarb–Shanno (BFGS) algorithm [45].
  - 2. The **lbfgs** method. The limited memory BFGS method [46].
  - 3. The Gradient descent method, denoted as **gradient**.
  - 4. The adam method. The adam local optimizer [47] is implemented also.
  - 5. Hill climbing. The hill climbing local search procedure denoted as hill is also implemented.

#### 2.3. Objective problem deployment

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

108

109

110

111

112

113

114

117

The objective problem must be coded in the C++ programming language. Figure 1 shows an example of objective function for the Rastrigin function. The implemented are as follows:

- 1. **void** init(QJsonObject data). The function init() is called before the objective function is executed and its purpose is to pass parameters from the execution environment to the objective function.
- 2. **int** getDimension(), the dimension of the objective problem.
- 3. **void** getmargins(vector<Interval> &x). The getmargins() functions returns in the vector x the bounds of the objective problem. The class Interval is a simple class located in the folder *PROBLEMS* of the distribution, that represents double precision intervals.
- 4. **double** funmin(vector<**double**> &x). This function returns the objective problem f(x) for a given point x.
- 5. **void** granal(vector<**double**> &x,vector<**double**> &g). This functions stores in vector g the gradient  $\nabla f(x)$  for a given point x.
- 6. QJsonObject done(vector<**double**> &x). This function is executed after the objective function optimization process is completed. The point x is the global minimum for the function f(x).

#### 2.3.1. Objective function compilation

In order to build the objective function the user should create an accompaniment project file as demonstrated in Figure 2. The software incorporates the utility qmake of the QT library to compile the objective function. The compilation is performed with the following series of commands in the terminal:

- 1. qmake file.pro
  - 2. make

where *file.pro* stands for the name of the project file. The final outcome of this compilation will be the shared library *libfile.so* 

#### 2.3.2. Objective function execution

A full working command for the Rastrigin problem using the utility program *OptimusApp* is shown below

```
./OptimusApp --filename=librastrigin.so --opt_method=
Pso\ --pso_particles=100 --pso_generations=10\
--localsearch_method=bfgs
```

The parameters for the above command line are as follows:

- 12. The argument of ——filename determines the objective problem in shared library format.
- 2. The argument of —opt\_method sets the used global optimization procedure.
- 3. The argument of —pso\_particles sets the number of particles of the PSO optimizer.
  - 4. The argument of −−pso\_generations sets the maximum number of generations allowed.
  - 5. The argument of ——localsearch\_method sets the used local optimization procedure.

The output of the previous command is shown in figure 3.

#### 3. Experiments

To assess the ability of the software package to adapt to different problems, a series of experiments were performed under different conditions and they are analyzed in the following subsections.

#### 3.1. Test functions

To measure the effect of the proposed software, a series of experiments were performed on test functions from the relevant literature [48, 49, 50, 51]. The experiments were performed 30 times for every test case using a different seed for the random number generator each time. Two variations of the genetic algorithm (DoubleGenetic method) were used: one without a local optimization method and one with periodic application of the bfgs method at a rate of 5% on the chromosomes in every generation. The execution parameters for the genetic algorithm are listed in Table 1 and the results are shown in Table 2. The numbers in parentheses show the percentage of finding the global minimum, where the absence of this number denotes that the algorithm discovered the global minimum in all executions. The experimental results indicate that the usage of a local search method in combination with the genetic algorithm significantly reduces the required number of average function calls and also improves the reliability of the method in finding the global minimum.

## 3.2. The Lennard Jones potential

The molecular conformation corresponding to the global minimum of the energy of N atoms interacting via the Lennard-Jones potential [52, 53] is used as a test case here. The function to be minimized is given by:

$$V_{LJ}(r) = 4\epsilon \left[ \left( \frac{\sigma}{r} \right)^{12} - \left( \frac{\sigma}{r} \right)^{6} \right]$$
 (2)

For testing purposes, the methods **NeuralMinimizer**, **DoubleGenetic** and **Pso** was applied for a variety of numbers of atoms and the results are shown in Table 3. The method NeuralMinimizer requires a significantly reduced number of function calls compared to the other two, while its reliability in finding the global minimum for the potential remains high even when the number of atoms participating in the potential increases significantly.

#### 3.3. Parallel optimization

165

166

175

176

177

178

179

180

181

182

183

184

185

186

187

188

The High Conditioned Elliptic function, defined as

$$f(x) = \sum_{i=1}^{n} (10^{6})^{\frac{i-1}{n-1}} x_{i}^{2}$$

is used as a test case to measure the scalability of the parallel global optimization technique denoted as ParallelDe. This method was applied to the problem with dimension increasing from 2 to 15 and for a different number of processing threads. The experimental results are shown in diagram form in Figure 4 and they indicate that the number of calls required to find the global minimum decreases as the total processing threads increases, even though the problem becomes increasingly difficult with increasing dimensions.

### 4. Conclusions

In this work, an environment for executing global optimization problems was presented, where the user can code the objective problem using some predefined functions and then has the possibility to choose one among several global optimization methods to solve the mentioned problem. This programming environment is freely available and easy to extend to accommodate more global optimization techniques and it can be extended in the near future with the following improvements:

- 1. Port the Optimums tool to other operating systems.
- 2. Use of modern parallel techniques to speed up the generated results.
- 3. Implementing a GUI interface to control the optimization process.
- 4. The ability to code the objective function in other programming languages such as Python, Ada, Fortran etc.
- 5. Creating a scripting language to efficiently guide the optimization of objective functions.

#### References

189

- [1] Zwe-Lee Gaing, Particle swarm optimization to solving the economic dispatch considering the generator constraints, IEEE Transactions on 18 Power Systems, pp. 1187-1195, 2003.
- [2] C. D. Maranas, I. P. Androulakis, C. A. Floudas, A. J. Berger, J.
   M. Mulvey, Solving long-term financial planning problems via global optimization, Journal of Economic Dynamics and Control 21, pp. 1405-1425, 1997.
- [3] Q. Duan, S. Sorooshian, V. Gupta, Effective and efficient global optimization for conceptual rainfall-runoff models, Water Resources Research 28, pp. 1015-1031, 1992.
- [4] P. Charbonneau, Genetic Algorithms in Astronomy and Astrophysics,
   Astrophysical Journal Supplement 101, p. 309, 1995
- [5] A. Liwo, J. Lee, D.R. Ripoll, J. Pillardy, H. A. Scheraga, Protein structure prediction by global optimization of a potential energy function, Biophysics **96**, pp. 5482-5485, 1999.
- puting global minima of nonconvex potential energy functions, Journal of Global Optimization 4, pp. 117-133, 1994.
- <sup>208</sup> [7] Eva K. Lee, Large-Scale Optimization-Based Classification Models in Medicine and Biology, Annals of Biomedical Engineering **35**, pp 1095-1109, 2007.
- <sup>211</sup> [8] Y. Cherruault, Global optimization in biology and medicine, Mathe-<sup>212</sup> matical and Computer Modelling **20**, pp. 119-132, 1994.
- [9] Y. Gao, H. Rong, J.Z. Huang, Adaptive grid job scheduling with genetic algorithms, Future Generation Computer Systems **21**, pp. 151-161, 2005.
- 216 [10] D.Y. Sha, H.H. Lin, A multi-objective PSO for job-shop scheduling problems, Expert Systems with Applications **37**, pp. 1065-1070, 2010.
- [11] X. Cai, D.C. McKinney, L.S. Lasdon, Solving nonlinear water management models using a combined genetic algorithm and linear programming approach, Advances in Water Resources 24, pp. 667-676, 2001.

- <sup>222</sup> [12] S.G. Gino Sophia, V. Ceronmani Sharmila, S. Suchitra et al, Water management using genetic algorithm-based machine learning, Soft Comput **24**, pp. 17153–17165, 2020.
- 225 [13] Z. Bankovic, D. Stepanovic, S. Bojanic, O. Nieto Taladriz, Improving network security using genetic algorithm approach, Computers & Electrical Engineering 33, pp. 438-451, 2007.
- <sup>228</sup> [14] S. Paul, I. Dutt, S.N. Choudhri, Design and implementation of network security using genetic algorithm. Int J Res Eng Technol **2**, pp. 172-177, 2013.
- [15] A. Tuncer, M. Yildrim, Dynamic path planning of mobile robots with improved genetic algorithm, Computers & Electrical Engineering 38, pp. 1564-1572, 2012.
- <sup>234</sup> [16] N. Kherici, Y.M. Ben Ali, Using PSO for a walk of a biped robot, Journal of Computational Science **5**, pp. 743-749, 2014.
- [17] M. Brunato, R. Battiti, RASH: A Self-adaptive Random Search
   Method. In: Cotta, C., Sevaux, M., Sörensen, K. (eds) Adaptive and
   Multilevel Metaheuristics. Studies in Computational Intelligence, vol
   136. Springer, Berlin, Heidelberg, 2008.
- <sup>240</sup> [18] S. Andradóttir, A.A. Prudius, A.A., Adaptive random search for continuous simulation optimization. Naval Research Logistics **57**, pp. 583-604, 2010.
- <sup>243</sup> [19] W.L. Price, Global optimization by controlled random search, J Optim Theory Appl **40**, pp. 333–348, 1983.
- <sup>245</sup> [20] P. Kaelo, M.M. Ali, Some Variants of the Controlled Random Search Algorithm for Global Optimization. J Optim Theory Appl **130**, pp. <sup>247</sup> 253–264 (2006).
- <sup>248</sup> [21] S. Kirkpatrick, C.D. Gelatt, M.P. Vecchi, Optimization by simulated annealing, Science **220**, pp. 671-680, 1983.
- [22] K.M.El-Naggar, M.R. AlRashidi, M.F. AlHajri, A.K. Al-Othman, Simulated Annealing algorithm for photovoltaic parameters identification,
   Solar Energy 86, pp. 266-274, 2012.
- [23] L.M. Rasdi Rere, M.I. Fanany, A.M. Arymurthy, Simulated Annealing
   Algorithm for Deep Learning, Procedia Computer Science 72, pp. 137 144, 2015.

- [24] J. Mc Call, Genetic algorithms for modelling and optimisation, Journal
   of Computational and Applied Mathematics 184, pp. 205-222, 2005.
- <sup>258</sup> [25] C.K.H. Lee, A review of applications of genetic algorithms in operations management, Elsevier Engineering Applications of Artificial Intelligence **76**, pp. 1-12, 2018.
- [26] B. Chandra Mohan, R. Baskaran, A survey: Ant Colony Optimization based recent research and implementation on several engineering domain, Expert Systems with Applications 39, pp. 4618-4627, 2012.
- [27] T. Liao, T. Stützle, M.A. Montes de Oca, M. Dorigo, A unified ant colony optimization algorithm for continuous optimization, European Journal of Operational Research 234, pp. 597-609, 2014.
- <sup>267</sup> [28] D. Wang, D. Tan, L. Liu, Particle swarm optimization algorithm: an overview. Soft Comput **22**, pp. 387–408, 2018.
- <sup>269</sup> [29] N.K. Jain, U. Nangia, J. Jain, A Review of Particle Swarm Optimization. J. Inst. Eng. India Ser. B **99**, pp. 407–411, 2018.
- [30] N.V. Sahinidis, BARON: A general purpose global optimization software package, J Glob Optim 8, pp. 201–205, 1996.
- [31] D.G. Papageorgiou, I.N. Demetropoulos, I.E. Lagaris, Computer Physics Communications **159**, pp. 70-71, 2004.
- 275 [32] K. Mullen, D. Ardia, D.L. Gil, D. Windover, J. Cline, DEoptim: An R Package for Global Optimization by Differential Evolution, Journal of Statistical Software **40**, pp. 1-26, 2011.
- [33] I.G. Tsoulos, A. Tzallas, D. Tsalikakis, PDoublePop: An implementation of parallel genetic algorithm for function optimization, Computer Physics Communications **209**, pp. 183-189, 2016.
- 281 [34] R. Storn, On the usage of differential evolution for function optimiza-282 tion, In: Proceedings of North American Fuzzy Information Processing, 283 pp. 519-523, 1996.
- <sup>284</sup> [35] V. Charilogis, I.G. Tsoulos, A. Tzallas, E. Karvounis, Modifications for the Differential Evolution Algorithm, Symmetry **14**, 447, 2022.
- <sup>286</sup> [36] V. Charilogis, I.G. Tsoulos, A Parallel Implementation of the Differential Evolution Method, Analytics **2**, pp. 17-30, 2023.

- 288 [37] R. Chandra, L. Dagum, D. Kohr, D. Maydan, J. McDonald and R. Menon, Parallel Programming in OpenMP, Morgan Kaufmann Publishers Inc., 2001.
- <sup>291</sup> [38] I.G. Tsoulos, Modifications of real code genetic algorithm for global optimization, Applied Mathematics and Computation **203**, pp. 598-607, 2008.
- <sup>294</sup> [39] V. Charilogis, I.G. Tsoulos, A. Tzallas, N. Anastasopoulos, An Improved Controlled Random Search Method, Symmetry **13**, 1981, 2021.
- <sup>296</sup> [40] V. Charilogis, I.G. Tsoulos, Toward an Ideal Particle Swarm Optimizer for Multidimensional Functions, Information **13**, 217, 2022.
- <sup>298</sup> [41] M.M. Ali, C. Storey, Topographical multilevel single linkage, J. Global Optimization **5**, pp. 349–358,1994
- <sup>300</sup> [42] V. Charilogis, I.G. Tsoulos, MinCentre: using clustering in global optimisation, International Journal of Computational Intelligence Studies <sup>301</sup> 11, pp. 24-35, 2022.
- J. Park, I.W. Sandberg, Approximation and Radial-Basis-Function Networks, Neural Computation 5, pp. 305-316, 1993.
- I.G. Tsoulos, A. Tzallas, E. Karvounis, D. Tsalikakis, NeuralMinimizer, a novel method for global optimization that incorporates machine learning, Information 14, 2, 2023.
- [45] M.J.D Powell, A Tolerant Algorithm for Linearly Constrained Optimization Calculations, Mathematical Programming 45, pp. 547-566, 1989.
- January Method for Large Scale Optimization, Mathematical Programming B **45**, pp. 503-528, 1989.
- <sup>313</sup> [47] D.P. Kingma, J. Ba, Adam: A Method for Stochastic Optimization, ICLR (Poster), 2015.
- [48] M.M. Ali and P. Kaelo, Improved particle swarm algorithms for global optimization, Applied Mathematics and Computation 196, pp. 578-593, 2008.
- [49] H. Koyuncu, R. Ceylan, A PSO based approach: Scout particle swarm algorithm for continuous global optimization problems, Journal of Computational Design and Engineering 6, pp. 129–142, 2019.

- [50] Patrick Siarry, Gérard Berthiau, François Durdin, Jacques Haussy,
   ACM Transactions on Mathematical Software 23, pp 209–228, 1997.
- [51] I.G. Tsoulos, I.E. Lagaris, GenMin: An enhanced genetic algorithm for global optimization, Computer Physics Communications **178**, pp. 843-851, 2008.
- [52] J.A. Northby, Structure and binding of Lennard-Jones clusters:  $13 \le n \le 147$ , J. Chem. Phys. **87**, pp. 6166–6178, 1987.
- 5328 [53] G.L. Xue, R.S. Maier, J.B. Rosen, Improvements on the Northby Algorithm for molecular conformation: Better solutions, J. Global. Optim. 4, pp. 425–440, 1994.
- <sup>331</sup> [54] O.A. Sauer, D.M. Shepard, T.R. Mackie, Application of constrained optimization to radiotherapy planning, Medical Physics **26**, pp. 2359-2366, 1999.
- [55] F.P. Seelos, R.E. Arvidson, Bounded variable least squares application
   of a constrained optimization algorithm to the analysis of TES Emissivity Spectra, in: 34th Annual Lunar and Planetary Science Conference,
   March 17-21, 2003, League City, Texas, abstract no.1817.
- 538 [56] M.J. Field, Constrained optimization of ab initio and semiempirical Hartree-Fock wave functions using direct minimization or simulated annealing, Journal of physical chemistry **95**, pp. 5104-5108, 1991.
- [57] G.A. Williams, J.M. Dugan, R.B. Altman, Constrained global optimization for estimating molecular structure from atomic distances,
   Journal of Computational Biology 8, pp. 523-547, 2001.
- <sup>344</sup> [58] P.E. Gill, W. Murray, The computation of Lagrange-multiplier esti-<sup>345</sup> mates for constrained minimization, Mathematical Programming **17**, <sup>346</sup> pp. 32-60, 1979.
- [59] M.J.D. Powell, Y. Yuan, A trust region algorithm for equality constrained optimization, Mathematical Programming 49, pp. 189-211, 2005.
- <sup>350</sup> [60] K. Ichida, Constrained optimization using interval analysis, Computers and Industrial Engineering **31**, pp. 933-937, 1996.
- [61] R.L. Becerra, C.A.C. Coello, Cultured differential evolution for constrained optimization, Computer Methods in Applied Mechanics and Engineering **195**, pp. 4303-4322, 2006.

- <sup>355</sup> [62] A.V. Levy, A. Montalvo, The tunneling algorithm for global optimiza-<sup>356</sup> tion of functions, SIAM Journal of Scientific and Statistical Computing <sup>357</sup> **6**, pp. 15-29, 1985.
- <sup>358</sup> [63] H.M. Salkin, Integer programming, Edison Wesley Publishing Com., Amsterdam, 1975.
- R. Hess, A heuristic search for estimating a global solution of non convex programming problems, Operations Research **21**, pp. 1267-1280, 1973.
- <sup>363</sup> [65] P. Chootinan, A. Chen, Constraint handling in genetic algorithms using a gradient based repair method, Computer and Operations Research <sup>365</sup> **33**, pp. 2263-2281, 2006.
- J.J. Liang, T.P. Runarsson, E. Mezura-Montes, M. Clerc, P.N. Suganthan, C.A.C. Coello, K. Deb, Problem definitions and evaluation criteria for the CEC2006 special session on constrained real-parameter optimization, http://www.ntu.edu.sg/home/EPNSugan/index\_files/CEC-06/CEC06.htm

Figure 3: Output for the minimization of the Rastrigin function using the PSO optimizer.

```
-1.7464048
Generation
                1 value:
Generation
                2 value:
                             -1.8619942
Generation
                3 value:
                             -1.8852439
Generation
                4 value:
                             -1.9490074
Generation
                  value:
                             -1.9490074
Generation
                6 value:
                             -1.9490074
Generation
                7 value:
                             -1.9490074
Generation
                8 value:
                             -1.9775267
Generation
                9 value:
                             -1.9972928
Generation
               10 value:
                             -1.9977027
Minimum:
                 -2.0000000000
                                 Function calls:
                                                      1028
```

Figure 1: A typical representation of an objective problem, suitable for the OPTIMUS programming tool.

```
# include <math.h>
# include <interval.h>
# include <vector>
# include <stdio.h>
# include <iostream>
# include <QJsonObject>
using namespace std;
extern "C" {
void
         init (QJsonObject data) {
         getdimension() {
int
         return 2;
}
void
         getmargins (vector < Interval > &x) {
  for (int i = 0; i < x . size(); i++)
         x[i] = Interval(-1,1);
double
         funmin (vector < double > &x) {
         return (x[0]*x[0])+(x[1]*x[1])-\cos(18.0*x[0])-\cos(18.0*x[1]);
}
void
         granal (vector < double > &x, vector < double > &g) {
         g[0] = 2.0 * x[0] + 18.0 * sin(18.0 * x[0]);
         g[1] = 2.0 * x[1] + 18.0 * sin(18.0 * x[1]);
QJsonObject
                 done(vector < double > \&x) {
return QJsonObject();
```

Figure 2: The associated project file for the Rastrigin problem.

```
TEMPLATE=lib
SOURCES+=rastrigin.cc interval.cpp
HEADERS += interval.h
```

Table 1: Experimental settings

PARAMETER	VALUE	
CHROMOSOMES	200	
CROSSOVER RATE	90%	
MUTATION RATE	5%	
GENERATIONS	200	
LOCAL SEARCH METHOD	bfgs	

Table 2: Experimental results for some test functions using a series of global optimization  $\underline{\text{methods}}$ .

FUNCTION	GENETIC	GENETIC WITH
		$\mathbf{LOCAL}$
GRIEWANK2	9298(0.97)	10684
RASTRIGIN	8967	11038
SHEKEl5	19403(0.70)	9222
SHEKEL7	16376(0.80)	8836
SHEKEL10	19829(0.77)	8729
TEST2N4	17109	7786
TEST2N5	19464	8264
TEST2N6	24217	8868
TEST2N7	26824	9376
$\mathbf{SUM}$	161487(0.92)	82803

Table 3: Optimizing the Potential problem for different number of atoms.

ATOMS	GENETIC	PSO	NEURALMINIMIZER
3	18902	9936	1192
4	17806	12560	1964
5	18477	12385	2399
6	19069(0.20)	9683	3198
7	16390(0.33)	10533(0.17)	3311(0.97)
8	15924(0.50)	8053(0.50)	3526
9	15041(0.27)	9276(0.17)	4338
10	14817(0.03)	7548(0.17)	5517(0.87)
11	13885(0.03)	6864(0.13)	6588(0.80)
12	14435(0.17)	12182(0.07)	7508(0.83)
13	14457(0.07)	10748(0.03)	6717(0.77)
14	13906(0.07)	14235(0.13)	6201(0.93)
15	12832(0.10)	12980(0.10)	7802(0.90)
AVERAGE	205941(0.37)	137134(0.42)	60258(0.93)




Figure 4: Scalabilty of the ParallelDe method.

# Required Metadata

# 372 Current code version

Nr.	Code metadata description	
C1	Current code version	1.0
C2	Permanent link to code/repository	https://github.com/itsoulos/
	used for this code version	OPTIMUS/
С3	Legal Code License	GNU General Public License (GPL)
C4	Code versioning system used	git
C5	Software code languages, tools, and	C++
	services used	
C6	Compilation requirements, operat-	Linux , QT Library
	ing environments & dependencies	
C7	If available Link to developer docu-	https://raw.githack.com/
	mentation/manual	itsoulos/OPTIMUS/master/
		MANUAL/docs/html/index.html
C8	Support email for questions	itsoulos@uoi.gr