

Course 5: Reinforcement Learning



Last session

- 1 Combinatorial game theory
- 2 Definition of a game
- 3 Proof of determined games

Today's session

- 1 Reinforcement Learning
- 2 Value and Policy Functions
- 3 Q-Learning

Note: reinforcement learning and combinatorial game theory share a common mathematical framework. But to ease access to online resources, we will adopt a new vocabulary.

Summary




It is good to tell them that we chose not to use the same notations as in the CGT lesson, although we could have.

- Combinatorial game theory
- Definition of a game
- Proof of determined games

- Reinforcement Learning
- Value and Policy Functions
- Q-Learning

Note: reinforcement learning and combinatorial game theory share a common mathematical framework. But to ease access to online resources, we will adopt a new vocabulary.


Learning Approaches

Learning Approaches		
Supervised L	Reinforcement L	Unsupervised L
1 Data: (x =data, y =labels)	1 Data: (state, action)	1 Data: x =data, no labels
2 Goal: Learn a mapping $x \rightarrow y$	2 Goal: Maximize future rewards	2 Goal: Learn structure in x
This thing is a cheese 	Eat this thing for reward 	This thing is like the other thing 

Supervised L

- 1 Data:**
(x =data, y =labels)
- 2 Goal:** Learn a
mapping $x \rightarrow y$


This thing is a cheese



Reinforcement L

- 1 Data:** (state,
action)
- 2 Goal:** Maximize
future rewards


Eat this thing for reward



Unsupervised L

- 1 Data:** x =data, no
labels
- 2 Goal:** Learn
structure in x

This thing is like the other thing



As for UL in Reinforcement learning the algorithm does not know what the object is (cheese) \rightarrow it learns by trial and error. RL stands in between supervised and unsupervised: kind of semi-supervised \rightarrow learns from sparse rewards, exploiting information about the world, state, actions

1 Definitions of Reinforcement Learning (RL)

- Fundamentals
- Example: PyRat
- Policy and values

2 Q-learning

- Q-learning definitions
- Example
- Approximate Q-learning
- Exploration/Exploitation

2023-11-23

Course 5: Reinforcement Learning

└ Outline of the course

■ Definitions of Reinforcement Learning (RL)

- Fundamentals
- Example: PyRat
- Policy and values

■ Q-learning

- Q-learning definitions
- Example
- Approximate Q-learning
- Exploration/Exploitation

1 Definitions of Reinforcement Learning (RL)


- Fundamentals
- Example: PyRat
- Policy and values

2 Q-learning

- Q-learning definitions
- Example
- Approximate Q-learning
- Exploration/Exploitation

Agent and environment

Our objective is to train an **agent** to maximize its **reward** through **actions** that affect an **environment**.




2023-11-23

Course 5: Reinforcement Learning

- Definitions of Reinforcement Learning (RL)
 - Fundamentals
 - Agent and environment

Agent and environment

Our objective is to train an **agent** to maximize its **reward** through **actions** that affect an **environment**.



Pretty much self-explanatory. At this point, there is no need to talk about the specificity of Pyrat, because we will detail all this in the next slides. Just go through the definition : the agent is the rat, the actions are its moves, the reward could be something related to winning the game, and the observation is what the rat sees. (don't detail here)

GL: Let's set the Vocabulary, little different from other approaches.

Agent: takes actions. Environment: where agent operates and exists.

Observation: data that the agent sees in return from the environment.

Reward: feedback on the success of agent action

Reward hypothesis

- *All goals can be described by the maximization of expected cumulated reward over time.*

Specificities of reinforcement learning

- No supervision, only a reward signal,
- Delayed feedback, the reward can come (much) later,
- Importance of the temporal dimension,
- Agent's actions affect the subsequent data it receives.

2023-11-23

Course 5: Reinforcement Learning

- └ Definitions of Reinforcement Learning (RL)
 - └ Fundamentals
 - └ Fundamentals

Fundamentals

Reward hypothesis

- All goals can be described by the maximization of expected cumulated reward over time.

Specificities of reinforcement learning

- No supervision, only a reward signal,
- Delayed feedback, the reward can come (much) later,
- Importance of the temporal dimension,
- Agent's actions affect the subsequent data it receives.

It is important to emphasize the fact that reinforcement learning is built upon the reward hypothesis, which is still an hypothesis. Some goals may not be described by maximizing reward.

For each of the specificities of RL, you may want to illustrate it with a very short example. GL: reward signal numeric (+1 if you eat a cheese). Delayed: you don't get a reward after each action, can be much later: in some applications you only have a reward at the end. Temporal: RL is based on step: start state s at time t , take an action, reach state s_{t+1} ... Actions modify the environment, changes observations the agent receives

Reward hypothesis

- *All goals can be described by the maximization of expected cumulated reward over time.*


Specificities of reinforcement learning

- No supervision, only a reward signal,
- Delayed feedback, the reward can come (much) later,
- Importance of the temporal dimension,
- Agent's actions affect the subsequent data it receives.

It is important to emphasize the fact that reinforcement learning is built upon the reward hypothesis, which is still an hypothesis. Some goals may not be described by maximizing reward.

For each of the specificities of RL, you may want to illustrate it with a very short example. GL: reward signal numeric (+1 if you eat a cheese). Delayed: you don't get a reward after each action, can be much later: in some applications you only have a reward at the end. Temporal: RL is based on step: start state s at time t , take an action, reach state s_{t+1} ... Actions modify the environment, changes observations the agent receives

Agent and environment




2023-11-23

Course 5: Reinforcement Learning

└ Definitions of Reinforcement Learning (RL)

└ Fundamentals

└ Agent and environment



Now we can finally put some notations on Pyrat in the context of Reinforcement Learning. At this stage, it is important to note that the state of the rat and the state of the environment are not the same.

GL: state: situation that agent perceives

Definitions

- The agent α ...

- 1 analyzes previous actions, states, rewards and observations,
- 2 computes action a_t ,
- 3 obtains reward r_t ,
- 4 obtains an observation o_{t+1} ,
- 5 deduce a new state s_{t+1}^α .

- The environment...

- 1 receives action a_t ,
- 2 produces reward r_t ,
- 3 deduce a new state s_{t+1}^e ,
- 4 produces o_{t+1} .

- Observability:

- The agent α :
 - analyzes previous actions, states, rewards and observations,
 - computes action a_t ,
 - obtains reward r_t ,
 - obtains an observation ϕ_{t+1} ,
 - deduce a new state s_{t+1} .
- The environment...
 - receives action a_t ,
 - produces reward r_t ,
 - deduce a new state s_{t+1} ,
 - produces ϕ_{t+1} .
- Observability:
 - Perfect: $s_t^* = s_t^o = s_t$.
 - Imperfect: no access to full environment state.
 - The agent indirectly observes the environment through a_t .
 - s_t^o is estimated by the agent and may differ from s_t^* .

■ The agent α ...

- 1 analyzes previous actions, states, rewards and observations,
- 2 computes action a_t ,
- 3 obtains reward r_t ,
- 4 obtains an observation o_{t+1} ,
- 5 deduce a new state s_{t+1}^α .

■ The environment...

- 1 receives action a_t ,
- 2 produces reward r_t ,
- 3 deduce a new state s_{t+1}^e ,
- 4 produces o_{t+1} .

■ Observability:

- **Perfect:** $s_t^\alpha = s_t^e = o_t$
- **Imperfect:** no access to full environment state:
 - The agent indirectly observes the environment through o_t ,
 - s_t^α is estimated by the agent and may differ from s_t^e .

- The agent α ...
 - analyzes previous actions, states, rewards and observations,
 - computes action a_t ,
 - obtains reward r_t ,
 - obtains an observation o_{t+1} ,
 - deduce a new state s_{t+1}^α .
- The environment...
 - receives action a_t ,
 - produces reward r_t ,
 - deduce a new state s_{t+1}^e ,
 - produces o_{t+1} .
- Observability:
 - **Perfect:** $s_t^\alpha = s_t^e = o_t$,
 - **Imperfect:** no access to full environment state.
 - The agent indirectly observes the environment through o_t ,
 - s_t^α is estimated by the agent and may differ from s_t^e .

And now we describe with even more detail what those definitions relate to exactly. In the right part of the slide, the discussion about observability can be related to perfect and imperfect information in the CGT lesson. The important (and sometimes tricky) thing to understand is that in the case of perfect (aka full) observability, the state of the environment, of the rat and the observation is the SAME thing ; basically, there is no need in differentiating them mathematically.

Definitions

- 1 receives action a_t ,
- 2 produces reward r_t ,
- 3 deduce a new state s_{t+1}^e ,
- 4 produces o_{t+1} .

And now we describe with even more detail what those definitions relate to exactly. In the right part of the slide, the discussion about observability can be related to perfect and imperfect information in the CGT lesson. The important (and sometimes tricky) thing to understand is that in the case of perfect (aka full) observability, the state of the environment, of the rat and the observation is the SAME thing ; basically, there is no need in differentiating them mathematically.

■ The agent α ...

- 1 analyzes previous actions, states, rewards and observations,
- 2 computes action a_t ,
- 3 obtains reward r_t ,
- 4 obtains an observation o_{t+1} ,
- 5 deduce a new state s_{t+1}^α .

■ The environment...

- 1 receives action a_t ,
- 2 produces reward r_t ,
- 3 deduce a new state s_{t+1}^e ,
- 4 produces o_{t+1} .

■ Observability:

- **Perfect:** $s_t^\alpha = s_t^e = o_t$
- **Imperfect:** no access to full environment state:
 - The agent indirectly observes the environment through o_t ,
 - s_t^α is estimated by the agent and may differ from s_t^e .

- The agent α ...
 - analyzes previous actions, states, rewards and observations,
 - computes action a_t ,
 - obtains reward r_t ,
 - obtains an observation o_{t+1} ,
 - deduce a new state s_{t+1}^α .
- The environment...
 - receives action a_t ,
 - produces reward r_t ,
 - deduce a new state s_{t+1}^e ,
 - produces o_{t+1} .
- Observability:
 - **Perfect:** $s_t^\alpha = s_t^e = o_t$
 - **Imperfect:** no access to full environment state.
 - The agent indirectly observes the environment through o_t ,
 - s_t^α is estimated by the agent and may differ from s_t^e .

And now we describe with even more detail what those definitions relate to exactly. In the right part of the slide, the discussion about observability can be related to perfect and imperfect information in the CGT lesson. The important (and sometimes tricky) thing to understand is that in the case of perfect (aka full) observability, the state of the environment, of the rat and the observation is the SAME thing ; basically, there is no need in differentiating them mathematically.

Definitions

- The agent is either the Rat or the Python,
- The opponent becomes part of the environment,
 - Note that the game can be with perfect observability if the opponent strategy is known,
- Seen this way, the game becomes sequential.

RL-based PyRat versus supervised approach

- Reward signal: number of picked up pieces of cheese,
- Delayed feedback: several moves required to reach a reward,
- Character's moves affect subsequent data it receives,
- Importance of the temporal dimension.

2023-11-23

Course 5: Reinforcement Learning

└ Definitions of Reinforcement Learning (RL)

└ Example: PyRat

└ Example: PyRat

In the final part of this slide (observability examples), we fully describe the case of PyRat with precise definitions. This enables us to define the policy function.

Definitions

- The agent is either the Rat or the Python,
- The opponent becomes part of the environment,
 - Note that the game can be with perfect observability if the opponent strategy is known,
- Seen this way, the game becomes sequential.

RL-based PyRat versus supervised approach

- Reward signal: number of picked up pieces of cheese,
- Delayed feedback: several moves required to reach a reward,
- Character's moves affect subsequent data it receives,
- Importance of the temporal dimension.

Example: PyRat

Definitions

- The agent is either the Rat or the Python,
- The opponent becomes part of the environment,
 - Note that the game can be with perfect observability if the opponent strategy is known,
- Seen this way, the game becomes sequential.

RL-based PyRat versus supervised approach

- Reward signal: number of picked up pieces of cheese,
- Delayed feedback: several moves required to reach a reward,
- Character's moves affect subsequent data it receives,
- Importance of the temporal dimension.

2023-11-23

Course 5: Reinforcement Learning

└ Definitions of Reinforcement Learning (RL)

└ Example: PyRat

└ Example: PyRat

Example: PyRat

Definitions

- The agent is either the Rat or the Python,
- The opponent becomes part of the environment,
 - Note that the game can be with perfect observability if the opponent strategy is known,
- Seen this way, the game becomes sequential.

RL-based PyRat versus supervised approach

- Reward signal: number of picked up pieces of cheese,
- Delayed feedback: several moves required to reach a reward,
- Character's moves affect subsequent data it receives,
- Importance of the temporal dimension.

In the final part of this slide (observability examples), we fully describe the case of PyRat with precise definitions. This enables us to define the policy function.

Observability examples

- Perfect: $s_t^{rat} = s_t^o = o_t$
 - a_t : Last move of the rat,
 - o_t : The entire maze with all cheese locations and python position,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.
- Imperfect:
 - a_t : Last move of the rat,
 - o_t : Neighboring cells of the rat,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.

To represent the strategy of the rat, we use a **policy function**.

- Perfect: $s_t^{rat} = s_t^o = o_t$
 - a_t : Last move of the rat,
 - o_t : The entire maze with all cheese locations and python position,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.
- Imperfect:
 - a_t : Last move of the rat,
 - o_t : Neighboring cells of the rat,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.

To represent the strategy of the rat, we use a **policy function**.

In the final part of this slide (observability examples), we fully describe the case of PyRat with precise definitions. This enables us to define the policy function.

Observability examples

- Perfect: $s_t^{rat} = s_t^o = o_t$
 - a_t : Last move of the rat,
 - o_t : The entire maze with all cheese locations and python position,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.
- Imperfect:
 - a_t : Last move of the rat,
 - o_t : Neighboring cells of the rat,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.

To represent the strategy of the rat, we use a **policy function**.

2023-11-23

Course 5: Reinforcement Learning

Definitions of Reinforcement Learning (RL)

Example: PyRat

Example: PyRat

Example: PyRat

Observability examples

- Perfect: $s_t^{rat} = s_t^o = o_t$
 - a_t : Last move of the rat,
 - o_t : The entire maze with all cheese locations and python position,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.
- Imperfect:
 - a_t : Last move of the rat,
 - o_t : Neighboring cells of the rat,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.

To represent the strategy of the rat, we use a **policy function**.

In the final part of this slide (observability examples), we fully describe the case of PyRat with precise definitions. This enables us to define the policy function.

Observability examples

- Perfect: $s_t^{rat} = s_t^o = o_t$
 - a_t : Last move of the rat,
 - o_t : The entire maze with all cheese locations and python position,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.
- Imperfect:
 - a_t : Last move of the rat,
 - o_t : Neighboring cells of the rat,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.

To represent the strategy of the rat, we use a [policy function](#).

Observability examples

- Perfect: $s_t^{rat} = s_t^o = o_t$
 - a_t : Last move of the rat,
 - o_t : The entire maze with all cheese locations and python position,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.
- Imperfect:
 - a_t : Last move of the rat,
 - o_t : Neighboring cells of the rat,
 - r_t : Binary variable which is 1 if the rat just got a piece of cheese.

To represent the strategy of the rat, we use a [policy function](#).

In the final part of this slide (observability examples), we fully describe the case of PyRat with precise definitions. This enables us to define the policy function.

Definition

The policy function of an agent α is:

$$\pi : \begin{cases} S^\alpha & \rightarrow A \\ s_t^\alpha & \mapsto a_t^\alpha \end{cases}$$

■ π can be deterministic or stochastic.

Playout

The playout $(s_t^{\alpha, \pi})_{t \in \mathbb{N}}$ associated with a policy π and initial state s_0 , is defined by considering agent α takes his/her actions using π .

2023-11-23

Course 5: Reinforcement Learning

Definitions of Reinforcement Learning (RL)

Policy and values

Policy Function

Definition

The policy function of an agent α is:

$$\pi : \begin{cases} S^\alpha & \rightarrow A \\ s_t^\alpha & \mapsto a_t^\alpha \end{cases}$$

■ π can be deterministic or stochastic.

Playout

The playout $(s_t^{\alpha, \pi})_{t \in \mathbb{N}}$ associated with a policy π and initial state s_0 , is defined by considering agent α takes his/her actions using π .

A policy is a function from the set of states to the set of actions. We can mirror here the previous course on CGT by defining the playout associated with a policy (in CGT, we were talking about strategies, but it is important to make the difference because strategies were defined on sequences of vertices in the arena).

Definition

The policy function of an agent α is:

$$\pi : \begin{cases} S^\alpha & \rightarrow A \\ s_t^\alpha & \mapsto a_t^\alpha \end{cases}$$

■ π can be deterministic or stochastic.

Playout

The playout $(s_t^{\alpha, \pi})_{t \in \mathbb{N}}$ associated with a policy π and initial state s_0 , is defined by considering agent α takes his/her actions using π .

2023-11-23

Course 5: Reinforcement Learning

- Definitions of Reinforcement Learning (RL)
 - Policy and values
 - Policy Function

Policy Function

Definition

The policy function of an agent α is:

$$\pi : \begin{cases} S^\alpha & \rightarrow A \\ s_t^\alpha & \mapsto a_t^\alpha \end{cases}$$

■ π can be deterministic or stochastic.

Playout

The playout $(s_t^{\alpha, \pi})_{t \in \mathbb{N}}$ associated with a policy π and initial state s_0 , is defined by considering agent α takes his/her actions using π .

A policy is a function from the set of states to the set of actions. We can mirror here the previous course on CGT by defining the playout associated with a policy (in CGT, we were talking about strategies, but it is important to make the difference because strategies were defined on sequences of vertices in the arena).

Definition

Fix $\gamma \in [0, 1]$, the value function v^π is defined as:

$$v^\pi : \begin{cases} S^\alpha & \rightarrow \mathbb{R} \\ s_{t_0}^{\alpha, \pi} & \mapsto \sum_{t=t_0}^{+\infty} \gamma^{t-t_0} r_t \end{cases}$$

- The value of a policy function is thus an expectation of cumulative future rewards, weakened by the geometrical coefficient γ to avoid divergence and prioritize short term reward,
- The best possible policy $\pi^*(s)$ is defined as:

$$\forall s \in S^\alpha, \forall \pi, V^{\pi^*}(s) \geq V^\pi(s).$$

- └ Definitions of Reinforcement Learning (RL)
 - └ Policy and values
 - └ Value Function

$$v^\pi : \begin{cases} S^\alpha & \rightarrow \mathbb{R} \\ s_{t_0}^{\alpha, \pi} & \mapsto \sum_{t=t_0}^{+\infty} \gamma^{t-t_0} r_t \end{cases}$$

- The value of a policy function is thus an expectation of cumulative future rewards, weakened by the geometrical coefficient γ to avoid divergence and prioritize short term reward,
- The best possible policy $\pi^*(s)$ is defined as:

$$\forall s \in S^\alpha, \forall \pi, V^{\pi^*}(s) \geq V^\pi(s).$$

This definition is quite self explanatory ; it is the core of RL as value is directly the sum of future rewards. The value function captures the expected total future reward an agent in state S can obtain applying an action a associated to the policy π . The best policy is the one that maximize the value function. This basic principle is the basis of RL algorithm, such as Q-learning. GL: the total expected reward is not just the sum of the rewards associated to subsequent actions, but future rewards are multiplied by a factor that gets smaller for future rewards. This is also called DISCOUNTED future rewards: the closest reward in time counts more than future ones. Gamma is also called discounted factor.

Definition

Fix $\gamma \in [0, 1]$, the value function v^π is defined as:

$$v^\pi : \begin{cases} S^\alpha & \rightarrow \mathbb{R} \\ s_{t_0}^{\alpha, \pi} & \mapsto \sum_{t=t_0}^{+\infty} \gamma^{t-t_0} r_t \end{cases}$$

- The value of a policy function is thus an expectation of cumulative future rewards, weakened by the geometrical coefficient γ to avoid divergence and prioritize short term reward,
- The best possible policy $\pi^*(s)$ is defined as:

$$\forall s \in S^\alpha, \forall \pi, V^{\pi^*}(s) \geq V^\pi(s).$$

2023-11-23

Course 5: Reinforcement Learning

- └ Definitions of Reinforcement Learning (RL)
 - └ Policy and values
 - └ Value Function

Value Function

Definition

Fix $\gamma \in [0, 1]$, the value function v^π is defined as:

$$v^\pi : \begin{cases} S^\alpha & \rightarrow \mathbb{R} \\ s_{t_0}^{\alpha, \pi} & \mapsto \sum_{t=t_0}^{+\infty} \gamma^{t-t_0} r_t \end{cases}$$

- The value of a policy function is thus an expectation of cumulative future rewards, weakened by the geometrical coefficient γ to avoid divergence and prioritize short term reward,
- The best possible policy $\pi^*(s)$ is defined as:

$$\forall s \in S^\alpha, \forall \pi, V^{\pi^*}(s) \geq V^\pi(s).$$

This definition is quite self explanatory ; it is the core of RL as value is directly the sum of future rewards. The value function captures the expected total future reward an agent in state S can obtain applying an action a associated to the policy π . The best policy is the one that maximize the value function. This basic principle is the basis of RL algorithm, such as Q-learning. GL: the total expected reward is not just the sum of the rewards associated to subsequent actions, but future rewards are multiplied but a factor that gets smaller for future rewards. This is also called DISCOUNTED future rewards: the closest reward in time counts more than future ones. Gamma is also called discounted factor.

1 Definitions of Reinforcement Learning (RL)

- Fundamentals
- Example: PyRat
- Policy and values

2 Q-learning

- Q-learning definitions
- Example
- Approximate Q-learning
- Exploration/Exploitation

2023-11-23

Course 5: Reinforcement Learning

└ Q-learning

└ Plan

Plan

■ Definitions of Reinforcement Learning (RL)

- Fundamentals
- Example: PyRat
- Policy and values

■ Q-learning

- Q-learning definitions
- Example
- Approximate Q-learning
- Exploration/Exploitation

Definition

In Q-learning, we aim to find V^{π^*} as a solution to the recursive system of equations (Bellman equation):

$$\forall s \in S^\alpha, \forall a \in A, Q(s, a) = r_{s,a} + \gamma \max_{a'} Q(s(a), a'),$$

where $r_{s,a}$ is the reward agent α performs action a in state s and $s(a)$ is the state observed by agent α after performing action a .

Pros and cons

Pros:

- Can be learned even if the agent is not following any specific π ,
- Self training is possible,

Cons:

- Scalability issues when S^α is large.

2023-11-23

Course 5: Reinforcement Learning

└ Q-learning

└ Q-learning definitions

└ Q-learning

Q-learning

Definition

In Q-learning, we aim to find V^{π^*} as a solution to the recursive system of equations (Bellman equation):

$$\forall s \in S^\alpha, \forall a \in A, Q(s, a) = r_{s,a} + \gamma \max_{a'} Q(s(a), a'),$$

where $r_{s,a}$ is the reward agent α performs action a in state s and $s(a)$ is the state observed by agent α after performing action a .

Pros and Cons

Pros:

- Can be learned even if the agent is not following any specific π ,
- Self training is possible,

Cons:

- Scalability issues when S^α is large.

The tricky part of the definition of Q learning is that students have to understand about (1) the fact that it is defined iteratively and (2) that Q is defined on couples (s,a) and not just s , and (3) that $r_{s,a}$ is the reward that has been obtained by performing action a in state s . So, we are estimating $Q(s,a)$ by summing the obtained reward with the maximum possible Q value across all actions from the next state.

Definition

In Q-learning, we aim to find V^{π^*} as a solution to the recursive system of equations (Bellman equation):

$$\forall s \in S^\alpha, \forall a \in A, Q(s, a) = r_{s,a} + \gamma \max_{a'} Q(s(a), a'),$$

where $r_{s,a}$ is the reward agent α performs action a in state s and $s(a)$ is the state observed by agent α after performing action a .

Pros and cons

Pros:

- Can be learned even if the agent is not following any specific π ,
- Self training is possible,

Cons:

- Scalability issues when S^α is large.

2023-11-23

Course 5: Reinforcement Learning

└ Q-learning

└ Q-learning definitions

└ Q-learning

Q-learning

Definition

In Q-learning, we aim to find V^{π^*} as a solution to the recursive system of equations (Bellman equation):

$$\forall s \in S^\alpha, \forall a \in A, Q(s, a) = r_{s,a} + \gamma \max_{a'} Q(s(a), a'),$$

where $r_{s,a}$ is the reward agent α performs action a in state s and $s(a)$ is the state observed by agent α after performing action a .

Pros and cons

Pros:

- Can be learned even if the agent is not following any specific π ,
- Self training is possible,

Cons:

- Scalability issues when S^α is large.

The tricky part of the definition of Q learning is that students have to understand about (1) the fact that it is defined iteratively and (2) that Q is defined on couples (s,a) and not just s , and (3) that $r_{s,a}$ is the reward that has been obtained by performing action a in state s . So, we are estimating $Q(s,a)$ by summing the obtained reward with the maximum possible Q value across all actions from the next state.

Definition

In Q-learning, we aim to find V^{π^*} as a solution to the recursive system of equations (Bellman equation):

$$\forall s \in S^\alpha, \forall a \in A, Q(s, a) = r_{s,a} + \gamma \max_{a'} Q(s(a), a'),$$

where $r_{s,a}$ is the reward agent α performs action a in state s and $s(a)$ is the state observed by agent α after performing action a .

Pros and cons

Pros:

- Can be learned even if the agent is not following any specific π ,
- Self training is possible,

Cons:

- Scalability issues when S^α is large.

2023-11-23

Course 5: Reinforcement Learning

└ Q-learning

└ Q-learning definitions

└ Q-learning

Q-learning

Definition

In Q-learning, we aim to find V^{π^*} as a solution to the recursive system of equations (Bellman equation):

$$\forall s \in S^\alpha, \forall a \in A, Q(s, a) = r_{s,a} + \gamma \max_{a'} Q(s(a), a'),$$

where $r_{s,a}$ is the reward agent α performs action a in state s and $s(a)$ is the state observed by agent α after performing action a .

Pros and cons

Pros:

- Can be learned even if the agent is not following any specific π ,
- Self training is possible,

Cons:

- Scalability issues when S^α is large.

The tricky part of the definition of Q learning is that students have to understand about (1) the fact that it is defined iteratively and (2) that Q is defined on couples (s,a) and not just s , and (3) that $r_{s,a}$ is the reward that has been obtained by performing action a in state s . So, we are estimating $Q(s,a)$ by summing the obtained reward with the maximum possible Q value across all actions from the next state.

Q-learning: value iteration

Definition

In Q-learning, we aim to find V^{π^*} as a solution to the recursive system of equations (Bellman equation):

$$\forall s \in S^\alpha, \forall a \in A, Q(s, a) = r_{s,a} + \gamma \max_{a'} Q(s(a), a'),$$

where $r_{s,a}$ is the reward agent α performs action a in state s and $s(a)$ is the state observed by agent α after performing action a .

	UP	DOWN	RIGHT	LEFT
s1	+2	0	+1	+2.5
s2	0	+1	+4	+1
s3	0	+1	0	0
s4	0	+1	+2.5	+2.5

initialize Q[s,a] arbitrarily
observe initial state s

repeat

select action a
observe reward r and new state s'
Q[s,a]=r + γ max(Q[s',a'])
s=s'

until end

2023-11-23

Course 5: Reinforcement Learning

- Q-learning
 - Q-learning definitions
 - Q-learning: value iteration

Q-learning: value iteration

Definition

In Q-learning, we aim to find V^{π^*} as a solution to the recursive system of equations (Bellman equation):

$$\forall s \in S^\alpha, \forall a \in A, Q(s, a) = r_{s,a} + \gamma \max_{a'} Q(s(a), a'),$$

where $r_{s,a}$ is the reward agent α performs action a in state s and $s(a)$ is the state observed by agent α after performing action a .

	UP	DOWN	RIGHT	LEFT
s1	+2	0	+1	+2.5
s2	0	+1	+4	+1
s3	0	+1	0	0
s4	0	+1	+2.5	+2.5

initialize Q[s,a] arbitrarily
observe initial state s



repeat

select action a
observe reward r and new state s'
Q[s,a]=r + γ max(Q[s',a'])
s=s'

until end

This table associates a reward (Q) for each couple action state it is randomly initialized. Then at every exploration it is updated with the Q function: Q function is recursively updated following this rule. When the space of action becomes large, updating this table can become intractable–this relates to the scalability issue

Example



https://leonardoaraujasantos.gitbook.io/artificial-intelligence/artificial_intelligence/reinforcement_learning/qlearning_simple

2023-11-23

Course 5: Reinforcement Learning

└ Q-learning

└ Example

└ Example

Example



https://leonardoaraujasantos.gitbook.io/artificial-intelligence/artificial_intelligence/reinforcement_learning/qlearning_simple

Actions: 0,1,2,3,4,5 States: 0,1,2,3,4,5 Rewards:0,100

Example

Step 1: state 1, random action 5

$$Q = \begin{matrix} & \begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \end{matrix} \\ \begin{matrix} 0 \\ 1 \\ 2 \\ 3 \\ 4 \\ 5 \end{matrix} & \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \end{matrix} \quad \left| \quad \begin{matrix} & \text{Action} \\ \text{State} & \begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \end{matrix} \\ \begin{matrix} 0 \\ 1 \\ 2 \\ 3 \\ 4 \\ 5 \end{matrix} & \begin{bmatrix} -1 & -1 & -1 & -1 & 0 & -1 \\ -1 & -1 & -1 & 0 & -1 & 100 \\ -1 & -1 & -1 & 0 & -1 & -1 \\ -1 & 0 & 0 & -1 & 0 & -1 \\ 0 & -1 & -1 & 0 & -1 & 100 \\ -1 & 0 & -1 & -1 & 0 & 100 \end{bmatrix} \end{matrix} \quad \left| \quad \begin{matrix} & \text{Action} \\ \text{State} & \begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \end{matrix} \\ \begin{matrix} 0 \\ 1 \\ 2 \\ 3 \\ 4 \\ 5 \end{matrix} & \begin{bmatrix} -1 & -1 & -1 & -1 & 0 & -1 \\ -1 & -1 & -1 & 0 & -1 & 100 \\ -1 & -1 & -1 & 0 & -1 & -1 \\ -1 & 0 & 0 & -1 & 0 & -1 \\ 0 & -1 & -1 & 0 & -1 & 100 \\ -1 & 0 & -1 & -1 & 0 & 100 \end{bmatrix} \end{matrix} \quad \left| \quad \begin{matrix} & \begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \end{matrix} \\ \begin{matrix} 0 \\ 1 \\ 2 \\ 3 \\ 4 \\ 5 \end{matrix} & \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 100 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \end{matrix}$$

Update Q(1,5):

$$Q(1,5) = R(1,5) + 0.8 \cdot \max([Q(5,1), Q(5,4), Q(5,5)]) = 100 + 0.8(0) = 100$$

Step 2: state 3, random action 1

$$Q(3,1) = R(3,1) + 0.8 \cdot \max([Q(1,3), Q(1,5)]) = 0 + 0.8(100) = 80$$

Step 3:continue to better estimate the Q table

Course 5: Reinforcement Learning

Q-learning

Example

Example

Example

Step 1: state 1, random action 5

Q	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	0	0	0	0	0
2	0	0	0	0	0	0
3	0	0	0	0	0	0
4	0	0	0	0	0	0
5	0	0	0	0	0	0

Update Q(1,5):

$$Q(1,5) = R(1,5) + 0.8 \cdot \max([Q(5,1), Q(5,4), Q(5,5)]) = 100 + 0.8(0) = 100$$

Step 2: state 3, random action 1

$$Q(3,1) = R(3,1) + 0.8 \cdot \max([Q(1,3), Q(1,5)]) = 0 + 0.8(100) = 80$$

Step 3:continue to better estimate the Q table

The agent does not know the matrix of reward: it will learn it by experience by updating the Q matrix. At the beginning of the exploration all Q are zero. Let's consider our initial state Room 1 and $\gamma = 0.8...$ Different steps, or episodes are needed to estimate the Q table.

Approximated Q-learning

Definition

- Train a model to approximate Q ,
 - Input is a state s and output is made of values of $Q(s, \cdot)$,
 - Representation learning can be used to compress S^α .

Problems

- Almost always needs a simulator for the game,
- Game duration can be bottleneck for training,
- Catastrophic forgetting and adversary specialization,
 - These effects can be alleviated by training using experience replay.

Experience replay

- Instead of using only the last decision to train, sample at random from the m previous decisions,
- Decisions taken before should remain considered now.

2023-11-23

Course 5: Reinforcement Learning

- └ Q-learning
 - └ Approximate Q-learning
 - └ Approximated Q-learning

Approximated Q-learning

Definition

- Train a model to approximate Q ,
- Input is a state s and output is made of values of $Q(s, \cdot)$,
- Representation learning can be used to compress S^α .

Problems

- Almost always needs a simulator for the game,
- Game duration can be bottleneck for training,
- Catastrophic forgetting and adversary specialization,
 - These effects can be alleviated by training using experience replay.

Experience replay

- Instead of using only the last decision to train, sample at random from the m previous decisions,
- Decisions taken before should remain considered now.

GL: Estimating the Q table becomes soon intractable, even for simple games! In the majority of RL application we learn a model that, given state and action approximate the Q function. AlphaGo,.. Experience Replay is one of the tricks that researchers have discovered to make (Deep) RL efficient and stable: by randomly sampling a batch of experiences from a buffer/memory, we avoid catastrophic forgetting (last experience cancel impact of first ones) and correlation between series of consequent experiences.

Approximated Q-learning

Definition

- Train a model to approximate Q ,
 - Input is a state s and output is made of values of $Q(s, \cdot)$,
 - Representation learning can be used to compress S^α .

Problems

- Almost always needs a simulator for the game,
- Game duration can be bottleneck for training,
- Catastrophic forgetting and adversary specialization,
 - These effects can be alleviated by training using experience replay.

Experience replay

- Instead of using only the last decision to train, sample at random from the m previous decisions,
- Decisions taken before should remain considered now.

2023-11-23

Course 5: Reinforcement Learning

- └ Q-learning
 - └ Approximate Q-learning
 - └ Approximated Q-learning

Approximated Q-learning	
Definition	<ul style="list-style-type: none">■ Train a model to approximate Q,■ Input is a state s and output is made of values of $Q(s, \cdot)$,■ Representation learning can be used to compress S^α.
Problems	<ul style="list-style-type: none">■ Almost always needs a simulator for the game,■ Game duration can be bottleneck for training,■ Catastrophic forgetting and adversary specialization,<ul style="list-style-type: none">■ These effects can be alleviated by training using experience replay.
Experience replay	<ul style="list-style-type: none">■ Instead of using only the last decision to train, sample at random from the m previous decisions,■ Decisions taken before should remain considered now.

GL: Estimating the Q table becomes soon intractable, even for simple games! In the majority of RL application we learn a model that, given state and action approximate the Q function. AlphaGo,.. Experience Replay is one of the tricks that researchers have discovered to make (Deep) RL efficient and stable: by randomly sampling a batch of experiences from a buffer/memory, we avoid catastrophic forgetting (last experience cancel impact of first ones) and correlation between series of consequent experiences.

Approximated Q-learning

Definition

- Train a model to approximate Q ,
 - Input is a state s and output is made of values of $Q(s, \cdot)$,
 - Representation learning can be used to compress S^α .

Problems

- Almost always needs a simulator for the game,
- Game duration can be bottleneck for training,
- Catastrophic forgetting and adversary specialization,
 - These effects can be alleviated by training using experience replay.

Experience replay

- Instead of using only the last decision to train, sample at random from the m previous decisions,
- Decisions taken before should remain considered now.

2023-11-23

Course 5: Reinforcement Learning

- └ Q-learning
 - └ Approximate Q-learning
 - └ Approximated Q-learning

Approximated Q-learning	
Definition	<ul style="list-style-type: none">■ Train a model to approximate Q,■ Input is a state s and output is made of values of $Q(s, \cdot)$,■ Representation learning can be used to compress S^α.
Problems	<ul style="list-style-type: none">■ Almost always needs a simulator for the game,■ Game duration can be bottleneck for training,■ Catastrophic forgetting and adversary specialization,<ul style="list-style-type: none">■ These effects can be alleviated by training using experience replay.
Experience replay	<ul style="list-style-type: none">■ Instead of using only the last decision to train, sample at random from the m previous decisions,■ Decisions taken before should remain considered now.

GL: Estimating the Q table becomes soon intractable, even for simple games! In the majority of RL application we learn a model that, given state and action approximate the Q function. AlphaGo,.. Experience Replay is one of the tricks that researchers have discovered to make (Deep) RL efficient and stable: by randomly sampling a batch of experiences from a buffer/memory, we avoid catastrophic forgetting (last experience cancel impact of first ones) and correlation between series of consequent experiences.

Dilemma

- Repeat with existing strategy (Exploitation)...
- ... or try a new strategy (Exploration)?

Example

- Always eating in restaurants that you know is exploitation,
- While that is a good heuristic, you have no way of knowing if you have the maximum reward possible,
- So exploring new restaurants from time to time may be needed to find the maximum reward.

2023-11-23

Course 5: Reinforcement Learning

- └ Q-learning
 - └ Exploration/Exploitation
 - └ Exploration/Exploitation

Exploration/Exploitation

Dilemma

- Repeat with existing strategy (Exploitation)...
- ... or try a new strategy (Exploration)?

Example

- Always eating in restaurants that you know is exploitation,
- While that is a good heuristic, you have no way of knowing if you have the maximum reward possible,
- So exploring new restaurants from time to time may be needed to find the maximum reward.

GL we have seen that in RL algorithm we get to know the best possible actions by exploring the world, by playing the game.. Q-table is filled by randomly choosing actions, then when we get a good estimation we can be more confident in our policy, and repeat it to get max reward. This describes well the exploitation/exploration dilemma: usually at the beginning we do more exploration, then more exploitation: and it's generally a good trick to have a SOFT policy

Dilemma

- Repeat with existing strategy (Exploitation)...
- ... or try a new strategy (Exploration)?

Example

- Always eating in restaurants that you know is exploitation,
- While that is a good heuristic, you have no way of knowing if you have the maximum reward possible,
- So exploring new restaurants from time to time may be needed to find the maximum reward.

2023-11-23

Course 5: Reinforcement Learning

- └ Q-learning
 - └ Exploration/Exploitation
 - └ Exploration/Exploitation

Exploration/Exploitation

Dilemma

- Repeat with existing strategy (Exploitation)...
- ... or try a new strategy (Exploration)?

Example

- Always eating in restaurants that you know is exploitation,
- While that is a good heuristic, you have no way of knowing if you have the maximum reward possible,
- So exploring new restaurants from time to time may be needed to find the maximum reward.

GL we have seen that in RL algorithm we get to know the best possible actions by exploring the world, by playing the game.. Q-table is filled by randomly choosing actions, then when we get a good estimation we can be more confident in our policy, and repeat it to get max reward. This describes well the exploitation/exploration dilemma: usually at the beginning we do more exploration, then more exploitation: and it's generally a good trick to have a SOFT policy

TP4 - PyRat with reinforcement learning

- Approximate Q-learning algorithm using experience replay and linear regression to beat the greedy algorithm,
- Approximation method (linear regression) and experience replay routine are given,
- Improve the performances of Reinforcement Learning to play PyRat.

Challenge

You can continue working in the challenge after finishing the RL practical. You can now integrate reinforcement learning in your solution.

Challenge

You can continue working in the challenge after finishing the RL practical. You can now integrate reinforcement learning in your solution.