Perl - Regular Expressions

Because Perl makes heavy use of strings, regular expressions are a very important component of the language.

They can be used:

- in conditional expressions to test whether a string matches a pattern
 - e.g. checking the contents of a string if (n = (0-9)) { print "name contains digit"; }
- in assignments to modify the value of a string e.g. convert McDonald to MacDonald
 - \$name =~ s/Mc/Mac/;
- e.g. convert to upper case
 - \$string =~ tr/a-z/A-Z/;

Perl Regular Expressions

Because Perl makes heavy use of strings, regular expressions are a very important component of the language.

They can be used:

- in conditional expressions to test whether a string matches a pattern
 - e.g. checking the contents of a string
 - if (name = (0-9)) { print "name contains digit\n"; }
- $\bullet\,$ in assignments to modify the value of a string
 - e.g. convert McDonald to MacDonald
 - \$name =~ s/Mc/Mac/;

Perl Regular Expressions

Perl extends POSIX regular expressions with some shorthand:

```
\d matches any digit, i.e. [0-9]
```

\D matches any non-digit, i.e. $[^0-9]$

 \warpoonup matches any "word" char, i.e. [a-zA-Z_0-9]

\W matches any non "word" char, i.e. [^a-zA-Z_0-9]

\s matches any whitespace, i.e. $[\t \r\f]$

\S matches any non-whitespace, i.e. $[^ \t \r\f]$

Perl Regular Expressions

Perl also adds some new anchors to regexps:

\b matches at a word boundary

\B matches except at a word boundary

And generalises the repetition operators:

```
patt* matches 0 or more occurences of patt
```

patt+ matches 1 or more occurences of patt

patt? matches 0 or 1 occurence of patt

 $patt{n,m}$ matches between n and m occurrences of patt

Perl Regular Expressions

The default semantics for pattern matching is "first, then largest". E.g. /ab+/ matches abbbabbb not abbbabbb or abbbabbbb or abbbabbbb

A pattern can also be qualified so that it looks for the shortest match.

If the repetition operator is followed by ? the "first, then shortest" string that matches the pattern is chosen.

E.g. /ab+?/ would match abbbabbbb

Using Matching Results

In a scalar context matching & substitute operators return how many times the match/substitute succeeded.

This allows them to be used as the controlling expression in if/while statements.

For example:

```
print "Destroy the file system? "
$answer = <STDIN>;
if ($answer =~ /yes||ok|affirmative/i) {
    system "rm -r /";
}
s/[aeiou]//g or die "now vowels to replace";
```

Perl Regular Expressions

```
Regular expressions can be formed by interpolating strings in
between /.../.
Example:

    $pattern = "ab+";
    $replace = "Yod";
    $text = "abba";

$text =~ s/$pattern/$replace/;
```

Note: Perl doesn't confuse the use of \$ in \$var and abc\$, because the anchor occurs at the end.

Using Matching Results

converts "abba" to "Yoda"

In a list context the matching operators returns a list of the matched strings.

For example:

```
$string = "-5==10zzz200_";
@numbers = $string =~ /\d+/g;
print join(",", @numbers), "\n";
# prints 5,10,200

If the regex contains ()s only the captured text is returned

$string = "Bradley, Marion Zimmer";
($family_name, $given_name) = $string =~ /([^,]*), (\S+)/;
print "$given_name $family_name\n";
# prints Marion Bradley
```

Pattern Matcher

```
A Perl script to accept a pattern and a string and show the match (if any):
```

```
#!/usr/bin/perl
```

```
$pattern = $ARGV[0]; print "pattern=/$pattern/\n";
```

You might find this a useful tool to test out your understanding of regular expressions.

