



DSA Arrays


[< Previous](#)[Next >](#)

Arrays

An array is a data structure used to store multiple elements.

Arrays are used by many algorithms.

For example, an algorithm can be used to look through an array to find the lowest value, like the animation below shows:



In Python, an array can be created like this:

```
my_array = [7, 12, 9, 4, 11]
```

Note: The Python code above actually generates a Python 'list' data type, but for the scope of this tutorial the 'list' data type can be used in the same way as an array. Learn more about Python lists [here](#).

Arrays are indexed, meaning that each element in the array has an index, a number that says where in the array the element is located. The programming languages in this tutorial (Python, Java, and C) use zero-based indexing for arrays, meaning that the first element in an array can be accessed at index 0.

In Python, this code use index 0 to write the first array element (value 7) to the console:

Example

Python:

```
my_array = [7, 12, 9, 4, 11]  
print( my_array[0] )
```

Algorithm: Find The Lowest Value in an Array


Let's create our first algorithm using the array data structure.

Below is the algorithm to find the lowest number in an array.

How it works:

1. Go through the values in the array one by one.
2. Check if the current value is the lowest so far, and if it is, store it.
3. After looking at all the values, the stored value will be the lowest of all values in the array.

Try the simulation below to see how the algorithm for finding the lowest value works (the animation is the same as the one on the top of this page):



This next simulation also finds the lowest value in an array, just like the simulation above, but here we can see how the numbers inside the array are checked to find the lowest value:



Implementation

Before implementing the algorithm using an actual programming language, it is usually smart to first write the algorithm as a step-by-step procedure.

If you can write down the algorithm in something between human language and programming language, the algorithm will be easier to implement later because we avoid drowning in all the details of the programming language syntax.

1. Create a variable 'minVal' and set it equal to the first value of the array.
2. Go through every element in the array.
3. If the current element has a lower value than 'minVal', update 'minVal' to this value.
4. After looking at all the elements in the array, the 'minVal' variable now contains the lowest value.

You can also write the algorithm in a way that looks more like a programming language if you want to, like this:

```
Variable 'minVal' = array[0]
For each element in the array
  If current element < minVal
    minVal = current element
```

Note: The two step-by-step descriptions of the algorithm we have written above can be called 'pseudocode'. Pseudocode is a description of what a program does, using language that is something between human language and a programming language.

After we have written down the algorithm, it is much easier to implement the algorithm in a specific programming language:

```
my_array = [7, 12, 9, 4, 11]
minVal = my_array[0]    # Step 1

for i in my_array:      # Step 2
    if i < minVal:       # Step 3
        minVal = i


print('Lowest value: ',minVal) # Step 4
```

Try it Yourself »

Algorithm Time Complexity

When exploring algorithms, we often look at how much time an algorithm takes to run relative to the size of the data set.

In the example above, the time the algorithm needs to run is proportional, or linear, to the size of the data set. This is because the algorithm must visit every array element one time to find the lowest value. The loop must run 5 times since there are 5 values in the array. And if the array had 1000 values, the loop would have to run 1000 times.



Try the simulation below to see this relationship between the number of compare operations needed to find the lowest value, and the size of the array.

See [this page](#) for a more thorough explanation of what time complexity is.

Each algorithm in this tutorial will be presented together with its time complexity.


☒ Random☐ Descending☐ Ascending

Operations: 0

☐ 10 Random

Run

Clear



DSA Exercises

Test Yourself With Exercises

Exercise:

How can we print value "7" from the array below?

```
my_array = [7, 12, 9, 4, 11]
```

[Tutorials ▼](#)[References ▼](#)[Exercises ▼](#)[Sign In](#)[SS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#)[Submit Answer »](#)[Start the Exercise](#)[◀ Previous](#)[Sign in to track progress](#)[Next >](#)


Get Certified!

Document your skills with all of
W3Schools Certificates

\$1,995

\$499

Save 75% 🎧



COLOR PICKER



[Tutorials ▼](#)[References ▼](#)[Exercises ▼](#)[Sign In](#)[≡](#) [SS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#)[PLUS](#)[SPACES](#)[GET CERTIFIED](#)[FOR TEACHERS](#)[FOR BUSINESS](#)[CONTACT US](#)

Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [AngularJS Reference](#)
- [jQuery Reference](#)

Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)

Get Certified

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [Front End Certificate](#)
- [SQL Certificate](#)
- [Python Certificate](#)
- [PHP Certificate](#)
- [jQuery Certificate](#)
- [Java Certificate](#)

[Tutorials](#) ▼[References](#) ▼[Exercises](#) ▼[Sign In](#)[≡](#) [SS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#)[FORUM](#) [ABOUT](#) [ACADEMY](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness

of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookies](#) and [privacy policy](#).

[Copyright 1999-2026](#) by Refsnes Data. All Rights Reserved. [W3Schools is Powered by W3.CSS](#).