

Odoo API Requirement

Master Data & Party Price APIs for FieldKonnnect

Version 1.4 · 07 Oct 2026 · From: FieldKonnnect team · To: Odoo development team

1. Purpose

FieldKonnnect needs five new APIs from Odoo:

- **API 1 – Category List:** category name and Odoo ID.
- **API 2 – Sub-category List:** sub-category name and Odoo ID.
- **API 3 – Product List:** product name and Odoo ID, with its category, sub-category, unit of measure and prices.
- **API 4 – Party-wise Product Price:** the price of each product for each party.
- **API 5 – Primary Customer List:** dealers and distributors (customers only, no vendors) with address, GST and salesperson.

All five APIs also return `active`, `is_deleted`, `created_at` and `updated_at` for every record.

FieldKonnnect will use the Odoo IDs as the permanent keys to map Odoo records to its own masters. The existing methods (`get_fieldkonnnect_categories`, `get_fieldkonnnect_subcategories`, `get_fieldkonnnect_products`, `get_customer_product_price`) stay as they are. These are new methods.

2. Connection (same as the existing APIs)

Item	Value
Endpoint	POST <code>https://<odoo-host>/json-call</code>
Header	Content-Type: <code>application/json</code>
Protocol	JSON-RPC 2.0, with "method": "call" at the top level
Authentication	<code>params.authenticate</code> block with <code>db</code> , <code>login (fieldkonnnect_API_user)</code> and <code>dev_key</code> , same as the existing APIs. No session cookie should be required.

3. API 1 – Category List

Item	Value
Model	<code>product.category</code>
Method name	<code>get_fieldkonnnect_category_list</code>
Returns	Product categories (for example: PVC Pipes, HDPE Pipe, Column Coupler)

Request parameters (inside `args[0]`)

Parameter	Type	Required	Description
<code>page</code>	integer	No	Page number. Default 1.
<code>page_size</code>	integer	No	Records per page. Default 100, maximum 500.

Response fields (each item in data)

Field	Type	Required	Description
category_odoo_id	integer	Yes	Odoo ID of the category (product.category id). Unique and never changes.
category_name	string	Yes	Category name exactly as stored in Odoo.
active	boolean	Yes	true when the record is active in Odoo, false when archived.
is_deleted	boolean	Yes	true when the record was deleted in Odoo.
created_at	string	Yes	Date-time the record was created, ISO 8601 in UTC, e.g. 2026-05-25T09:14:29Z.
updated_at	string	Yes	Date-time the record was last changed, ISO 8601 in UTC, e.g. 2026-10-06T11:11:14Z.

No other fields are needed in data.

Example request

```
POST https://<odoo-host>/json-call
Content-Type: application/json

{
  "jsonrpc": "2.0",
  "method": "call",
  "params": {
    "authenticate": [{
      "db": "<odoo db>",
      "login": "fieldkconnect_API_user",
      "dev_key": "<dev_key>"
    }],
    "model": "product.category",
    "method": "get_fieldkconnect_category_list",
    "args": [{ "page": 1, "page_size": 500 }]
  }
}
```

Example response

```
{
  "jsonrpc": "2.0",
  "id": null,
  "result": {
    "success": true,
    "message": "Records fetched successfully",
    "data": [
      {
        "category_odoo_id": 14,
        "category_name": "PVC Pipes",
        "active": true,
        "is_deleted": false,
        "created_at": "2026-05-25T09:14:29Z",
        "updated_at": "2026-10-06T11:11:14Z"
      }
    ],
    "pagination": {
      "page": 1, "page_size": 500, "total_records": 1,
      "total_pages": 1, "has_next": false
    }
  }
}
```

4. API 2 – Sub-category List

Item	Value
Model	product.category
Method name	get_fieldkconnect_subcategory_list
Returns	Product sub-categories (for example: Column Pipe, Heavy Pipe, HDPE PE 100 Pipe)

Request parameters (inside args[0])

Parameter	Type	Required	Description
page	integer	No	Page number. Default 1.
page_size	integer	No	Records per page. Default 100, maximum 500.

Response fields (each item in data)

Field	Type	Required	Description
subcategory_odoo_id	integer	Yes	Odoo ID of the sub-category (product.category id). Unique and never changes.
subcategory_name	string	Yes	Sub-category name exactly as stored in Odoo.
active	boolean	Yes	true when the record is active in Odoo, false when archived.
is_deleted	boolean	Yes	true when the record was deleted in Odoo.
created_at	string	Yes	Date-time the record was created, ISO 8601 in UTC, e.g. 2026-05-25T09:14:29Z.
updated_at	string	Yes	Date-time the record was last changed, ISO 8601 in UTC, e.g. 2026-10-06T11:11:14Z.

No other fields are needed in data.

Example request

```
POST https://<odoo-host>/json-call
Content-Type: application/json

{
  "jsonrpc": "2.0",
  "method": "call",
  "params": {
    "authenticate": [{
      "db": "<odoo db>",
      "login": "fieldkconnect_API_user",
      "dev_key": "<dev_key>"
    }],
    "model": "product.category",
    "method": "get_fieldkconnect_subcategory_list",
    "args": [{ "page": 1, "page_size": 500 }]
  }
}
```

Example response

```
{
  "jsonrpc": "2.0",
  "id": null,
  "result": {
    "success": true,
    "message": "Records fetched successfully",
    "data": [
      {
        "subcategory_odoo_id": 27,
        "subcategory_name": "Column Pipe",
        "active": true,
        "is_deleted": false,
        "created_at": "2026-05-25T09:14:29Z",
        "updated_at": "2026-10-06T11:11:14Z"
      }
    ],
    "pagination": {
      "page": 1, "page_size": 500, "total_records": 1,
      "total_pages": 1, "has_next": false
    }
  }
}
```

5. API 3 – Product List

Item	Value
Model	<code>product.product</code>
Method name	<code>get_fieldkconnect_product_list</code>
Returns	Products, with their category, sub-category, unit of measure and prices

Request parameters (inside `args[0]`)

Parameter	Type	Required	Description
<code>page</code>	integer	No	Page number. Default 1.
<code>page_size</code>	integer	No	Records per page. Default 100, maximum 500.

Response fields (each item in data)

Field	Type	Required	Description
<code>product_name</code>	string	Yes	Product name exactly as stored in Odoo.
<code>product_odoo_id</code>	integer	Yes	Odoo ID of the product (<code>product.product id</code>). Unique and never changes.
<code>category_name</code>	string	Yes	Name of the product's category.
<code>category_odoo_id</code>	integer	Yes	Odoo ID of the product's category. Same value as <code>category_odoo_id</code> in API 1.
<code>subcategory_name</code>	string	No	Name of the product's sub-category. <code>null</code> when the product has no sub-category.
<code>subcategory_odoo_id</code>	integer	No	Odoo ID of the product's sub-category. Same value as <code>subcategory_odoo_id</code> in API 2. <code>null</code> when the product has no sub-category.
<code>uom_name</code>	string	Yes	Unit of measure name, for example NOS.
<code>uom_id</code>	integer	Yes	Odoo ID of the unit of measure (<code>uom.uom id</code>).
<code>mrp</code>	number	Yes	Maximum retail price (0 or more), up to 2 decimals.
<code>standard_price</code>	number	Yes	Standard price / cost from Odoo (0 or more), up to 2 decimals.
<code>gst_percent</code>	number	Yes	GST rate in percent, for example 18. 0 when the product has no GST.
<code>active</code>	boolean	Yes	<code>true</code> when the record is active in Odoo, <code>false</code> when archived.
<code>is_deleted</code>	boolean	Yes	<code>true</code> when the record was deleted in Odoo.
<code>created_at</code>	string	Yes	Date-time the record was created, ISO 8601 in UTC, e.g. 2026-05-25T09:14:29Z.
<code>updated_at</code>	string	Yes	Date-time the record was last changed, ISO 8601 in UTC, e.g. 2026-10-06T11:11:14Z.

No other fields are needed in data.

Example request

```
POST https://<odoo-host>/json-call
Content-Type: application/json

{
  "jsonrpc": "2.0",
  "method": "call",
  "params": {
    "authenticate": [{
      "db": "<odoo db>",
      "login": "fieldkconnect_API_user",
      "dev_key": "<dev_key>"
    }],
    "model": "product.product",
    "method": "get_fieldkconnect_product_list",
    "args": [{ "page": 1, "page_size": 500 }]
  }
}
```

Example response

```
{
  "jsonrpc": "2.0",
  "id": null,
  "result": {
    "success": true,
    "message": "Records fetched successfully",
    "data": [
      {
        "product_name": "FMED 1\\(25mm ND)Belling Column Pipe",
        "product_odoo_id": 8432,
        "category_name": "PVC Pipes",
        "category_odoo_id": 14,
        "subcategory_name": "Medium Pipe",
        "subcategory_odoo_id": 31,
        "uom_name": "NOS",
        "uom_id": 1,
        "mrp": 245.5,
        "standard_price": 180.0,
        "gst_percent": 18.0,
        "active": true,
        "is_deleted": false,
        "created_at": "2026-05-25T09:14:29Z",
        "updated_at": "2026-10-06T11:11:14Z"
      }
    ],
    "pagination": {
      "page": 1, "page_size": 500, "total_records": 1,
      "total_pages": 1, "has_next": false
    }
  }
}
```

6. API 4 – Party-wise Product Price

Item	Value
Model	<code>product.pricelist</code>
Method name	<code>get_fieldkconnect_party_price_list</code>
Returns	The final price of each product for each party

Request parameters (inside `args[0]`)

Parameter	Type	Required	Description
<code>party_odoo_id</code>	integer	No	Return the prices of this party only.
<code>product_odoo_id</code>	integer	No	Return the prices of this product only.
<code>page</code>	integer	No	Page number. Default 1.
<code>page_size</code>	integer	No	Records per page. Default 100, maximum 500.

Response fields (each item in data)

Field	Type	Required	Description
<code>product_name</code>	string	Yes	Product name exactly as stored in Odoo.
<code>product_odoo_id</code>	integer	Yes	Odoo ID of the product. Same value as <code>product_odoo_id</code> in API 3.
<code>party_odoo_id</code>	integer	Yes	Odoo ID of the party (res.partner id). Unique and never changes.
<code>party_name</code>	string	Yes	Party name exactly as stored in Odoo.
<code>party_price</code>	number	Yes	Final price of this product for this party (0 or more), up to 2 decimals.
<code>active</code>	boolean	Yes	<code>true</code> when the record is active in Odoo, <code>false</code> when archived.
<code>is_deleted</code>	boolean	Yes	<code>true</code> when the record was deleted in Odoo.
<code>created_at</code>	string	Yes	Date-time the record was created, ISO 8601 in UTC, e.g. 2026-05-25T09:14:29Z.
<code>updated_at</code>	string	Yes	Date-time the record was last changed, ISO 8601 in UTC, e.g. 2026-10-06T11:11:14Z.

No other fields are needed in data.

Example request

```
POST https://<odoo-host>/json-call
Content-Type: application/json

{
  "jsonrpc": "2.0",
  "method": "call",
  "params": {
    "authenticate": [{
      "db": "<odoo db>",
      "login": "fieldkconnect_API_user",
      "dev_key": "<dev_key>"
    }],
    "model": "product.pricelist",
    "method": "get_fieldkconnect_party_price_list",
    "args": [{
      "party_odoo_id": 8421,
      "product_odoo_id": 8432,
      "page": 1, "page_size": 500 }]
  }
}
```

Example response

```
{
  "jsonrpc": "2.0",
  "id": null,
  "result": {
    "success": true,
    "message": "Records fetched successfully",
    "data": [
      {
        "product_name": "FMED 1\"(25mm ND)Belling Column Pipe",
        "product_odoo_id": 8432,
        "party_odoo_id": 8421,
        "party_name": "Shree Ganesh Traders",
        "party_price": 232.75,
        "active": true,
        "is_deleted": false,
        "created_at": "2026-05-25T09:14:29Z",
        "updated_at": "2026-10-06T11:11:14Z"
      }
    ],
    "pagination": {
      "page": 1, "page_size": 500, "total_records": 1,
      "total_pages": 1, "has_next": false
    }
  }
}
```

7. API 5 – Primary Customer List

Item	Value
Model	res.partner
Method name	get_fieldkconnect_customer_list
Returns	Primary customers (dealers and distributors) only. Vendors must not be returned. Return one row per customer firm (the parent record), not its child contacts or delivery addresses.

Request parameters (inside args[0])

Parameter	Type	Required	Description
page	integer	No	Page number. Default 1.
page_size	integer	No	Records per page. Default 100, maximum 500.

Response fields (each item in data)

Field	Type	Required	Description
odoo_parent_id	integer	Yes	Odoo ID of the customer firm (parent res.partner id). Unique and never changes. Same value as party_odoo_id in API 4.
firm_name	string	Yes	Firm / company name exactly as stored in Odoo.
contact_person_name	string	No	Name of the main contact person.
mobile	string	No	Mobile number, digits only, e.g. 9876543210.
phone	string	No	Landline / other phone number.
email	string	No	Email address.
street	string	No	Address line 1.
street2	string	No	Address line 2.
city	string	No	City name.
district	string	No	District name.
state	string	No	State name, e.g. Rajasthan.
pin_code	string	No	6-digit PIN code, sent as a string.
country	string	No	Country name, e.g. India.
gst_in	string	No	Party GSTIN (15 characters). Empty when the party is unregistered.
salesperson	string	No	Name of the salesperson assigned to this customer in Odoo.
customer_type	string	Yes	Always the fixed text Distributor for now.

Field	Type	Required	Description
customer_type_id	integer	Yes	Always the fixed value 1 for now (FieldKconnect ID of the Distributor customer type).
active	boolean	Yes	true when the record is active in Odoo, false when archived.
is_deleted	boolean	Yes	true when the record was deleted in Odoo.
created_at	string	Yes	Date-time the record was created, ISO 8601 in UTC, e.g. 2026-05-25T09:14:29Z.
updated_at	string	Yes	Date-time the record was last changed, ISO 8601 in UTC, e.g. 2026-10-06T11:11:14Z.

No other fields are needed in data.

Example request

```
POST https://<odoo-host>/json-call
Content-Type: application/json

{
  "jsonrpc": "2.0",
  "method": "call",
  "params": {
    "authenticate": [{
      "db": "<odoo db>",
      "login": "fieldkconnect_API_user",
      "dev_key": "<dev_key>"
    }],
    "model": "res.partner",
    "method": "get_fieldkconnect_customer_list",
    "args": [{ "page": 1, "page_size": 500 }]
  }
}
```

Example response

```
{
  "jsonrpc": "2.0",
  "id": null,
  "result": {
    "success": true,
    "message": "Records fetched successfully",
    "data": [
      {
        "odoo_parent_id": 8421,
        "firm_name": "Shree Ganesh Traders",
        "contact_person_name": "Ramesh Sharma",
        "mobile": "9876543210",
        "phone": "01412345678",
        "email": "ganesh.traders@example.com",
        "street": "12, Industrial Area",
        "street2": "Near Bus Stand",
        "city": "Jaipur",
        "district": "Jaipur",
        "state": "Rajasthan",
        "pin_code": "302013",
        "country": "India",
        "gst_in": "08ABCDE1234F1Z5",
        "salesperson": "Amit Verma",
        "customer_type": "Distributor",
        "customer_type_id": 1,
        "active": true,
        "is_deleted": false,
        "created_at": "2026-05-25T09:14:29Z",
        "updated_at": "2026-10-06T11:11:14Z"
      }
    ],
    "pagination": {
      "page": 1, "page_size": 500, "total_records": 1,
      "total_pages": 1, "has_next": false
    }
  }
}
```

8. Rules for all APIs

- **IDs:** every `..._id` field must be an integer (the Odoo record id, not a string like "product.category:7"). An ID must never change or be reused.
- **Names:** send the name exactly as in Odoo. Do not change its case or add a prefix.
- **Archived and deleted records:** return them too, with `active` / `is_deleted` set, so FieldKconnect can stop using them. Do not silently drop a record that was returned before.
- **Dates:** `created_at` and `updated_at` in ISO 8601, UTC, ending with Z. `updated_at` must change whenever any returned field changes.
- **Order:** sort by ID ascending, so that pagination is stable between calls.
- **Pagination:** always return the pagination block. FieldKconnect keeps calling the next page while `has_next` is true.
- **Empty result:** return `success: true` with an empty data array, not an error.

9. Error response

When the request is invalid (for example, a bad `page_size`), return `success: false` with a clear message. Authentication failures can keep the standard Odoo JSON-RPC error object (`AccessDenied`).

```
{
  "jsonrpc": "2.0",
  "id": null,
  "result": {
    "success": false,
    "message": "page_size must be between 1 and 500",
    "data": []
  }
}
```

10. Acceptance check

FieldKconnect will treat the APIs as ready when:

- All five methods work on the stage database with the `fieldkconnect_API_user` login and `dev_key`, without a session cookie.
- Every record has a non-empty integer ID, a non-empty name, and all fields listed above.
- The IDs match the record IDs visible in Odoo (`product.category`, `product.product`, `uom.uom`, `res.partner`).
- In API 3, every `category_odoo_id` and `subcategory_odoo_id` exists in API 1 and API 2.
- In API 4, every `product_odoo_id` exists in API 3, and each party and product pair appears only once.
- API 5 returns only dealers and distributors (no vendors, no child contacts), each with `customer_type` "Distributor" and `customer_type_id` 1, and every `odoo_parent_id` matches the `party_odoo_id` used in API 4.
- Paging through all pages returns every record exactly once.