

Grid Interconnection Application Form

Distribution connection — mixed

PROJECT ID: DX-MIX-006

PROJECT NAME: Meadowbank Solar + Storage

APPLICANT: Meadowbank Energy Ltd

LEVEL: distribution

CONNECTION TYPE: mixed

CAPACITY: 15 MW PV + 10 MW / 20 MWh BESS

STATUS: Under review

DATE SUBMITTED: 2026-05-09

SECTION 1: Per-technology applications

REQUIREMENT:

One G99 application per generator / storage unit, each with its own Type and form set. Source: G99 §2.2; DCode DPC §6.

SUBMITTED:

Two G99 modules: PV array 15 MW (Type C) and BESS 10 MW / 20 MWh (Type C). Each declared with its own technical data set and registered capacity.

SUPPORTING DOCS:

none

SECTION 2: Combined site capacities

REQUIREMENT:

Firm export capacity and total import capacity for the whole site. Source: DCUSA capacity registration.

SUBMITTED:

Firm export capacity 15 MW (site controller caps combined export). Total import capacity 10 MW for BESS charging plus 0.3 MW auxiliaries.

SUPPORTING DOCS:

single_line_diagram.pdf

SECTION 3: Storage flow declaration

REQUIREMENT:

BESS declared as import-only, export-only, or import + export, and whether it can charge from the grid or only from co-located generation. Source: G99; DCUSA.

SUBMITTED:

The BESS is configured export-only and charges exclusively from the co-located PV array. It qualifies for a single export-only commercial registration and cannot import from the grid.

SUPPORTING DOCS:

single_line_diagram.pdf

SECTION 4: Site dispatch logic

REQUIREMENT:

How the technologies share the connection — priority rules, curtailment order, BESS charge/discharge logic. Source: NESO Co-location Guidance (technical principles).

SUBMITTED:

Master site controller prioritises direct PV export to the firm limit; surplus PV charges the BESS; the BESS discharges in the evening peak. Combined export is hard-limited to 15 MW.

SUPPORTING DOCS:

control_philosophy.pdf

SECTION 5: Curtailment / flexible-connection terms

REQUIREMENT:

Acceptance of an active network management (ANM) contract — curtailment in exchange for an earlier connection. Source: DCode DPC §6 (flexible).

SUBMITTED:

Meadowbank accepts an ANM-managed flexible connection and will install the DNO's ANM interface for real-time export curtailment.

SUPPORTING DOCS:

none