

CEILING SADDLE

Technical data / extra information sheet

Mechanical Theatre Equipment Compliance Portal

Purpose of this sheet

A technical record template for this equipment. Complete and review it using the actual manufacturer instructions, installation design, inspection records and site assessment. It does not certify an asset or assign a load rating.

1. Equipment identification

Field	Details
Equipment name	Ceiling Saddle
Equipment category	Accessories
Manufacturer / supplier	To be confirmed for the actual asset.
Model / product variant	To be confirmed; include part number and version.
Asset / serial / batch ID	To be completed; attach a photograph of identification markings.
Site / location	To be completed.
Owner / responsible person	To be completed.
Status / record date	Generic template - asset details and approval outstanding. Date: _____

2. Description and typical use

A saddle fitting used to support a compatible bar or tube from a ceiling attachment. The saddle, stud or bolt, anchors and supporting structure form one load path.

- Use only for the attachment and load direction allowed for the identified product.
- Record the supported equipment and the complete load path to the building or lifting system.

3. Technical data to confirm

Enter confirmed values and the document/drawing reference in the asset record. WLL means working load limit. No numerical load rating is assigned by this sheet.

Parameter	Required confirmation
Saddle geometry	Confirm compatible tube diameter and the intended position of the saddle.
Suspension connection	Record stud/bolt size, grade, thread engagement and locking arrangement.
Ceiling substrate	Identify the structural substrate; attach the anchor design and installation record.
Support layout	Record saddle spacing, distance from bar ends and any lateral restraint.
Load allocation	Record the design reaction at each saddle, including eccentric loads.
Tube retention	Confirm the approved method preventing tube escape, rotation or sliding.
Operating limits	Record all manufacturer/designer restrictions and the approved load arrangement.
Inspection / maintenance	Record pre-use checks, periodic inspections and servicing responsibilities; use the exact product instructions.
Documents / traceability	Attach applicable instructions, drawings, certificates and inspection/examination reports. Record reference and revision.

Important limitation

The saddle capacity does not establish the capacity of the ceiling, anchor or supported bar.

4. Regulatory and good practice context

Topic	Application to record
Work equipment	Apply relevant PUWER duties for suitability, maintenance, inspection and safe use.
Lifting equipment	Assess the actual role in any lifting system. A fixed support or structural component should not be classified solely from its name or portal category.
Standards / instructions	Identify relevant product/structural standards and any BS EN 17206 machinery interface. Confirm applicable editions and scope; use maker/designer limits.

5. Pre-use and periodic inspection

Use competent personnel and a safe inspection method. These checks support the asset-specific regime; they do not replace maintenance or a statutory thorough examination. Record Pass / Fail / N/A and findings.

Check	What to confirm	Result / notes
Identification/records	Asset and configuration identifiable; instructions and previous defect actions available.	
Ceiling connection	No loosening, movement, cracking of substrate or displaced anchors.	
Saddle seat	Tube correctly located and retained; no sharp damage or distortion.	
Stud and nuts	Correct assembly with secure locking; no bent stud or corroded threads.	
Load position	No added loads outside the recorded support arrangement.	
Change or damage history	Check for overload, impact, modification, repair or changed environment since last assessment.	
Safe function check	Where applicable, verify intended operation using an authorised safe procedure; do not improvise a proof-load test.	
Outcome/actions	Record defects, restrictions and actions; confirm who authorises return to use.	

6. Removal from service triggers

- Movement or deterioration of the ceiling fixing or supporting structure.
- Bent saddle/stud, insecure tube retention or an undocumented change of loading.
- Damage, wear, corrosion or malfunction beyond the manufacturer/designer acceptance criteria, or uncertainty about safe condition.
- Suspected overload, significant impact or an unapproved modification: isolate the affected asset pending competent assessment.
- Tag and prevent use of unsafe equipment; record the defect and authorised repair/replacement and reinspection before return.

Inspection planning

Where LOLER applies, record the correct examination interval or a competent person's written scheme. Do not assume that an annual visual check is sufficient for every asset. Include examinations after relevant exceptional events.

7. Site-specific notes and limitations

Topic	Site entry / supporting document reference
Permitted loads / uses	
Prohibited uses / limits	
Location / environment	
Inspection / servicing plan	
Related assets / drawings	

8. Inspection and document record

Date	Check / document	Completed by	Outcome / action

Asset details verified by: _____ Date: _____

Release / approval reference: _____

Reference guidance

[Doughty - Ceiling Saddle \(example; verify actual model\)](#)

[HSE - PUWER overview](#)

[HSE - LOLER overview](#)

[HSE - thorough examinations](#)

References reviewed 9 October 2026. Example-brand documents do not identify the asset or approve another manufacturer's product. Keep the exact product manual and installation evidence with the portal record.

Portal document note

Suggested portal path: documents/ceiling_saddle_technical_datasheet.pdf. Uploading the file only makes it available; the equipment record must link to this exact filename.