

TRIPLE E UNITRACK CURTAIN TRACK

Technical data / extra information sheet

Mechanical Theatre Equipment Compliance Portal

Purpose of this sheet

A technical record template for this equipment. Complete and review it using the actual manufacturer instructions, installation design, inspection records and site assessment. It does not certify an asset or assign a load rating.

1. Equipment identification

Field	Details
Equipment name	Triple E UniTrack Curtain Track
Equipment category	Curtain Track
Manufacturer / supplier	To be confirmed for the actual asset.
Model / product variant	To be confirmed; include part number and version.
Asset / serial / batch ID	To be completed; attach a photograph of identification markings.
Site / location	To be completed.
Owner / responsible person	To be completed.
Status / record date	Generic template - asset details and approval outstanding. Date: _____

2. Description and typical use

Triple E UniTrack is a modular fabricated-steel track system used in permanent and touring arrangements. Joint alignment, matched carriers and the suspension layout are essential to its performance.

- Support the intended curtain or scenic fabric within an approved track design.
- Account for the curtain when fully spread, bunched and moving, including overlap/curved sections.

3. Technical data to confirm

Enter confirmed values and the document/drawing reference in the asset record. WLL means working load limit. No numerical load rating is assigned by this sheet.

Parameter	Required confirmation
Rail identification	Record product/variant, section, material, lengths and any curved pieces.
Layout/support plan	Attach support spacing, joint positions, fixing details, bends and overlap drawing.
Curtain load	Record curtain mass, attachments, fullness and the maximum bunched load position.
Carrier system	Identify runners, master carriers, spacing, individual limits and retention.
Operating arrangement	Record installed operating method, cord/drive components and controls, where fitted.
Load evidence	Confirm rail/span capacity, support reactions and drive/pulling forces for this layout.
Operating limits	Record all manufacturer/designer restrictions and the approved load arrangement.
Inspection / maintenance	Record pre-use checks, periodic inspections and servicing responsibilities; use the exact product instructions.
Documents / traceability	Attach applicable instructions, drawings, certificates and inspection/examination reports. Record reference and revision.

Important limitation

Record the UniTrack joint and carrier system. Touring reassembly must restore the documented supports, joints and end stops.

4. Regulatory and good practice context

Topic	Application to record
Work equipment	Apply relevant PUWER duties for suitability, maintenance, inspection and safe use.
Lifting equipment	Assess whether the actual mechanism raises/lowers a load and falls within LOLER. Manual adjustment or the asset name alone is not a classification decision.
Standards / instructions	Identify relevant product/structural standards and any BS EN 17206 machinery interface. Confirm applicable editions and scope; use maker/designer limits.

5. Pre-use and periodic inspection

Use competent personnel and a safe inspection method. These checks support the asset-specific regime; they do not replace maintenance or a statutory thorough examination. Record Pass / Fail / N/A and findings.

Check	What to confirm	Result / notes
Identification/records	Asset and configuration identifiable; instructions and previous defect actions available.	
Rail/joints	No distortion, damaged running surfaces, loose joints or poor alignment.	
Supports/stops	Secure hangers/fixings and all required end stops/retainers.	
Carriers/curtain	Correct runners in sound condition; secure attachments and free travel.	
Operation	No jamming, excessive pull, fouled cord or collision at bunching/overlap areas.	
Change or damage history	Check for overload, impact, modification, repair or changed environment since last assessment.	
Safe function check	Where applicable, verify intended operation using an authorised safe procedure; do not improvise a proof-load test.	
Outcome/actions	Record defects, restrictions and actions; confirm who authorises return to use.	

6. Removal from service triggers

- Missing stop, loose suspension, damaged rail or carrier at risk of leaving the track.
- Jamming, uncontrolled powered motion or an unsupported change of curtain load/layout.
- Damage, wear, corrosion or malfunction beyond the manufacturer/designer acceptance criteria, or uncertainty about safe condition.
- Suspected overload, significant impact or an unapproved modification: isolate the affected asset pending competent assessment.
- Tag and prevent use of unsafe equipment; record the defect and authorised repair/replacement and reinspection before return.

Inspection planning

Where LOLER applies, record the correct examination interval or a competent person's written scheme. Do not assume that an annual visual check is sufficient for every asset. Include examinations after relevant exceptional events.

7. Site-specific notes and limitations

Topic	Site entry / supporting document reference
Permitted loads / uses	
Prohibited uses / limits	
Location / environment	
Inspection / servicing plan	
Related assets / drawings	

8. Inspection and document record

Date	Check / document	Completed by	Outcome / action

Asset details verified by: _____ Date: _____

Release / approval reference: _____

Reference guidance

[Triple E - UniTrack](#)

[HSE - PUWER overview](#)

[HSE - LOLER overview](#)

[HSE - thorough examinations](#)

References reviewed 9 October 2026. Example-brand documents do not identify the asset or approve another manufacturer's product. Keep the exact product manual and installation evidence with the portal record.

Portal document note

Suggested portal path: documents/triple_e_unitrack_curtain_track_technical_datasheet.pdf. Uploading the file only makes it available; the equipment record must link to this exact filename.