

ROUND SLINGS

Technical data / extra information sheet

Mechanical Theatre Equipment Compliance Portal

Purpose of this sheet

This editable datasheet supports the portal entry for round slings. It is intended to record the key technical details, inspection considerations and site-specific limitations for textile round slings used in theatre, entertainment and production environments. It should be used alongside the manufacturer instructions, certificates, inspection records and local risk assessment.

1. Equipment identification

Field	Information to confirm / complete
Equipment name	Round Slings
Equipment category	Lifting accessory
Manufacturer / supplier	To be confirmed
Model / product range	To be confirmed
Serial / batch / traceability ID	To be confirmed
Site / venue / location	To be confirmed
Owner / responsible person	To be confirmed
Date added to portal	To be completed
Datasheet status	Generic template - edit with manufacturer and site-specific information

2. Description and typical use

Round slings are textile lifting accessories used to connect, lift, support or suspend loads. They are commonly used where a flexible connection is needed and where the load or attachment point would benefit from a softer contact surface than chain or wire rope.

- Typical theatre uses may include lifting or suspending production equipment, scenic elements, truss or other approved loads as part of a planned lifting operation.
- The sling must only be used within its stated WLL and in an approved configuration.

- The complete load path should be considered, including the sling, shackles, hooks, beams, truss, lifting machine and supporting structure.
- Textile slings are vulnerable to cuts, abrasion, heat, chemicals, UV degradation, contamination and edge damage.
- Sharp edges, rough surfaces and unsuitable contact points should be avoided or controlled using suitable protection.

3. Technical data to confirm

Field	Information to confirm / complete
WLL / SWL	To be confirmed from sling label, certificate and manufacturer data
Sling material	To be confirmed - for example polyester, polyamide or other manufacturer-stated material
Effective working length	To be confirmed
Colour / capacity marking	To be confirmed and cross-checked with label/certificate
Configuration limits	Straight lift, choke, basket, multi-leg or other configurations to be confirmed
Sling angle limits	To be confirmed for the intended lifting arrangement
Temperature range	To be confirmed from manufacturer guidance
Chemical limitations	To be confirmed from manufacturer guidance and site substances
Edge protection requirements	To be confirmed for each use and contact point
Inspection interval	To be confirmed by competent person / written scheme / local procedure
Relevant certification	Certificate of conformity, thorough examination report and any batch/traceability records
Manufacturer instructions	Manual or product data sheet reference to be inserted

Important limitation

Do not rely on colour alone to identify capacity. The sling label, certificate, traceability information and condition must all be checked. If the label is missing, unreadable or inconsistent with the certificate, the sling should be removed from service until assessed by a competent person.

4. Regulatory and good-practice context

Field	Information to confirm / complete
LOLER 1998	A round sling used for lifting is a lifting accessory. It should be suitable, strong enough for the intended use, marked with its WLL/SWL and subject to thorough examination by a competent person at suitable intervals.
PUWER 1998	As work equipment, the sling must be suitable for the task, maintained in a safe condition, inspected where deterioration could create risk, and used by trained/competent people.
BS EN 17206:2020	Relevant where the sling forms part of an entertainment lifting or suspension system. The sling should be considered as part of the complete load path and system safety assessment.
ABTT Technical Standards	Supports theatre-industry good practice for competent selection, inspection, use, documentation and management of lifting accessories.
Manufacturer guidance	Manufacturer instructions, WLL tables, configuration factors and discard criteria should take precedence for product-specific use.

5. Pre-use and periodic inspection checks

Check	What to confirm	Result / notes
Identification	Label present, legible and matching the certificate or inspection record.	
WLL / SWL	Capacity confirmed for the exact lifting configuration, angle and method of use.	
Outer sleeve	No cuts, tears, holes, fraying, abrasion, pulled stitching or signs of exposed core.	
Core condition	No suspected internal damage, bunching, hard spots, uneven thickness or loss of integrity.	

Check	What to confirm	Result / notes
Heat damage	No glazing, melting, charring, hardening, discolouration or heat exposure beyond manufacturer limits.	
Chemical damage	No acid/alkali attack, softening, stiffness, contamination or unknown chemical exposure.	
UV / ageing	No excessive fading, brittleness, powdering or degradation from storage or exposure.	
Edge protection	Suitable protection fitted where the sling contacts sharp, rough or abrasive edges.	
Configuration	Correct sling method used; no knots, unauthorised shortening, twisting or choke misuse.	
Connections	Hooks, shackles, eyes and load points compatible with the sling width, contact radius and loading direction.	
Storage	Stored clean, dry, away from sharp objects, chemicals, heat sources and direct sunlight where practicable.	
Records	Current inspection/thorough examination record available and defects actioned.	

6. Removal from service triggers

- Missing, unreadable or detached identification label.
- Cuts, tears, holes, severe abrasion or exposed load-bearing core fibres.
- Heat damage, melting, charring, hardening or other evidence of thermal exposure.
- Chemical damage, unknown contamination or evidence of material attack.
- Broken or damaged stitching where present, especially at eyes or sleeves.
- Knots, unauthorised repairs, modifications or shortening methods.
- Distortion, uneven thickness, hard spots or suspected internal core damage.
- Evidence of overloading, shock loading or use in an unsuitable configuration.
- Uncertainty over WLL/SWL, certificate, traceability or previous use.

7. Site-specific notes and limitations

Complete this section for each venue or sling group. Include any restrictions on use, storage location, inspection regime, permitted equipment combinations, edge protection requirements or known limitations.

Topic	Site-specific note
Permitted uses	
Prohibited uses	
Storage location	
Inspection frequency	
Compatible equipment	
Additional controls	

8. Inspection and document record

Date	Inspection / document type	Completed by	Outcome / next action

Portal upload note

Suggested portal file path: documents/round_slings_technical_datasheet.pdf. Keep the Word version as the editable master copy and upload the PDF version to the portal documents folder.