

WEB SLINGS

Technical data / extra information sheet

Mechanical Theatre Equipment Compliance Portal

Purpose of this sheet

This editable datasheet supports the portal entry for web slings. It is intended to record the key technical details, inspection considerations and site-specific limitations for flat textile web slings used in theatre, entertainment and production environments. It should be used alongside the manufacturer instructions, certificates, inspection records and local risk assessment.

1. Equipment identification

Field	Information to confirm / complete
Equipment name	Web Slings
Equipment category	Lifting accessory
Manufacturer / supplier	To be confirmed
Model / product range	To be confirmed
Serial / batch / traceability ID	To be confirmed
Site / venue / location	To be confirmed
Owner / responsible person	To be confirmed
Date added to portal	To be completed
Datasheet status	Generic template - edit with manufacturer and site-specific information

2. Description and typical use

Web slings are flat textile lifting accessories used to connect, lift, support or suspend loads. They are commonly used where a broad, flexible contact surface is needed and where the load or attachment point would benefit from a softer interface than chain or wire rope.

- Typical theatre uses may include lifting or suspending production equipment, scenic elements, truss or other approved loads as part of a planned lifting operation.
- The sling must only be used within its stated WLL and in an approved configuration.
- The complete load path should be considered, including the sling, hooks, shackles, beams, truss, lifting machine and supporting structure.
- Textile web slings are vulnerable to cuts, abrasion, damaged stitching, heat, chemicals, UV degradation, contamination and edge damage.
- Sharp edges, rough surfaces, small contact radii and unsuitable attachment points should be avoided or controlled using suitable protection.

3. Technical data to confirm

Field	Information to confirm / complete
WLL / SWL	To be confirmed from sling label, certificate and manufacturer data
Sling material	To be confirmed - for example polyester, polyamide or other manufacturer-stated material
Effective working length	To be confirmed
Webbing width and construction	To be confirmed from manufacturer data and sling label/certificate
Eye type / end fitting	To be confirmed - for example flat eye, folded eye, reinforced eye or other manufacturer-stated arrangement
Colour / capacity marking	To be confirmed and cross-checked with label/certificate
Configuration limits	Straight lift, choke, basket, multi-leg or other configurations to be confirmed
Sling angle limits	To be confirmed for the intended lifting arrangement
Temperature range	To be confirmed from manufacturer guidance
Chemical limitations	To be confirmed from manufacturer guidance and site substances
Edge protection requirements	To be confirmed for each use and contact point
Inspection interval	To be confirmed by competent person / written scheme / local procedure
Relevant certification	Certificate of conformity, thorough examination report and any batch/traceability records
Manufacturer instructions	Manual or product data sheet reference to be

Field	Information to confirm / complete
	inserted
Important limitation Do not rely on colour alone to identify capacity. The sling label, certificate, traceability information and condition must all be checked. If the label is missing, unreadable or inconsistent with the certificate, the sling should be removed from service until assessed by a competent person.	

4. Regulatory and good-practice context

Field	Information to confirm / complete
LOLER 1998	A web sling used for lifting is a lifting accessory. It should be suitable, strong enough for the intended use, marked with its WLL/SWL and subject to thorough examination by a competent person at suitable intervals.
PUWER 1998	As work equipment, the sling must be suitable for the task, maintained in a safe condition, inspected where deterioration could create risk, and used by trained/competent people.
BS EN 17206:2020	Relevant where the sling forms part of an entertainment lifting or suspension system. The sling should be considered as part of the complete load path and system safety assessment.
ABTT Technical Standards	Supports theatre-industry good practice for competent selection, inspection, use, documentation and management of lifting accessories.
Manufacturer guidance	Manufacturer instructions, WLL tables, configuration factors and discard criteria should take precedence for product-specific use.

5. Pre-use and periodic inspection checks

Check	What to confirm	Result / notes
Identification	Label present, legible and matching the certificate or inspection record.	
WLL / SWL	Capacity confirmed for the exact lifting configuration, angle and method of use.	

Check	What to confirm	Result / notes
Webbing body	No cuts, holes, tears, fraying, broken yarns, severe abrasion or reduction in webbing width/thickness.	
Eyes and stitching	Eyes, loops, reinforced areas and stitching are intact, secure and free from cuts, pulled threads or wear.	
Surface condition	No excessive wear, glazing, hard spots, contamination, embedded grit or localised damage.	
Heat damage	No melting, charring, glazing, hardening, discolouration or heat exposure beyond manufacturer limits.	
Chemical damage	No acid/alkali attack, softening, stiffness, contamination or unknown chemical exposure.	
UV / ageing	No excessive fading, brittleness, powdering or degradation from storage or exposure.	
Edge protection	Suitable protection fitted where the sling contacts sharp, rough or abrasive edges.	
Configuration	Correct sling method used; no knots, unauthorised shortening, twisting, bunching or choke misuse.	
Connections	Hooks, shackles, eyes and load points compatible with the sling width, contact radius and loading direction.	
Storage	Stored clean, dry, away from sharp objects, chemicals, heat sources and direct sunlight where practicable.	

6. Removal from service triggers

- Missing, unreadable or detached identification label.
- Cuts, tears, holes, fraying, broken yarns, severe abrasion or damaged webbing edges.
- Heat damage, melting, charring, glazing, hardening or other evidence of thermal exposure.
- Chemical damage, unknown contamination or evidence of material attack.
- Damaged, broken, pulled or missing stitching, especially at eyes, loops or reinforced areas.
- Knots, unauthorised repairs, modifications or shortening methods.
- Hard spots, embedded grit, stiffening, softening, embrittlement or suspected fibre damage.
- Evidence of overloading, shock loading or use in an unsuitable configuration.
- Uncertainty over WLL/SWL, certificate, traceability or previous use.

7. Site-specific notes and limitations

Complete this section for each venue or sling group. Include any restrictions on use, storage location, inspection regime, permitted equipment combinations, edge protection requirements or known limitations.

Topic	Site-specific note
Permitted uses	
Prohibited uses	
Storage location	
Inspection frequency	
Compatible equipment	
Additional controls	

8. Inspection and document record

[illegible]

Portal upload note

Suggested portal file path: documents/web_slings_technical_datasheet.pdf. Keep the Word version as the editable master copy and upload the PDF version to the portal documents folder.