

A+ Core 1 Playbook

IT Labs

Prepared by Garrick White

10.2.9 Replace a Printer Toner

A user reports their printer is no longer printing yellow. You determine the yellow toner cartridge must be replaced. You will need to replace the existing yellow toner cartridge with a new one.

Step 1: Open the Front Cabinet Door

Step 2: Open the Toner Cartridge Tray

Step 3: Remove the Toner Cartridge

Step 4: Unbox the New Toner Cartridge

Step 5: Replace the Cartridge (avoid touching the imaging drum on the bottom of the toner cartridge. Fingerprints or other debris or markings can cause print quality problems. Also, do not expose the cartridge to light if possible)

Step 6: Replace Toner Cartridge Tray

Step 7: Close Cabinet Door

Step 8: Check Printer Status

Question 1

To access the toner cartridges so they can be removed, what step do you take after you open the front cabinet door?

Grasp the blue handle and pull the toner tray straight out

Question 2

When handling a new toner cartridge, why must you make sure not to touch the roller unit?

Oil or debris from your hands can degrade print quality

Question 3

When integrating the toner in the cartridge, what motion should you use?

Hold the cartridge horizontally and tip it back and forth

Question 4

Once the toner cartridge is replaced and the cabinet door is closed, what is the last step to make sure the printer is ready to use?

Check the printer status after the self-diagnosis