

CompTIA A+ Core 1 Playbook

IT Labs

Prepared by Garrick White

6.1.6 Connect Fiber Optic Cables

You are working on a small office/home office (SOHO) network. You have just signed up for fiber Internet access for the network. The fiber company has installed the line into your home and given you a preconfigured router for your network.

Your task in this lab is to:

- Connect the components to make the network connection.
 - Add the fiber router to the Workspace.
 - Connect the router to the ISP's fiber line using the SC to SC cable.
 - Connect the computer to the fiber router using a Cat6a Ethernet cable.
 - Use the AC to DC power adapter to plug the router into the power strip.

Complete the following steps:

1. Add the router to the workspace and connect it to the data line.
 1. In the Inventory, expand the **Networking Devices** category.
 2. Drag the fiber router from the Inventory to the Workspace.
 3. To connect the router to the Internet connection, switch to the back view of the fiber router.
 4. In the Inventory, expand the **Cables** category.
 5. Select the **SC to SC** cable.
 6. In the Selected Component window, drag a connector to the port on the fiber router.
 7. In the Selected Component window, drag the other connector to the port on the wall plate.
2. Connect the router to the computer.
 1. Switch to the back view of the computer.
 2. In the Inventory, select the Cat6a Ethernet cable.
 3. In the Selected Component window, drag a connector to an Ethernet port on the fiber router.
 4. In the Selected Component window, drag the other connector to the Ethernet port on the computer.
3. Connect the router to the power strip.
 1. Select the power adapter in the Inventory.
 2. In the Selected Component window, drag the DC power connector to the port on the fiber router.
 3. In the Selected Component window, drag the AC adapter end to an outlet on the power strip.