

# FUTURA

# LA SCUOLA PER L'ITALIA DI DOMANI



Finanziato  
dall'Unione europea  
NextGenerationEU



Ministero dell'Istruzione  
e del Merito



**Italiadomani**  
PIANO NAZIONALE DI RIPRESA E RESILIENZA

DOCENTE	Shadi Lahham
Corso	Software Developer
Unità Formativa	Programmazione WEB – Javascript
Argomento	Specificato nel titolo della slide successiva

Intervento realizzato da  
**ITS**  
TECNOLOGIE  
DELL'INFORMAZIONE  
E DELLA COMUNICAZIONE

COESIONE  
ITALIA 21-27  
PIEMONTE



Cofinanziato  
dall'Unione europea



**REGIONE  
PIEMONTE**

# Objects

Flexible data structures

Shadi Lahham - Web development

Objects

# Objects

Objects are a data type that let us store a collection of properties and methods

```
let objectName = {  
  propertyName: propertyValue,  
  propertyName: propertyValue,  
  ...  
};
```

```
let aboutMe = {  
  city: 'Madrid, ES',  
  hair: 'brown'  
};
```

# Objects

Objects are a data type that let us store a collection of properties and methods

```
let objectName = {  
  propertyName: propertyValue,  
  propertyName: propertyValue,  
  ...  
};
```

```
let myCat = {  
  age: 8,  
  furColor: 'grey',  
  likes: ['water', 'milk', 'meat'],  
  birthday: {'month': 7, 'day': 17, year: 1994}  
};
```

# Objects Access - dot notation

```
let aboutMe = {  
  city: 'Madrid, ES',  
  hair: 'brown'  
};
```

```
// access properties using 'dot notation'
```

```
let myCity = aboutMe.city;
```

```
// non-existent properties will return undefined
```

```
let myGender = aboutMe.gender;
```

# Objects Access - bracket notation

```
let aboutMe = {  
  city: 'Madrid, ES',  
  hair: 'brown'  
};
```

```
// access properties using 'bracket notation'
```

```
let myHair = aboutMe['hair'];
```

```
// non-existent properties will return undefined
```

```
let myGender = aboutMe['gender'];
```

```
// properties can also be accessed with variable keys
```

```
let myProperty = 'hair';
```

```
let myHair = aboutMe[myProperty];
```

# Changing Objects

Use dot or bracket notation with the assignment operator to change objects

```
let aboutMe = {  
  city: 'Madrid, ES',  
  hair: 'brown'  
};
```

Change existing properties:

```
aboutMe.hair = 'blue';
```

Or add new properties:

```
aboutMe.gender = 'female';
```

You can also delete properties:

```
delete aboutMe.gender;
```



# Arrays of Objects

*// since arrays can hold any data type, they can also hold objects*

```
let myCats = [
  {name: 'Cleo',
   age: 8},
  {name: 'Simba',
   age: 1}
];

for (let i = 0; i < myCats.length; i++) {
  let myCat = myCats[i];
  console.log(myCat.name + ' is ' + myCat.age + ' years old.');
```

# Objects as Arguments

*// just like other data types, objects can be passed into functions*

```
let myCat = {  
  age: 8,  
  furColor: 'grey',  
  likes: ['water', 'milk', 'meat'],  
  birthday: {'month': 7, 'day': 17, 'year': 1994}  
};  
  
function describeCat(cat) {  
  console.log('This cat is ' + cat.age + ' years old with ' + cat.furColor + ' fur.');}  
  
describeCat(myCat);
```

# Object methods

*// object properties can also be functions. Object functions are called 'methods'*

```
let myCat = {  
  age: 8,  
  furColor: 'grey',  
  meow: function() {  
    console.log('meowww');  
  },  
  eat: function(food) {  
    console.log('Yum, I love ' + food);  
  },  
  sleep: function(numMinutes) {  
    for (let i = 0; i < numMinutes; i++) {  
      console.log('z');  
    }  
  }  
};
```

# Object methods

*// invoke object methods using dot notation*

```
myCat.meow();  
myCat.eat('cat food');  
myCat.sleep(10);
```

# This in methods

*// when a method is invoked, `this` refers to the object containing the method.*

```
let myCat = {  
  age: 8,  
  name: 'Cleo',  
  sayName: function() {  
    console.log('I am ' + this.name);  
  },  
};
```

```
myCat.sayName();
```

# Object.keys()

*// object.keys() Lists all the property names of an object in an array*

```
let myCat = {  
  age: 8,  
  furColor: 'grey',  
  meow: function() {  
    console.log('meowww');  
  },  
  sleep: function(numMinutes) {  
    for (let i = 0; i < numMinutes; i++) {  
      console.log('z');  
    }  
  }  
};
```

```
Object.keys(myCat); // ['age', 'furColor', 'meow', 'sleep']
```

# Built-in Objects

Javascript has a lot of useful built-in objects

## Array

`Array.isArray()`

## Number

`Number()`

`Number.parseInt()`

`Number.parseFloat()`

## Date

`Date.UTC()`

`Date.now()`

`Date.parse()`

## Math

May useful functions | see also [Number Formatting in JavaScript](#)



# In depth

Detailed usage



# Copying by value or by reference

```
// copying by value (primitives)
```

```
let a = 5;
```

```
let b = a; // b is now a copy of a
```

```
b = 10; // changing b won't affect a
```

```
console.log(a); // output: 5
```

```
console.log(b); // output: 10
```

```
// copying by reference (objects)
```

```
let obj1 = { name: 'John' };
```

```
let obj2 = obj1; // obj2 is now a reference to obj1
```

```
obj2.name = 'Jane'; // changing obj2 will also affect obj1
```

```
console.log(obj1.name); // output: Jane
```

```
console.log(obj2.name); // output: Jane
```

# Passing parameters: value vs. reference

```
function updateValues(num, obj, arr) {  
  num = 10;  
  obj.name = 'Jane';  
  arr.push(4);  
}
```

```
let a = 5;  
let person = { name: 'John' };  
let numbers = [1, 2, 3];
```

```
updateValues(a, person, numbers);
```

```
console.log(a); // output: 5 - unchanged because passed by value  
console.log(person.name); // output: jane - changed because passed by reference  
console.log(numbers); // output: [1, 2, 3, 4] - changed because passed by reference
```

# Invoke with bracket notation

```
let car = {  
  startEngine: function () {  
    console.log('Engine started.');  }  
};
```

```
// invoking the method using bracket notation  
car['startEngine']();
```

# Invoke with bracket notation

```
let car = {  
  startEngine: function (fuelType) {  
    console.log('Engine started. Fuel type: ' + fuelType);  
  },  
  stopEngine: function () {  
    console.log('Engine stopped.');  }  
};
```

*// invoking the methods using bracket notation*

```
car['startEngine']('gasoline');  
car['stopEngine']();
```

*// invoking the methods using dot notation*

```
car.startEngine('gasoline');  
car.stopEngine();
```

# Immutable Objects

*// myCat is a constant, but it's mutable so its properties can change*

```
const myCat = {  
  name: 'Cleo',  
  age: 8  
};
```

```
myCat.name = 'Adam';  
console.log(myCat.name); // 'Adam' not 'Cleo'
```

```
myCat = {}; // TypeError: Assignment to constant variable
```

# Immutable Objects

*// mutable objects can be changed over time, while immutable ones cannot be altered after creation*

```
const myCat = {  
  name: 'Cleo',  
  age: 8  
};
```

```
Object.freeze(myCat);
```

```
myCat.name = 'Sam';  
console.log(myCat.name); // 'Cleo' not 'Sam'
```

[Immutable - MDN](#)

[Object.freeze\(\)](#)

[JavaScript Immutability](#)

Your turn

# 1.Recipe

- Create an object to hold information on your favorite recipe. It should have properties for title (a string), servings (a number), and ingredients (an array of strings).
- On separate lines (one console.log statement for each), log the recipe information

**Bonus:** Create an array that holds several recipes and log them all



## 2. Reading list

- Create an array of objects, where each object describes a book and has properties for the title (a string), author (a string), and alreadyRead (a boolean indicating if you read it yet).
- Iterate through the array of books. For each book, log the book title and book author like so: "The Hobbit by J.R.R. Tolkien".
- Now use an if/else statement to change the output depending on whether you read it yet or not. If you read it, log a string like 'You already read "The Hobbit" by J.R.R. Tolkien', and if not, log a string like 'You still need to read "The Lord of the Rings" by J.R.R. Tolkien.'

## 3.Movie database

- Create an object to store the following information about a movie: title (a string), duration (a number), and stars (an array of strings).
- Create an Array of objects that can hold several movies.
- Create a function to print out the movie information like so: "Puff the Magic Dragon lasts for 30 minutes. Stars: Puff, Jackie, Living Sneezes."
- Test the function by printing one movie.
- Use the function to print all the movies in the Array.

## 4.Cash register

- Write a function called `cashRegister` that takes a shopping cart object.
- The object contains item names and prices (`itemName: itemPrice`).
- The function returns the total price of the shopping cart, e.g. :

// Input

```
let cartForParty = {  
  banana: "1.25",  
  handkerchief: ".99",  
  Tshirt: "25.01",  
  apple: "0.60",  
  nalgene: "10.34",  
  proteinShake: "22.36"  
};
```

// Output

```
cashRegister(cartForParty)); // 60.55
```

## 5.Credit card validation

- Write a function called “validateCreditCard” that checks credit card numbers according to the following rules:
  - Number must be 16 digits, all of them must be numbers
  - You must have at least two different digits represented (all of the digits cannot be the same)
  - The final digit must be even
  - The sum of all the digits must be greater than 16

Continues on next page >>>

## 5.Credit card validation

- The following credit card numbers are valid:
  - 9999-9999-8888-0000
  - 6666-6666-6666-1666
- The following credit card numbers are invalid:
  - a923-3211-9c01-1112 invalid characters
  - 4444-4444-4444-4444 only one type of number
  - 1111-1111-1111-1110 sum less than 16
  - 6666-6666-6666-6661 odd final number
- Hint
  - Remove the dash '-' from the input string before checking if the input credit card number is valid

Continues on next page >>>

## 5. Credit card validation

Call the function with several credit card numbers:

```
validateCreditCard('9999-9999-8888-0000');  
validateCreditCard('4444-4444-4444-4444');  
validateCreditCard('6666-6666-6666-1666');
```

The function returns an object saying that the credit card is valid, or what the error is:

```
{ valid: true, number: '9999-9999-8888-0000' }  
{ valid: false, number: 'a923-3211-9c01-1112', error: 'wrong_length' }
```

For each card check, print out the result to the log in this format:

```
=====  
= number : a923-3211-9c01-1112 =  
= valid  : false                =  
= error   : wrong length        =  
=====
```

# References

[JavaScript Objects](#)

[Working with objects - JavaScript](#)

More advanced:

[JavaScript Object Methods](#)

# References

[JavaScript Math Object](#)

[JavaScript Number Methods](#)



# © Copyright & Attribution

Unless otherwise stated, all materials are © 2017–2025 [Shadi Lahham](#)

For personal use only. May not be shared or reproduced without written permission

Brief excerpts may be used with proper attribution

External links and resources are copyrighted by their respective owners