

FUTURA

LA SCUOLA PER L'ITALIA DI DOMANI



Finanziato
dall'Unione europea
NextGenerationEU



Ministero dell'Istruzione
e del Merito



Italiadomani
PIANO NAZIONALE DI RIPRESA E RESILIENZA

DOCENTE	Shadi Lahham
Corso	Software Developer
Unità Formativa	Programmazione WEB – Javascript
Argomento	Specificato nel titolo della slide successiva

Intervento realizzato da
ITS
TECNOLOGIE
DELL'INFORMAZIONE
E DELLA COMUNICAZIONE

COESIONE
ITALIA 21-27
PIEMONTE



Cofinanziato
dall'Unione europea



**REGIONE
PIEMONTE**

Flow

Conditions and loops

Shadi Lahham - Web development

if/else

The if statement

Use `if` to tell JS which statements to execute, based on a condition

```
if (condition) {  
  // statements to execute  
}  
let x = 5;
```

```
if (x > 0) {  
  console.log('x is a positive number!');  
}
```

Comparison Operators

```
let myFavoriteNumber = 28;
```

== Equality

```
myFavoriteNumber == 28
```

```
myFavoriteNumber == '28'
```

```
28 == '28'
```

=== Strict equality

```
myFavoriteNumber === 28
```

!= Inequality

```
myFavoriteNumber != 29
```

!== Strict inequality

```
myFavoriteNumber !== '28'
```

```
28 !== '28'
```

Common mistake

Do not confuse the assignment operator = with ==

Comparison Operators

```
let myFavoriteNumber = 28;
```

```
> Greater than  
myFavoriteNumber > 25  
'28' > 25
```

```
>= Greater than or equal  
myFavoriteNumber >= 28  
'28' >= 25
```

```
< Less than  
myFavoriteNumber < 30  
'28' < 30
```

```
<= Less than or equal  
myFavoriteNumber <= 28  
'28' <= 28
```

Logical Operators

Operators

<code>&&</code>	<code>and</code>
<code> </code>	<code>or</code>
<code>!</code>	<code>not</code>

When combining together multiple conditions, use parentheses to group

```
let myAge = 28;
if ((myAge >= 0 && myAge < 3) || myAge > 90) {
  console.log('You\'re not quite in your peak.');
}
```

Truthy vs Falsey

If you don't use a comparison or logical operator, JS tries to figure out if the value is "truth-y"

```
let catsRule = true;  
if (catsRule) {  
  console.log('Yay cats!');  
}
```


Truthy vs Falsey

Values that are "false-y":

false, the empty string (""), the number 0, the number -0, undefined, null, NaN

```
let firstName = '';  
if (firstName) {  
  console.log('Hello, ' + firstName);  
}
```

```
let points = 0;  
if (points) {  
  console.log('You have ' + points + ' points');  
}
```

```
let firstName;  
if (firstName) {  
  console.log('Your name is ' + firstName);  
}
```

Short-Circuit Evaluation

JS evaluates logical operators from left to right and stops evaluating as soon as it knows the answer

```
(falsey && anything) => falsey
```

```
(truthy || anything) => truthy
```

Examples:

```
let nominator = 5;  
let denominator = 0;  
if (denominator !== 0 && (nominator/denominator > 0)) {  
  console.log('Thats a valid, positive fraction');  
}
```

The if/else statement

```
let age = 28;  
if (age > 16) {  
  console.log('Yay, you can drive!');  
} else {  
  console.log('Sorry, but you have ' + (16 - age) + ' years till you can drive.');
```

The if/else if/else statement

```
let age = 20;
if (age >= 35) {
  console.log('You can vote AND hold any place in government!');
} else if (age >= 25) {
  console.log('You can vote AND run for the Senate!');
} else if (age >= 18) {
  console.log('You can vote!');
} else {
  console.log('You have no voice in government!');
}
```

while & for

The while loop

The while loop tells JS to repeat statements until a condition is true

```
while (expression) {  
  // statements to repeat  
}  
let x = 0;  
while (x < 5) {  
  console.log(x);  
  x = x + 1;  
}
```

The for loop

```
for (initialize; condition; update) {  
  // statements to repeat  
}
```

```
for (let i = 0; i < 5; i = i + 1) {  
  console.log(i);  
}
```

The for loop

Some developers prefer to declare variables in advance

```
let people = ['James', 'Richard', 'Robert'];
let i = 0;
let len = people.length;
let text = '';
for (; i < len; i++) {
  text += people[i] + ',';
}
console.log(text);
```

However this is not required.

Count backwards:

```
for (let c=20; c > 0; c--) {
  // do something with c
}
```


The break statement

To prematurely exit a loop, use the break statement

```
for (let current = 100; current < 200; current++) {  
  console.log('Testing ' + current);  
  if (current % 7 == 0) {  
    console.log('Found it! ' + current);  
    break;  
  }  
}
```

Diving deeper

// how many times is each of the following executed:

// initialize? condition? update? statements?

```
for (initialize; condition; update) {  
    // statements to repeat  
}
```

// what does this code do?

```
for (; 8; ) {  
    console.log('hi');  
}
```

// what does this code do?

```
while (') {  
    console.log('print me please');  
}
```

switch

The switch statement

// using if-else

```
let dayOfWeek = 'Monday';
```

```
let message;
```

```
if (dayOfWeek === 'Monday') {
```

```
  message = "It's Monday!";
```

```
} else if (dayOfWeek === 'Wednesday') {
```

```
  message = "It's Wednesday!";
```

```
} else if (dayOfWeek === 'Friday') {
```

```
  message = "It's Friday!";
```

```
} else {
```

```
  message = 'Invalid day of the week';
```

```
}
```

```
console.log(message);
```

The switch statement

```
// using switch
let dayOfWeek = 'Monday';
let message;

switch (dayOfWeek) {
  case 'Monday':
    message = "It's Monday!";
    break;
  case 'Wednesday':
    message = "It's Wednesday!";
    break;
  case 'Friday':
    message = "It's Friday!";
    break;
  default:
    message = 'Invalid day of the week';
}

console.log(message);
```

Switch with fall-through

```
// forgot to use break
let dayOfWeek = 'Monday';
let message;

switch (dayOfWeek) {
  case 'Monday':
    message = "It's Monday!";
  case 'Wednesday':
    message = "It's Wednesday!";
    break;
  case 'Friday':
    message = "It's Friday!";
    break;
  default:
    message = 'Invalid day of the week';
}

console.log(message); // what's the output?
```

Switch with intentional fall-through

```
let dayOfWeek = 'Monday';
let message;

switch (dayOfWeek) {
  case 'Monday':
    // fall-through
  case 'Tuesday':
    // fall-through
  case 'Friday':
    message = "It's a weekday";
    break;
  case 'Saturday':
    // fall-through
  case 'Sunday':
    message = "It's the weekend";
    break;
  default:
    message = 'Invalid day of the week';
}
console.log(message);
```

Your turn

1.Big numbers

- Write a function named `greaterNum` that:
 - takes 2 parameters, both numbers.
 - returns whichever number is the greater (higher) number.
- Call that function 2 times with different number pairs, and log the output to make sure it works (e.g. "The greater number of 5 and 10 is 10.").

2.Universal Translator

- Write a function named `helloWorld` that:
 - takes 1 parameter, a language code (e.g. "es", "de", "en")
 - returns "Hello, World" for the given language, for at least 3 languages. It should default to returning English.
- Call that function for each of the supported languages and log the result to make sure it works.

3. Grade master

- Write a function named `assignGrade` that:
 - takes 1 parameter, a number score.
 - returns a grade for the score, either "A", "B", "C", "D", or "F".
- Call that function for a few different scores and log the result to make sure it works.

4.Odd or even

- Write a for loop that will iterate from 0 to 20.
- For each iteration, it will check if the current number is odd or even, and report that to the screen (e.g. "2 is even").

Bonus

5. One to many

- Write a function named `oneToMany()` that:
 - takes 2 parameters, a noun and a number.
 - returns the number and pluralized form, like "5 cats" or "1 dog".
- Call that function for a few different scores and log the result to make sure it works.
- Bonus: Make it handle a few collective nouns like "sheep" and "geese".

6.Easy multiplication

- Write a for loop that will iterate from 0 to 10.
- For each iteration of the for loop, it will multiply the number by 9 and log the result (e.g. "2 * 9 = 18").
- Bonus: Use a nested for loop to show the tables for every multiplier from 1 to 10 (100 results total).

7. Grade checker

- Write a loop that tests the function that you wrote earlier “assignGrade”.
- Check every value from 60 to 100:
 - your log should show
 - “For 88, you got a B.”
 - “For 89, you got a B.”
 - “For 90, you got an A.”
 - etc.

References

[JavaScript for Loop](#)

[JavaScript while Loop](#)

[JavaScript Switch](#)

Old resource

[Eloquent JavaScript - values, variables, and control flow](#)

© Copyright & Attribution

Unless otherwise stated, all materials are © 2017–2025 [Shadi Lahham](#)

For personal use only. May not be shared or reproduced without written permission

Brief excerpts may be used with proper attribution

External links and resources are copyrighted by their respective owners