Analysed Article Summary Format – Draft 1

This is the standard output for the “Summariser MCP Server”, and it is the standard input for the “Analyst MCP Server” (or more precisely, a list of such objects, one for each article).

```
{
    "article_id" : "%unique_ascii_id%",
    "article_title" : "%title%",
    "publication_time" : "%utc+00:00 time: hour-minute%",
    "source" : {
        "source_id" : "%unique_ascii_id%",
        "source_name" : "%name%"
    },

    "initial_categories" : ["%entries must be one of 5-10 predetermined,
very broad categories"],
    "actors" : [
        {
            "name" : "%country1%",
            "actor_type" : "%country%",
            "occurences" : 1
        },
        {
            "name" : "%politician1%",
            "actor_type" : "%politician%",
            "occurences" : 2
        }
    ],

    "events" : ["%recent_event1%", "%ongoing_event2%"],
    "claims" : [
        {
            "claim" : "%simple_claim%",
            "opinion" : 0.0
        }
    ],
    "themes" : ["%existing_theme1%", "%new_theme1%"]
}
```

Justifications

-

Guidance on populating

- The “actors” field should be expanded with actors found in the body of the text, as well those already found in the title. Once again, SpaCy may be good for this (though if an LLM is doing the rest, might be able to get it to do this too – possible consistency concerns with SpaCy being used to title actor extraction?)
- The entries in the array of the “events” field should attempt to be populated with values from an external copy of events encountered if possible, to avoid accidentally generating similar but subtly different event names for the same event. Likewise for the “themes” field.
- All entries in the “claims” array should be objects of the form shown in the template. The “opinion” subfield should be a numerical score from -10 to +10, where +10 indicates full agreement, and -10 indicates full disagreement. These values should be symmetric, in that negating the score would coincide with the agreement for a reversed statement (e.g. “sky is blue”, 10 -> “sky is not blue”, -10)