Collected Article Summary Format – Draft 1

This is the standard output for the “Collector MCP Server”, and it is the standard input for the “Summariser MCP Server” (or more precisely, a list of such objects, one for each article).

```
{
    "article_id" : "%unique_ascii_id%",
    "article_title" : "%title%",
    "publication_time" : "%utc+00:00 time: hour-minute%",
    "source" : {
        "source_id" : "%unique_ascii_id%",
        "source_name" : "%name%"
    },

    "initial_categories" : ["%entries must be one of 5-10 predetermined,
very broad categories"],
    "actors" : [
        {
            "name" : "%country1%",
            "actor_type" : "%country%",
            "occurences" : 1
        }
    ]
}
```

Justifications

- No “title_themes” field, because this is often hard to determine from the title
- No “publication_date” field, because all entries should come from the last 24hrs, only a publication time
- No server log field, because the server can keep their own logs at a higher level, and these can be incorporated into a separate JSON file returned at the very end

Guidance on populating

- “publication_time” should hold the UTC+00:00 equivalent of the publication time, to allow us to track advances throughout the day (and consider later, more informed articles as more reliable)
- The allowed values for “initial_category” are (may be expanded/updated):
    - conflict
    - politics
    - tragedy
    - crime
    - product review

    - advice
    - finance
- Every entry in the array of the “actors” field should be of the object type shown in the template. Actors may be easily extracted using the ‘SpaCy’ library.
- All names of actors should be standardised (e.g. Forename Surname for people)
- The only allowed values for the “actor_type” subfield are (may be expanded/updated):
    - country
    - company
    - politician
    - celebrity
    - other