User Manual

Project Kitchen Occupation TSBB11 HT 2013 Version 1.0



Status

Reviewed	_	2013-12-13
Approved		

Project Kitchen Occupation

Bilder och Grafik CDIO, HT 2013 Department of Electrical Engineering (ISY), Linköping University

Participants

Name	Tag	Responsibilities	Phone	E-mail
Mattias Tiger	MT	Project manager	073-695 71 53	matti166@student.liu.se
Erik Fall	EF	-	076-186 98 84	erifa226@student.liu.se
Gustav Häger	GH	System integration	070-649 03 97	gusha124@student.liu.se
Malin Rudin	MR	_	073-800 35 77	malru103@student.liu.se
Alexander Sjöholm	AS	-	076-225 11 74	alesj050@student.liu.se
Martin Svensson	MS	Documentation	070-289 01 49	marsv106@student.liu.se
Nikolaus West	NW	Testing	073-698 92 60	nikwe491@student.liu.se

Homepage: TBA

Customer: Joakim Nejdeby, Linköping University, Origo 3154 Customer contact: 013–281757, joakim.nejdeby@liu.se Project supervisor: Fahad Khan, Linköping University, fahad.khan@liu.se Examiner: Michael Felsberg, michael.felsberg@liu.se Kitchen Occupation iii

	c		4		-4	١_
l) []	ш	еι	H	. >

1	Introduction 1.1 About this document	1
2	Installing the system 2.0.1 Hardware	2 2 2
3	Calibrating the system	3
4	Configuration the system	4
\mathbf{R}_{0}	eferences	5
\mathbf{L}	ist of Figures	
	3.1 Overview of the entire system	3

List of Tables

Document history

Version	Date	Changes	Sign	Reviewed
0.1	2013-12-13	Initial draft	MS	MT

Kitchen Occupation 1

1 Introduction

1.1 About this document

This document contains instructions on how to setup and use the system. How to install the necessary hardware and software is described as well as how to calibrate and configure the system.

2 Installing the system

2.0.1 Hardware

Each Kinect camera must be installed above a door with no overlapping view shared with any other Kinect camera. The Kinect must point down or slightly angled towards the room. A minimum distance of 50 cm is required from the lense of the Kinect and the top of the door. Each Kinect must be connected to a power source, and to a device running the system software using USB.

2.0.2 Software

There are two versions of the software, one with a calibration and configuration GUI and one lightweight version without a GUI. In order for the lightweight version to work a configuration file, persumably generated by the GUI version, is required.

Linux, OS-X or Windows is required on the machine running the software. At least one Kinect camera must be connected before starting the software. More than one Kinect camear is currently only working on Linux and OS-X.

Kitchen Occupation 3

3 Calibrating the system

Calibrate the height...



Figure 3.1: System overview.

variables...

4 Configuration the system

 ${\rm Erik...}$

Kitchen Occupation 5

References

- [1] Gardel, A., Bravo, I., Jimenez, P., Lazaro, J.L. & Torquemada, A. "Statistical Background Models with Shadow Detection for Video Based Tracking," Intelligent Signal Processing, 2007. WISP 2007. IEEE International Symposium on?? Page: 1-6.
- [2] Zivkovic, Z. & Heijden, F. "Efficient Adaptive Density Estimation per Image Pixel for the Task of Background Subtraction," Pattern recognition letters, Vol. 27, No. 7. (2006), pp. 773-780.
- [3] Bernardin, K. & Stiefelhagen, R (2008) "Evaluating Multiple Object Tracking Performance: The CLEAR MOT Metrics," Interactive Systems Lab, Institut für Theoretische Informatik, Universität Karlsruhe, 76131 Karlsruhe, Germany

EXAMPLE REFERENCES ONLY, REMOVE BEFORE HANDING IN

- [4] Sonka, M., Hlavac, V. & Boyle, R. Image Processing, Analysis, and Machine Vision. Toronto: Thompson Learning, cop. 2008, 3rd ed., ISBN 0495244384.
- [5] Wood, J. (2007) "Statistical Background Models with Shadow Detection for Video Based Tracking," Master thesis, Linköping University, Department of Electrical Engineering.
- [6] Gustafsson, F., Ljung, L. & Millnert, M. Signal Processing. Studentlitteratur, Lund, Sweden, 2011, 1st ed., ISBN 978-91-44-05835-1.
- [7] "CAVIAR: Context Aware Vision using Image-based Active Recognition,"
 EC Funded CAVIAR project/IST 2001 37540
 http://homepages.inf.ed.ac.uk/rbf/CAVIAR/