LIBXS

LIBXS is a portable C library with common (and not so common) functionality that has proven useful across a variety of applications. It provides building blocks for memory operations, numerics, synchronization, and more — with a focus on performance and minimal dependencies. LIBXS targets x86-64, AArch64, and RISC-V, and requires only a C89 compiler.

LIBXS was originally developed as part of LIBXSMM (its existence started even before LIBXSMM).

Functionality

| Domain | Header | Description | |---|---|---| | Memory | `libxs_mem.h` | Comparison (`memcmp`/`diff`), hashing (CRC32), matrix copy, transpose, and data shuffling. | | GEMM | `libxs_gemm.h` | Batched dense matrix multiplication (strided, pointer-array, grouped) with pluggable BLAS/JIT kernels. | | Math | `libxs_math.h` | Matrix comparison, GCD/LCM, coprime calculation, and BF16 conversion. | | MHD | `libxs_mhd.h` | Read and write MetaImage (MHD/MHA) format files for multidimensional arrays. | | Histogram | `libxs_hist.h` | Thread-safe histogram with running statistics and per-entry callbacks. | | Malloc | `libxs_malloc.h` | Pool-based allocator for steady-state performance without system calls. | | RNG | `libxs_rng.h` | Thread-safe pseudo-random number generation (SplitMix64). | | Sync | `libxs_sync.h` | Portable atomics, locks, thread-local storage, and file locking. | | Timer | `libxs_timer.h` | High-resolution timing via calibrated TSC with OS clock fallback. | | CPUID | `libxs_cpuid.h` | CPU feature detection for x86-64 (SSE–AVX-512), AArch64, and RISC-V. | | Registry | `libxs_reg.h` | Thread-safe key-value store backed by hash table with per-thread caching. | | Utils | `libxs_utils.h` | Target-attribute machinery, ISA feature gates, bit-scan, and SIMD helpers. |

See also: Fortran Interface, Scripts.

Build

The primary build system is GNU Make:

```
make
```

Strict C89 pedantic build (recommended for development):

```
make GNU=1 DBG=1 PEDANTIC=2
```

CMake is also supported (header-only or library):

```
cmake -S . -B build -DLIBXS_HEADER_ONLY=ON
cmake --build build
```

Usage

Library — link against `libxs.a` (or `.so`) and include the desired headers:

```
#include <libxs_mem.h>
#include <libxs_timer.h>
```

Header-only — include `libxs_source.h` in exactly one translation unit (no separate library needed):

```
#include <libxs_source.h>
```

Fortran — use the provided module (documentation):

```
USE :: libxs, ONLY: libxs_memcmp
```

Samples

| Sample | Description | |---|---| | gemm | Batched DGEMM (strided, pointer-array, grouped) with OpenMP and optional MKL JIT. | | memory | Benchmarks for `libxs_diff`, `libxs_memcmp`, matrix copy, and transpose. | | ozaki | Ozaki-scheme low-precision GEMM with intercepted BLAS dispatch. | | registry | Registry dispatch microbenchmark under various access patterns. | | scratch | Pool allocator (`libxs_malloc`/`libxs_free`) vs. system `malloc`. | | shuffle | Comparison of shuffling strategies and throughput. | | sync | Lock implementation microbenchmarks. |

License

LIBXS is licensed under the BSD 3-Clause License.

LIBXS Domains

CPU Identification

Header: `libxs_cpuid.h`

Portable CPU feature detection for x86-64, AArch64, and RISC-V targets. Returns an ISA level that can be compared numerically — higher values indicate more capable instruction sets.

ISA Constants

Constant	Value	Architecture
`LIBXS_TARGET_ARCH_UNKNOWN`	0	Unknown / unsupported
`LIBXS_TARGET_ARCH_GENERIC`	1	Portable scalar baseline
`LIBXS_X86_GENERIC`	1002	x86-64 baseline
`LIBXS_X86_SSE3`	1003	SSE3
`LIBXS_X86_SSE42`	1004	SSE4.2
`LIBXS_X86_AVX`	1005	AVX
`LIBXS_X86_AVX2`	1006	AVX2 + FMA
`LIBXS_X86_AVX512`	1100	AVX-512 (Foundation + VL/BW/DQ)
`LIBXS_AARCH64`	2001	ARMv8.1 baseline
`LIBXS_AARCH64_SVE128`	2201	SVE 128-bit
`LIBXS_AARCH64_SVE256`	2301	SVE 256-bit
`LIBXS_AARCH64_SVE512`	2401	SVE 512-bit
`LIBXS_RV64_MVL128`	3001	RISC-V RVV 128-bit
`LIBXS_RV64_MVL256`	3002	RISC-V RVV 256-bit
`LIBXS_RV64_MVL128_LMUL`	3003	RISC-V RVV 128-bit (non-unit LMUL)
`LIBXS_RV64_MVL256_LMUL`	3004	RISC-V RVV 256-bit (non-unit LMUL)
`LIBXS_X86_ALLFEAT`	1999	x86 sentinel (all features)
`LIBXS_AARCH64_ALLFEAT`	2999	AArch64 sentinel (all features)
`LIBXS_RV64_ALLFEAT`	3999	RISC-V sentinel (all features)

Types

```
typedef struct libxs_cpuid_t {
  char model[256];   /* CPU model name from OS */
  int constant_tsc;  /* non-zero if TSC is invariant */
} libxs_cpuid_t;
```

Functions

```
int libxs_cpuid(libxs_cpuid_t* info);
```

Detect the ISA level of the current platform. Optionally fills `info` with the CPU model name and TSC capability. Returns a constant from the table above.

```
const char* libxs_cpuid_name(int id);
```

Returns a human-readable string for the given ISA constant, e.g., `"avx2"`.

```
int libxs_cpuid_id(const char* name);
```

Translates a name (e.g., `"avx512"`) to the corresponding ISA constant.

```
int libxs_cpuid_vlen(int id);
```

Returns the SIMD vector length in bytes for the given ISA level (0 for scalar-only targets).

project: LIBXS author: Intel Corporation license: BSD 3-Clause License summary: Small utility library. project_github: https://github.com/hfp/libxs/ project_download: https://github.com/hfp/libxs/releases/latest/ favicon: ../.theme/img/favicon.png css: ../.theme/ford.css output_dir: fortran src_dir: ../include search: true

Reference Documentation

GEMM: Matrix Multiplication

Header: `libxs_gemm.h`

Batched general matrix-matrix multiplication (GEMM). Operations are expressed as C := alpha * op(A) * op(B) + beta * C, where op() is an optional transpose. The caller can supply BLAS or MKL JIT kernels; otherwise a built-in default kernel (auto-vectorized) is used.

Types

```
typedef void (*libxs_dgemm_blas_t)(
  const char* transa, const char* transb,
  const int* m, const int* n, const int* k,
  const double* alpha, const double* a, const int* lda,
                       const double* b, const int* ldb,
  const double* beta,        double* c, const int* ldc);
```

Standard Fortran BLAS dgemm signature (e.g., `dgemm_`).

```
typedef void (*libxs_sgemm_blas_t)(
  const char* transa, const char* transb,
  const int* m, const int* n, const int* k,
  const float* alpha, const float* a, const int* lda,
                      const float* b, const int* ldb,
  const float* beta,        float* c, const int* ldc);
```

Standard Fortran BLAS sgemm signature (e.g., `sgemm_`).

```
typedef void (*libxs_dgemm_jit_t)(void* jitter,
  const double* a, const double* b, double* c);
typedef void (*libxs_sgemm_jit_t)(void* jitter,
  const float* a, const float* b, float* c);
```

MKL JIT kernel signatures. Shape, alpha, beta, and transpose info are baked into the jitter handle.

```
typedef enum libxs_gemm_flags_t {
  LIBXS_GEMM_FLAGS_DEFAULT = 0,
  LIBXS_GEMM_FLAG_NOLOCK = 1
} libxs_gemm_flags_t;
```

Flags controlling batch synchronization. By default, `_task` variants synchronize C-matrix updates. Set `LIBXS_GEMM_FLAG_NOLOCK` when no duplicate C pointers exist.

```
typedef struct libxs_gemm_config_t {
  libxs_dgemm_blas_t dgemm_blas;
  libxs_sgemm_blas_t sgemm_blas;
  libxs_dgemm_jit_t dgemm_jit;
  libxs_sgemm_jit_t sgemm_jit;
  void* jitter;
  libxs_gemm_flags_t flags;
} libxs_gemm_config_t;
```

Configuration supplying GEMM kernels. Pass NULL to batch functions to use the built-in default kernel. Kernel selection priority: (1) JIT kernel if non-NULL, (2) BLAS kernel if non-NULL, (3) built-in default. Only the function pointers matching the datatype need to be set.

Functions

```
void libxs_gemm_strided(
  libxs_data_t datatype, const char* transa, const char* transb,
  int m, int n, int k,
  const void* alpha, const void* a, int lda, int stride_a,
                     const void* b, int ldb, int stride_b,
  const void* beta,        void* c, int ldc, int stride_c,
  int batchsize, const libxs_gemm_config_t* config);
```

Process a batch of GEMMs with strided access (constant offsets between matrices). Matrices are at A + i*stride_a*elemsize, etc. Pass `config=NULL` to use the built-in kernel.

```
void libxs_gemm_strided_task(
  libxs_data_t datatype, const char* transa, const char* transb,
  int m, int n, int k,
  const void* alpha, const void* a, int lda, int stride_a,
                     const void* b, int ldb, int stride_b,
  const void* beta,        void* c, int ldc, int stride_c,
  int batchsize, const libxs_gemm_config_t* config,
  int tid, int ntasks);
```

Per-thread form of `libxs_gemm_strided`. The caller distributes work by passing its `tid` and `ntasks`.

```
void libxs_gemm_batch(
  libxs_data_t datatype, const char* transa, const char* transb,
  int m, int n, int k,
  const void* alpha, const void* a_array[], int lda,
                     const void* b_array[], int ldb,
  const void* beta,        void* c_array[], int ldc,
  int batchsize, const libxs_gemm_config_t* config);
```

Process a batch of GEMMs given arrays of pointers to matrices.

```
void libxs_gemm_batch_task(
  libxs_data_t datatype, const char* transa, const char* transb,
  int m, int n, int k,
  const void* alpha, const void* a_array[], int lda,
                     const void* b_array[], int ldb,
  const void* beta,        void* c_array[], int ldc,
  int batchsize, const libxs_gemm_config_t* config,
  int tid, int ntasks);
```

Per-thread form of `libxs_gemm_batch`.

```
void libxs_gemm_groups(
  libxs_data_t datatype,
  const char transa_array[], const char transb_array[],
  const int m_array[], const int n_array[], const int k_array[],
  const void* alpha_array, const void* a_array[], const int lda_array[],
                           const void* b_array[], const int ldb_array[],
  const void* beta_array,        void* c_array[], const int ldc_array[],
  int ngroups, const int batchsize[],
  const libxs_gemm_config_t* config);
```

Process groups of batched GEMMs with varying parameters. Each group has its own transa, transb, m, n, k, lda, ldb, ldc, and batchsize. The pointer arrays are concatenated across groups. `alpha_array` and `beta_array` are arrays of `ngroups` scalars (each `LIBXS_TYPESIZE` bytes).

Histogram

Header: `libxs_hist.h`

Thread-safe histogram that accumulates values and provides running statistics. Values are bucketed by the first element of each inserted tuple; additional per-entry values track user-defined statistics (e.g., timing data).

Types

```
typedef struct libxs_hist_t libxs_hist_t;  /* opaque */
```

```
typedef void (*libxs_hist_update_t)(double* dst, const double* src);
```

Per-value accumulation callback. Two built-in update functions are provided: `libxs_hist_update_avg` (sliding average) and `libxs_hist_update_add` (additive accumulation).

Functions

```
libxs_hist_t* libxs_hist_create(int nbuckets, int nvals,
  const libxs_hist_update_t update[]);
```

Create a histogram with `nbuckets` resolution. `nvals` is the number of values per entry (the first value determines the bucket). The `update` array (length `nvals`) specifies the accumulation function for each value slot; NULL entries default to `libxs_hist_update_avg`. Returns NULL on failure.

```
void libxs_hist_destroy(libxs_hist_t* hist);
```

Destroy a histogram. Accepts NULL.

```
void libxs_hist_push(libxs_lock_t* lock,
  libxs_hist_t* hist, const double vals[]);
```

Insert one sample. `vals[0]` selects the bucket; remaining entries are accumulated according to the update functions. The `lock` parameter can be NULL (internal locking is used).

```
void libxs_hist_get(libxs_lock_t* lock,
  const libxs_hist_t* hist,
  const int** buckets, int* nbuckets,
  double range[2], const double** vals, int* nvals);
```

Query statistics. Output pointers can be NULL to skip fields.

```
void libxs_hist_print(FILE* ostream,
  const libxs_hist_t* hist, const char title[],
  const int prec[]);
```

Render the histogram to a stream. `prec` controls decimal precision per value. NULL `ostream` is accepted.

```
void libxs_hist_update_avg(double* dst, const double* src);
void libxs_hist_update_add(double* dst, const double* src);
```

Built-in update functions: `libxs_hist_update_avg` computes a sliding average (arithmetic mean), `libxs_hist_update_add` sums values.

Memory Allocation

Header: `libxs_malloc.h`

Pool-based memory allocator designed for steady-state performance: after an initial warm-up phase, allocations are served from a recycled pool without system calls.

Types

```
typedef struct libxs_malloc_info_t {
  size_t size;  /* allocated size in bytes */
} libxs_malloc_info_t;

typedef struct libxs_malloc_pool_info_t {
  size_t size;      /* total pool size in bytes */
  size_t nactive;   /* pending (not yet freed) allocations */
  size_t nmallocs;  /* total allocation count */
} libxs_malloc_pool_info_t;

typedef struct libxs_malloc_pool_t libxs_malloc_pool_t; /* opaque */

typedef void* (*libxs_malloc_fn)(size_t size);
typedef void  (*libxs_free_fn)(void* pointer);

typedef void* (*libxs_malloc_xfn)(size_t size, const void* extra);
typedef void  (*libxs_free_xfn)(void* pointer, const void* extra);
```

Pool Management

```
libxs_malloc_pool_t* libxs_malloc_pool(libxs_malloc_fn malloc_fn, libxs_free_fn free_fn);
```

Create a memory pool. If `malloc_fn` and `free_fn` are both NULL, the standard `malloc`/`free` are used. Both must be NULL or both must be non-NULL.

```
libxs_malloc_pool_t* libxs_malloc_xpool(libxs_malloc_xfn malloc_fn, libxs_free_xfn free_fn,
  int max_nthreads);
```

Create a memory pool with extended allocator functions that receive a per-thread extra argument (see `libxs_malloc_arg`). The `max_nthreads` parameter determines the size of the internal per-thread argument table (indexed by `libxs_tid`). Both function pointers must be non-NULL and `max_nthreads` must be positive; otherwise NULL is returned.

```
void libxs_malloc_arg(libxs_malloc_pool_t* pool, const void* extra);
```

Set the per-thread extra argument for an extended pool (created by `libxs_malloc_xpool`). The pointer is stored at the calling thread's slot (`libxs_tid() % max_nthreads`) and passed to the registered `malloc_xfn`/`free_xfn` on subsequent allocations and frees from this thread. No-op for standard pools. Access is lock-free since each thread writes only its own slot.

```
void libxs_free_pool(libxs_malloc_pool_t* pool);
```

Destroy the pool and release all associated memory. Accepts NULL.

```
int libxs_malloc_pool_info(const libxs_malloc_pool_t* pool, libxs_malloc_pool_info_t* info);
```

Query aggregate pool statistics.

General Allocation

```
void* libxs_malloc(libxs_malloc_pool_t* pool, size_t size, int alignment);
```

Allocate `size` bytes from the given `pool`. `LIBXS_MALLOC_AUTO` uses automatic alignment with inline metadata. `LIBXS_MALLOC_NATIVE` preserves the allocator's native pointer (out-of-band metadata via registry). Values greater than 1 are interpreted as explicit alignment in Bytes (inline metadata). Returns NULL on failure or if `pool` is NULL.

```
void libxs_free(void* pointer);
```

Return memory to its originating pool (derived internally). Accepts NULL.

```
int libxs_malloc_info(const void* pointer, libxs_malloc_info_t* info);
```

Query the size of an allocation made with `libxs_malloc`. The pool is derived internally.

Fixed-Size Pool

A lightweight fixed-size pool for scenarios where the element size is known at initialization time.

```
void libxs_pmalloc_init(size_t size, size_t* num,
  void* pool[], void* storage);
```

Partition `storage` into `*num` chunks of `size` bytes and register them in `pool`.

```
void* libxs_pmalloc(void* pool[], size_t* num);
void* libxs_pmalloc_lock(void* pool[], size_t* num,
  libxs_lock_t* lock);
```

Pop one chunk from the pool. The `_lock` variant uses a caller-provided lock; the plain variant uses an internal lock.

```
void libxs_pfree(void* pointer, void* pool[], size_t* num);
void libxs_pfree_lock(void* pointer, void* pool[],
  size_t* num, libxs_lock_t* lock);
```

Push a chunk back into the pool.

Math Utilities

Header: `libxs_math.h`

Matrix comparison, number-theoretic helpers, modular arithmetic, and BF16 conversion functions.

Matrix Difference

```
typedef struct libxs_matdiff_t {
  double norm1_abs, norm1_rel;   /* one-norm */
  double normi_abs, normi_rel;   /* infinity-norm */
  double normf_rel;              /* Frobenius-norm (relative) */
  double linf_abs, linf_rel;    /* max element-wise difference */
  double l2_abs, l2_rel, rsq;   /* L2-norm and R-squared */
  double l1_ref, min_ref, max_ref, avg_ref, var_ref;  /* reference stats */
  double l1_tst, min_tst, max_tst, avg_tst, var_tst;  /* test stats */
  double v_ref, v_tst;          /* values at location of max diff */
  int m, n, i, r;               /* location and reduction count */
} libxs_matdiff_t;

int libxs_matdiff(libxs_matdiff_t* info,
  libxs_data_t datatype, int m, int n,
  const void* ref, const void* tst,
  const int* ldref, const int* ldtst);
```

Compute a collection of scalar differences between two matrices. Supports all `libxs_data_t` element types. The location of the largest absolute difference is recorded.

```
double libxs_matdiff_epsilon(const libxs_matdiff_t* input);
```

Combine absolute and relative norms into a single margin value. Can optionally log to a calibration file via the `LIBXS_MATDIFF` environment variable.

```
int libxs_matdiff_combine(libxs_matdiff_t* output, const libxs_matdiff_t* input);
```

Combine two single-matrix infos (each from `libxs_matdiff` with `ref=NULL`) into a meta-diff. The output supplies the reference side, the input the test side. Per-side statistics (l1, min, max, avg, var) are exact. Difference norms are summary bounds: `linf_abs` is the mean shift, `l2_abs` is a statistical bound from pooled variance. Element-wise norms are set to zero. No-op if neither side is a single-matrix info. Returns `EXIT_FAILURE` if only one side is single-matrix. Also called implicitly by `libxs_matdiff_reduce` when the input is a single-matrix info.

```
void libxs_matdiff_reduce(libxs_matdiff_t* output,
  const libxs_matdiff_t* input);
void libxs_matdiff_clear(libxs_matdiff_t* info);
```

Thread-safe reduction (max) of matdiff results. Initialize `output` with `libxs_matdiff_clear` before the first reduction.

Number Theory

```
size_t libxs_gcd(size_t a, size_t b);
size_t libxs_lcm(size_t a, size_t b);
```

Greatest common divisor (GCD of 0 and 0 is 1) and least common multiple.

```
int libxs_primes_u32(unsigned int num,
  unsigned int num_factors_n32[], int num_factors_max);
```

Find prime factors of `num` in ascending order. Returns the number of factors found (zero if `num` is prime and not 2).

```
size_t libxs_coprime(size_t n, size_t minco);
size_t libxs_coprime2(size_t n);
```

Find a co-prime of `n` not exceeding `minco` (or sqrt(n) for `coprime2`).

```
unsigned int libxs_remainder(unsigned int a, unsigned int b,
  const unsigned int* limit, const unsigned int* remainder);
```

Find the smallest multiple of `b` whose remainder mod `a` is minimized, subject to optional limit and remainder constraints.

```
unsigned int libxs_product_limit(unsigned int product,
  unsigned int limit, int is_lower);
```

Select prime factors of `product` such that the resulting sub-product stays within `limit` (0/1-Knapsack).

Scalar Utilities

```
double libxs_kahan_sum(double value, double* accumulator,
  double* compensation);
```

Kahan compensated summation: adds `value` to `*accumulator` while tracking rounding error in `*compensation`.

```
unsigned int libxs_isqrt_u64(unsigned long long x);
unsigned int libxs_isqrt_u32(unsigned int x);
unsigned int libxs_isqrt2_u32(unsigned int x);
```

Integer square root (Newton's method). `libxs_isqrt2_u32` returns a result that is also a factor of `x`.

```
double libxs_pow2(int n);
```

Compute 2^n by direct IEEE-754 exponent manipulation. Valid for n in [-1022, 1023]; returns 0 for underflow, +Inf for overflow.

Modular Arithmetic

```
unsigned int libxs_mod_inverse_u32(unsigned int a, unsigned int m);
```

Modular inverse via the extended Euclidean algorithm. Requires gcd(a, m) = 1.

```
unsigned int libxs_barrett_rcp(unsigned int p);
unsigned int libxs_barrett_pow18(unsigned int p);
unsigned int libxs_barrett_pow36(unsigned int p);
```

Precompute Barrett reduction constants for modulus `p`.

```
unsigned int libxs_mod_u32(uint32_t x, unsigned int p,
  unsigned int rcp);                          /* inline */
unsigned int libxs_mod_u64(uint64_t x, unsigned int p,
  unsigned int rcp, unsigned int pow18,
  unsigned int pow36);                        /* inline */
```

Fast modular reduction using precomputed Barrett constants. `libxs_mod_u64` uses a radix-2^18 split to avoid 64-bit division.

BF16 Conversion

```
typedef uint16_t libxs_bf16_t;
```

Storage type for BF16 values (1 sign + 8 exponent + 7 fraction bits).

```
libxs_bf16_t libxs_round_bf16(double x);   /* inline */
double libxs_bf16_to_f64(libxs_bf16_t v);  /* inline */
```

Round a double to BF16 (round-to-nearest-even) and expand BF16 back to double (exact). When the compiler provides native `__bf16` support (`LIBXS_BF16` defined), the compiler's built-in conversions are used; otherwise a portable bit-manipulation fallback is used.

Memory and Hashing Utilities

Header: `libxs_mem.h`

Byte-level memory operations (macros), comparison, hashing, string search, value formatting, and data-shuffling primitives.

Memory Macros

```
LIBXS_MEMSET(DST, SRC, SIZE)
```

Set `SIZE` bytes at `DST` to the value `SRC`, unrolled at compile-time.

```
LIBXS_MEMZERO(DST)
```

Zero all bytes of `*DST` (size derived from `sizeof(*DST)`).

```
LIBXS_MEMCPY(DST, SRC, SIZE)
```

Copy `SIZE` bytes from `SRC` to `DST`, unrolled at compile time.

```
LIBXS_ASSIGN(DST, SRC)
```

Copy `sizeof(*SRC)` bytes from `SRC` to `DST`. Asserts `sizeof(*SRC) <= sizeof(*DST)`.

```
LIBXS_MEMSWP(PTR_A, PTR_B, SIZE)
```

Swap SIZE bytes between PTR_A and PTR_B. Asserts PTR_A != PTR_B.

```
LIBXS_VALUE_ASSIGN(DST, SRC)
LIBXS_VALUE_SWAP(A, B)
```

Operate on L-values directly (address-of is taken internally). VALUE_ASSIGN can cast away const qualifiers. VALUE_SWAP asserts equal size.

Offset and Alignment

```
size_t libxs_offset(size_t ndims, const size_t offset[],
  const size_t shape[], size_t* size);
```

Compute the linear offset of an n-dimensional coordinate within a shape. Optionally returns the total linear size of the shape.

```
int libxs_aligned(const void* ptr, const size_t* inc,
  int* alignment);
```

Check whether ptr is SIMD-aligned (optionally considering the next access at ptr + *inc). Optionally writes the pointer alignment in bytes to *alignment.

Comparison

```
unsigned char libxs_diff(const void* a, const void* b,
  unsigned char size);
```

Compare two short buffers. Returns zero when equal, non-zero otherwise.

```
unsigned int libxs_diff_n(const void* a, const void* bn,
  unsigned char elemsize, unsigned char stride,
  unsigned int hint, unsigned int count);
```

Compare a against count elements in bn. Returns the first index that matches a, or count if none match. hint supplies the initial search position.

```
int libxs_memcmp(const void* a, const void* b, size_t size);
```

Boolean variant of the C memcmp. Returns zero when equal.

Hashing

```
unsigned int libxs_hash(const void* data, unsigned int size,
  unsigned int seed);
unsigned int libxs_hash8(unsigned int data);
unsigned int libxs_hash16(unsigned int data);
unsigned int libxs_hash32(unsigned long long data);
```

Produce a 32-bit hash from a buffer (with seed) or from an 8/16/32-bit key directly. NULL buffer is accepted (returns seed).

```
unsigned long long libxs_hash_string(const char string[]);
```

64-bit hash of a character string. NULL-string is accepted.

String Search

```
const char* libxs_stristrn(const char a[], const char b[],
  size_t maxlen);
const char* libxs_stristr(const char a[], const char b[]);
```

Case-insensitive substring search. `stristrn` limits the search to `maxlen` characters. Returns the pointer to the first match, or NULL.

```
int libxs_strimatch(const char a[], const char b[],
  const char delims[], int* count);
```

Word-level fuzzy matching. Counts how many words in `a` (or `b`) appear in the other string (case-insensitive, symmetric). Optional `delims` define word separators; optional `count` receives the total word count.

Value Formatting

```
size_t libxs_format_value(char buffer[], int buffer_size,
  size_t nbytes, const char scale[], const char* unit, int base);
```

Format a scalar value with SI-style scaling. Example: `libxs_format_value(buf, sizeof(buf), nbytes, "KMGT", "B", 10)` produces a human-readable byte count. Returns the value in the selected unit.

Matrix Copy and Transposition

```
void libxs_matcopy(void* out, const void* in,
  unsigned int typesize, int m, int n, int ldi, int ldo);
void libxs_matcopy_task(void* out, const void* in,
  unsigned int typesize, int m, int n, int ldi, int ldo,
  int tid, int ntasks);
```

Copy an m-by-n matrix from `in` to `out` with leading dimensions `ldi` and `ldo`. If `in` is NULL the destination is zeroed. The `_task` variant distributes work across `ntasks` threads (caller passes its `tid`).

```
void libxs_otrans(void* out, const void* in,
  unsigned int typesize, int m, int n, int ldi, int ldo);
void libxs_otrans_task(void* out, const void* in,
  unsigned int typesize, int m, int n, int ldi, int ldo,
  int tid, int ntasks);
```

Out-of-place matrix transposition. The `_task` variant distributes work across `ntasks` threads.

```
void libxs_itrans(void* inout, unsigned int typesize,
  int m, int n, int ldi, int ldo, void* scratch);
void libxs_itrans_task(void* inout, unsigned int typesize,
  int m, int n, int ldi, int ldo, void* scratch,
  int tid, int ntasks);
```

In-place matrix transposition (square or via scratch buffer). `scratch` can be NULL (auto-allocated).

```
void libxs_itrans_batch(void* inout, unsigned int typesize,
  int m, int n, int ldi, int ldo,
  int index_base, int index_stride,
  const int stride[], int batchsize,
  int tid, int ntasks);
```

Batch of in-place matrix transpositions (per-thread form).

Shuffling

```
int libxs_shuffle(void* inout, size_t elemsize, size_t count,
  const size_t* shuffle, const size_t* nrepeat);
```

In-place shuffle of `count` elements. The `shuffle` stride must be co-prime to `count` (NULL selects `libxs_coprime2(count)`). `nrepeat` defaults to 1.

```
int libxs_shuffle2(void* dst, const void* src, size_t elemsize,
  size_t count, const size_t* shuffle, const size_t* nrepeat);
```

Out-of-place shuffle from `src` to `dst`. If `*nrepeat` is zero an ordinary copy is performed.

```
size_t libxs_unshuffle(size_t count, const size_t* shuffle);
```

Return the number of `libxs_shuffle2` applications needed to restore the original order.

MetaImage I/O

Header: `libxs_mhd.h`

Read and write image data in the MetaImage (MHD/MHA) format. Files are compatible with ITK-SNAP, ParaView, and similar tools.

Types

```
typedef enum libxs_mhd_element_conversion_hint_t {
  LIBXS_MHD_ELEMENT_CONVERSION_DEFAULT,
  LIBXS_MHD_ELEMENT_CONVERSION_MODULUS
} libxs_mhd_element_conversion_hint_t;
```

Hint controlling element conversion behaviour (default clamping vs. modulus mapping).

```
typedef struct libxs_mhd_element_handler_info_t {
  libxs_data_t type;
  libxs_mhd_element_conversion_hint_t hint;
} libxs_mhd_element_handler_info_t;
```

Destination type and conversion hint, passed to built-in or custom element handlers.

```
typedef int (*libxs_mhd_element_handler_t)(void* dst,
  const libxs_mhd_element_handler_info_t* dst_info,
  libxs_data_t src_type,
  const void* src, const void* src_min, const void* src_max);
```

Per-element callback for reading or converting image data. The value range (`src_min`, `src_max`) is available for scaling.

```
typedef struct libxs_mhd_info_t {
  size_t ndims;         /* dimensionality */
  size_t ncomponents;   /* interleaved image channels */
  libxs_data_t type;  /* pixel element type */
  size_t header_size;   /* header size in bytes (LOCAL data) */
} libxs_mhd_info_t;
```

Image descriptor populated by `libxs_mhd_read_header` and consumed by read/write.

```
typedef struct libxs_mhd_write_info_t {
  const libxs_mhd_element_handler_info_t* handler_info;
  libxs_mhd_element_handler_t handler;
  const char* extension_header;
  const void* extension;
  size_t extension_size;
} libxs_mhd_write_info_t;
```

Optional write parameters (conversion, custom handler, extension data). NULL is accepted for all-defaults.

Element Helpers

```
int libxs_mhd_element_conversion(void* dst,
  const libxs_mhd_element_handler_info_t* dst_info,
  libxs_data_t src_type,
  const void* src, const void* src_min, const void* src_max);
```

Built-in element conversion. Scales values when `src_min` and `src_max` are non-NULL; otherwise clamps to the destination type.

```
int libxs_mhd_element_comparison(void* dst,
  const libxs_mhd_element_handler_info_t* dst_info,
  libxs_data_t src_type,
  const void* src, const void* src_min, const void* src_max);
```

Check an in-memory buffer against file content (element-wise comparison with optional type conversion).

Type Queries

```
const char* libxs_mhd_typename(libxs_data_t type,
  const char** ctypename);
```

Return the MHD element-type name (e.g. `"MET_FLOAT"`) for the given `libxs_data_t`. Optionally writes the C type name. Returns NULL for unknown types.

```
libxs_data_t libxs_mhd_typeinfo(const char elemname[]);
```

Return the `libxs_data_t` for a given MHD element-type string.

Read

```
int libxs_mhd_read_header(const char header_filename[],
  size_t filename_max_length, char filename[],
  libxs_mhd_info_t* info, size_t size[],
  char extension[], size_t* extension_size);
```

Parse an MHD header file. `info->ndims` is an in/out parameter (maximum on input, actual on output). `filename` receives the data-file path (may differ from the header when data is stored separately). Extension data is optional.

```
int libxs_mhd_read(const char filename[],
  const size_t offset[], const size_t size[],
  const size_t pitch[], const libxs_mhd_info_t* info,
  void* data,
  const libxs_mhd_element_handler_info_t* handler_info,
  libxs_mhd_element_handler_t handler);
```

Read image data into `data`. Optional `handler_info` triggers type conversion; optional `handler` supplies a custom per-element callback (can also serve as a comparison function without allocating a buffer).

Write

```
int libxs_mhd_write(const char filename[],
  const size_t offset[], const size_t size[],
  const size_t pitch[], libxs_mhd_info_t* info,
  const void* data,
  const libxs_mhd_write_info_t* write_info);
```

Write image data in the extended MHD format. `info->header_size` is updated on output. Pass NULL for `write_info` when no conversion or extension is needed.

Registry

Header: `libxs_reg.h`

Thread-safe key-value store backed by a hash table with per-thread caching.

Configuration Macros

Macro	Default	Description
`LIBXS_REGKEY_MAXSIZE`	64	Maximum key size in bytes
`LIBXS_REGISTRY_NBUCKETS`	64	Initial number of hash-table buckets (must be a power of two)
`LIBXS_REGCACHE_NENTRIES`	16	Thread-local cache entries per thread (power of two; 0 disables caching)

Types

```
typedef struct libxs_registry_t libxs_registry_t;   /* opaque */

typedef struct libxs_registry_info_t {
  size_t capacity, size, nbytes;
} libxs_registry_info_t;
```

Lifetime

```
libxs_registry_t* libxs_registry_create(void);
```

Create a new registry. Returns `NULL` in case of an error.

```
void libxs_registry_destroy(libxs_registry_t* registry);
```

Destroy a registry and release all entries.

Iteration

```
void* libxs_registry_begin(libxs_registry_t* registry,
  const void** key, size_t* cursor);
void* libxs_registry_next(libxs_registry_t* registry,
  const void** key, size_t* cursor);
```

Enumerate entries. Initialize `*cursor` to 0 before the first `begin` call. Each call returns the value pointer and writes the key pointer to `*key`, or returns NULL when iteration is complete.

Access

```
void* libxs_registry_set(libxs_registry_t* registry,
  const void* key, size_t key_size,
  const void* value_init, size_t value_size,
  libxs_lock_t* lock /* = NULL */);
```

Insert or update a key-value pair. The key must be binary-reproducible (zero-initialize padding). `value_init` may be NULL to defer initialization. Re-registering an existing key reallocates if the new value is larger. When `lock` is NULL the registry's internal lock is used. Returns a pointer to the stored value.

```
void* libxs_registry_get(const libxs_registry_t* registry,
  const void* key, size_t key_size,
  libxs_lock_t* lock /* = NULL */);
```

Look up a value by key. Returns NULL if not found.

```
int libxs_registry_get_copy(const libxs_registry_t* registry,
  const void* key, size_t key_size,
  void* value_out, size_t value_size,
  libxs_lock_t* lock /* = NULL */);
```

Thread-safe query: copies up to `value_size` bytes of the stored value into `value_out` under the lock. Unlike `libxs_registry_get`, the caller never receives a raw pointer into the registry's internal storage, making this safe under concurrent modifications. Returns non-zero if the key was found, zero otherwise.

```
int libxs_registry_has(libxs_registry_t* registry,
  const void* key, size_t key_size,
  libxs_lock_t* lock /* = NULL */);
```

Check whether a key exists. Non-zero if found.

```
size_t libxs_registry_value_size(libxs_registry_t* registry,
  const void* key, size_t key_size,
  libxs_lock_t* lock /* = NULL */);
```

Query the stored value size in bytes. Returns 0 if not found.

```
void libxs_registry_remove(libxs_registry_t* registry,
  const void* key, size_t key_size,
  libxs_lock_t* lock /* = NULL */);
```

Remove a key-value pair and release its memory.

```
int libxs_registry_extract(libxs_registry_t* registry,
  const void* key, size_t key_size,
  void* value_out, size_t value_size,
  libxs_lock_t* lock /* = NULL */);
```

Atomically retrieve and remove a key-value pair. Copies up to `value_size` bytes of the stored value into `value_out` (may be NULL to discard the value), then removes the entry and releases its memory. The lookup, copy, and removal are performed under a single lock hold, eliminating the race that exists when calling `libxs_registry_get` followed by `libxs_registry_remove` separately. Returns non-zero if the key was found, zero otherwise.

Status

```
int libxs_registry_info(libxs_registry_t* registry,
  libxs_registry_info_t* info);
```

Query registry capacity, number of entries, and total bytes stored.

Random Number Generator

Header: `libxs_rng.h`

Thread-safe pseudo-random number generation (SplitMix64 with per-thread TLS state).

Matrix Initialization Macros

```
LIBXS_MATRNG(INT_TYPE, REAL_TYPE, SEED, DST, NROWS, NCOLS, LD, SCALE)
LIBXS_MATRNG_SEQ(INT_TYPE, REAL_TYPE, SEED, DST, NROWS, NCOLS, LD, SCALE)
LIBXS_MATRNG_OMP(INT_TYPE, REAL_TYPE, SEED, DST, NROWS, NCOLS, LD, SCALE)
```

Fill a column-major matrix (`NROWS` x `NCOLS`, leading dimension `LD`) with deterministic values. When `SEED != 0` the fill is linear; when `SEED == 0` a shuffle-based initialization normalizes values into [-SCALE, +SCALE]. The `_OMP` variant parallelizes with OpenMP; `_SEQ` is serial.

Functions

```
void libxs_rng_set_seed(unsigned int seed);
```

Set the seed of the calling thread's PRNG state. Each thread maintains independent state via TLS. Unseeded threads start with a deterministic default (seed = 1).

```
unsigned int libxs_rng_u32(unsigned int n);
```

Return a pseudo-random value in [0, n) with uniform distribution (Lemire's nearly-divisionless method). Thread-safe.

```
double libxs_rng_f64(void);
```

Return a double-precision value in [0, 1) with full 53-bit mantissa resolution. Thread-safe.

```
void libxs_rng_seq(void* data, size_t nbytes);
```

Fill a buffer with pseudo-random bytes. Thread-safe.

Synchronization

Header: `libxs_sync.h`

Thread-local storage, atomic operations, lock abstractions (spin/mutex/rwlock/atomic), file locking, and stdio synchronization.

Thread-Local Storage

```
LIBXS_TLS
```

Storage-class qualifier for thread-local variables. Maps to `__thread`, `__declspec(thread)`, or `thread_local` depending on the compiler. Defined as empty when TLS is unavailable or disabled (`LIBXS_NO_TLS`).

Atomic Operations

The header provides a suite of macros for atomic loads, stores, compare-and-swap, and arithmetic. The implementation selects among GCC builtins (`__atomic_*`), legacy GCC sync builtins, Windows Interlocked intrinsics, or no-op fallbacks depending on the compiler and `LIBXS_SYNC` setting.

| Macro | Description | |:|:| | `LIBXS_ATOMIC_LOAD(SRC, KIND)` | Atomic load | | `LIBXS_ATOMIC_STORE(DST, VALUE, KIND)` | Atomic store | | `LIBXS_ATOMIC_STORE_ZERO(DST, KIND)` | Atomic store of zero | | `LIBXS_ATOMIC_CMPSWP(DST, OLDVAL, NEWVAL, KIND)` | Compare-and-swap | | `LIBXS_ATOMIC_FETCHADD(SRC, VALUE, KIND)` | Fetch-and-add | | `LIBXS_ATOMIC_ADDFETCH(SRC, VALUE, KIND)` | Add-and-fetch | | `LIBXS_ATOMIC_SUBFETCH(SRC, VALUE, KIND)` | Subtract-and-fetch | | `LIBXS_ATOMIC_TRYLOCK(DST, KIND)` | Try-lock (returns acquired state) | | `LIBXS_ATOMIC_ACQUIRE(DST, KIND)` | Spin-acquire | | `LIBXS_ATOMIC_RELEASE(DST, KIND)` | Release (store zero) | | `LIBXS_ATOMIC_SYNC(KIND)` | Full memory fence |

The `KIND` parameter selects the memory order but is ignored on most backends (sequential consistency is always used).

Lock Abstraction

```
LIBXS_LOCK_TYPE(KIND)
LIBXS_LOCK_INIT(KIND, LOCK, ATTR)
LIBXS_LOCK_DESTROY(KIND, LOCK)
LIBXS_LOCK_ACQUIRE(KIND, LOCK)
LIBXS_LOCK_TRYLOCK(KIND, LOCK)
LIBXS_LOCK_RELEASE(KIND, LOCK)
```

Generic lock interface parameterized by `KIND`:

| KIND | Backend | |:|:| | `LIBXS_LOCK_SPINLOCK` | Atomic spin-lock | | `LIBXS_LOCK_MUTEX` | Pthreads / Windows CRITICAL_SECTION | | `LIBXS_LOCK_RWLOCK` | Pthreads reader-writer lock | | `LIBXS_LOCK_ATOMIC` | Lightweight atomic lock |

The default lock kind used by the library is `LIBXS_LOCK` (resolves to one of the above based on build configuration).

```
typedef LIBXS_LOCK_TYPE(LIBXS_LOCK) libxs_lock_t;
```

General-purpose lock type. Instances of `libxs_lock_t` are used by the registry and other library components; users may also create their own.

Reader-writer variants are available for `LIBXS_LOCK_RWLOCK`:

```
LIBXS_LOCK_ACQREAD(KIND, LOCK)
LIBXS_LOCK_RELREAD(KIND, LOCK)
LIBXS_LOCK_TRYREAD(KIND, LOCK)
```

File Locking

```
LIBXS_FLOCK(FILE)
LIBXS_FUNLOCK(FILE)
```

Per-file locking for thread-safe I/O. Maps to `flockfile`/`funlockfile` on POSIX, `_lock_file`/`_unlock_file` on Windows, or no-ops when synchronization is disabled.

Functions

```
unsigned int libxs_pid(void);
```

Return the process ID of the calling process.

```
unsigned int libxs_tid(void);
```

Return a zero-based, consecutive thread ID for the calling thread. TID = 0 does not necessarily correspond to the main thread.

```
void libxs_stdio_acquire(void);
void libxs_stdio_release(void);
```

Acquire/release a global lock around console output. The macros `LIBXS_STDIO_ACQUIRE()` and `LIBXS_STDIO_RELEASE()` expand to these calls.

Timer

Header: `libxs_timer.h`

High-resolution timing via a calibrated TSC when available, with an OS real-time clock fallback.

Types

```
typedef unsigned long long libxs_timer_tick_t;
```

Integer type representing a single timer sample.

```
typedef struct libxs_timer_info_t {
  int tsc;   /* non-zero if a calibrated TSC is used */
} libxs_timer_info_t;
```

Functions

```
int libxs_timer_info(libxs_timer_info_t* info);
```

Query timer properties. `info->tsc` is non-zero when RDTSC (x86), CNTVCT_EL0 (AArch64), or MFTB (PPC64) is available. Triggers lazy library initialization if necessary.

```
libxs_timer_tick_t libxs_timer_tick(void);
```

Sample the current tick of the monotonic timer. The tick unit is platform-specific; convert with `libxs_timer_duration` or `libxs_timer_ncycles`.

```
libxs_timer_tick_t libxs_timer_ncycles(
  libxs_timer_tick_t tick0, libxs_timer_tick_t tick1);   /* inline */
```

Unsigned difference `tick1 - tick0`, handling wrap-around safely. Implemented via `LIBXS_DELTA`.

```
double libxs_timer_duration(
  libxs_timer_tick_t tick0, libxs_timer_tick_t tick1);
```

Convert a pair of ticks to elapsed wall-clock time in seconds.

Low-Level Utilities and SIMD

Header: `libxs_utils.h`

Target-attribute machinery, ISA feature gates, intrinsic fix-ups, bit-scan operations, and AVX-512 inline helpers.

Target Attributes

```
LIBXS_INTRINSICS(TARGET)
```

Expands to a `__attribute__((target(...)))` clause for the given ISA level. Used to compile individual functions for a higher ISA than the baseline without changing compiler flags. The macro is a no-op when the baseline already covers the requested level or when the compiler does not support multi-versioning.

```
LIBXS_ATTRIBUTE_TARGET(TARGET)
```

Lower-level macro that resolves `TARGET` (an integer ISA constant such as `LIBXS_X86_AVX512`) to the corresponding target string, e.g. `target("avx2,fma,avx512f,...")`.

ISA Feature Gates

Preprocessor symbols defined when the compiler can generate code for a given ISA:

Macro	ISA level
`LIBXS_INTRINSICS_X86`	x86 baseline (SSE2)
`LIBXS_INTRINSICS_SSE3`	SSE3
`LIBXS_INTRINSICS_SSE42`	SSE4.2
`LIBXS_INTRINSICS_AVX`	AVX
`LIBXS_INTRINSICS_AVX2`	AVX2 + FMA
`LIBXS_INTRINSICS_AVX512`	AVX-512 (F + CD + DQ + BW + VL)

`LIBXS_STATIC_TARGET_ARCH` records the highest ISA provided by the compiler flags. `LIBXS_MAX_STATIC_TARGET_ARCH` records the highest ISA reachable via target attributes.

Intrinsic Fix-ups

Portability wrappers for intrinsics whose signatures differ across compilers:

Macro	Purpose
`LIBXS_INTRINSICS_LOADU_SI128`	`_mm_loadu_si128`
`LIBXS_INTRINSICS_MM512_LOAD_PS/PD`	Unaligned 512-bit float/double load
`LIBXS_INTRINSICS_MM512_STREAM_*`	Non-temporal 512-bit stores
`LIBXS_INTRINSICS_MM256_STORE_EPI32`	256-bit integer store
`LIBXS_INTRINSICS_MM512_SET_EPI16`	Portable 512-bit set from 32 int16 values
`LIBXS_INTRINSICS_MM512_UNDEFINED_*`	Undefined-value initializers (zero in debug)
`LIBXS_INTRINSICS_MM512_EXTRACTI64X4_EPI64`	256-bit extract from 512-bit
`LIBXS_INTRINSICS_MM512_ABS_PS`	Absolute value of packed floats
`LIBXS_INTRINSICS_MM512_MASK_I32GATHER_EPI32`	Masked gather
`LIBXS_INTRINSICS_MM512_STORE/LOAD_MASK*`	Mask register I/O (8/16/32/64-bit)
`LIBXS_INTRINSICS_MM512_CVTU32_MASK*`	Convert uint32 to mask register

Bit-Scan Operations

```
LIBXS_INTRINSICS_BITSCANFWD32(N)   /* count trailing zeros, 32-bit */
LIBXS_INTRINSICS_BITSCANFWD64(N)   /* count trailing zeros, 64-bit */
LIBXS_INTRINSICS_BITSCANBWD32(N)   /* bit index of highest set bit, 32-bit */
LIBXS_INTRINSICS_BITSCANBWD64(N)   /* bit index of highest set bit, 64-bit */
```

Use GCC `__builtin_ctz`/`__builtin_clz` when available, Windows `_BitScanForward`/`_BitScanReverse` intrinsics on MSVC, or portable software fallbacks (`*_SW` variants). All return 0 when `N` is 0.

Derived Macros

```
LIBXS_NBITS(N)      /* minimum bits to represent N */
LIBXS_ISQRT2(N)     /* fast power-of-two approximation of sqrt(N) */

unsigned int LIBXS_ILOG2(unsigned long long n);   /* ceil(log2(n)) */
```

`LIBXS_ILOG2` is a function (not a macro) and handles the n = 0 case.

AVX-512 Inline Functions

Available only when `LIBXS_INTRINSICS_AVX512` is defined.

```
__m512i libxs_mulhi_epu32(__m512i a, __m512i b);   /* inline */
```

Unsigned 32-bit high-multiply for 16 lanes: floor(a * b / 2^32). Emulates the missing `_mm512_mulhi_epu32` via even/odd `_mm512_mul_epu32`.

```
__m512i libxs_mod_u32x16(__m512i x,
  unsigned int p, unsigned int rcp);               /* inline */
```

Vectorized Barrett reduction: x mod p for 16 uint32 lanes. `rcp` is the Barrett reciprocal from `libxs_barrett_rcp()`. This is the SIMD counterpart of the scalar `libxs_mod_u32`.

Appendix

Overview

LIBXS's collection of scripts consists of Python and Bash scripts falling into two categories:

- Configuration scripts
- Development tools

Scripts related to configuring LIBXS are distributed with source code archives. Development tools mostly for software development purpose and are (indirectly) used by contributors, but some scripts are distributed by source code archives as well. The latter are mostly related to running tests (indirectly used by upstream maintainers, e.g., of Linux distributions).

Development

Parallel Execution

The script `tool_pexec.sh` can execute commands read from standard input (see `-h` or `--help`). The execution may be concurrent on a per-command basis. The level of parallelism is determined automatically but can be adjusted (oversubscription, nested parallelism). Separate logfiles can be written for every executed command (`-o /path/to/basename.ext` used as template for individual logfiles like /path/to/*basename*-case_xyz.*ext*). File I/O can become a bottleneck on distributed filesystems (e.g., NFS), or generally hinders nested parallelism (`-o /dev/null -k`).

Every line of standard input denotes a separate command:

```
seq 100 | xargs -I{} echo "echo \"{}\"" \
        | tool_pexec.sh
```

The script considers an allow-list which permits certain error codes. Allow-lists can be automatically generated (`-u`). Most if not all settings can be determined by environment variables as well (prefix `PEXEC_`), e.g., `export PEXEC_LG=/path/to/basename.ext` allows to omit `-o` on the command line and to always generate logfiles (see earlier explanation).

Performance Report The script `tool_report.py` collects performance results given in two possible formats: (1) native "telegram" format, and (2) JSON format. The script aims to avoid encoding domain knowledge. In fact, the collected information is not necessarily performance data but a time series in general. Usually, the script is not executed directly but launched using a wrapper supplying the authorization token and further adapting to the execution environment (setup):

```
#!/usr/bin/env bash

## authorization token
TOKEN=0123456789abcdef0123456789abcdef01234567

PYTHON=$(command -v python3)
if [ ! "${PYTHON}" ]; then
  PYTHON=$(command -v python)
fi

if [ "${PYTHON}" ]; then
  HERE=$(cd "$(dirname "$0")" && pwd -P)
  NAME=$(basename "$0" .sh)
  SCRT=${NAME}.py

  if [ "${HERE}" ]; then SCRT_A=${HERE}/${SCRT}; fi
  if [ "${LIBXSROOT}" ]; then SCRT_B=${LIBXSROOT}/scripts/${SCRT}; fi
  if [ "${REPOREMOTE}" ]; then SCRT_C=${REPOREMOTE}/libxs/scripts/${SCRT}; fi

  if [ "${SCRT_A}" ] && [ -e "${SCRT_A}" ]; then
    ${PYTHON} "${SCRT_A}" --token "${TOKEN}" "$@"
  elif [ "${SCRT_B}" ] && [ -e "${SCRT_B}" ]; then
    ${PYTHON} "${SCRT_B}" --token "${TOKEN}" "$@"
  elif [ "${SCRT_C}" ] && [ -e "${SCRT_C}" ]; then
    ${PYTHON} "${SCRT_C}" --token "${TOKEN}" "$@"
  else
    >&2 echo -n "ERROR: missing ${SCRT_A}"
    if [ "${SCRT_B}" ]; then >&2 echo -n " or ${SCRT_B}"; fi
    if [ "${SCRT_C}" ]; then >&2 echo -n " or ${SCRT_C}"; fi
    >&2 echo "!"
    exit 1
  fi
else
  >&2 echo "ERROR: missing prerequisites!"
  exit 1
fi
```

The following flow is established:

1. Connect to a specified pipeline (online) or load a logfile directly (offline).
2. Populate an entry (JSON-block or telegram) under a "build number", "category", and "case".
3. Plot "execution time" over the history of build numbers.

There are several command-line options to customize each of the above steps (`--help` or `-h`):

- To only plot data (already collected), use `-i ""` to omit a network connection.
- To query, e.g., ResNet-50 results, use `-y resnet-50` (case-insensitive).
- Multiple results can be combined, i.e., use `-y` (space-separated words).
- To exactly match (single results) use `-x` in addition to `-y`.
- To limit and select a specific "category" (instead of all), use `-s`.
- Select exactly using `-z`, e.g., `-z -s "clx"` (omits, e.g., "clx").
- Create a PDF (vector graphics have infinite resolution), use `-g myreport.pdf`.
- Adjust pixel resolution, aspect ratio, or density, use `-d 1200x800`.

The level of verbosity (`-v`) can be adjusted (0: quiet, 1: automation, 2: progress). Default verbosity shows progress (downloading results) whereas "automation" allows to further automate reports, e.g., get the filename of the generated plot (errors are generally printed to `stderr`). Loading a logfile into the database directly can serve two purposes: (1) debugging the supported format like "telegram" or JSON, and (2) offline operation. The latter can be also useful if for instance a CI-agents produces a log, i.e., it can load into the database right away. Command-line options also allow for "exact placement" (`-j`) by specifying the build number supposed to take the loaded data (data is appended by default, i.e., it is assumed to be a new build, or the build number is incremented).

The tool automatically performs database backups of the historic values (`-n`) according to the retention (`-k`). The retention can also be used to prune the history (by forcing an earlier backup). Backups carry a timestamp as part of the filename (database), and contain the full history of value at the time of the backup.

Examples (omit `-i ""` if downloading results is desired):

- Plot ResNet-50 results from CI-pipeline "tpp-libxs" for "clx" systems:
  `scripts/tool_report.sh -p tpp-libxs -i "" -y "resnet-50" -z -s "clx"`.
- Like above request, but only FP32 results:
  `scripts/tool_report.sh -p tpp-libxs -i "" -x -y "ResNet-50 (fwd, mb=1, f32)" -z -s "clx"`.
- Like above request, but alternatively ("all" operator is also default):
  `scripts/tool_report.sh -p tpp-libxs -i "" -u "all" -y "resnet f32" -z -s "clx"`.
- Plot ResNet-50 results from CI-pipeline "tpp-plaidml":
  `scripts/tool_report.sh -p tpp-plaidml -i "" -r "duration_per_example,1000,ms"`
- Plot "GFLOP/s" for "conv2d_odd_med" from CI-pipeline "tpp-plaidml":
  `scripts/tool_report.sh -p tpp-plaidml -i "" -y "conv2d_odd_med" -r "gflop"`
- Plot "tpp-benchmark" pipeline (MLIR benchmarks, main-branch):
  `scripts/tool_report.sh -p tpp-benchmark -i "" -y "" -r "mlir" -b "main"`
- Plot "tpp-benchmark" pipeline (MLIR benchmarks, main-branch, untied plots):
  `scripts/tool_report.sh -p tpp-benchmark -i "" -y "" -r "mlir" -b "main" -u`
- Plot "tpp-benchmark" pipeline (reference benchmarks; selected entries `-y`):
  `scripts/tool_report.sh -p tpp-benchmark -i "" -q "any" -y "gemm matmul" -r "dnn"`
- Plot "tpp-benchmark" pipeline (MLIR benchmarks without "single", untied plots):
  `scripts/tool_report.sh -p tpp-benchmark -i "" -q "not" -y "single" -r "mlir" -u`
- Plot "tpp-performance" pipeline (MLIR benchmarks only "mlp", untied plots):
  `scripts/tool_report.sh -p tpp-performance -i "" -y "mlp" -r "mlir" -u`

The exit code of the script is non-zero in case of an error, or if the latest value deviates and exceeds the margin (`--bounds`). For the latter, the meaning of the values must be given (like "higher is better"). The first argument of the bounds is a factor such that the standard deviation of historic values is amplified to act as margin of the relative deviation (latest versus previous value). The second argument of the bounds determines the accepted percentage of deviation (latest versus previous value).

The exit code is only impacted if an explicit sign is given to determine "bad" values (`+` or `-`). For example, `2.0` gives a factor of two over standard deviation (no impact for the exit code), `2.0 10` is likewise but also limits the deviation to 10% at most, `+3.0` gives a factor of three over standard deviation and considers a positive deviation as regression (like for timing values) and thereby impacts the exit code. Also, it is possible to just determine the meaning and keep default bounds, .i.e., only `-` determines negative deviation as a regression (like for higher-is-better values).

By default, only the last/current vs the previous value (history) determines the deviation. This can miss a historic slow/steady regession if the last value is always below threashold. To consider the full history value (median) as part of the deviation, a leading `0` can be given in front of the afore mentioned factor (after the sign). For example, `-02.1`

specifies an aplification factor of 2.1 over standard deviation with deviation considering the median of all historic values. Consequently, a fractional factor requires two leading zeros, e.g., `-00.4`.