



Zimbra™ Collaboration Suite Multi-Server Installation Guide

**Open Source Edition 3.0 Beta 3
January 2006**

Copyright Zimbra, Inc. 2006. All rights reserved. The Zimbra logo and logo type are trademarks of Zimbra, Inc.

No part of this document may be reproduced, in whole or in part, without the express written permission of Zimbra Inc.

Trademark and Licensing

MySQL is a registered trademark of MySQL AB in the United States, the European Union and other countries.

OpenLDAP is a registered trademark of the OpenLDAP Foundation.

Postfix is copyright © 1999 International Business Machines Corporation and others and it was created by Wietse Venema <wietse@porcupine.org>.

SpamAssassin is a trademark of Deersoft, Inc.

This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>).

All other marks are the property of their respective owners.

Building Better Products within the Open Source Community

Zimbra Collaboration Suite leverages many great technologies from the open source community: MySQL, OpenLDAP, Postfix, SpamAssassin, and Apache. Zimbra believes that great products come from contributing to and leveraging open source technologies. We are thankful for the great contributions that led to the creation of MySQL, OpenLDAP, Postfix, SpamAssassin, and Apache software.

Zimbra, Inc.
1500 Fashion Island Boulevard, Suite 100
San Mateo, California 94404
650. 212.0505
www.zimbra.com

Table of Content

Introduction	3
Audience	3
For More Information	3
Support and Contact Information	4
 Chapter 1 Multi-Server Installation System Requirements and Prerequisites	 5
System Requirements	5
.....	7
Installation Modifications for Red Hat Enterprise Linux	8
Installation Modifications for Fedora	10
 Chapter 2 Zimbra Installation Overview	 13
Configuration Examples	14
Downloading the Zimbra Software	14
Basic Menu Configuration	15
 Chapter 3 Multiple-Server Installation	 19
Starting the installation process	19
Installing Zimbra LDAP Server	21
Installing Zimbra MTA on a Server	24
Installing Zimbra Mailbox Server	25
Installing the Zimbra-SNMP package	28
Verifying Server Configuration	28
Post Installation Tasks	29
Logging on to the Administration Console	29
Defining Classes of Service	29
Provisioning Accounts	30

Introduction

Information in this guide is intended for persons responsible for installing the Zimbra Collaboration Suite. This guide will help you plan and perform all installation procedures necessary to deploy a fully functioning email system based on Zimbra's messaging technology.

This guide covers the installation of Zimbra Collaboration Suite 3.0 Open Source Edition Beta 3.

Audience

This installation guide assumes you have a thorough understanding of system administration concepts and tasks and are familiar with email communication standards, security concepts, directory services, and database management.

For More Information

Zimbra documentation, including a readme text file, release notes, the administration guide, and other Zimbra guides are copied to the servers during the installation. They are also available from www.zimbra.com and from the administration console.

- **Administrator's Guide.** This guide describes product architecture, server functionality, administration tasks, configuration options, and backup and restore procedures. The guide is available in pdf format from the administrator's console.
- **Administrator Help.** The administrator Help provides instructions about how to add and maintain your servers, domains, and user accounts from the admin console.
- **Web Client Help.** The Web Client Help provides instructions about how to use the Zimbra Web Client features.
- **Migration Wizard Guide.** This guide describes how to migrate Microsoft® Exchange users to the Zimbra Collaboration Suite.

Support and Contact Information

Visit **www.zimbra.com** to join the community and to be a part of building the best open source messaging solution. We appreciate your feedback and suggestions.

- Contact sales@zimbra.com to purchase Zimbra Collaboration Suite
- Network Edition customers can contact support at support@zimbra.com
- Explore the Zimbra Forums for answers to installation or configurations problems
- Join the [Zimbra Community Forum](#), to participate and learn more about the Zimbra Collaboration Suite.
- Send an email to feedback@zimbra.com to let us know what you like about the product and what you would like to see in the product. Or, if you prefer, post your ideas to the Zimbra Forum.

If you encounter problems with this software, visit Zimbra.com and submit a bug report. Make sure you provide enough detail so that the bug can be easily duplicated.

Chapter 1 Multi-Server Installation System

Requirements and Prerequisites

In order to successfully install and run Zimbra Collaboration Suite, ensure your system meets the requirements described in this section.

System Requirements

	Requirements
Servers	<p>Minimum requirements</p> <ul style="list-style-type: none">• Intel/AMD CPU 1.5 GHz• 1 GB RAM• 5 GB free disk space for software and logs• Additional disk space for mail storage <p>Recommended requirements</p> <ul style="list-style-type: none">• Intel/AMD CPU 2.0GHZ+• 2 GB RAM• 10 GB free disk space for software and logs (SATA or SCSI for performance, and RAID/Mirroring for redundancy)• Additional disk space for mail storage
Operating System Open Source Edition	<ul style="list-style-type: none">• Red Hat® Enterprise Linux®, Version 4, Update 2 or <ul style="list-style-type: none">• Fedora Core 3 or 4• Mac OS® X 10.4• SUSE ES 9 or 10 (Zimbra Alpha) <p>Red Hat Enterprise Linux and Fedora Core OS configuration requirements are described in this guide.</p>

Other Applications	<p>For Red Hat , Fedora Core and SuSE Enterprise operating systems, the server must also have the following installed:</p> <ul style="list-style-type: none"> • NPTL. Native POSIX Thread Library • Sudo. Superuser, required to delegate admins. • libidn. For internationalizing domain names in applications (IDNA) • cURL. A command line tool for transferring files with URL syntax • fetchmail. A remote-mail retrieval and forwarding utility used for on-demand TCIP/IP links. • GMP. GNU Multiple-Precision Library. • compat-libstdc++-33. Compatibility Standard C++ libraries.
Miscellaneous	<ul style="list-style-type: none"> • SSH client software to transfer and install the Zimbra Collaboration Suite software. • Access to DNS server
Administrator Computers *These OS configurations have been tested and are known to work. Other configurations may work.	<ul style="list-style-type: none"> • Windows XP with either Internet Explorer 6.0 or Firefox 1.5 • Macintosh OS X 10.4 with Firefox 1.5
End User Computers using Zimbra Web Client *These OS configurations have been tested and are known to work. Other configurations may work.	<p><i>Minimum</i></p> <ul style="list-style-type: none"> • Intel/AMD/Power PC CPU 750MHz • 256MB RAM <p><i>Recommended</i></p> <ul style="list-style-type: none"> • Intel/AMD/Power PC CPU 1.5GHz • 512MB RAM <p>Operating system/ browser combinations</p> <ul style="list-style-type: none"> • Windows XP with either Internet Explorer 6.0 or Firefox 1.5 • Fedora Core 4 with Firefox 1.5 • Mac OS X 10.4 with Firefox 1.5

End User Computers Using Other Clients *These OS configurations have been tested and are known to work. Other configurations may work.	<i>Minimum</i> <ul style="list-style-type: none">• Intel/AMD/Power PC CPU 750MHz• 256MB RAM <i>Recommended</i> <ul style="list-style-type: none">• Intel/AMD/Power PC CPU 1.5GHz• 512MB RAM• Operating system IMAP combinations <ul style="list-style-type: none">• Windows XP with either Outlook Express 6, Outlook 2003 for MAPI or IMAP, or Thunderbird 1.0.7• Fedora Core 4 with Thunderbird 1.0.7• Mac OS X 10.4 with Apple Mail
Monitor	Display minimum resolution 1024 x 768
Internet Connection Speed	128 kbps or higher

This guide describe configuration modifications for only two of the operating systems that Zimbra Collaboration Suite supports. Other operating systems may have similar configuration requirements. When you prepare to install the ZCS application, use this information as a reference point.


This guide describe configuration modifications for only two of the operating systems that Zimbra Collaboration Suite supports. Other operating systems may have similar configuration requirements. When you prepare to install the ZCS application, use this information as a reference point.

Installation Modifications for Red Hat Enterprise Linux


The Zimbra Collaboration Suite runs on the Red Hat Enterprise Linux, 4, Update 2 operating system. When you install the Red Hat software for the Zimbra Collaboration Suite, you should accept the default setup answers to install the minimum configuration, except the following steps must be modified.

Refer to the Red Hat Enterprise Linux installation guide for detailed documentation about installing their software.

- **Disk Partitioning Setup.** Check **Manually partition with DiskDruid**. The disk partition should be set up as follows:
 - The **Mount Point/RAID Volume** size for the **/boot** partition should be 100 MB.
 - The **Swap** partition should be set to twice the size of the RAM on your machine.
 - The **Root** partition (/) should be set with the remaining disk space size.




- **Network Configuration>Network Devices>Hostname** should be configured manually with the hostname *[mailhost.example.com]* of the Zimbra server.



- Enter the **Gateway** and **Primary DNS** addresses.
- In the **Edit Interface** pop-up screen, check **Activate on Boot**. Enter the **IP Address** and **Netmask** of the device. This allows the interface to start when you boot.



- **Firewall Configuration** should be set to **No firewall**, and the **Security Enhanced Linux (SELinux)** should be disabled.



Important: The following should also be considered before you install the Zimbra Collaboration Suite.


- You must disable Sendmail in order to run the Zimbra Collaboration Suite. Disable the Sendmail service with this command, **chkconfig sendmail off**.
- Make sure that FQDN entry in **/etc/hosts** appear before the hostnames. If this is missing, the creation of the Zimbra certificate fails. The FQDN entry should look like this example.

127.0.0.1	localhost.localdomain localhost
your.ip.address	FQDN yourhostname


Installation Modifications for Fedora

The Zimbra Collaboration Suite runs on the Fedora, Core 3 operating system. When you install the Fedora software for the Zimbra Collaboration Suite, accept the default setup answers, except for the following steps. Refer to the Fedora installation guide for detailed documentation about installing their software.


- **Disk Partitioning Setup.** Check **Manually partition with DiskDruid**. The disk partition should be set up as follows:
 - The **Mount Point/RAID Volume** size for the **/boot** partition should be 100 MB.
 - The **Swap** partition should be set to twice the size of the RAM on your machine.
 - The **Root** partition (**/**) should be set with the remaining disk space size.



- **Network Configuration>Network Devices>Hostname** should be configured manually with the hostname name [*mailhost.example.com*] of the Zimbra server.



- Enter the **Gateway** and **Primary DNS** addresses.
- In the **Edit Interface** pop-up screen, check **Activate on Boot**. Enter the **IP Address** and **Netmask** of the device. This allows the interface to start when you boot.
- **Firewall Configuration** should be set to **No firewall**, and the **Security Enhanced Linux (SELinux)** should be disabled.



Important: The following should also be considered before you install the Zimbra Collaboration Suite.

- You must disable Sendmail in order to run the Zimbra Collaboration Suite application. The Sendmail command to stop the service is `/etc/init.d/sendmail stop`, to disable, is `chkconfig sendmail off`. The Postfix command to stop the service is `/etc/init.d/postfix stop`, to disable, is `chkconfig postfix stop`.
- Make sure that FQDN entry in `/etc/hosts` appear before the hostnames. If this is missing, the creation of the Zimbra certificate fails. The FQDN entry should look like this example.

127.0.0.1	localhost.localdomain localhost
your.ip.address	FQDN yourhostname

Chapter 2 Zimbra Installation Overview

Zimbra architecture includes open-source integrations using industry standard protocols. The third-party software has been tested and configured to work with the Zimbra software. The following describes the Zimbra packages that are installed.

- **Zimbra Core.** This package includes the libraries, utilities, monitoring tools, and basic configuration files. Zimbra Core is automatically installed on each server.
- **Zimbra LDAP.** User authentication is provided through OpenLDAP® software. Each account on the Zimbra server has a unique mailbox ID that is the primary point of reference to identify the account. The OpenLDAP schema has been customized for the Zimbra Collaboration Suite. The Zimbra LDAP server must be configured before the other servers.
- **Zimbra MTA.** Postfix is the open source mail transfer agent (MTA) that receives email via SMTP and routes each message to the appropriate Zimbra mailbox server using Local Mail Transfer Protocol (LMTP). The Zimbra MTA also includes the anti-virus and anti-spam components.
- **Zimbra Store.** The Zimbra store includes the components for the mailbox server, including Apache Tomcat, which is the servlet container the Zimbra software runs within. The Zimbra mailbox server includes the following components:
 - **Data store.** The data store is a MySQL® database.
 - **Message store.** The message store is where all email messages and file attachments reside.
 - **Index store.** Index and search technology is provided through Lucene. Index files are maintained for each mailbox.
- **Zimbra SNMP.** Installing the Zimbra SNMP package is optional. If you choose to install Zimbra-SNMP for monitoring, this package should be installed on every Zimbra server.
- **Zimbra Logger.** Installing the Zimbra Logger package is optional and is installed on one mailbox server. The Zimbra logger installs tools for syslog aggregation, reporting, and message tracing. If you do not install Logger, you cannot use the message trace feature. In addition, the server statistics are not captured, and the server statistics section of the administration console will not display.

- **Zimbra Spell.** Installing the Zimbra Spell package is optional. Aspell is the open source spell checker used on the Zimbra Web Client. When Zimbra-spell is installed, the Zimbra-apache package is also installed.

The Zimbra server configuration is menu driven. The installation menu displays the default configuration values. The menu displays the logical host name and email domain name [example.com] as configured for the computer.

Configuration Examples

Zimbra Collaboration Suite can be easily scaled for any size of email environment, from very small businesses with fewer than 25 email accounts to large businesses with thousands of email accounts. The following table shows examples of different configuration options.

Table 1 Zimbra Collaboration Suite Configuration Options

Small	Medium	Large	Very Large
<p>All ZCS components installed on one server.</p> <p>See the Zimbra Installation Quick Start for installation instructions.</p>	<ul style="list-style-type: none"> • Zimbra LDAP and Zimbra message store on one server • Zimbra MTA on a separate server. • Possibly include additional Zimbra MTA servers configured 	<ul style="list-style-type: none"> • Zimbra LDAP on one server • Multiple Zimbra mailbox servers • Multiple Zimbra MTA servers 	<ul style="list-style-type: none"> • Zimbra LDAP server as master • LDAP replicas • Multiple Zimbra mailbox servers • Multiple Zimbra MTA servers

Downloading the Zimbra Software

For the latest Zimbra software download, go to [www. Zimbra.com](http://www.Zimbra.com). The download file is a standard compressed tar file. Save the Zimbra Collaboration Suite archive file to the computer from which you will install the software.

When the Zimbra Collaboration Suite is installed, the following Zimbra applications are saved to the Zimbra server:

- **Zimbra Collaboration Suite Migration Wizard for Exchange** .exe file to migrate Microsoft® Exchange server email accounts to the Zimbra server.
- **Zimbra Collaboration Suite Import Wizard for Outlook** .exe file to allow users to import their Outlook .pst files to the Zimbra server.
- ZCS documents, including administrator's guide, installation guides, Migration Wizard guide, and release notes.

See the Administrator's Guide for information about the PST Import Wizard.
See the Migration Wizard Guide for information about the Migration Wizard file.

Basic Menu Configuration

The menu driven installation displays the components and their existing default values. During the installation process you can modify the default values. Only those menu options associated with the package being installed are displayed.

The table below describes the Main menu options

Table 2 Main Menu Options

Server Configured	Main Menu	Description
All	Hostname	The host name configured in the operating system installation
All	LDAP master host	The LDAP host name. This LDAP host name is configured on every server.
All	LDAP port	The default port is 389.
All	LDAP password	The root LDAP password for the host. This LDAP password is configured on every server.

Table 2 Main Menu Options

Server Configured	Main Menu	Description
Zimbra LDAP Server	zimbra-ldap	<p>Configuration includes the following:</p> <ul style="list-style-type: none"> You can create one domain during installation. Additional domains can be created from the administration console. Define the domain name. The default domain is the fully qualified hostname of the server. If you created a valid mail domain on your DNS server, enter it when installing the ldap server. The administrator account is created during installation, and allows you to log on to the administration console. The default is typed as admin@example.com. You must set the admin account password. The password is case sensitive and must be a minimum of six characters. The administrator name, mail address, and password are required to log on to the administration console. By default, the automated spam training filter is enabled and two mail accounts are created. <p><i>Spam Training User</i> to receive mail notification about mail that was not marked as junk, but should be.</p> <p><i>Non-spam (HAM) training user</i> to receive mail notification about mail that was marked as junk, but should not have been.</p> <p>These addresses are automatically configured to work with the spam training filter.</p>

Table 2 Main Menu Options

Server Configured	Main Menu	Description
Zimbra Mailbox Server	zimbra-store	<p>Configuration includes the following. The defaults are shown.</p> <ul style="list-style-type: none"> • SMTP host • Web server mode http. • IMAP server port: 143 • IMAP server SSL port: 993 • POP server port: 110 • POP server SSL port: 995 • Use spell checker server: yes (if installed) • Spell server URL: http://<example.com>:7780/aspell.php <p>About Web server mode. The communication protocol options are HTTP, HTTPS, or mixed. Mixed mode uses HTTPS for logging in and HTTP for normal session traffic. All modes use SSL encryption for back-end administrative traffic.</p>
Zimbra MTA Server	zimbra-mta	<p>The following options can be modified.</p> <ul style="list-style-type: none"> • MTA Auth host. This is configured automatically if the MTA authentication server host is on the same server, but must be configured if the authentication server is not on the MTA. • Enable Spamassassin. Default is enabled. • Enable ClamAV. Default is enabled. • Identify the notification address for AV alerts. The default address that is displayed should be changed. Use the admin address configured in the LDAP server, or create a new address. If you create a new address, remember to provision this address from the admin console.

Table 2 Main Menu Options

Server Configured	Main Menu	Description
All servers, if installed	zimbra-snmpp Installing SNMP is optional, but installed it must be on all servers.	<p>You can modify the following options</p> <ul style="list-style-type: none"> • Enable SNMP notification. The default is No. If you enter yes, you must type the SNMP Trap hostname. • Enable SMTP notification. The default is No. If you enter yes, you must type the SMTP source email address and destination email address.
Installed on one mailbox server	zimbra-logger	If installed, it is automatically enabled. Logs from all the hosts are sent to the mailbox server where the logger package is installed. This data is used to generate the statistics graphs and is used for message tracing.
	zimbra-spell	If installed, it is automatically enabled. When composing messages in the Zimbra Web Client, spell check can be run.
	r) Start servers after configuration	When the installation and configuration is complete, if this is set to Yes, the Zimbra server is automatically started.
	s) Save config to file	At any time during the installation, you can save the configuration to a file.
	q) Quit	Quit can be used at any time to quit the installation.

Chapter 3 Multiple-Server Installation

The installation is straight-forward and easy to run. You run the same install script on each server, select which component(s) to install, and use the menu to configure the system. When the server installation is complete, the servers are started, and the status is displayed.

Important: *The Zimbra-LDAP server must be installed and configured first.*

Step 1 through step 4 are performed for each server to be installed.

Starting the installation process

1. Log in as **root** to the Zimbra server and **cd** to the directory where the Zimbra Collaboration Suite archive file is saved (**cd /var/<tmp>/var**). Type the following commands.
 - **tar xzvf [zcs.tgz]** to unpack the file
 - **cd zcs** to change to the correct directory
 - **./install.sh** to begin the installation

Note: *As the installation proceeds, press **Enter** to accept the defaults that are shown in brackets [] or enter the appropriate answer for your configuration.*

The screen shots are examples of the Zimbra installation script.

```
[root@mailhost tmp]# tar xzvf zcs.tgz
zcs/
zcs/install.sh
zcs/packages/
zcs/packages/zimbra-ldap-3.0.M2_316.RHEL4-20051007080249.i386.rpm
zcs/packages/zimbra-logger-3.0.M2_316.RHEL4-20051007080249.i386.rpm
zcs/packages/zimbra-snmp-3.0.M2_316.RHEL4-20051007080249.i386.rpm
zcs/packages/zimbra-mta-3.0.M2_316.RHEL4-20051007080249.i386.rpm
zcs/packages/zimbra-core-3.0.M2_316.RHEL4-20051007080249.i386.rpm
zcs/packages/zimbra-store-3.0.M2_316.RHEL4-20051007080249.i386.rpm
zcs/README.txt
zcs/readme_binary.txt
zcs/docs/
zcs/docs/quick_start.pdf
zcs/docs/RNZCSN.pdf
zcs/docs/admin.pdf
.
.
.
[root@ tmp]# cd zcs
[root@ zcs]# ./install.sh

Operations logged to /tmp/install.log.9496
Checking for existing installation...
  zimbra-ldap...NOT FOUND
  zimbra-logger...NOT FOUND
  zimbra-mta...NOT FOUND
  zimbra-snmp...NOT FOUND
  zimbra-store...NOT FOUND
  zimbra-apache...NOT FOUND
  zimbra-spell...NOT FOUND
  zimbra-core...NOT FOUND
```

-
2. The installation process checks to see if Sendmail, Postfix, and MySQL software are running. If any application is running, you are asked to disable it. The default is **Yes** to disable the applications. Disabling MySQL is optional, but highly recommended. Sendmail and Postfix must be disabled for the Zimbra Collaboration Suite to start correctly.

```
Checking for sendmail/postfix

Checking for mysql
Sendmail appears to be running. Shut it down [Y]
```

-
-
3. The Zimbra software agreement is displayed and includes the link to the license terms for the Zimbra Collaboration Suite. Please read the agreement and to continue, press **Enter**.

```
PLEASE READ THIS AGREEMENT CAREFULLY BEFORE USING THE SOFTWARE.
ZIMBRA, INC. ("ZIMBRA") WILL ONLY LICENSE THIS SOFTWARE TO YOU IF YOU
FIRST ACCEPT THE TERMS OF THIS AGREEMENT. BY DOWNLOADING OR
INSTALLING THE SOFTWARE, OR USING THE PRODUCT, YOU ARE CONSENTING TO
BE BOUND BY THIS AGREEMENT. IF YOU DO NOT AGREE TO ALL OF THE TERMS
OF THIS AGREEMENT, THEN DO NOT DOWNLOAD, INSTALL OR USE THE PRODUCT.
```

```
License Terms for the Zimbra Collaboration Suite:
http://www.zimbra.com/license/index.html
```

```
Press Return to continue
```

4. Next, the installer checks to see that the prerequisite software is installed. If NPTL, sudo, libidn, cURL, fetchmail, GMP or compat-libstdc++ are not installed, the install process fails. You must fix the problem and start the installation over.

Installing Zimbra LDAP Server

You must configure the Zimbra-LDAP server before you can install the other Zimbra servers.

1. Follow steps 1 through 4 in **Starting the Installation Process** section to open a SSH session to the LDAP server, log on to the server as root, and unpack the Zimbra software.
2. The **zimbra-ldap** package should be marked **y**. The MTA, Store and Logger packages should be marked **n**. If you are using SNMP, SNMP package is marked **y**.

```
Select the packages to install
Install zimbra-ldap [Y]
Install zimbra-mta [Y]N
Install zimbra-snmp [Y]N
Install zimbra-store [Y]N
Install zimbra-logger [Y]N
Install zimbra-spell [Y]N

Installing:
  zimbra-core
  zimbra-ldap

This system will be modified. Continue [N] Y
Configuration section
```

3. Type **y**, and press **Enter** to modify the system. The selected packages are installed on the server.

The Main menu displays showing the default entries for the Zimbra component you are installing. To expand the menu to see the configuration values type **x** and press **Enter**. The main menu expands to display configuration details for the package being installed. Values that require further configuration are marked with asterisks (*).

To navigate the Main menu, select the menu item to change. You can modify any of the defaults. See [Table 2, "Main Menu Options," on page 15](#) for a description of the Main menu.

```

Main menu

  1) Hostname:                        ldap.example.com
  2) Ldap host:                       ldap.example.com
  3) Ldap port:                       389
  4) Ldap password:                   set
  5) zimbra-ldap:                     Enabled
    +Create Domain:                   yes
    +Domain to create:                 ldap.example.com
    +Create Admin User:                yes
    +Admin user to create:              admin@ldap.example.com
*****+Admin Password                 UNSET
    +Enable automated spam training:   yes
    +Spam training user:                ilb278@mailhost.example.com
    +Non-spam (Ham)training user:       qkgan4@mailhost.example.com

  r) Start servers after configuration  yes
  s) Save config to file
  x) Expand menu
  q) Quit

Address unconfigured (**) items  (? - help)

```

Items with an asterisks must be configured.

4. Type **4** to display the automatically generated LDAP password. You can change this password.

Remember the LDAP password, the LDAP host name, and the LDAP port. You must configure this information, when you install the MTA server and the mailbox servers.

5. Type **5** to change the zimbra-ldap settings.
 - Type **3** to change the default domain name to the email domain name.
 - Type **6** to set the password for the administrator account. The password is case sensitive and must be a minimum of six characters. The admin account is provisioned on the Zimbra server and allows you to log on to the administration console. The administrator name, mail address, and password are required to log in to the administration console.


```
Ldap configuration

1) Status: Enabled
2) Create Domain: yes
3) Domain to create: ldap.example.com
4) Create Admin User: yes
5) Admin user to create: admin@ldap.example.com
** 6) Admin Password UNSET
7) Enable automated spam training: yes
8) Spam training user: ilb278@mailhost.example.com
9) Non-spam (Ham)training user: qkgan4@mailhost.example.com

Select, or 'r' for previous menu [r] 3

Create Domain: [ldap.example.com] example.com

Ldap configuration

1) Status: Enabled
2) Create Domain: yes
3) Domain to create: example.com
4) Create Admin User: yes
5) Admin user to create: admin@example.com
** 6) Admin Password UNSET

Select, or 'r' for previous menu [r] 6

Password for admin@example.com (min 6 characters): [Rv0sX7IJ] admin1
```

6. When the LDAP server is configured, type **a** to apply the configuration changes. Press **Enter** to save the configuration data.
7. When **Save Configuration data to a file** appears, press **Enter**.
8. When **The system will be modified - continue?** appears, type **y** and press **Enter**.

The server is modified. Installing all the components and configuring the server can take a few minutes.

9. When **Installation complete - press return to exit** displays, press **Enter**.

The installation of the LDAP server is complete.

```
Select, or press 'a' to apply config (? - help) a
Save configuration data? [Yes]
Save config in file: [/opt/zimbra/config.2843]
Saving config in /opt/zimbra/config.2843...Done
The system will be modified - continue? [No] y
Operations logged to /tmp/zmsetup.log.2843
Setting local config zimbra_server_hostname to [ldap.example.com]
.
Operations logged to /tmp/zmsetup.log.2843

Installation complete - press return to exit
```

Installing Zimbra MTA on a Server

When the Zimbra MTA is being installed the root LDAP password and the Zimbra LDAP password must be known to the MTA server. If not, the MTA cannot contact the LDAP server and will not be able to complete the installation.

1. Follow steps 1 through 4 in **Starting the Installation Process** section to open a SSH session to the MTA server, log on to the server as root, and unpack the Zimbra software.
2. Enter **y** to install the **zimbra-mta** package. The other packages should be marked **n**. Note: If you installed the SNMP package on the LDAP server, install it here also.
3. Press **Enter** to modify the system. The selected packages are installed on the server.

At this point the Main menu displays the default entries for the Zimbra component you are installing. To expand the menu to see all the configuration values type **X** and press **Enter**.

To navigate the Main menu, select the menu item to change. You can modify any of the defaults.

```

Main menu

  1) Hostname:                               mta.example.com
** 2) Ldap host:                             UNSET
  3) Ldap port:                             389
** 4) Ldap password:                         UNSET
  5) zimbra-mta:                             Enabled
***** +MTA Auth host:                       UNSET
        +Enable Spamassassin:                yes
        +Enable Clam AV:                     yes
        +Notification address for AV alerts:  admin@example.com
r) Start servers after configuration          yes
s) Save config to file
x) Expand menu
q) Quit

Address unconfigured (**) items or correct ldap configuration (? -
help) 2

Please enter the ldap server hostname ldap.company.com
Checking ldap on ldap.company.com:389...FAILED

```

4. The Main menu displays. The Hostname is displayed. You must set the LDAP host and password configured on the LDAP server.
 - Type **2** and then type the LDAP host name.
 - Type **4** and then type the LDAP password.

The server immediately contacts the LDAP server. If it cannot contact the server, you cannot proceed.

5. Type **5** and then type **2** to set the **MTA Auth host**. This is the MTA authentication server host name.

You can change **5**, **AV alerts notification address**. The administrator's address is configured by default.

Note: *If you enter a new address, you will need to configure this address on the administration console.*

```
Select, or press 'a' to apply config (? - help) 5

Mta configuration

  1) Status:                               Enabled
**2) MTA Auth host:                        UNSET
  3) Enable Spamassassin:                  yes
  4) Enable Clam AV:                       yes
  5) Notification address for AV alerts:    admin@mta.example.com
```

6. When the MTA server is configured, type **a** to apply the configuration changes. Press **Enter** to save the configuration data.
7. When **Save Configuration data to a file** appears, press **Enter**.
8. When **The system will be modified - continue?** appears, type **y** and press **Enter**.

The server is modified. Installing all the components and configuring the server can take a few minutes.

9. When **Installation complete - press return to exit** displays, press **Enter**.

The installation of the MTA server is complete.

Installing Zimbra Mailbox Server

The Zimbra-store can be installed with the LDAP server, the MTA server, or as a separate mailbox server. You can have more than one mailbox server and new servers can be added at any time.

Note: *The Zimbra logger is installed on only one Zimbra mailbox server.*

1. Follow steps 1 through 4 in **Starting the Installation Process** section to log on to the server as root and unpack the Zimbra software.
2. Type **y** to install the **zimbra-store**, **zimbra-logger** (optional and only on one mailbox server), and **zimbra-spell** (optional) packages. When zimbra-spell is installed the zimbra-apache package is also installed.

```
Installing:
  zimbra-core
  zimbra-store
  zimbra-logger
  zimbra-apache
  zimbra-spell
```

3. Press **Enter** to modify the system. The selected packages are installed on the server.

At this point the Main menu displays the default entries for the Zimbra component you are installing. To expand the menu to see the configuration values type **x** and press **Enter**.

To navigate the Main menu, select the menu item to change. You can modify any of the defaults.

```
Main menu

  1) Hostname:                               mailbox.example.com
** 2) Ldap host:                             UNSET
  3) Ldap port:                              389
** 4) Ldap password:                         UNSET
  5) zimbra-store:                           Enabled
***** +SMTP host:                           UNSET
        +Web server mode:                     http
        +Use spell check server:              yes
        +IMAP server port:                    143
        +IMAP server SSL port:                993
        +POP server port:                     110
        +POP server SSL port:                 995
        +Use spell check server:              yes
        +Spell server URL:                    http://example.com:
7780/aspell.php
  6) zimbra-logger                           Enabled
  6) zimbra-spell                             Enabled
  r) Start servers after configuration         yes
  s) Save config to file
  x) Expand menu
  q) Quit

Address unconfigured (**) items or correct ldap configuration (? -
help) x

Checking ldap on :389...FAILED
```

4. The Hostname is displayed. You must set the LDAP host and password configured on the LDAP server.

- Type **2** and then type the LDAP host name.
- Type **4** and then type the LDAP password.

The server immediately contacts the LDAP server. If it cannot contact the server, you cannot proceed.

5. Type **5** to configure the SMTP host and set the web server mode, if it is not http.
 - Type **2**, and then type the Zimbra MTA host name.
 - Type **3**, if you are changing the default. The communication protocol options are HTTP, HTTPS, or mixed. Mixed mode uses HTTPS for logging in and HTTP for normal session traffic. All modes use SSL encryption for back-end administrative traffic
 - The default IMAP and POP server ports are listed. You can change these.

```

Address unconfigured (**) items (? - help) 5

Store configuration

  1) Status:                               Enabled
** 2) SMTP host:                           UNSET
  3) Web server mode:                       http
  4) IMAP server port:                      143
  5) IMAP server SSL port:                  993
  6) POP server port:                      110
  7) POP server SSL port:                   995
  8) Use spell check server:                yes
  9) Spell server URL:                      http://example.com:7780
aspell.php

Select, or 'r' for previous menu [r] 2

Please enter the SMTP server hostname mta.example.com

Store configuration

  1) Status:                               Enabled
  2) SMTP host:                           mta.example.com
  3) Web server mode:                       http
  4) IMAP server port:                      143
  5) IMAP server SSL port:                  993
  6) POP server port:                      110
  7) POP server SSL port:                   995
  8) Use spell check server:                yes
  9) Spell server URL:                      http://example.com:7780
aspell.php

Select, or 'r' for previous menu [r] 3

Please enter the web server mode (http,https,mixed) [http] https

Select, or 'r' for previous menu [r]

```

6. When the mailbox server is configured, type **a** to apply the configuration changes. Press **Enter** to save the configuration data.
7. When **Save Configuration data to a file** appears, press **Enter**.

8. When **The system will be modified - continue?** appears, type **y** and press **Enter**.

The server is modified. Installing all the components and configuring the server can take a few minutes.

9. When **Installation complete - press return to exit** displays, press **Enter**.

The installation of the mailbox server is complete.

```
Select, or press 'a' to apply config (? - help) a
Save configuration data? [Yes]
Save config in file: [/opt/zimbra/config.2843]
Saving config in /opt/zimbra/config.2843...Done
The system will be modified - continue? [No] y
Operations logged to /tmp/zmsetup.log.2843
Setting local config zimbra_server_hostname to [mailhost.example.com]
.
Operations logged to /tmp/zmsetup.log.2843

Installation complete - press return to exit
```

Installing the Zimbra-SNMP package

Installing the Zimbra-SNMP package is optional, but if you use SNMP monitoring, this package should be installed on each Zimbra server.

In the Main menu select the zimbra-snm to make changes to the default values.

The following questions are asked for SNMP configuration.

- Configure whether to be notified by SNMP or SMTP. The default is **No**. If you enter yes, you must enter additional information.
 - For SNMP type the SNMP Trap host name.
 - For SMTP type the SMTP source email address and destination email address.

```
8) zimbra-snm:                               Enabled
+Enable SNMP notifications:                   yes
+SNMP Trap hostname:                           mailhost.example.com
+Enable SMTP notifications:                   yes
+SMTP Source email address:                   admin@example.com
+SMTP Destination email address:              admin@example.com
```

Verifying Server Configuration

When **Configuration complete - press return to exit** is displayed, the installation is finished and the server has been started. Before going to the next server, you should verify that the server is running.

Use the CLI command, **zmcontrol status**, to verify that each server is running.

1. For each server in the Zimbra Collaboration Suite environment, log on as a Zimbra administrator, from the root.
2. Type **su - zimbra**.
3. Type **zmcontrol status**. The services status information is displayed. The server status is displayed.

Post Installation Tasks

Once the Zimbra Collaboration Suite is installed, you can log on to the administration console and configure additional domains, create Classes of Service, and provision accounts. See the Zimbra Administrator's Guide.

Logging on to the Administration Console

To log on to the administration console, open your browser, type the administration console URL and log on to the console. The administration console URL is entered as

`https://[example.com]:7071/zimbraAdmin`.

Note: *The administration console address must be typed with "https", even if you configured only "http".*

The first time you log on, a certificate authority (CA) alert may be displayed. Click **Accept this certificate permanently** to accept the certificate and be able connect to the Zimbra administration console. Then click **OK**.

Enter the admin user name and password configured during the installation process. Enter the user name as **admin@[example.com]**

Defining Classes of Service

A default Class of Service (COS) is automatically created during the installation of Zimbra software. The COS controls mailbox quotas, message lifetime, password restrictions, attachment blocking and server pools. You can modify the default COS and create new COSs to assign to accounts according to your group management policies.

In an environment with multiple mailbox servers the COS is used to assign the new accounts to a mailbox server. The COS server pool tab lists the mailbox servers in your Zimbra environment. When you configure the COS, select which servers to add to the server pool. Within each pool of servers, a random algorithm assigns new mailboxes to any available server.

To create or modify a COS, from the administration console, click COS. If you have questions, refer to the Help.

Provisioning Accounts

From the administration console, you can quickly create accounts using the New Account Wizard that steps you through the account information to be completed.

To provision accounts:

1. From the admin console navigation pane, click **Accounts**.
2. Click **New**, page 1 of the **New Account Wizard** opens.
3. Enter the account name to be used as the email address. The only required information is the account name and last name.
4. You can click **Finish** at this point, and the account will be configured with the default COS and global features.

If you want to configure aliases, forwarding addresses, and specific features for this account, proceed through the dialog.

Accounts are now ready to send and receive mail.

Refer to the administration guide to learn more about provisioning accounts, including how to provision multiple accounts at once.