北京理工大学
BEIJING INSTITUTE OF TECHNOLOGY

学德以精工明以理

A brief English demo

BIT Beamer Theme

BIT Beamer Theme

School of Management and Economics
Beijing Institute of Technology
⟨lr.wu.interact@outlook.com⟩

June 28, 2026

Outline

1. Introduction
   - The Project
2. Blocks
3. Acknowledgement

Info.

lr.wu.interact@outlook.com
https://github.com/FvNCCR228/bit_beamer_theme

- A compact English demo for BIT Beamer Theme.
- Built with XeLaTeX and the Beamer theme system.
- Derived from SCU Beamer Theme with BIT visual identity.

Outline

Math Blocks I

Theorem 2.1: A Theorem

$$\frac{1}{n}\sum_{k=1}^{n} X_k - \frac{1}{n}\sum_{k=1}^{n} E(X_k) \xrightarrow{P} 0 \tag{1}$$

Proof.

A proof block. □

Example 2.1: An Example

An example block.

Math Blocks II

Algorithm 2.1: An Algorithm

Require: LaTeX
Ensure: Computer
1: ST
2: A
3: TE
4: **return** Beamer

Definition 2.1: A Definition

A definition block.

Axiom 2.1: An Axiom

An axiom block. Reference to Definition 2.1

Math Blocks III

Property 2.1: A Property

A property block. Reference to Axiom 2.1

Proposition 2.1: A Proposition

A proposition block. Reference to property 2.1

$$\Delta x \Delta p \geq \frac{h}{4\pi} \tag{2}$$

where h is Planck's constant.

Lemma 2.1: A Lemma

A lemma block. Reference to proposition 2.1

Math Blocks IV

Corollary 2.1: A Corollary

A corollary block.

Remark

A remark block.

Condition 2.1: A Condition

A condition block.

Conclusion 2.1: A Conclusion

A conclusion block.

Math Blocks V

Assumption 2.1: An Assumption

An assumption block.

A Starred Block

Theorem: A Starred Theorem Block(after title: Theorem)

- One
- Two
- Three
- Four

Another Starred Theorem Block(after title: Theorem)

- Five
- Six
- Seven
- Eight

A Starred Block

Theorem: A Starred Theorem Block(after title: Theorem)

- One
- Two Two
- Three
- Four

Another Starred Theorem Block(after title: Theorem)

- Five
- Six
- Seven
- Eight

A Starred Block

Theorem: A Starred Theorem Block(after title: Theorem)

- One
- Two
- Three
- Four

Another Starred Theorem Block(after title: Theorem)

- Five
- Six Six
- Seven
- Eight

A Starred Block

Theorem: A Starred Theorem Block(after title: Theorem)

- One
- Two
- Three
- Four

Another Starred Theorem Block(after title: Theorem)

- Five
- Six
- Seven
- Eight

A Starred Block

Theorem: A Starred Theorem Block(after title: Theorem)

- One
- Two
- Three
- Four

Another Starred Theorem Block(after title: Theorem)

- Five
- Six
- Seven
- Eight

Outline

Source Code Block | With frame option “fragile”

Source Code 2.1: A Cpp Program.

```cpp
#include <iostream>
int main()
{
  std::cout << "Hello World!" << std::endl;
  std::cin.get();
}
```

Source Code 2.2: A Python Program.

```python
for i in range(1,5):
 for j in range(1,5):
  for k in range(1,5):
   if( i != k ) and (i != j) and (j != k):
    print (i,j,k)
```

Source Code Block | With frame option “fragile”

Source Code 2.1: A Cpp Program.

```
#include <iostream>
int main()
{
  std::cout << "Hello␣World!" << std::endl;
  std::cin.get();
}
```

Source Code 2.2: A Python Program.

```
for i in range(1,5):
  for j in range(1,5):
    for k in range(1,5):
      if( i != k ) and (i != j) and (j != k):
        print (i,j,k)
```

A Starred Source Code Block

Source Code: A Starred Block.

```cpp
#include <iostream>
int main()
{
  std::cout << "Hello␣World!" << std::endl;
  std::cin.get();
}
```

Another Starred Theorem Block.

```python
for i in range(1,5):
 for j in range(1,5):
  for k in range(1,5):
   if( i != k ) and (i != j) and (j != k):
    print (i,j,k)
```

Line Emphasis

Source Code 2.4: Emphasized C++ lines.

```cpp
#include <iostream>
int main()
{
  std::cout << "Hello␣World!" << std::endl;
  std::cin.get();
}
```

Source Code 2.5: Emphasized Python lines.

```python
for i in range(1,5):
 for j in range(1,5):
  for k in range(1,5):
   if( i != k ) and (i != j) and (j != k):
    print(i,j,k)
```

References to source code 2.4 and source code 2.5.

LaTeX Comment | Escapeinline

Use native comments for ordinary notes; use escape delimiters only for inline LaTeX.

Source Code 2.6: Comment.

```
#include <iostream>
int main()
{// $\pi$
  std::cout << "Hello␣World!" << std::endl; # LaTeX out hEllo wOrld
  $\sum_{\pi}^{\phi} \alpha + \Gamma$ std::cin.get();
}
```

Source Code 2.7: Comment

```
for i in range(1,5):
  for j in range(1,5): $\sum_{\pi}^{\phi} \alpha + \Gamma$
    for k in range(1,5): # $\sum_{\pi}^{\phi} \alpha + \Gamma$
      if( i != k ) and (i != j) and (j != k):
        print (i,j,k)
```

Overlay & Label | Escapeinline

Source Code 2.8: Comment.

```
#include <iostream>
int main()
{
  std::cout << "Hello␣World!" << std::endl; // Value 1
  std::cin.get();
}
```

Source Code 2.9: Comment

```
1 for i in range(1,5):
2   for j in range(1,5):
3     for k in range(1,5):
4       if( i != k ) and (i != j) and (j != k):
5         print (i,j,k)
```

Reference to Line 4, the if statement.

Overlay & Label | Escapeinline

Source Code 2.8: Comment.

```
#include <iostream>
int main()
{
  std::cout << "Hello␣World!" << std::endl; // Value 2
  std::cin.get();
}
```

Source Code 2.9: Comment

```
1 for i in range(1,5):
2   for j in range(1,5):
3     for k in range(1,5):
4       if( i != k ) and (i != j) and (j != k):
5         print (i,j,k)
```

Reference to Line 4, the if statement.

Source Code From File

Source Code 2.10: Source Code From File

以下是文件 A cpp.cpp 中包含的源码:

```cpp
#include <iostream>

void Log(const char* message);

int main()
{
  Log("Hello World!");
  std::cin.get();
}
```

Outline

Acknowledgement

BIT Beamer Theme is derived from SCU Beamer Theme, and this sample keeps `SCU-Version` as source-lineage attribution.

Thanks to the authors and maintainers of Beamer, Tcolorbox, BibLaTeX, FontAwesome, and related packages.

Thanks to the community discussions that helped shape the original template behavior.

Thanks!