



北京理工大学
BEIJING INSTITUTE OF TECHNOLOGY

A brief example in English

For BIT Beamer Theme

LR Wu

School of Management and Economics
Beijing Institute of Technology
<lr.wu.interact@outlook.com>

June 28, 2026



Outline

1 Introduction

■ The Project

2 Blocks

Info.



lr.wu.interact@outlook.com



https://github.com/FvNCCR228/bit_beamer_theme

Outline

1 Introduction

2 Blocks

- Math Blocks
- Source Code Block

Math Blocks I

Theorem 2.1: A Theorem

$$\frac{1}{n} \sum_{k=1}^n X_k - \frac{1}{n} \sum_{k=1}^n E(X_k) \xrightarrow{P} 0 \quad (1)$$

Proof.

A proof block. □

Example 2.1: An Example

An example block.

Math Blocks II

Algorithm 2.1: An Algorithm

Require: $\text{\LaTeX}$

Ensure: Computer

- 1: ST
- 2: A
- 3: TE
- 4: **return** Beamer

Definition 2.1: A Definition

A definition block.

Axiom 2.1: An Axiom

An axiom block. Reference to Definition 2.1

Math Blocks III

Property 2.1: A Property

A property block. Reference to Axiom 2.1

Proposition 2.1: A Proposition

A proposition block. Reference to property 2.1

$$\Delta x \Delta p \geq \frac{h}{4\pi} \quad (2)$$

其中 h 为普朗克常数.

Lemma 2.1: A lemma

A lemma block. Reference to proposition 2.1

Math Blocks IV

Corollary 2.1: A Corollary

A corollary block.

Remark

A remark block.

Condition 2.1: A Condition

A condition block.

Conclusion 2.1: A Conclusion

A conclusion block.

Math Blocks V

Assumption 2.1: An Assumption

An assumption block.

A Stared Block

Theorem: A Stared Theorem Block(after title: Theorem)

- One
- Two
- Three
- Four

Another Stared Theorem Block(after title: Theorem)

- Five
- Six
- Seven
- Eight

A Stared Block

Theorem: A Stared Theorem Block(after title: Theorem)

- One
- Two Two
- Three
- Four

Another Stared Theorem Block(after title: Theorem)

- Five
- Six
- Seven
- Eight

A Stared Block

Theorem: A Stared Theorem Block(after title: Theorem)

- One
- Two
- Three
- Four

Another Stared Theorem Block(after title: Theorem)

- Five
- Six Six
- Seven
- Eight

A Stared Block

Theorem: A Stared Theorem Block(after title: Theorem)

- One
- Two
- Three
- Four

Another Stared Theorem Block(after title: Theorem)

- Five
- Six
- Seven
- Eight

A Stared Block

Theorem: A Stared Theorem Block(after title: Theorem)

- One
- Two
- Three
- Four

Another Stared Theorem Block(after title: Theorem)

- Five
- Six
- Seven
- Eight

Outline

1 Introduction

2 Blocks

- Math Blocks
- Source Code Block

Source Code Block | With frame option “fragile”

Source Code 2.1: A Cpp Program.



```
1  #include <iostream>
2  int main()
3  {
4      std::cout << "Hello_World!" << std::endl;
5      std::cin.get();
6  }
```

Source Code 2.2: A Python Program.



```
1  for i in range(1,5):
2      for j in range(1,5):
3          for k in range(1,5):
4              if( i != k ) and ( i != j ) and ( j != k):
5                  print (i,j,k)
```

Source Code Block | With frame option "fragile"

Source Code 2.1: A Cpp Program.



```
1  #include <iostream>
2  int main()
3  {
4      std::cout << "Hello_World!" << std::endl;
5      std::cin.get();
6  }
```

Source Code 2.2: A Python Program.



```
1  for i in range(1,5):
2      for j in range(1,5):
3          for k in range(1,5):
4              if( i != k ) and ( i != j ) and ( j != k):
5                  print (i,j,k)
```

A Stared Source Code Block

Source Code: A Stared Block.



```
1  #include <iostream>
2  int main()
3  {
4      std::cout << "Hello_World! " << std::endl;
5      std::cin.get();
6  }
```

Another Stared Theorem Block.



```
1  for i in range(1,5):
2      for j in range(1,5):
3          for k in range(1,5):
4              if( i != k ) and ( i != j ) and ( j != k ):
5                  print (i,j,k)
```

Highlight Line

Source Code 2.4: Highlight Line.



```
1  #include <iostream>
2  int main()
3  {
4      std::cout << "Hello_World! " << std::endl;
5      std::cin.get();
6  }
```

Source Code 2.5: Highlight Line.



```
1  for i in range(1,5):
2      for j in range(1,5):
3          for k in range(1,5):
4              if( i != k ) and ( i != j ) and ( j != k ):
5                  print (i,j,k)
```

refer source codes 2.4 and 2.5

L^AT_EX Comment | Escape inline

If you wanna add comments to the back of the line, it is recommended to use the corresponding language comment directly.

Source Code 2.6: Comment.



```

1  #include <iostream>
2  int main()
3  { //  $\pi$ 
4    std::cout << "Hello World! " << std::endl; # LATEX out hEllo wOrld
5     $\sum_{\pi}^{\phi} \alpha + \Gamma$  std::cin.get();
6  }
```

Source Code 2.7: Comment



```

1  for i in range(1,5):
2    for j in range(1,5):  $\sum_{\pi}^{\phi} \alpha + \Gamma$ 
3      for k in range(1,5): #  $\sum_{\pi}^{\phi} \alpha + \Gamma$ 
4        if( i != k ) and ( i != j ) and ( j != k ):
5          print (i,j,k)
```

Overlay & Label | Escapeinline

Source Code 2.8: Comment.



```
1  #include <iostream>
2  int main()
3  {
4      std::cout << "Hello_World! " << std::endl; // Value 1
5      std::cin.get();
6  }
```

Source Code 2.9: Comment



```
1  for i in range(1,5):
2      for j in range(1,5):
3          for k in range(1,5):
4              if( i != k ) and ( i != j ) and ( j != k ):
5                  print (i,j,k)
```

Reference to Line 4, the if statement.

Overlay & Label | Escapeinline

Source Code 2.8: Comment.



```
1  #include <iostream>
2  int main()
3  {
4      std::cout << "Hello_World! " << std::endl; // Value 2
5      std::cin.get();
6  }
```

Source Code 2.9: Comment



```
1  for i in range(1,5):
2      for j in range(1,5):
3          for k in range(1,5):
4              if( i != k ) and ( i != j ) and ( j != k ):
5                  print (i,j,k)
```

Reference to Line 4, the if statement.

Source Code From File

Source Code 2.10: Source Code From File



以下是文件 A cpp.cpp 中包含的源码:

```
1 #include <iostream>
2
3 void Log(const char* message);
4
5 int main()
6 {
7     Log("Hello_World!");
8     std::cin.get();
9 }
```

Thanks!