

CS323 SPL Compiler - Phase 1

GuTao
GuTaoZi@GitHub

Artanisax
Artanisax@GitHub

ShadowStorm
Jayfeather233@GitHub

1 Quick Start

1.1 Project Structure

```
Phase_1
├── Makefile
├── report
│   ├── Phase1.pdf
│   └── Requirements.pdf
├── src
│   ├── lex.l
│   ├── syntax.y
│   ├── treeNode.c
│   └── treeNode.h
├── test          // self-written testcases for basic features
├── test-ex       // self-written testcases for bonus features
├── test_ex.sh
├── test-others   // testcases by other students
├── test_others.sh
├── test_self.sh
├── test-std      // official testcases
└── test_std.sh
```

1.2 Environment

Tool	Version
C	C99
Bison	3.0.4+
Flex	2.6.4

1.3 How to Run

Under the root folder of this project, execute the following commands to generate the parser executable splc under ./bin folder:

- make splc: Generate the parser, and clean the intermediate files.(For Bison 3.0.4)
- make splcb: Generate the parser, and clean the intermediate files.(For Bison 3.8.2)
- make splcc: Generate the parser, reserve the intermediate files.(For Bison 3.8.2)
- make splcd: Generate the parser, print examples of shift-reduce conflicts.(For Bison 3.8.2)

Execute make clean to clean the ./src and ./bin folder.

For an SPL source file filename.spl, execute ./bin/splc filename.spl to write the output into filename.out; or execute ./bin/splc filename.spl result.out to write the output into the given file result.out.

2 Basic Features

2.1 Lexical Part

In the file `lex.l`, we detect valid and invalid tokens and build nodes of the parse tree for them, and invalid tokens are used for error recovery for subsequent syntax analysis.

In this section, we define a `has_error` variable to record whether or not an error occurred during compilation. `has_error` is initialized to 0 and is set to 1 after either a TYPE A or TYPE B error. The parser will output a parse tree after analysis if `has_error` is 0, otherwise it will report the errors.

2.2 Syntactical Part

In the file `syntax.y`, we formulate the matching rules used to analyze the syntax and use the node pointers of the parse tree as nonterminal values, so that a complete parse tree can be constructed by Bison's syntax analysis.

2.3 Parse Tree

`treeNode.c` and `treeNode.h` define the structure `treeNode` of the syntactic analysis tree, as well as a set of functions necessary to build the tree. Each tree node holds the following variables:

- `name`: the name of the node of the (non)terminal
- `val`: the content of the terminal
- `lineno`: the line number in the source file that corresponds to this (non)terminal
- `child`: head of the list of child nodes
- `nxt`: pointer to a sibling node

3 Bouns Features

For bouns features, we implemented for statements, include statements, single-line and multi-line comments, and the parser can match string with multiple lines.

3.1 for Statements

We add extra patterns to `Stmt` in `syntax.y`:

`Stmt :`

```
...
| FOR LP DeclList SEMI Exp SEMI Exp RP Stmt %prec UPPER_FOR
| FOR LP VarDec COLON Exp RP Stmt %prec LOWER_FOR
| FOR DeclList SEMI Exp SEMI Exp RP Stmt %prec UPPER_FOR
| FOR LP DeclList SEMI Exp SEMI Exp error Stmt %prec UPPER_FOR
| FOR VarDec COLON Exp RP Stmt %prec LOWER_FOR
| FOR LP VarDec COLON Exp error Stmt %prec LOWER_FOR
```

So the parser can recognize `for(;;)` and `for(:)` in C89 style.

3.2 File Inclusion

We modified the high-level specification:

```
Program : HeaderDefList ExtDefList
        ;
HeaderDefList :
    | Headers HeaderDefList
    ;
Headers : IncDef
```

```

;
IncDef : SHARP INCLUDE ABSTR
      | SHARP INCLUDE error
;

```

So the parser can recognize programs with/without file inclusions in format of `include <filename>`.

3.3 Comments

In `lex.l`, we designed regexps to match single-line comments or multi-line comments. The parser simply ignores the comments during syntax analysis.

The parser will output line numbers of comments before printing the parse tree or reporting errors, if any comment recognized.

```

"/".*$ {
    fprintf(yyout, "Single LINE COMMENT at Line %d\n", yylineno);
}
"/"*((("[^/])?)|([^*])"*"/" {
    fprintf(yyout, "MULTI LINE COMMENT at Line %d\n", yylineno);
}

```

3.4 String

We designed regexps in `lex.l` to match strings, supporting ESC and C-style multi-line strings.

The parser will consider them similar to other constant types and can be reduced into `Exp`.

```

VALID_STRING_LINE ([^\\\"\\n]*(\\.\\.))*[^\\\"\\n]*
STRING \"({VALID_STRING_LINE}\\{new_line\\})*{VALID_STRING_LINE}\"

```

4 Explanations for Test Cases

4.1 Basic tests

We designed 5 test cases for basic features under `./test` folder.

1. test_12111624_1.spl

This piece of code has no syntax error. Basic variable definitions and numerical calculations.

2. test_12111624_2.spl

This piece of code has no syntax error. Do nothing in `if` and `while`, with a useless semicolon.

3. test_12111624_3.spl

This piece of code contains 2 TYPE B errors: `else` without an `if`.

4. test_12111624_4.spl

This piece of code contains 3 TYPE B errors: unclosed `{}`, `[]`, `()`.

5. test_12111624_5.spl

This piece of code contains 3 TYPE A errors: `1test_r05`, `@`, `998244353.2147483647.19260817`.

4.2 Extra tests

We designed one correct case and one error case for each bonus feature under `./test-ex` folder, 8 test cases in total.

1. test_1.spl

Test for single-line and multi-line comments.

2. test_2.spl
Test for multi-line comments with only /*.
3. test_3.spl
Test for for(;;) and for(:).
4. test_4.spl
Test for missing closing curly bracket for(;;){
5. test_5.spl
Test for #include <FILENAME>.
6. test_6.spl
Test for #include error.
7. test_7.spl
Test for string and multiple-line-string.
8. test_8.spl
Test for string error due to wrong use of escape character.