

CS323 SPL Parser - Phase 3

陈康睿(A)

12110524

樊斯特(A)

12111624

肖佳辰(A)

12112012

1 Quick Start

1.1 Project Structure

12110524-12111624-12112012-phase3

```
├── bin
│   ├── optimizer
│   └── splc
├── include
│   ├── GAS_utility.h
│   ├── IRgen.h
│   ├── IRortho.h
│   ├── ortho.h
│   ├── treeNode.h
│   ├── type.h
│   ├── type_op.h
│   ├── uthash.h
│   └── utstack.h
├── Makefile
├── report
│   ├── 12110524-12111624-12112012-phase3.pdf
│   └── requirements.pdf
├── src
│   ├── GAS_utility.c
│   ├── IRgen.c
│   ├── IRortho.c
│   ├── lex.l
│   ├── optimizer.c
│   ├── ortho.c
│   ├── syntax.y
│   ├── treeNode.c
│   ├── type.c
│   └── type_op.c
├── test-ex
├── test_ex.sh
├── test-std
└── test_std.sh
```

1.2 Environment

Tool	Version
C	C99
Bison	3.0.4+
Flex	2.6.4

1.3 How to Run

Under the root folder of this project, execute the following commands to build the compiler executable `splc` under `./bin` folder (gcc by default):

- `make splc`: Build the compiler, and clean the intermediate files.(For Bison 3.0.4)
- `make splcb`: Build the compiler, and clean the intermediate files.(For Bison 3.8.2)
- `make splcc`: Build the compiler, reserve the intermediate files.(For Bison 3.8.2)
- `make splct`: Build the compiler using Tiny C Compiler (TCC).(For Bison 3.8.2)

Execute `make clean` to clean the `./src` and `./bin` folder.

For an SPL source file `filename.spl`, execute `./bin/splc filename.spl` to write the output into `filename.ir0`; or execute `./bin/splc filename.spl result.out` to write the output into the given file `result.out`.

The optimizer is compiled into a separated executable file `./bin/optimizer`. Executing `./bin/optimizer filename.ir0` will generate a optimized IR code file `filename.ir`.

The generated IR code can be executed in the IR simulator with command `irsim filename.ir -i [input]`.

2 Basic Features

2.1 TAC Generation

In Phase 3, our compiler translates SPL into an linear intermediate representation, three-address code that can be executed on the IR simulator.

During translation, the compiler translates the variables into abstract names as `v[num]`, splits compound operations into multiple instructions, and introduces temporary variables `t[num]` to hold the intermediate results. When reading or writing the arrays and members of a structure, the compiler calculates the offset relative to the pointer, and then accesses the value.

We maintain the intermediate representation in a tree structure. For each grammar specified in the previous phases, we implement a translate function `build_[tokenName]_IR_tree` in `IRgen.h` to create an intermediate representation node according to the give node from semantic tree. Each node of the IR tree maintains a `stmt` attribute and the connections to its children and sibling nodes.

Also, the variables and temporary values are maintained by an orthogonal linked list, supporting local scopes and shadowing definition using a same variable name. The function of the list here is a map from variable name to `v[name]`.

2.2 IR Optimizer

To improve the efficacy of raw IR codes, we developed an optimizer designed to optimize these codes. It will read generated IR codes and organize them into a list, then do operations on list add and delete. We operate optimization in the following steps:

- Eliminate redundant `GOTO` which just goto the next line.
- Directly assign constant values to variables which may need multi-statements to calculate.
- If two variables store the same value, we use only one to present those.
- Remove the variables that not using after.

3 Bouns Features

3.1 Structure as Parameter

The compiler accepts program containing functions with structure as parameters. Similar to array, the member of a structure is accessed using offset. We implement pass-by-reference feature for structure

parameters, meaning that modifying the structure inside a function will synchronously change the structure in the caller's scope.

3.2 Multi-Dimensional Array as Parameter

The compiler also accepts program containing functions with multi-dimensional arrays as parameters. The implementation is similar to the structure parameter. Therefore, structure with multi-dimensional arrays and another structure as members can also be a function parameter.

3.3 for, continue and break

This feature is implemented in the previous 2 phases so we continue to generate IR for these keywords. for is handled as loop, while break and continue is implemented by adding GOTO instructions.

4 Explanations for Extra Cases

1. test_12111624_1.spl

This program calculates the fibonacci series with matrix acceleration. The time complexity is $O(\log N)$ and the space complexity is $O(1)$.

This program contains bonus features like structure variables in parameters and multi-dimensional arrays as local variables.

Performance comparasion:

n	Recursive Fib	Iterative Fib	Matrix-Accelerated Fib	MA Fib with Optimization
10	1050	130	2808	
20	*	?	3213	
20000	*	*		

2. test_12111624_2.spl

This program is a DFS-based maze solver, outputing 1 if the maze is solvable otherwise 0. The recursive solver function accepts a structure with 2D array member as parameter.

3. test_12111624_3.spl

This program is a simple sample showing the feature of continue and break keywords.

4. test_12111624_4.spl

This program is an example of Gaussian elimination, containing a function with a 2D matrix as the parameter.

5. test_12111624_5.spl

This program is an example showing local scope shadowing. An inner array has the same name as the outer array, accessing inside/outside the block with the same name corresponds to accessing inner/outer array.