


Modelo físico de la base de datos

10 tablas · Todas las columnas · Tipos y llaves verificados contra PostgreSQL y schema.sql

player		
LLAVE	COLUMNA	TIPO
PK	player_id *	bigint
	full_name *	text
	first_name	text
	last_name	text
	is_active *	boolean



player_attribute		
LLAVE	COLUMNA	TIPO
PK/FK	player_id *	bigint
	birthdate	date
	school	text
	country	text
	height	varchar(10)
	weight	numeric(6,2)
	season_experience	smallint
	position	varchar(20)
	roster_status	text
	current_team_id	bigint
	current_team_name	text
	from_year	smallint
	to_year	smallint
	draft_year	smallint
	draft_round	smallint
	draft_number	smallint
	points	numeric(8,3)
	assists	numeric(8,3)
	rebounds	numeric(8,3)
	all_star_appearances	smallint
	pie	numeric(10,5)


team		
LLAVE	COLUMNA	TIPO
PK	team_id *	bigint
	full_name *	text
	abbreviation *	varchar(5)
	nickname	text
	city	text
	state	text
	year_founded	smallint

team_salary		
LLAVE	COLUMNA	TIPO
PK	team_name *	text
	team_slug	varchar(5)
	salary_2020_21	numeric(14,2)
	salary_2021_22	numeric(14,2)
	salary_2022_23	numeric(14,2)
	salary_2023_24	numeric(14,2)
	salary_2024_25	numeric(14,2)
	salary_2025_26	numeric(14,2)

game		
LLAVE	COLUMNA	TIPO
PK	game_id *	varchar(20)
	season_id	varchar(20)
	season_start_year	smallint
	game_date *	date
	home_team_id *	bigint
	home_team_name	text
	home_win_loss	char(1)
	home_points	smallint
	away_team_id *	bigint
	away_team_name	text
	away_win_loss	char(1)
	away_points	smallint
	attendance	integer



game_official		
LLAVE	COLUMNA	TIPO
PK/FK	game_id *	varchar(20)
PK/FK	official_id *	bigint



official		
LLAVE	COLUMNA	TIPO
PK	official_id *	bigint
	first_name	text
	last_name	text
	jersey_number	varchar(10)

draft_pick		
LLAVE	COLUMNA	TIPO
PK	draft_year *	smallint
PK	overall_pick *	smallint
	round_number	smallint
	round_pick	smallint
	player_id	bigint
PK	player_name *	text
	team_id	bigint
	team_name	text
	organization_from	text

player_salary		
LLAVE	COLUMNA	TIPO
PK	salary_id *	bigint
	season *	varchar(7)
	team_name *	text
	player_name *	text
	player_status	text
	is_final_season	boolean
	is_waived	boolean
	is_on_roster	boolean
	contract_detail *	text
	salary_value *	numeric(14,2)

player_season_stat		
LLAVE	COLUMNA	TIPO
PK	player_id *	bigint
PK	season *	varchar(7)
PK	team_id *	bigint
	player_name *	text
	team_abbreviation	varchar(5)
	games_played	smallint
	points	numeric(8,3)
	assists	numeric(8,3)
	rebounds	numeric(8,3)
	plus_minus	numeric(8,3)
	loaded_at *	timestamp

Relaciones lógicas y reglas del modelo

Estos enlaces describen el análisis; no son restricciones FOREIGN KEY de PostgreSQL.

PADRE / CATÁLOGO		TABLA QUE LO REFERENCIA	ENLACE PROPUESTO	CARDINALIDAD ESPERADA Y LÍMITE
team	-----	game	team_id = home_team_id	1 a 0..N como local; históricos sin catálogo
team	-----	game	team_id = away_team_id	1 a 0..N como visitante; sin FK
team	-----	player_attribute	team_id = current_team_id	1 a 0..N; equipo de la captura, no historial
team	-----	draft_pick	team_id = team_id	1 a 0..N; selecciones históricas
player	-----	draft_pick	player_id = player_id	1 a 0..N; no hay UNIQUE sobre player_id
team	-----	player_season_stat	team_id = team_id	1 a 0..N; varias temporadas y jugadores
player	-----	player_season_stat	player_id = player_id	1 a 0..N; el API puede agregar jugadores
team	-----	team_salary	lower(full_name) = lower(team_name)	0..1 nómina por equipo, si el nombre coincide
team	-----	player_salary	lower(full_name) = lower(team_name)	1 a 0..N; nombre sin FK
player	-----	player_salary	full_name ~ player_name (por resolver)	1 a 0..N esperado; no usar sin validar nombres

Cómo leer las cardinalidades

1 = exactamente uno; 0..1 = opcional y único; 0..N = cero o varios. En esta página son expectativas del modelo, no garantías del motor.

Un registro histórico puede no encontrar padre en los catálogos actuales. Los nombres y abreviaturas tampoco garantizan identidad.

Restricciones que sí existen

draft_pick: PK (draft_year, overall_pick, player_name). El nombre evita sobrescribir selecciones históricas con número 0.

game_oficial: PK (game_id, oficial_id). Borrar un partido elimina sus vínculos con árbitros (ON DELETE CASCADE).

player_season_stat: PK (player_id, season, team_id). Permite separar periodos de un jugador traspasado.

player_salary: salary_id es IDENTITY; UNIQUE (season, team_name, player_name, contract_detail, salary_value).

game: CHECK (home_team_id <> away_team_id). Las otras dos FK usan NO ACTION al borrar.

Vistas auxiliares: v_team_seasons, v_team_talent, v_investment_metrics y v_investment_ranking. No son tablas adicionales.

Fuente: database/schema.sql + catálogo de restricciones de nba_project. El ER.docx anterior queda como referencia histórica.