
Discrete Optimization

Local Search: Part IV


Goals of the Lecture

- Local search
 - optimization under constraints
 - -graph coloring


Coloring a Map




Coloring a Map



Coloring a Map



Graph Coloring



Graph Coloring

- Two aspects
 - optimization
 - reducing the number of colors
 - -feasibility:
 - two adjacent vertices must be colored differently

Graph Coloring

- Two aspects
 - optimization
 - reducing the number of colors
 - -feasibility:
 - two adjacent vertices must be colored differently
- ► How to combine them in local search?
 - -sequence of feasibility problems
 - -staying in the space of solutions
 - -considering feasible and infeasible configurations

Optimization as Feasibility

- Sequence of feasibility problems
 - find an initial solution with k colors
 - greedy algorithms
 - -remove one color, say k.
 - reassign randomly all vertices colored with k with a color in the range 1..k-1
 - find a feasible solution with k-1 colors
 - -repeat

Optimization as Feasibility

- Sequence of feasibility problems
 - find an initial solution with k colors
 - greedy algorithms
 - -remove one color, say k.
 - reassign randomly all vertices colored with k with a color in the range 1..k-1
 - find a feasible solution with k-1 colors
 - repeat
- ► How to find a solution with k-1 colors
 - we have seen that in the first two lectures
 - just minimize the violations

- Neighborhood
 - -change the color of a vertex

- Neighborhood
 - -change the color of a vertex
- Objective function
 - -minimizing the number of colors

- Neighborhood
 - -change the color of a vertex
- Objective function
 - -minimizing the number of colors
- ► How to guide the search?
 - changing the color of a vertex typically does not change the number of colors


- Color classes
 - -C_i is the set of vertices colored with i

- Color classes
 - -C_i is the set of vertices colored with i
- ► How to drive the search?
 - -use a proxy as objective function
 - favor large color classes


- Color classes
 - -C_i is the set of vertices colored with i
- ► How to drive the search?
 - -use a proxy as objective function
 - -favor large color classes
- ► The objective function becomes

maximize
$$\sum_{i=1}^{n} |C_i|^2$$


- Richer neighborhoods
 - -exploiting problem structure better
- Kemp Chains




- Richer neighborhoods
 - exploiting problem structure better
- Kemp Chains




- Richer neighborhoods
 - exploiting problem structure better
- Kemp Chains




- Richer neighborhoods
 - exploiting problem structure better
- Kemp Chains



- Richer neighborhoods
 - exploiting problem structure better
- Kemp Chains




- Richer neighborhoods
 - -exploiting problem structure better
- Kemp Chains




选择所有这些相关联的点,交换

- Richer neighborhoods
 - exploiting problem structure better
- Kemp Chains



- Richer neighborhoods
 - exploiting problem structure better
- Kemp Chains



- Explore both feasible and infeasible colorings
 - the search must focus on reducing the number of colors and on ensuring feasibility.

- Explore both feasible and infeasible colorings
 - the search must focus on reducing the number of colors and on ensuring feasibility.
- How to combine optimization and feasibility
 - make sure that local optima are feasible
 - use an objective function that balances feasibility and optimality

minimize $w_f f + w_o O$

- Neighborhood
 - -change the color of a vertex

- Neighborhood
 - -change the color of a vertex
- Bad edges
 - a bad edge is an edge whose adjacent vertices have the same color
 - B_i is the set of bad edges between vertices colored with i

- Neighborhood
 - -change the color of a vertex
- Decreasing the number of colors

maximize
$$\sum_{i=1}^{n} |C_i|^2$$

- Neighborhood
 - -change the color of a vertex
- Decreasing the number of colors

maximize
$$\sum_{i=1}^{n} |C_i|^2$$

Removing violations

- Neighborhood
 - -change the color of a vertex
- Decreasing the number of colors

maximize
$$\sum_{i=1}^{n} |C_i|^2$$

Removing violations

minimize
$$\sum_{i=1}^{n} |B_i|$$

- Neighborhood
 - -change the color of a vertex
- Decreasing the number of colors

maximize
$$\sum_{i=1}^{n} |C_i|^2$$

Removing violations

► How to combine them?

The Combined Objective Function

- Neighborhood
 - -change the color of a vertex
- Objective function

minimize
$$\sum_{i=1}^{n} 2 |B_i| |C_i| - \sum_{i=1}^{n} |C_i|^2$$

The Combined Objective Function

- Neighborhood
 - -change the color of a vertex
- Objective function

minimize
$$\sum_{i=1}^{n} 2 |B_i| |C_i| - \sum_{i=1}^{n} |C_i|^2$$

► Why?

The Combined Objective Function

- Neighborhood
 - -change the color of a vertex
- Objective function

minimize
$$\sum_{i=1}^{n} 2 |B_i| |C_i| - \sum_{i=1}^{n} |C_i|^2$$

► Why?

local minima of this objective are legal colorings

- ► Consider a coloring C₁,...,C_k
 - -assume that B_i is not empty
 - we show that this coloring is not a local minimum

- ► Consider a coloring C₁,...,C_k
 - -assume that B_i is not empty
 - we show that this coloring is not a local minimum
- ► Consider an additional color k+1
 - select an edge in B_i and color one of its vertices with k+1 (instead of i)

- ► Consider a coloring C₁,...,C_k
 - -assume that B_i is not empty
 - we show that this coloring is not a local minimum
- ► Consider an additional color k+1
 - select an edge in B_i and color one of its vertices with k+1 (instead of i)
- Consider the objective

minimize
$$\sum_{i=1}^{n} 2 |B_i| |C_i| - \sum_{i=1}^{n} |C_i|^2$$

- ► Consider a coloring C₁,...,C_k
 - -assume that B_i is not empty
 - we show that this coloring is not a local minimum
- ► Consider an additional color k+1
 - select an edge in B_i and color one of its vertices with k+1 (instead of i)
- Consider the objective

minimize
$$\sum_{i=1}^{n} 2 |B_i| |C_i| - \sum_{i=1}^{n} |C_i|^2$$

► How does it vary?

- ► Consider a coloring C₁,...,C_k
- Consider an additional color k+1
 - Select an edge in B_i and color one vertex with k+1
- ► How does the objective vary?

- ► Consider a coloring C₁,...,C_k
- ► Consider an additional color k+1
 - Select an edge in B_i and color one vertex with k+1
- ► How does the objective vary?
 - -the left term decreases by

$$2|B_i||C_i| - 2(|B_i| - 1)(|C_i| - 1) = 2|B_i| + 2|C_i| - 2 \ge 2|C_i|$$

- ► Consider a coloring C₁,...,C_k
- Consider an additional color k+1
 - Select an edge in B_i and color one vertex with k+1
- ► How does the objective vary?
 - -the left term decreases by

$$2|B_i||C_i| - 2(|B_i| - 1)(|C_i| - 1) = 2|B_i| + 2|C_i| - 2 \ge 2|C_i|$$

-the right term increases by

$$|C_i|^2 - ((|C_i| - 1)^2 + 1) = 2|C_i| - 2.$$

- ► Consider a coloring C₁,...,C_k
- Consider an additional color k+1
 - Select an edge in B_i and color one vertex with k+1
- ► How does the objective vary?
 - the left term decreases by

$$2|B_i||C_i| - 2(|B_i| - 1)(|C_i| - 1) = 2|B_i| + 2|C_i| - 2 \ge 2|C_i|$$

- the right term increases by

$$|C_i|^2 - ((|C_i| - 1)^2 + 1) = 2|C_i| - 2.$$

Overall, the objective decreases by at least 2

当碰到有约束的优化问题:

- 1. 解一个feasibility序列问题
- 2. 在feasible space中优化 (color class)
 3. balance (构造cost function)

Until Next Time