

5. Block Diagram Analysis

5.1 Introduction


- In section 3 of the notes, we examined the modelling of various static and dynamical systems and ended up with mathematical models in the form of linear differential equations.
- In section 4 we effectively described the same systems as transfer function models, using the Laplace transform.
- Large, complicated systems may consist of many components, each of which may be represented by a transfer function.
- A **block diagram** shows these transfer functions and illustrates the functional relationship between them.
- In general, a block diagram consists of a specific configuration of four types of elements:
 - blocks,
 - summing points,
 - take-off points and
 - arrows representing unidirectional signal flow.




5.2 Block diagram algebra

- Complicated block diagrams can be simplified by combining different blocks together in a step-by-step fashion using block diagram algebra.
- There are 3 basic operations, depending on the type of connection between blocks.
- Series, parallel and feedback connections are possible. We will now look at each of these in turn.
- **Series (or cascade) connection** – the blocks are connected as shown below.

- **Blocks in series** are simply combined by **multiplying** them together.




- *Ex. 5.1 Simplify the following system:*




Solution:

$$\begin{aligned} \frac{Y(s)}{U(s)} &= \left(\frac{s+1}{s+5} \right) \left(\frac{2}{s+3} \right) \\ &= \frac{2(s+1)}{(s+3)(s+5)} \\ &= \frac{2s+2}{s^2+8s+15} \end{aligned}$$

- **Parallel connection** – the blocks are connected as shown below.
- **Blocks in parallel** are simply combined by **adding** them together.





- *Ex. 5.2 Simplify the following system:*



Solution:

$$\begin{aligned}\frac{Y(s)}{U(s)} &= \left(\frac{s+1}{s+5} \right) + \left(\frac{2}{s+3} \right) = \frac{(s+1)(s+3) + 2(s+5)}{(s+3)(s+5)} \\ &= \frac{s^2 + 4s + 3 + 2s + 10}{s^2 + 8s + 15} = \frac{s^2 + 6s + 13}{s^2 + 8s + 15}\end{aligned}$$

- **Feedback connection** – when the output of a block is fed back to the input of an earlier block in the block diagram, a feedback mechanism is introduced.
- This is usually referred to as *closing the loop*.
- The resulting transfer function is called the **closed loop transfer function**.
- The fundamental closed loop diagram for a feedback system is as follows:



- This is known as the **canonical block diagram** and is characterised by:
 - $G(s)$ is the direct or forward path transfer function.

- $H(s)$ is the feedback transfer function (a unity feedback system has $H(s) = 1$).
- $\frac{X(s)}{U(s)} = G(s)H(s)$, **with feedback disconnected**, is the **open-loop transfer function (OLTF)**.
- $\frac{Y(s)}{U(s)} = \frac{G(s)}{1 + G(s)H(s)}$ is the **closed-loop transfer function (CLTF)**.

- Looking at the block diagram, we can derive the CLTF as follows:

$$Y(s) = G(s)E(s)$$

$$E(s) = U(s) - X(s) \quad \Rightarrow Y(s) = G(s)(U(s) - X(s))$$


$$X(s) = H(s)Y(s) \quad \Rightarrow Y(s) = G(s)(U(s) - H(s)Y(s))$$

$$\Rightarrow Y(s) = G(s)U(s) - G(s)H(s)Y(s)$$

$$\Rightarrow Y(s)(1 + G(s)H(s)) = G(s)U(s)$$

$$\Rightarrow \frac{Y(s)}{U(s)} = \frac{G(s)}{1 + G(s)H(s)} = \text{CLTF}$$

- **Ex. 5.3 Simplify the following system:**




Solution:

$$\frac{Y(s)}{U(s)} = \frac{\left(\frac{2}{s+3}\right)}{1 + \left(\frac{2}{s+3}\right)\left(\frac{s+1}{s+5}\right)}$$

Multiplying up and down by $(s+3)(s+5)$ gives:

$$\begin{aligned} \frac{2(s+5)}{(s+3)(s+5) + 2(s+1)} \\ = \frac{2s+10}{s^2 + 8s + 15 + 2s + 2} = \frac{2s+10}{s^2 + 10s + 17} \end{aligned}$$

- **Ex. 5.4 Find the closed-loop transfer function (CLTF) for the following system:**



Solution:


Firstly, we can combine the two transfer functions in cascade, $G_2(s)$ and $G_3(s)$ to give one transfer function:

$$G_2 G_3$$

Then, the inner loop can be reduced using the closed-loop formula for a canonical block diagram to give:

$$\frac{Y(s)}{X(s)} = \frac{G_2 G_3}{1 + G_2 G_3 H_2}$$

Hence:




Finally, we can, once again, combine the two blocks in the forward path and use the canonical formula to find the closed-loop transfer function, as follows:

$$\frac{Y(s)}{R(s)} = \frac{\frac{G_1 G_2 G_3}{1 + G_2 G_3 H_2}}{1 + \left(\frac{G_1 G_2 G_3}{1 + G_2 G_3 H_2} \right) H_1} = \frac{G_1 G_2 G_3}{1 + G_2 G_3 H_2 + G_1 G_2 G_3 H_1}$$


5.3 Dealing with multiple inputs

- When multiple inputs are present in a linear system, the *superposition theorem* is used.
- In other words, each input is treated independently of the others and the resultant output is given by the sum of the outputs due to each input separately.
- The procedure is as follows:
 - Set all inputs to zero, except for one.
 - Calculate the response due to the chosen input acting alone.
 - Repeat the above two steps for all inputs.
 - Algebraically add all of the responses (outputs) determined.
- **Ex 5.5 Simplify the following system:**



Solution:


Firstly, set $U(s) = 0$. Thus, the system reduces to:




Hence, the output due to input R is given by:

$$C_R(s) = \frac{G_1 G_2}{1 + G_1 G_2} R$$

Now, set $R(s) = 0$. Thus, the system reduces to:



This is equivalent to:



Hence, the output due to input U is given by:


$$C_U(s) = \frac{G_2}{1 + G_1 G_2} U$$

Finally, the total response is:

$$\begin{aligned}
 C(s) &= C_R(s) + C_U(s) \\
 &= \frac{G_1 G_2}{1 + G_1 G_2} R + \frac{G_2}{1 + G_1 G_2} U \\
 &= \frac{G_1 G_2 R(s) + G_2 U(s)}{1 + G_1 G_2}
 \end{aligned}$$


5.4 Block diagram reduction

- The procedure for block diagram reduction is:
 - Assign intermediate variables to signals between blocks.
 - Write a complete set of equations for the system.
 - Eliminate the intermediate variables.
 - Where possible, use standard results (series, parallel, feedback) to simplify analysis.
- **Ex 5.6 Determine the CLTF for the system represented by the following block diagram:**




Solution:

For clarity, we can redraw this diagram as follows:



We can now replace the inner loop containing G_2 and H_1 as follows:



Assigning the intermediate variable $X(s)$ shown above, we can now write down the following set of equations for the system:

$$Y(s) = \frac{G_2}{1 + G_2 H_1} (X(s) + U(s))$$

and

$$X(s) = G_1 (U(s) - H_2 Y(s))$$

Eliminating $X(s)$, by substituting the second equation into the first gives:

$$\begin{aligned} Y(s) &= \frac{G_2}{1 + G_2 H_1} (G_1 (U(s) - H_2 Y(s)) + U(s)) \\ \Rightarrow Y(s) &= \frac{G_1 G_2}{1 + G_2 H_1} U(s) - \frac{G_1 G_2 H_2}{1 + G_2 H_1} Y(s) + \frac{G_2}{1 + G_2 H_1} U(s) \\ \Rightarrow Y(s) \left(1 + \frac{G_1 G_2 H_2}{1 + G_2 H_1} \right) &= U(s) \left(\frac{G_1 G_2}{1 + G_2 H_1} + \frac{G_2}{1 + G_2 H_1} \right) \\ \Rightarrow \frac{Y(s)}{U(s)} &= \frac{\left(\frac{G_1 G_2}{1 + G_2 H_1} + \frac{G_2}{1 + G_2 H_1} \right)}{\left(1 + \frac{G_1 G_2 H_2}{1 + G_2 H_1} \right)} \\ &= \frac{G_1 G_2 + G_2}{1 + G_2 H_1 + G_1 G_2 H_2} = \text{CLTF} \end{aligned}$$



"Look, Bernie, all I'm saying is
I think you're riding the new guy pretty hard."