

# BenchResources.Net

Java, Collection, JDBC, Spring, Web Services, Maven, Android, Oracle SOA-OSB & Open Source

## Importance of SerialVersionUID in Serialization

🕒 November 10, 2016 👤 SJ 📁 Serialization 💬 2

In this article, we will discuss *importance of SerialVersionUID in Serialization* and *De-Serialization process*. And finally *compare* the *compiler generated SerialVersionUID v/s programmer defined SerialVersionUID* and decide *which one to use?*

In all the previous articles, *we haven't discussed* anything about serialVersionUID

- [Introduction to Serialization](#)
- [Serializable interface in detail with example](#)
- [Transient modifier in serialization process](#)
- [Order of serialization and de-serialization](#)
- [Serialization with Aggregation](#)
- [Serialization with Inheritance](#)
- [Externalizable interface in detail with example](#)

But there is always serialVersionUID *associated* with every serializable class.

### SEARCH TUTORIALS

### SUBSCRIBE VIA EMAIL


Join 194 other subscribers

### POPULAR ARTICLES

JDBC: An example to connect MS Access database in Java 8

If you are using *IDE like Eclipse*, then it *warns* with following message

*"The serializable class <class-name> does not declare static final serialVersionUID field of type long"*



As we stated earlier that there is always a `serialVersionUID` associated with every serializable class, then **where we have declared in earlier example?**

**Serialization:** Actually, we haven't declared this field and if it isn't declared then compiler does the job for us by declaring this static field and it get saved to serialized file along with Object values

**De-Serialization:** while restoring object back from file storage then first thing it does is, compare stored `serialVersionUID` inside serialized file with serializable class

**Exception:** if there is a mismatch between `serialVersionUID` present in the serialized file and serializable class, then *InvalidClassException* will be thrown


Now, the *next question with serialVersionUID* is whether to use compiler generated `serialVersionUID` or programmer explicitly declaring `serialVersionUID` i.e.;

Spring JDBC: An example on JdbcTemplate using Annotation  
Java JDBC: An example to connect MS Access database  
Oracle OSB 12c: Service Callout and Routing Table example  
Oracle OSB 12c: Hello World service with both Business and Proxy Service

BenchR

G+ Fc

88 follower



Be the first of your friends to l

# serialVersionUID: *Compiler generated v/s programmer defined*

- Compiler generated serialVersionUID is **highly complex** as it uses combination of class name and properties to generate this unique Id
- Due to the **complexity in creation** of this unique Id, **performance** of serialization and de-serialization process **becomes slow**
- Therefore, it is **highly recommended to define serialVersionUID** inside serializable class and use for both serialization and de-serialization process
- Firstly it **reduces the complexity** in creating compiler generated serialVersionUID and comparing this unique Id during **de-serialization process**
- Programmer has the **flexibility** of declaring any **Long value**

Lets us see a simple demo program for both cases:

## Exercise 1: serialVersionUID is same

Below customer class is a serializable class i.e.; it implements `java.io.Serializable` interface and programmer provides `serialVersionUID` with value `19L`

### Customer.java

```
1 package in.bench.resources.serial.version.uid;
2
3 import java.io.Serializable;
4
5 class Customer implements Serializable {
6
7     // default serialVersionUID
8     private static final long serialVersionUID
9
10    // member variables for Customer
11    int customerId;
12    String customerName;
13    String customerSSN;
14
```

```

15 // 3-arg parameterized constructor for Cust
16 public Customer(int customerId, String cust
17     String customerSSN) {
18     super();
19     this.customerId = customerId;
20     this.customerName = customerName;
21     this.customerSSN = customerSSN;
22 }
23
24 // to print nicely - customer object
25 @Override
26 public String toString() {
27     return "Customer [customerId=" + custom
28         + ", customerName=" + customerN
29         + ", customerSSN=" + customerSS
30 }
31 }

```

This class is the main class which *serializes the Customer class* with *serialVersionUID 19L*

#### SerializeCustomer.java

```

1 package in.bench.resources.serial.version.uid;
2
3 import java.io.FileNotFoundException;
4 import java.io.FileOutputStream;
5 import java.io.IOException;
6 import java.io.ObjectOutputStream;
7
8 public class SerializeCustomer {
9
10     public static void main(String[] args) {
11
12         // create a customer object using 3-arg
13         Customer customer = new Customer(101, "
14
15         // creating output stream variables
16         FileOutputStream fos = null;
17         ObjectOutputStream oos = null;
18
19         try {
20             // for writing or saving binary dat
21             fos = new FileOutputStream("Custome
22
23             // converting java-object to binary
24             oos = new ObjectOutputStream(fos);
25
26             // writing or saving customer objec
27             oos.writeObject(customer);
28             oos.flush();
29             oos.close();
30         }
31         catch (FileNotFoundException fnfex) {
32             fnfex.printStackTrace();
33         }
34         catch (IOException ioex) {
35             ioex.printStackTrace();
36         }

```

```

37 |
38 |         System.out.println("Customer object sav
39 |     }
40 | }

```

### Output:

```

1 | Customer object saved to Customer.ser file

```

This class de-serializes the *Customer class with the same serialVersionUID* used for serialization (i.e.; 19L)

### DeSerializeCustomer.java

```

1 | package in.bench.resources.serial.version.uid;
2 |
3 | import java.io.FileInputStream;
4 | import java.io.FileNotFoundException;
5 | import java.io.IOException;
6 | import java.io.ObjectInputStream;
7 |
8 | public class DeSerializeCustomer {
9 |
10 |     public static void main(String[] args) {
11 |
12 |         // creating input stream variables
13 |         FileInputStream fis = null;
14 |         ObjectInputStream ois = null;
15 |
16 |         // creating customer object reference
17 |         // to hold values after de-serializatio
18 |         Customer customer = null;
19 |         try {
20 |             // reading binary data
21 |             fis = new FileInputStream("Customer
22 |
23 |             // converting binary-data to java-o
24 |             ois = new ObjectInputStream(fis);
25 |
26 |             // reading object's value and casti
27 |             customer = (Customer) ois.readObjec
28 |         }
29 |         catch (FileNotFoundException fnfex) {
30 |             fnfex.printStackTrace();
31 |         }
32 |         catch (IOException ioex) {
33 |             ioex.printStackTrace();
34 |         }
35 |         catch (ClassNotFoundException ccex) {
36 |             ccex.printStackTrace();
37 |         }
38 |
39 |         System.out.println("Customer object de-
40 |             + "Customer.ser file\nLet's pri
41 |
42 |         // printing customer object to console
43 |         System.out.println(customer);
44 |     }

```

**Output:**

```

1 | Customer object de-serialized from Customer.ser?
2 | Let's print to console...
3 |
4 | Customer [customerId=101, customerName=SJ, custo

```

**Exercise 2: serialVersionUID is different**

Let us tweak above example by *changing serialVersionUID* after serialization process

- We will keep same *serialVersionUID* i.e.; **19L** while *serialization*
- **Change** serialVersionUID *after serialization*
- That's, **change** to **21L**
- **Serialization** program will be executed and same **output** will be seen *as per earlier case*
- But during **de-serialization** process, due to the **difference of serialVersionUID**, runtime exception will be thrown i.e.; **InvalidClassException**

**Steps:**

- Keep same serialVersionUID (i.e.; **19L**) in Customer class and **execute serialize customer** class
- Above step help in storing or **saving customer object to serialized file**
- Now, **change serialVersionUID** to **21L** in Customer class and compile again
- Next step, **execute de-serialize** customer class

**Output:**

```

1 | java.io.InvalidClassException: in.bench.resou?
2 | Customer; local class incompatible:
3 | stream classdesc serialVersionUID = 19, local c
4 |     at java.io.ObjectStreamClass.initNonProxy(
5 | ObjectStreamClass.java:616)
6 |     at java.io.ObjectInputStream.readNonProxyDe
7 | ObjectInputStream.java:1623)
8 |     at java.io.ObjectInputStream.readClassDesc(
9 | ObjectInputStream.java:1518)
10 |    at java.io.ObjectInputStream.readOrdinaryOb
11 | ObjectInputStream.java:1774)
12 |    at java.io.ObjectInputStream.readObject0(
13 | ObjectInputStream.java:1351)

```

```
14         at java.io.ObjectInputStream.readObject(  
15     ObjectInputStream.java:371)  
16         at in.bench.resources.serial.version.uid.De  
17     main(DeSerializeCustomer.java:27)  
18     Customer object de-serialized from Customer.ser  
19     Let's print to console...  
20  
21     null
```

## References:

<https://docs.oracle.com/javase/7/docs/api/java/io/Serializable.html>

<https://docs.oracle.com/javase/7/docs/platform/serialization/spec/serial-arch.html>

<https://docs.oracle.com/javase/7/docs/api/java/io/ObjectOutputStream.html>

<https://docs.oracle.com/javase/7/docs/api/java/io/ObjectInputStream.html>

<https://docs.oracle.com/javase/7/docs/api/java/io/FileOutputStream.html>

<https://docs.oracle.com/javase/7/docs/api/java/io/FileInputStream.html>

<http://docs.oracle.com/javase/specs/jls/se7/html/jls-8.html#jls-8.3.1.3>

## Read Also:

- [Java Serialization and De-Serialization Tutorial Index](#)
- [Serialization and De-Serialization in Java](#)
- [Serializable interface](#)
- [Transient keyword with Serialization in Java](#)
- [Transient keyword with static variable in Serialization](#)
- [Transient keyword with final variable in Serialization](#)
- [Serializing a variable with transient modifier or keyword](#)
- [Order of Serialization and De-Serialization](#)
- [Serialization with Aggregation](#)
- [Serialization with Inheritance](#)
- [Externalizable interface with example](#)
- [Serializable v/s Externalizable](#)
- [Singleton Design pattern with Serialization](#)
- [How to stop Serialization in Java](#)

- [How to construct a singleton class in a multi-threaded environment in Java](#)
- [How to serialize and de-serialize ArrayList in Java](#)

Happy Coding !!

Happy Learning !!



**Singleton Design pattern with  
Serialization**

**Serializable v/s Externalizable**



### Related Posts:

1. [Singleton Design pattern with Serialization](#)
2. [How to stop Serialization in Java](#)
3. [Serialization interview question and answer in Java](#)
4. [Serialization with Inheritance](#)

DESERIALIZATION

JAVA

SERIALIZABLE

SERIALIZATION

SERIALVERSIONUID





infoj • a year ago

Both the name of the class and its serialVersionUID are written to the object stream. One thing to notice here is that even if serialVersionUID field is static it is still serialized and stored.

 |  • Reply • Share ›BenchResources.Net Mod  infoj • a year ago

Yes, it is possible to serialize and de-serialize static variables but there mechanism is bit different from instance variables.

Take a look at the below article for more explanation with example <http://www.benchresources.net>

 |  • Reply • Share ›

## ALSO ON BENCHRESOURCES.NET

**Sorting list of objects on multiple fields using**

1 comment • 2 years ago

**Juan Daniel Ornella** — Thank You!!

**JDBC: An example to connect MS Access database in Java 8**

18 comments • 2 years ago

**Daroga Jee** — then tell us.. Where to go and connect to MS-Excel..

**Java features version-wise**

2 comments • a year ago

**Java: StringBuffer length() method**