

NAME

ksi pubfile - Verify and dump KSI publications file with KSI command-line tool.

SYNOPSIS

ksi pubfile -P URL --dump

ksi pubfile -P URL -o pubfile.bin --cnstr oid=value ... [-V cert.pem]... [-W dir]... [more options]

ksi pubfile -P URL -v --cnstr oid=value ... [-V cert.pem]... [-W dir]... [more options]

ksi pubfile -T time -X URL [--ext-user user --ext-key key] [more options]

DESCRIPTION

Verifies and dumps the content of KSI publications file. The KSI publications file contains information on all the existing publications records and the PKI certificates that are used to verify the calendar authentication records of KSI signatures.

OPTIONS

-P URL Publications file URL (or file with URI scheme 'file:/').

--cnstr oid=value

OID of the PKI certificate field (e.g. e-mail address) and the expected value to qualify the certificate for verification of publications file PKI signature. At least one constraint must be defined. All values from lower priority source are ignored.

For more common OID's there are convenience names defined:

- **E** or **email** for OID 1.2.840.113549.1.9.1
- **CN** or **cname** for OID 2.5.4.3
- **C** or **country** for OID 2.5.4.6
- **O** or **org** for OID 2.5.4.10

-v Perform publications file verification. Note that when **-o** is used to save publications file, the verification is performed implicitly.

-V file Certificate file in PEM format for publications file verification. All values from lower priority source are ignored.

-W dir OpenSSL-style trust store directory for publications file PKI signature verification. All values from lower priority source are ignored.

-o file Output file path to store publications file. Use '-' as file name to redirect publications file binary stream to *stdout*. Publications file is always verified before saving.

-X URL

Extending service (KSI Extender) URL.

--ext-user str

Username for extending service.

--ext-key str

HMAC Key for extending service.

-T time Specify a time to create a publication string for as the number of seconds since 1970-01-01 00:00:00 UTC or time string formatted as "YYYY-MM-DD hh:mm:ss".

-d Print detailed information about processes and errors to *stderr*.

--dump

Dump publications file in human-readable format to *stdout*. Without any extra flags publications file verification is not performed.

--conf file

Read configuration options from given file. It must be noted that configuration options given explicitly on command line will override the ones in the configuration file. See **ksi-conf(5)** for

more information.

--log *file*

Write Write libksi log to given file. Use '-' as file name to redirect log to *stdout*.

EXIT STATUS

See **ksi**(1) for more information.

EXAMPLES

In the following examples it is assumed that KSI service configuration options (URLs, access credentials) are defined. See **ksi-conf**(5) for more information.

1 To dump the publications file from default URL call:

ksi pubfile --dump

2 To dump the publications file *pubfile.bin* on local file system (verification is not performed):

ksi pubfile --dump -P file://pubfile.bin

3 To verify a publications file *pubfile.bin* from local disk call:

ksi pubfile -v -P file:///home/user/publications/pubfile.bin

4 To download, verify and save the publications file to *pubfile.bin* from default URL (verification is performed automatically when saving) call:

ksi pubfile -o pubfile.bin --cnstr email=publications@guardtime.com

5 To verify the publications file with only certificates defined on command-line call:

ksi pubfile -v -V certificate_1.bin -V certificate_2.bin --cnstr email=publications@guardtime.com

6 To create a publication string call:

ksi pubfile -T "2015-10-15 00:00:00"

ENVIRONMENT

Use the environment variable **KSI_CONF** to define the default configuration file. See **ksi-conf**(5) for more information.

AUTHOR

Guardtime AS, <http://www.guardtime.com/>

SEE ALSO

ksi(1), **ksi-sign**(1), **ksi-verify**(1), **ksi-extend**(1), **ksi-conf**(5)