

NAME

ksi.conf - KSI (Keyless Signature Infrastructure) service configuration file.

DESCRIPTION

This file is read by KSI command-line tool **ksi(1)** as KSI service configurations file. Configurations file is composed of the following parameters described under section **OPTIONS**. If configurations file with unknown or invalid key-value pairs is used, an error is generated until user applies all the fixes needed.

All the key-value pairs must be placed one per line. A short parameter or multiple flags must have prefix **-** and long parameters must have prefix **--**. To write a comment start the line with **#**. If some parameter values contain whitespace characters a double quote marks (") must be used to wrap the entire value. If double quote mark have to be used inside the value part an escape character (\) must be typed before the quote mark (\").

OPTIONS

-S URL Specify signing service URL.

--aggr-user str
User name for signing service.

--aggr-key str
HMAC Key for signing service.

-X URL
Specify extending service URL.

--ext-user str
User name for extending service

--ext-key str
HMAC Key for extending service.

-P URL Specify publications file URL (or file with URI scheme 'file://').

--cnstr oid=value
OID and its expected value to verify publications file PKI signature. At least one constraint must be defined to be able to verify publications file but it is possible to define more.

-V file Specify an OpenSSL-style trust store file for publications file verification.

-W dir Specify an OpenSSL-style trust store directory for publications file verification.

-c int Set network transfer timeout, after successful connect, in seconds.

-C int Set network connect timeout in seconds (is not supported with TCP client).

--publications-file-no-verify
A flag to force the tool to trust the publications file without verifying it. The flag can only be defined on command-line to avoid the usage of insecure configurations files. It must be noted that the **option is insecure** and may only be used for testing.

ENVIRONMENT

Program **ksi(1)** uses environment variable **KSI_CONF** to point to the default configurations file.

EXAMPLES

An example of configurations file:

```
# --- BEGINNING ---
#
# KSI Signing service parameters:
-S http://example.gateway.com:3333/gt-signingservice
--aggr-user anon
--aggr-key anon

# KSI Extending service:
```

```
# Note that ext-key real value is &h/J"kv\G##  
-X http://example.gateway.com:8010/gt-extending-service  
--ext-user anon  
--ext-key "&h/J"kv\G##"  
  
# KSI Publications file:  
-P http://verify.guardtime.com/ksi-publications.bin  
--cnstr email=publications@guardtime.com  
--cnstr "org=Guardtime AS"  
#  
# --- END ---
```

AUTHOR

Guardtime AS, <http://www.guardtime.com/>

SEE ALSO

ksi-sign(1), **ksi-verify(1)**, **ksi-extend(1)**, **ksi-pubfile(1)**, **ksi-conf(5)**