

**NAME**

**ksi pubfile** - Guardtime command-line tool for verifying and dumping KSI publications file.

**SYNOPSIS**

**ksi pubfile -P url --dump**

**ksi pubfile -P url -o pubfile.bin --cnstr oid=value ... [-V cert.pem]... [-W dir]... [more options]**

**ksi pubfile -P url -v --cnstr oid=value ... [-V cert.pem]... [-W dir]... [more options]**

**ksi pubfile -T time -X url [--ext-user user --ext-key key] [more options]**

**DESCRIPTION**

This is a KSI publications file tool for performing publications file related general tasks.

**OPTIONS**

**-P url** Specify publications file URL (or file with uri scheme 'file://').

**--cnstr oid=value**

OID and its expected value to verify publications file PKI signature. At least one constraint must be defined to be able to verify publications file but it is possible to define more. All values from lower priority source are ignored, where default configurations file is the lowest and command-line is the highest.

**-v** Perform publications file verification. Note that when **-o** is used to save signatures file verifications is always performed.

**-V file** Specify an OpenSSL-style trust store file for publications file verification. All values from lower priority source are ignored, where default configurations file is the lowest and command-line is the highest.

**-W dir** Specify an OpenSSL-style trust store directory for publications file verification. All values from lower priority source are ignored, where default configurations file is the lowest and command-line is the highest.

**-o file** Output file name to store publications file. Use '-' as file name to redirect publications file binary stream to *stdout*. Publications file is always verified before saving.

**-X url** Specify extending service URL.

**--ext-user str**

User name for extending service.

**--ext-key str**

HMAC Key for extending service.

**-T time** Specify a time to create a publication string for as the number of seconds since 1970-01-01 00:00:00 UTC or time string formatted as "YYYY-MM-DD hh:mm:ss".

**-d** Print detailed information about processes and errors to *stderr*.

**--dump**

Dump Publications file to *stdout*. Without any extra flags publications file verification is not performed.

**--conf file**

Specify a configurations file to override default service information. It must be noted that service info from command-line will override the configurations file. See **ksi(1)** and **ksi-conf(5)** for more information.

**--log file**

Write libksi log into file. Use '-' as file name to redirect log to *stdout*.

**EXIT STATUS**

See **ksi(1)** for more information.

## EXAMPLES

In the following examples it is assumed that default service urls are defined (see **ksi(1)** for more information).

**1** To dump a publications file from default url call:

```
ksi pubfile --dump
```

**2** To dump a publications file *pubfile.bin* from local disk call (verification is not performed):

```
ksi pubfile --dump -P file://pubfile.bin
```

**3** To download and verify a publication file *pubfile.bin* call:

```
ksi pubfile -o pubfile.bin --cnstr email=publications@guardtime.com
```

**4** To verify a publications file with only certificates defined on command-line call:

```
ksi pubfile -v -V certificate_1.bin -V certificate_2.bin --cnstr email=publications@guardtime.com
```

**5** To create a publication string call:

```
ksi pubfile -T "2015-10-15 00:00:00"
```

## ENVIRONMENT

Environment variable **KS1\_CONF** can be defined to set default KSI configurations file. See **ksi(1)** and **ksi-conf(5)** for more information.

## AUTHOR

Guardtime AS, <http://www.guardtime.com/>

## SEE ALSO

**ksi(1)**, **ksi-sign(1)**, **ksi-verify(1)**, **ksi-extend(1)**, **ksi-conf(5)**