

Structurale properties of decomposable digraphs

by

Gabriella Juhl Jensen

supervised by

Prof. Jørgen Bang-Jensen



UNIVERSITY OF SOUTHERN DENMARK

DEPARTMENT OF MATHEMATICS AND COMPUTER SCIENCE

Contents

I	Primitive graphs and gabbigubbi	2
0.1	Introduction	3
1	Graphs and digraphs	4

Part I

Primitive graphs and gabbigubbi

0.1 Introduction

Why we need graphs.


Chapter 1

Graphs and digraphs


Before going deep into structural properties of decomposable digraphs we first need to establish what a graph is. For some graph $G(V, E)$ where V and E are two sets containing the vertices (also commonly called nodes) and edges of the graph respectively. We define the **size** of the graph to be the number of vertices $|V|$ this is also known as **cardinality** of V . An **edge** $e \in E$ where $e \equiv (a, b)$ and $\{a, b\} \subseteq V$ then e is an edge in G , e is said to be **incident** to a and b . We call $a, b \in V$ **adjacent** if there is an edge (a, b) or (b, a) (an edge between the two given vertices is said to be adjacent). If an edge goes from and to the same vertex (a, a) it is called a **loop**. The set of edges e_1, \dots, e_k is usually describe with the letter E where each edge contains a pair of vertices that are adjacent.

In a graph we have something called a **walk** which is a alternately ordering of vertices and edges in the graph G where the edge in between the two vertices in the ordering is an edge between the vertices in G (for (a, e_1, b) to be a walk the edge e_1 has to be between a and b). We call a walk closed if the first vertex in the walk is the same as the last.

A **path** in a graph is a walk where each vertex in the ordering can only appear one time. A cycle is a closed walk where the only vertex present more than one time is the first vertex (for the walk to be closed the first vertex has to appear last to also called a closed path).



(a) graph $G(V, E)$ is an example of a graphs, the red edge is a loop, and all pair of vertices in this graph is adjacent.



(b) This is an orientation of the edges in the graph which makes this a digraph

Before delving more specific into graphs and digraphs we must establish some important prerequisite and properties. A graph is called **simple** if there is no loops and no multiple edges. With multiple edges it means multiple edges between the same pair of vertices like in Figure 1.1a between b and c .

A graph is **connected** if there exists a path between all pair of vertices in the graph and **disconnected** otherwise. A graph is called **complete** if there for all pair of vertices in the graph is an edge between them see Figure 1.2.




Figure 1.2: Complete graph with 5 vertices.

If we instead of edges have **arcs** between the vertices we call it a **digraph**. An arc is describe just like an egde with two adjacent vertices (a, b) the first vertex mentioned in an arc is the vertex **from** where the arc starts also called the **tail**, the second vertex is where the arc is pointing **to** also called **head**. The set of arcs is normaly denoted A like the set of edges is denoted E . So the arc (a, b) goes from a to b , if you wanted it the other way around the arc is (b, a) . These graph contaning only arcs and no edges is called a digraph $G(V, A)$ which is what we in this project are focusing on see Figure 1.1b.

In a digraph we have something called the **underlying graph**. An underlying graph of a digraph is where all arcs are replaced by edges (edge is used every time we talk about undirected edges between vertices, when using directions it is called an arc). A digraph is **connected** if the underlying graph is connected, (also called weakly connected), a digraph can be **strongly connected** and **semi connected** too. A digraph is called **semi connected** if there for each pair u and v exists a path from either u to v or v to u . It is said to be **strongly connected** if for each pair of vertices u and v there exists a path from both u to v and v to u . We can use **these** to describe som specific collection of graphs as the graph **tournaments**. **Tournaments** is a digraph where the underlying graph is complete. So a complete graph of order 5 any orientation of the edges concludes in a tournament. If instead of replacing the one edge by one arc in either direction, but instead replace it by two arcs the digraph is called **semicomplete**.

The reason for grouping the digraphs into smaller collections of digraphs (like tournaments is a smaller collection of semicomplete digraphs) is because of problems that is hard to solve on general graph but is easy/polynomial solvable on specific graphs.

A group of these problems is called NP-hard problems which sometimes sound easy solvable for graphs but only for some specific graphs we know how to solve it in polynomial time.

Definition 1.0.1. *define NP-hard problems*

In this paper we focusing on the specific digraphs that are **decomposable**. A **decomposable** digraph is a digraph $D = H[G_1, G_2, \dots, G_{|H|}]$ where each G_i is sconnected graphs replacing each vertex of the digraph H