

main.c

Share

Run

```
1 //experiment 4:
2 #include <stdio.h>
3 int main()
4 {
5     int bt[20], p[20], wt[20], tat[20];
6     int i, j, n, total = 0, pos, temp;
7     float avg_wt, avg_tat;
8     printf("Enter number of processes: ");
9     scanf("%d", &n);
10    printf("Enter Burst Time:\n");
11    for (i = 0; i < n; i++)
12    {
13        printf("P%d: ", i + 1);
14        scanf("%d", &bt[i]);
15        p[i] = i + 1;
16    }
17    for (i = 0; i < n; i++)
18    {
19        pos = i;
20        for (j = i + 1; j < n; j++)
21        {
22            if (bt[j] < bt[pos])
23                pos = j;
24        }
25        temp = bt[i];
26        bt[i] = bt[pos];
27        bt[pos] = temp;
28        temp = p[i];
29        p[i] = p[pos];
30        p[pos] = temp;
31    }
32    wt[0] = 0;
33    for (i = 1; i < n; i++)
34    {
35        wt[i] = 0;
36        for (j = 0; j < i; j++)
```

Output

Enter number of processes: 4
Enter Burst Time:
P1: 8
P2: 4
P3: 6
P4: 2

Process	Burst Time	Waiting Time	Turnaround Time
P4	2	0	2
P2	4	2	6
P3	6	6	12
P1	8	12	20

Average Waiting Time = 5.00
Average Turnaround Time = 10.00

=== Code Execution Successful ===