



VIT[®]
AP

CSE2007 : Database Management Systems

Name : Gudi Varaprasad

Reg. No. : 19BCE7048

School of Computer Science and Engineering

Lab Slot : L45 + L46

Date : 18 – 02 – 2021

Submitted to : Ms. Dhanavanthini madam

Lab Cycle-I (SQL)

(up to 10 questions)

Creation of General Hardware Database (GHD), Insertion of data into GHD and writing and executing queries for the questions.

I. General Hardware Database:

SalesPerson(SalesPersonNumber, SalesPersonName, CommPercentage, YearHire, OfficeNumber)

Customer (CustomerNumber, CustomerName, SalesPersonNumber, HeadQuarterCity)

CustomerEmployee (CustomerNumber, EmployeeNumber, EmployeeName, Title)

Product (ProductNumber, ProductName, UnitPrice)

Sales (SalesPersonNumber, ProductNumber, Quantity)

Office (OfficeNumber, Telephone, Size)

```
Run SQL Command Line

SQL> CREATE TABLE SalesPerson(SalesPersonNumber number(10) not null, SalesPersonName varchar2(15), CommPercentage number(5), YearHire number(5), OfficeNumber number(10), PRIMARY KEY(SalesPersonNumber));

Table created.

SQL> CREATE TABLE Customer(CustomerNumber number(10) not null, CustomerName varchar2(15), SalesPersonNumber number(10), HeadQuarterCity varchar2(15), PRIMARY KEY(CustomerNumber), FOREIGN KEY(SalesPersonNumber) REFERENCES SalesPerson);

Table created.

SQL> CREATE TABLE CustomerEmployee(CustomerNumber number(10), EmployeeNumber number(10) not null, EmployeeName varchar2(15), Title varchar2(15), PRIMARY KEY(EmployeeNumber), FOREIGN KEY(CustomerNumber) REFERENCES Customer);

Table created.

SQL> CREATE TABLE Product(ProductNumber number(10) not null, ProductName varchar2(15), UnitPrice number(5), PRIMARY KEY(ProductNumber));

Table created.

SQL> CREATE TABLE Sales(SalesPersonNumber number(10), ProductNumber number(10), Quantity number(10), FOREIGN KEY(SalesPersonNumber) REFERENCES SalesPerson, FOREIGN KEY(ProductNumber) REFERENCES Product);

Table created.

SQL> CREATE TABLE Office(OfficeNumber number(10), Telephone number(10), officeSize number(10), FOREIGN KEY(OfficeNumber) REFERENCES SalesPerson);

Table created.

SQL> commit;

Commit complete.

SQL>
```

Tables Description :

- > DESC SalesPerson;
- > DESC Customer;
- > DESC CustomerEmployee;
- > DESC Product;
- > DESC Sales;
- > DESC Office;

```
Run SQL Command Line

SQL> DESC SalesPerson;
Name                               Null?   Type
-----
SALESPERSONNUMBER                 NOT NULL NUMBER(10)
SALESPERSONNAME                   VCHAR2(15)
COMMPERCENTAGE                    NUMBER(5)
YEARHIRE                          NUMBER(5)
OFFICENUMBER                      NUMBER(10)

SQL> DESC Customer;
Name                               Null?   Type
-----
CUSTOMERNUMBER                   NOT NULL NUMBER(10)
CUSTOMERNAME                     VCHAR2(15)
SALESPERSONNUMBER                NUMBER(10)
HEADQUATERCITY                   VCHAR2(15)

SQL> DESC CustomerEmployee;
Name                               Null?   Type
-----
CUSTOMERNUMBER                   NUMBER(10)
EMPLOYEENUMBER                   NOT NULL NUMBER(10)
EMPLOYEEENAME                    VCHAR2(15)
TITLE                            VCHAR2(15)

SQL> DESC Product;
Name                               Null?   Type
-----
PRODUCTNUMBER                   NOT NULL NUMBER(10)
PRODUCTNAME                     VCHAR2(15)
UNITPRICE                       NUMBER(5)

SQL> DESC Sales;
Name                               Null?   Type
-----
SALESPERSONNUMBER                NUMBER(10)
PRODUCTNUMBER                   NUMBER(10)
QUANTITY                        NUMBER(10)

SQL> DESC Office;
Name                               Null?   Type
-----
OFFICENUMBER                     NUMBER(10)
TELEPHONE                       NUMBER(10)
OFFICESIZE                       NUMBER(10)

SQL>
```

Inserting Values :

SalesPerson Table

```
Run SQL Command Line

SQL> INSERT INTO SalesPerson VALUES(146,'gudi',10,2000,1);

1 row created.

SQL> INSERT INTO SalesPerson VALUES(186,'vara',7,2001,2);

1 row created.

SQL> INSERT INTO SalesPerson VALUES(176,'prasad',3,2002,3);

1 row created.

SQL> INSERT INTO SalesPerson VALUES(137,'prasad',14,2003,4);

1 row created.

SQL> INSERT INTO SalesPerson VALUES(203,'devgudi',10,2004,5);

1 row created.

SQL> INSERT INTO SalesPerson VALUES(227,'cryptokid',1,2005,6);

1 row created.

SQL> SELECT * FROM SalesPerson;

SALESPERSONNUMBER SALESPERSONNAME COMMPERCENTAGE   YEARHIRE  OFFICENUMBER
-----
          146   gudi                10         2000           1
          186   vara                 7         2001           2
          176   prasad                3         2002           3
          137   prasad               14         2003           4
          203   devgudi              10         2004           5
          227   cryptokid             1         2005           6

6 rows selected.

SQL>
```

Customer Table

```
Run SQL Command Line

SQL> INSERT INTO Customer VALUES(1533, 'idug', 146, 'atlanta');
1 row created.

SQL> INSERT INTO Customer VALUES(1733, 'arav', 186, 'newyork');
1 row created.

SQL> INSERT INTO Customer VALUES(2131, 'dasarp', 176, 'arizona');
1 row created.

SQL> INSERT INTO Customer VALUES(1041, 'dasarpg', 137, 'mexico');
1 row created.

SQL> INSERT INTO Customer VALUES(1551, 'idugved', 203, 'dallas');
1 row created.

SQL> INSERT INTO Customer VALUES(1244, 'dikotpyrc', 227, 'washington');
1 row created.

SQL> SELECT * FROM Customer;

CUSTOMERNUMBER  CUSTOMERNAME      SALESPERSONNUMBER  HEADQUATERCITY
-----
          1533  idug                    146  atlanta
          1733  arav                    186  newyork
          2131  dasarp                  176  arizona
          1041  dasarpg                 137  mexico
          1551  idugved                 203  dallas
          1244  dikotpyrc               227  washington

6 rows selected.

SQL>
```

CustomerEmployee

```
Run SQL Command Line

SQL> INSERT INTO CustomerEmployee VALUES(1533, 7048, 'idug1', 'dbms');
1 row created.

SQL> INSERT INTO CustomerEmployee VALUES(1733, 7049, 'arav1', 'crypto');
1 row created.

SQL> INSERT INTO CustomerEmployee VALUES(2131, 7050, 'dasarp1', 'oops');
1 row created.

SQL> INSERT INTO CustomerEmployee VALUES(1041, 7051, 'dasarpg1', 'ececoa');
1 row created.

SQL> INSERT INTO CustomerEmployee VALUES(1551, 7052, 'idugved1', 'french');
1 row created.

SQL> INSERT INTO CustomerEmployee VALUES(1244, 7053, 'dikotpyrc1', 'softskills');
1 row created.

SQL> SELECT * FROM CustomerEmployee;

CUSTOMERNUMBER  EMPLOYEENUMBER  EMPLOYEEENAME      TITLE
-----
          1533          7048  idug1              dbms
          1733          7049  arav1              crypto
          2131          7050  dasarp1            oops
          1041          7051  dasarpg1           ececoa
          1551          7052  idugved1           french
          1244          7053  dikotpyrc1         softskills

6 rows selected.

SQL>
```

Product Table

```
Run SQL Command Line

SQL> INSERT INTO Product VALUES(21765, 'gudi1', 40);
1 row created.

SQL> INSERT INTO Product VALUES(21565, 'vara1', 50);
1 row created.

SQL> INSERT INTO Product VALUES(21465, 'prasad1', 60);
1 row created.

SQL> INSERT INTO Product VALUES(21365, 'prasadg1', 70);
1 row created.

SQL> INSERT INTO Product VALUES(21665, 'devgudi1', 80);
1 row created.

SQL> INSERT INTO Product VALUES(21265, 'cryptokid1', 30);
1 row created.

SQL> SELECT * FROM Product;

PRODUCTNUMBER PRODUCTNAME      UNITPRICE
-----
          21765 gudi1              40
          21565 vara1             50
          21465 prasad1           60
          21365 prasadg1          70
          21665 devgudi1          80
          21265 cryptokid1        30

6 rows selected.

SQL>
```

Sales Table

```
Run SQL Command Line

SQL> INSERT INTO Sales VALUES(146, 21765, 3261);
1 row created.

SQL> INSERT INTO Sales VALUES(186, 21565, 1869);
1 row created.

SQL> INSERT INTO Sales VALUES(176, 21465, 2332);
1 row created.

SQL> INSERT INTO Sales VALUES(176, 21365, 4500);
1 row created.

SQL> INSERT INTO Sales VALUES(203, 21665, 1600);
1 row created.

SQL> INSERT INTO Sales VALUES(176, 21265, 2500);
1 row created.

SQL> SELECT * FROM Sales;

SALESPERSONNUMBER PRODUCTNUMBER  QUANTITY
-----
          146          21765      3261
          186          21565      1869
          176          21465      2332
          176          21365      4500
          203          21665      1600
          176          21265      2500

6 rows selected.

SQL>
```

Office Table

```
Run SQL Command Line

SQL> INSERT INTO Office VALUES(146, 1234, 11);
1 row created.

SQL> INSERT INTO Office VALUES(186, 1234, 20);
1 row created.

SQL> INSERT INTO Office VALUES(176, 1888, 10);
1 row created.

SQL> INSERT INTO Office VALUES(137, 2033, 28);
1 row created.

SQL> INSERT INTO Office VALUES(227, 5211, 33);
1 row created.

SQL> INSERT INTO Office VALUES(203, 7251, 93);
1 row created.

SQL> SELECT * FROM Office;

OFFICENUMBER  TELEPHONE  OFFICESIZE
-----
          146          1234           11
          186          1234           20
          176          1888           10
          137          2033           28
          227          5211           33
          203          7251           93

6 rows selected.

SQL>
```

Answer the following queries :

1. Find the commission percentage and year of hire of salesperson number 186.

```
Run SQL Command Line

SQL> SELECT * FROM SalesPerson;

SALESPERSONNUMBER SALESPERSONNAME  COMMPERCENTAGE  YEARHIRE  OFFICENUMBER
-----
          146   gudi              10         2000           1
          186   vara              7         2001           2
          176  prasad              3         2002           3
          137  prasad             14         2003           4
          203  devgudi             10         2004           5
          227  cryptokid            1         2005           6

6 rows selected.

SQL> SELECT COMMPERCENTAGE, YEARHIRE FROM SalesPerson WHERE SALESPERSONNUMBER = 186;

COMMPERCENTAGE  YEARHIRE
-----
              7         2001

SQL>
```

2. List the salesperson numbers and salesperson names of those salespersons who have a commission percentage of 10.

```
SQL> SELECT SALESPERSONNUMBER, SALESPERSONNAME FROM SalesPerson WHERE COMMPERCENTAGE = 10;

SALESPERSONNUMBER SALESPERSONNAME
-----
146 gudi
203 devgudi

SQL>
```

3. List the salesperson number and salesperson name of all of the salespersons.

```
SQL> SELECT SALESPERSONNUMBER, SALESPERSONNAME FROM SalesPerson;

SALESPERSONNUMBER SALESPERSONNAME
-----
146 gudi
186 vara
176 prasad
137 prasad
203 devgudi
227 cryptokid

6 rows selected.
```

4. List the salesperson numbers, salesperson names, and commission percentages of the salespersons whose commission percentage is less than 12.

```
SQL> SELECT SALESPERSONNUMBER, SALESPERSONNAME, COMMPERCENTAGE FROM SalesPerson WHERE COMMPERCENTAGE < 12;

SALESPERSONNUMBER SALESPERSONNAME COMMPERCENTAGE
-----
146 gudi 10
186 vara 7
176 prasad 3
203 devgudi 10
227 cryptokid 1
```

5. List the customer numbers and headquarters cities of the customers that have a customer number of at least 1700.

```
SQL> SELECT * FROM Customer;

CUSTOMERNUMBER CUSTOMERNAME SALESPERSONNUMBER HEADQUATERCITY
-----
1533 idug 146 atlanta
1733 arav 186 newyork
2131 dasarp 176 arizona
1041 dasarpg 137 mexico
1551 idugved 203 dallas
1244 dikotpyrc 227 washington

6 rows selected.

SQL> SELECT CUSTOMERNUMBER, HEADQUATERCITY FROM Customer WHERE CUSTOMERNUMBER > 1700;

CUSTOMERNUMBER HEADQUATERCITY
-----
1733 newyork
2131 arizona
```

6. List the customer numbers, customer names, and headquarters cities of the customers that are headquartered in New York and that have a customer number higher than 1500.

```
SQL> SELECT CUSTOMERNUMBER, CUSTOMERNAME, HEADQUATERCITY FROM Customer WHERE HEADQUATERCITY = 'newyork' AND CUSTOMERNUMBER> 1500;
```

CUSTOMERNUMBER	CUSTOMERNAME	HEADQUATERCITY
1733	arav	newyork

7. List the customer numbers, customer names, and headquarters cities of the customers that are headquartered in New York or that have a customer number higher than 1500.

```
SQL> SELECT CUSTOMERNUMBER, CUSTOMERNAME, HEADQUATERCITY FROM Customer WHERE HEADQUATERCITY = 'newyork' OR CUSTOMERNUMBER> 1500;
```

CUSTOMERNUMBER	CUSTOMERNAME	HEADQUATERCITY
1533	idug	atlanta
1733	arav	newyork
2131	dasarp	arizona
1551	idugved	dallas

8. List the customer numbers, customer names, and headquarters cities of the customers that are headquartered in New York or that satisfy the two conditions of having a customer number higher than 1500 and being headquartered in Atlanta.

```
SQL> SELECT CUSTOMERNUMBER, CUSTOMERNAME, HEADQUATERCITY FROM Customer WHERE HEADQUATERCITY = 'newyork' OR CUSTOMERNUMBER> 1500 AND HEADQUATERCITY = 'atlanta';
```

CUSTOMERNUMBER	CUSTOMERNAME	HEADQUATERCITY
1533	idug	atlanta
1733	arav	newyork

9. Which cities serve as headquarters cities for General Hardware customers ?

```
SQL> SELECT HEADQUATERCITY FROM Customer;
```

HEADQUATERCITY
atlanta
newyork
arizona
mexico
dallas
washington

6 rows selected.

10. Find the customer numbers, customer names, and headquarters cities of those customers with customer numbers greater than 1000. List the results in alphabetic order by headquarters cities.

Run SQL Command Line

```
SQL> SELECT CUSTOMERNUMBER, CUSTOMERNAME, HEADQUATERCITY FROM Customer WHERE CUSTOMERNUMBER > 1000 ORDER BY HEADQUATERCITY ASC;
```

CUSTOMERNUMBER	CUSTOMERNAME	HEADQUATERCITY
2131	dasarp	arizona
1533	idug	atlanta
1551	idugved	dallas
1041	dasarpg	mexico
1733	arav	newyork
1244	dikotpyrc	washington

6 rows selected.
